Index

| a | basin oil removal system 130 |
|--|--|
| accelerated sedimentation units 88 | |
| activated sludge systems 221, 225, 234 | biochemical oxygen demand (BOD) 9, 56–58 |
| activated sludge technology 225, 226 | biochemical reactions 216 |
| active approach 269–270 | biolocial nutrient removal (BNR) 60 |
| advanced oxidation processes (AOP) 215 | biological aerated filter (BAF) 226 |
| aeration 226, 229 | |
| aerators 217, 228, 229, 244 | biological organic removal 215–231 |
| aerobic suspended bioreactors 226 | biological removal nitrogen compounds |
| air bubblers 229, 230 | 232 |
| air diffusers 228, 309 | biomass 219 |
| air distribution network 230 | bioreactions 232 |
| air movers 230 | bioreactor effluent 226 |
| air stripping 240 | bioreactors 221 |
| alkalinity 42–44 | blowers 309–310 |
| America Petroleum Institute (API) 125, | body feed filtration aid 105 |
| 131 | boiler blow down water 8 |
| ammonia removal 246 | boiler make up water 8 |
| ammonium sulfite 244 | brackish water RO (BWRO) 193, 194, |
| amorphous silica 47 | 298 |
| anaerobic ponds 305, 307 | break point chlorination test 261 |
| anaerobic suspended bioreactors 226 | brush aerators 229 |
| animal oils/fats 38 | |
| anionic coagulants 249 | C |
| anionic resins 169 | cake filters 104 |
| apparent volumetric concentration 18 | calcium carbonate (CaCO ₃) 323 |
| asphaltenes 34 | calcium hypochlorite 256 |
| atmospheric deaerators 244 | capacity 271 |
| | capital cost (CAPEX) 332 |
| b | capturing solids 101 |
| back pressure, RO 194 | carbon dioxide removal 244–245 |
| bacteria 73 | cartridge filter 113–114 |
| base flowrate 273 | cationic coagulants 249 |
| | 8 |

Rules of Thumb for Water and Wastewater Engineers, First Edition. Moe Toghraei. © 2022 WILEY-VCH GmbH. Published 2022 by WILEY-VCH GmbH.

| cationic resins 169 | cross flow filtration 106 |
|---|--|
| cells 301 | crystallizers 161–167 |
| centrifuges 97–99, 145–146 | cumulative curve 23 |
| chemical addition methods 287 | |
| chemical denitrification 246 | d |
| chemical emulsions 33 | dead end filtration 106 |
| chemical injection packages 314–317 | decarbonators 244 |
| chemical injection systems 315, 317 | degassing 243 |
| chemical oxygen demand (COD) | demulsification methods 153 |
| 57, 58 | denitrification bacteria 233 |
| chemical precipitation 246 | deoileing hydrocyclones 143 |
| chlorination 17 | deoiling L-L hydrocyclones 143 |
| chlorine gas injectors 256 | depth filters 104 |
| chlorine-releasing chemicals 256 | discrete particle size distribution curves |
| city potable water 1 | 22 |
| clays 34 | discrete PSD 21 |
| coagulancy effect 249 | disc type centrifuge 97 |
| coagulants 249 | dispersed gas system 140 |
| coagulation-flocculation-sedimentation | disposal wells 328 |
| 297 | dissolved ammonia 67 |
| coalescer-filter 151 | dissolved carbon dioxide 66, 67 |
| coalescer-gravity separator 151 | dissolved contaminant 13 |
| coalescers 151–152 | dissolved gases 64 |
| coaxial jet mixing 317 | dissolved gases/volatile liquids |
| COD/BOD ratio 211 | advantages and disadvantages 239 |
| cold lime softener (CLS) 209 | ammonia removal 246 |
| coliforms 73, 74 | carbon dioxide removal 244-245 |
| colloidal silica 47 | hydrogen sulfide removal 245-246 |
| colloids 12, 71 | oxygen removal 243–244 |
| characteristics 71 | stripping 240–243 |
| hydrophobic and hydrophilic | dissolved hydrogen sulfide 68 |
| classification of 72 | dissolved inorganics removal methods |
| specification 71 | co-precipitation 203-209 |
| completely mixed reactor vs. plug reactor | evaporators and crystallizers 161–167 |
| 224 | ion exchange 167–186 |
| containerized units 282 | ions adsorption 202–203 |
| contaminants 9, 71 | reverse osmosis 186–202 |
| continuously stirred-tank reactor (CSTR) | specific ions removals 202 |
| 224 | three categories 159 |
| continuous regeneration (CR) 207 | dissolved ions 39 |
| conventional wastewater treatment | dissolved materials 12, 39 |
| 332 | dissolved oil 36 |
| cooling tower blow down water 8 | dissolved organic materials 54 |
| cooling tower make up water 8 | dissolved organics removal |
| co-precipitation 251 | advance oxidation processes 215 |

| biological organic removal 215–231 | fiber reinforced plastic (FRP) |
|--|---|
| granular activated carbon 212 | 191, 321 |
| ion exchange beds 214 | field erected units 283 |
| nitrogen removal 231–236 | filtration 104–117, 250 |
| non-biological organic removal | final untreatable liquids 327–328 |
| 211–212 | flash evaporators 162 |
| removal methods from high | flash slop treating system 156 |
| concentration organic 215 | floatables 10 |
| traditional chemical oxidation | group of 29 |
| processes 214–215 | oil feature of 30 |
| dissolved oxygen (DO) 64, 244 | removal strategy 123 |
| dissolved phosphorus 62 | flocculation 249 |
| dissolved-release gas bubbles 139 | flotation system 138 |
| dissolved specific ions | |
| alkalinity 42–44 | foaming problem 72 |
| hardness 40–42 | foot print 330–331 |
| iron and manganese 44–46 | fragility of oil globules 313 |
| nitrate and nitrite 46–47 | free oil measurement 35 |
| pH 39-40 | Free Water Knock out drums (FWKO |
| silica 47–48 | drums) 124 |
| dissolved total ions 49–54 | froth stream 138 |
| dissolved volatile organic carbons (VOC) | fully mixed aerated ponds 307 |
| 69 | functional group method 55 |
| drying bed ponds 304 | fungi 73 |
| e | g |
| E.Coli 73 | gas assisted floatation 136, 139 |
| eggshell 323 | gas-assisted gravity separation 136–143 |
| electric conductivity of water 52 | gas bubble generation 141 |
| empty bed contact time (EBCT) 150, 212 | gas by-products 324 |
| emulsified oil 33 | gas dispersion 140 |
| emulsions 29, 32, 72 | gaseous waste streams 325 |
| emulsion type polyelectrolytes 250 | geological survey 327 |
| energy recovery devices 197 | |
| equalization tanks 279 | granular activated carbon (GAC) 150, |
| evaporate water 161 | 211, 212 |
| evaporation ponds 304, 327 | granular carbon adsorption units 247 |
| evaporator plus crystallizers 166 | granulated activated carbon (GAC) 247 |
| evaporators 161–167 | gravitational solid removal 94 |
| exhaustive method 55 | greases in wastewater streams 29 |
| | grease traps 136 |
| f | grit chambers 99 |
| facultative ponds 305 | groundwater |
| fats in wastewaters 29 | colloid concentration 71 |
| fecal coliforms 73 | vs. surface water 1, 5 |

| n | ions removais 202–203 |
|--|--------------------------------------|
| handling dry solids 310–312 | iron and manganese 44–46 |
| hardness 40-42 | _ |
| heating emulsion-breaking system 156 | j |
| heating type slop treatment system 156 | jet mixing 317 |
| helminth 74 | |
| Henry's law constant 241 | k |
| hexane extractable material (HEM) 35 | kettle evaporators 162 |
| high brackish water 51 | _ |
| high lift pump stations 319 | l |
| hollow fine fiber (HFF) 191 | Langelier stability Index (LSI) 323 |
| horizontal flow sedimentation basins 94 | large industries 9 |
| hospital odor of water 82 | lime softeners 208 |
| hot lime softener (HLS) 209 | liquid-liquid hydrocyclones (LLHC) |
| H type skim tank 133 | 124, 125, 143–145 |
| human-affected water cycle 1 | liquid streams 325 |
| hydraulic dispersed gas system 141 | liquid tanks 310 |
| hydraulic removal systems 94 | L-L cyclones 144 |
| hydrocyclones 96–97 | low brackish water 51 |
| hydrogen sulfide removal 245–246 | low lift pump stations 319 |
| hydrophilic classification, of colloids 72 | |
| hydrophobic classification, of colloids | m |
| 72 | make-down water 250 |
| hydro-pneumatic tank 276 | man-made methods 299 |
| , | marine odor 82 |
| i | masking effect 17 |
| impure silica 47 | material analysis 25 |
| incineration 211 | mechanical aerators 228 |
| industrial wastewater 82 | mechanical emulsion 33 |
| industrial water plants 275 | mechanical evaporators 161 |
| inherent approach 269–270 | mechanical sludge removal systems 94 |
| injection by quills 317 | mechanical solid removal 94 |
| in-line coagulation 251 | mechanical vapor compressor (MVC) |
| inline installation 279 | 163 |
| inline neutralization 318 | membrane disk bubblers 230 |
| inorganic coagulants 249 | membrane filtration 114–117 |
| inorganic ion removal methods | membranes 81 |
| 159 | mesh size 21 |
| intermittent regeneration (IR) 207 | metallic ion colloids 71 |
| ion exchange (IX) 159, 167–186 | Micro emulsion 155 |
| beds 214 | micro filtration systems (MF) 248 |
| cycle operation 168 | microorganisms 253 |
| resins 168, 169, 172, 211 | mineral oils 36 |
| systems 175 | minimum shear 314 |
| vessels 175, 181 | mixed bed ion exchange (MBIX) 175 |
| | e , . |

| mixed liquor 236 mixed salt crystallizers 166 molds 73 moving bed biofilm reactor (MBBR) 226 multiple effect distillation (MED) evaporator 166 municipal wastewater 9, 220, 272, 297 | oil removal filter (ORF) 146–148 oil removal methods 124 centrifuges 145–146 coalescers 151–152 gas-assisted gravity separation 136–143 liquid-liquid hydrocyclones 143–145 |
|--|---|
| municipal water plants 274 | meso-and micro-emulsions 153–155 |
| | oil adsorption units 148–151 |
| n | oil filters 146–148 |
| natural emulsifiers 34 | oil gravity separation 126 |
| natural evaporation ponds 304 | skimmed oil 155–158 |
| natural water cycle 1 | oil removal systems 124, 152 |
| nature-based methods 299, 300 | oil separations methodologies 153 |
| nephelometric turbidity unit (NTU) | oily streams 313–314 |
| 27 | operating cost (OPEX) 332 |
| neutralized colloids particles-flocculation | organic colloids 72 |
| 248 | organic materials 25 |
| nitrate (NO ₃) 46–47, 60 | organic nitrogen 60, 61 |
| nitrification bacteria 232 | organic particles and fibres 29 |
| nitrite (NO ₂) 46–47, 60 | organic removal methods 305 |
| nitrogen and phosphorous 60 | organics 54 |
| nitrogen compounds in water 61 | organic suspended solids 25 |
| nitrogen removal 231–236 | organic trap 214 |
| non-biological organic removal 211–212 | organoclay 148 |
| non-condensing gas 70 | oxygen removal 243–244 |
| non-ionic coagulants 249 | |
| non-membrane type filters 104 | p |
| non-micro-organisms 74 | particle size distribution (PSD) 20 |
| non-specific method 56 | particle size spectrum 25 |
| • | particulate phosphorus 62 |
| O | passive approach 269 |
| offline installation 279 | pathogen deactivation 254 |
| oil adsorption units 148–151 oil coalescing 128 | pathogenic worms 74 |
| • | pathogens 13, 17, 73, 253 pH 39–40 |
| oil excursion 124 oil globules 137, 138, 313 | pH adjustment and neutralization |
| oil globule size distribution (OGD) 36 | 317–318 |
| oil globule sizes 33 | phosphorous compounds in water 62 |
| oil gravity separation 126 | photometric method 36 |
| oil in wastewater streams 29 | pipe flocculators 251 |
| oil-in-water (O/W) | pneumatic transferring 312 |
| emulsion 30, 35, 156 | polyelectrolytes 249 |
| mixtures 32 | polymeric coagulants 249 |
| oil layer removal, basin 130 | pond-based systems 221 |
| on my or round var, basili 130 | Police busice by stollis 221 |

| pond treatment systems | scavengers 239 |
|---|---------------------------------------|
| area and cell 301 | screenings 99–103 |
| depths of 301 | scroll-type centrifuges 97 |
| terminology 302 | s curve 23 |
| units 302, 304 | seawater reverse osmosis (SWRO) 193, |
| post-disinfection 255 | 194, 295, 298 |
| powdered activated carbon (PAC) 150 | sedimentation 88, 89, 250 |
| pressure filtration 105 | sedimentation basins 128 |
| pressure vessel (PV) 191 | sedimentation ponds 303 |
| primary clarifier 293 | segregation 269 |
| procedural approach 269 | selective ion exchange (IX) 203, 246 |
| process flow diagram (PFD) 285 | sensitive streams 313 |
| protozoa 73 | settleables 10, 17 |
| pumps 309 | settleables removal |
| | cartridge filter 113–114 |
| r | centrifuges 97–99 |
| reactive silica 47 | cut-off sizes 87 |
| recycled activated sludge (RAS) 226 | filtration 104–117 |
| recycling 221 | grit chambers 99 |
| removal methods from high concentration | hydrocyclones 96-97 |
| organic 215 | membrane filtration 114–117 |
| removing oil grease traps 136 | screening 99–103 |
| residual chlorine 260 | sedimentation 89 |
| residual disinfectant 255, 260 | sieving 88–99 |
| resin beads 170, 171 | suspended solid removals 87 |
| resin beds 167 | shallow depth sedimentation basins 96 |
| resins | shallow depth settling basins 96 |
| characteristics 169-170 | shear generating devices 314 |
| form or cycle 171 | side-entry jet mixing 317 |
| IX systems 185 | side streams 298 |
| regenerants process 176 | sieve mesh sizes 21 |
| reverse emulsion 29 | sieve test 20 |
| reverse osmosis (RO) 81, 159, 161, 187, | sieving 88–89, 99 |
| 194, 246 | silica (SiO ₂) 5, 72 |
| membranes 187 | forms of 47–48 |
| non-exhaustive list 197 | numerical values 48 |
| pressure of 194, 196 | single solid crystallizers 166 |
| rotating biological contactor (RBC) 226 | single stage vertical centrifugal 322 |
| | skid-mounted units 282 |
| S | skimmed oil 155–158 |
| SAC-H form 172 | skim tanks 132, 133, 152 |
| SAC-Na resin 173 | slop handling systems 155 |
| salt rejection (SR) 190, 197 | slop tank 156 |
| SBA-OH 172 | slop water treatment systems 156 |
| scaling from silica 48 | sludge handling 121 |
| | |

| sludge processing units 329–330 | t |
|---|--|
| sludge removal systems 94 | thin film composite (TFC) 189 |
| sludge/slurry handling 312-313 | thin film/droplet evaporation 162 |
| small industries 9 | total ammonia nitrogen (TAN) 68 |
| sodium hypochlorite 256 | total dissolved solids (TDS) 159, 187 |
| sodium sulfite 244 | RO 199 |
| solid-liquid hydrocyclone 125 | in water 49 |
| solid separation methods 117 | total ions 39 |
| solid's type 26 | total Kjeldahl nitrogen (TKN) 60 |
| solid wastes 328–329 | total oil content 34 |
| soluble oil 35 | total organic carbon (TOC) 57, 58 |
| soluble silica 47 | total phosphorus (TP) content 62 |
| sour water 245 | traditional chemical oxidation processes |
| specific ions 39 | 214–215 |
| specific water consumption 273 | treated wastewater 1 |
| spiral wound (SW) element 190 | treated water 325 |
| stagnant oil gravity separation 126 | turbidity 5, 26–28 |
| stagnant water sedimentation 90 | type IV water 54 |
| stainless steel (SS) 191 | type I water 54 |
| standard operating procedure (SOP) | |
| 269 | u |
| steam evaporators 162 | ultrafiltration (UF) 81, 248 |
| steam stripping 240 | ultrapure water 54 |
| Stiff & Davis Stability Index (S&DSI) 323 | UV disinfection 262 |
| Stokes' equation 88, 124 | |
| storage ponds 303 | V |
| storm water 303 | vacuum stripping 240 |
| stripping 240–243 | vapor compressor evaporators 162, 165 viruses 73 |
| strong acid cation (SAC) 172 | |
| strong basic anion (SBA) 172 | volatile organic carbons (VOC) 69 volatile suspended solids (VSS) 25, 219 |
| strong basic anion in chloride cycle | volatile suspended solids (VSS) 25, 219 volatilization 303 |
| (SBA-Cl) 172 | volume of settled solids 19 |
| sumps 320 | Vortex flotation units 142 |
| surface aerator 229 | voitex notation units 142 |
| surface filters 104 | W |
| surface water | WAC-H 172 |
| colloid concentration 71 | WAC-Na 173 |
| vs. groundwater 1, 5 | warm lime softener (WLS) 209 |
| streams 82 | wasted activated sludge (WAS) 226 |
| suspended contaminant 12 | waste water management |
| suspended culture bacteria 224 | active approach 269–270 |
| suspended solids (SS) 9, 17, 47 | flowrate estimation 271–275, 283 |
| synthetic oils 38 | fluctuations 275–276, 283 |
| synthetic organic liquids 38 | inherent approach 269–270 |

| waste water management (contd.) | features of 299–300 |
|---|--------------------------------------|
| materials of construction 282 | fundamentals of 300 |
| passive approach 269, 270 | oily streams 313–314 |
| plants' construction options 282-283 | pH adjustment and neutralization |
| procedural approach 269, 270 | 317–318 |
| procedures 267–269 | pumps 309 |
| surge 276, 277, 279, 281 | sludge/slurry handling 312-313 |
| treatment facilities 281, 283 | sumps 320 |
| wastewaters, in industries 9 | water consumers 5 |
| wastewater treatment 1 | water-in-oil (W/O) emulsion 29, 156 |
| cost matters 332–333 | water in process 8 |
| decision making and option selection | water-media interactions 323-324 |
| 333–334 | water streams, in industries 9 |
| final untreatable liquids 327–328 | water/wastewater plants |
| foot print 330–331 | basic design of 285 |
| site selection and enclosing 331-332 | biological methods 286-287 |
| sludge processing units 329-330 | chemical addition methods 287 |
| solid wastes 328–329 | chemical injection 287 |
| water-media interactions 323-324 | chemical methods and 286-287 |
| water wells 330 | developing string of units 289–292 |
| ZLD 324-326 | rule of thumbs in 292–293, 295–297 |
| water 5, 6 | mechanical methods 286 |
| water analysis | removal methodology 288 |
| estimation of existence of contaminants | residual streams 298 |
| 82 | water wells 330 |
| preparing of 78–79 | WBA-OH 172 |
| report 77–79 | weak acid cation (WAC) 172 |
| study and investigating 79-80 | weak basic anion (WBA) 172 |
| temperature 80–81 | well head injection pressure 328 |
| units of concentration 82-84 | wet air oxidation (WAO) 215 |
| water and wastewater | wet well lift stations 319 |
| blowers 309–310 | WHO standard for drinking water 6 |
| chemical injection packages | |
| 314–317 | у |
| handling dry solids 310–312 | yeasts 73 |
| lift stations 318–319 | |
| liquid tanks 310 | Z |
| man-made methods 299 | zero liquid discharge (ZLD) 324–246, |
| nature-based methods | 325 |
| applicability of 299 | zeta potential meter 71 |