

Index

a

acetamidine hydrochloride (AceCl) 186
 acidic additives 188
 active area width (W_a) 250
 additive engineering 183
 acidic additives 188–190
 functional molecular additives 183–187
 Al_2O_3 insulating mesoscopic layers, in FP-MPSCs 117–120
 Al_2O_3 slurry 118, 119
 ambient stability, of halide perovskites 218–219
 4-(aminomethyl) benzoic acid hydroiodide (ABI) 185–186
 5-aminovaleic acid (5-AVA) iodide 107, 249
 ammonium salt additives 183, 186
 5-ammoniumvaleric acid hydroiodide (5-AVAI) 172, 184–186, 217, 223, 225, 228
 $(4AMP)(FA)_{n-1}Sn_nI_{3n+1}$ 182
 aprotic sulfonium cations 156
 A site cation 178–180
 atomic force microscopy (AFM) 31–33, 187

b

back-contact porous carbon 100–101
 back electrode, for PSCs 209, 212–215, 222, 225, 226
 bar coating 67–69, 72–73, 82, 170
 Beer-Lambert's law 26

bias dependent photoluminescence imaging 37
 bifunctional molecular additives 184
 blade coating 65, 67–70, 82
 breakdown voltage (V_{br}), for halide perovskites 226
 Brunauer-Bennet-Teller (BET) method 21
 brush painting method 80–82
 B-site metal cation 180–183
 “built-in” potential 3, 57, 110, 111
 bulk heterojunction (BHJ) architecture 9
 bulk heterojunction OSC 9, 11
 1-butyl-3-methylimidazolium (BMIMBF₄) 223, 224
 1-butyl-1-methylpiperidinium tetrafluoroborate ([BMP]⁺[BF₄]⁻) 223

c

carbon-based, hole-conductor-free FP-MPSCs 107, 113, 119, 120, 123, 130
 carbon-graphite based perovskite solar cells (CG-PSC) 25
 carrier management methods, for printable cells vs. regular devices 272
 cation optimization 150–151
 certification, of PV performance 57–58
 certified efficiency measurements 57

- characterization techniques 19
 - atomic force microscopy 31–33
 - bias dependent photoluminescence imaging 37
 - contact angle measurement 32–33
 - current-voltage (I-V) characterization 50–51
 - current-voltage (I-V) hysteresis 51–52
 - dark lock-in thermography 39–42
 - electroluminescence imaging 36–37
 - energy dispersive x-ray spectroscopy 30–31
 - light-beam induced current 42
 - long term stability measurements 58–59
 - microscopic photoluminescence spectroscopy mapping 35–36
 - parallel and series resistance effect 55–56
 - photoluminescence microscopy imaging 34–35
 - printing layer quality
 - porosity estimation 21–23
 - sheet resistance 23–24
 - shunt resistance of unfilled cell 24
 - thickness measurement 19–21
 - Raman shift spectroscopy 26–28
 - real-time photoluminescence measurement 37–40
 - saturation current effect 56–57
 - scanning electron microscopy 28–31
 - spatially resolved steady-state photo-physical methods 33–42
 - SR/EQE patterns 52–54
 - stabilized efficiency measurement 52
 - transient optoelectronic methods 42–50
 - UV-Vis-NIR spectroscopy 25–26
 - V_{oc} vs. light intensity measurement 54–55
 - X-ray diffraction 25
 - charge transfer dynamics 157
 - chemical bath deposition (CBD) 65, 67, 78–79, 82, 91, 93, 271
 - chemically inert back electrodes 213
 - chloride additives 188, 190
 - $\text{CH}_3\text{NH}_3\text{PbI}_3$ -based FP-MPSCs 118, 128
 - commercialization, of photovoltaic module 89
 - commercialization, of PSCs 65, 78, 89, 180
 - composition engineering
 - A site cation 178–180
 - B-site metal cation and X-site anion 180–183
 - contact angle (CA) measurement 32–33
 - contact mode 32
 - contact profilometry 20
 - cost of silicon photovoltaic devices 269
 - cryogenic process 146
 - $\text{Cs}_{0.1}\text{Rb}_{0.05}\text{FA}_{0.85}\text{PbI}_3$ perovskite 179, 180
- d**
- dark lock-in thermography (DLIT) 39–42
 - dead area 251, 253, 258
 - depletion region 3, 5, 53
 - dimethylammonium iodide (DMAI) 218
 - drop-casting method 14, 48, 118, 169
 - dye-sensitized solar cells (DSSCs) 7–9, 11, 12, 76, 94, 103, 107, 114, 116, 167, 210, 260, 270
 - dynamic antisolvent quenching (DAS) process 67, 68
- e**
- edge seal encapsulant 216
 - electroluminescence imaging 36–37
 - electron beam interaction principle 30
 - electron-transport-free PSCs 168
 - electron transport materials (ETMs), for PSCs 191–193, 210, 211
 - ellipsometry 20–21
 - encapsulant polymers 215
 - encapsulation, for PSCs 215, 219, 227
 - energy dispersive X-ray spectroscopy (EDX) 30–31
 - equivalent circuit, of two-diode model 55

evaporation regime, in blade coating 69, 70
 external quantum efficiency (EQE) 38, 52–54, 271, 274

f

(FAPbI₃)_{1-x}(MAPbBr₃)_x perovskite 179
 FASnI₃ PSCs 180, 181
 Ferrocene (Fc) 226
 fill factor (FF) 5, 13, 19, 28, 50, 52, 90, 100, 102, 106, 111, 115, 116, 122, 127, 140, 182, 237, 240, 256, 262, 270, 271
 first-generation solar cells 269
 flame assisted CVD (FACVD) 249
 fluorine-doped tin oxides (FTO) substrate 12, 90, 93, 94, 210
 focused ion beam (FIB) milling process 22, 23
 force connections 24
 four-point probe sheet resistivity measurement 23–24
 four-point probe sheet resistivity measurements setup 24
 Frenkel excitons 9, 10
 FTO/mp-TiO₂/carbon-graphite, OCVD analysis on 45
 FTO/TiO₂/perovskite samples, TAS studies of 157
 functional molecular additives 183–187

g

GaAs solar cells, photovoltaic parameters of 271, 273
 geometric fill-factor (g-FF) 240, 251, 253, 256, 258, 259
 glass frit 260
 glass-glass encapsulation 260
 Goldschmidt's rule 153
 Goldschmidt's tolerance factor (τ) 150, 178, 179, 181, 217
 grain boundaries 38, 39, 79, 113, 147–153, 174, 183, 184, 217, 219, 221, 223, 224, 228

Grätzel cells 7, 8
 grazing incidence XRD (GIXRD) 25
 guanidine hydrochloride (GuaCl) 186

h

halide perovskite light absorbing layer
 ambient stability 218–219
 operational stability 219–226
 phase stability 217–218
 thermal stability 216–217
 halide perovskites
 crystal structure stability of 138
 synthesis 144–147
 three dimensional (3D) 137–142
 two dimensional (2D) 142–144
 halide segregation 142, 150, 155
 Han Cells 13
 hole-conductor-free PSCs 168, 169, 188–189, 193
 hole-transport-free PSCs 168
 hot carrier solar cells (HCSCs) 222
 hydrothermal synthesis 146

i

incident photon-to-current efficiency (IPCE) 100–103, 180
 indium tin oxides (ITO) substrate 82, 210
 industrialization, of PSCs 82, 228, 237
 inkjet method 240, 243, 248
 inkjet printing 67, 75–76
 inorganic CsPbI_{3-x}Br_x perovskite layer 75
 in situ single crystal transfer (ICT) process 174
 insulating layers, for printable MPSCs
 Al₂O₃ 117–120
 Al₂O₃ vs. ZrO₂ 108–110
 functions 105
 materials used for 105
 multilayer 124–130
 SiO₂ 121–124
 zirconium dioxide 106–117

- intensity-modulated photocurrent/
photovoltage spectroscopy
(IMPS/IMVS) 42–43
- interface engineering 155, 156, 190
perovskite and counter electrode
193–197
perovskite and electron transport layer
191–193
- intermittent contact mode 32
- International Electrotechnical
Commission (IEC) test conditions
58
- International Summit on Organic
Photovoltaic Stability (ISOS) test
conditions 58
- j**
- J-V measurements, of MPLE-PSC 102
- l**
- lab-scale MPLE 92
- Landau-Levich regime, in blade coating
69, 70
- laser ablation 260
- lead-free perovskite 181
- levelized cost of energy (LCOE) 209
- light-beam induced current (LBIC) 42
- Li-TFSI salt additive 212
- lock-in frequency 41
- m**
- Maobi 80, 81
- MAPbI_{2.95}(BF₄)_{0.05} perovskite 182
- megasonic spray coating 74
- meniscus coating 68, 69
- mesoscopic carbon PSC (mCPSC)
advantage 240
architecture 239
carbon cells and contact resistance
258
characteristic 240
double glass sealing modules 253
encapsulation and outdoor
performance 259–261
indoor applications 261–262
manufacture 240
additional interlayers deposition
248–249
compact TiO₂ deposition 246–248
mesoscopic layers deposition 248
perovskite infiltration method
249–250
screen-printing 240–246
modules design 250, 251, 253
modules optimization 253, 258
modules performance 258
power generation 262
2D Poisson's equation 255–257
- metal oxide ETMs 211
- 2-methoxyethanol (2-ME) 170, 171,
191
- methylamine-induced CH₃NH₃PbI₃
liquefaction and recrystallization
38
- methylammonium lead iodide perovskite
(CH₃NH₃PbI₃, MAPI) 249
- methylammonium lead triiodide
(MAPbI₃) 11–13, 26, 31, 40, 70,
79, 107, 111, 127–130, 137–141,
143–145, 149, 150, 153, 155–157,
167, 170–172, 174, 177–180, 184,
186–191, 196, 212, 217, 218
- microscopic photoluminescence (μ -PL)
spectroscopy mapping 35–36
- microwave irradiation process 147
- Mie-scattering theory 96
- mixed cation 3D perovskites 139
- mixed (5-AVA)_xMA_{1-x}PbI_{3-y}(BF₄)_y
perovskite 183
- mixed-halide perovskites 151, 155
- monolithic DSSCs, role of spacer layer in
107, 114
- multilayer insulating mesoscopic layers
Al₂O₃+NiO 126–128
Al₂O₃+ZrO₂ 124–126
ZrO₂+NiO 128–130
- multiple exciton generation (MEG) effect
274
- multi-porous-layered-electrode perovskite
solar cells (MPLE-PSC) 89

- back-contact porous carbon 100–101
 - compact anode TiO₂ layer 92–95
 - cross-sectional illustration 90
 - fabrication methods 90–93
 - IPCE measurements 102
 - J-V measurements 102
 - mesoporous anodes 95–99
 - mesoporous-NiO cathode 99–100
 - photoenergy conversion efficiency 89
 - photonics-electronics-materials effects
 - of anode particle size on photovoltaics 95
 - photovoltaic characteristics 90
 - sub-module, screen-printing design
 - example 92, 93
 - super stability 89
 - multi-tip pipette (MC) process 67, 68
- n**
- nano-TiO₂ colloid
 - acid-route synthesis of 96
 - basic-route synthesis 97
 - N-methylformamide (NMF) 172, 176, 177
 - non-contact mode 32
 - non-fullerene acceptors (NFAs) 9, 11
 - N719 190
- o**
- open circuit voltage decay (OCVD)
 - analysis, for shunt detection 44–45
 - operational stability, of halide perovskites
 - defect degeneration 225–226
 - degradation pathways 219–222
 - grain boundary modification 223–224
 - heat management 222–223
 - interface strengthening 223–225
 - reverse-bias voltages 226
 - optical microscopes 28, 34, 73
 - optical power density, solar simulators 50
 - opto-electro-modulated transient
 - photocurrent/photovoltage (M-TPC/ M-TPV) configuration 44
 - organic ETLs 211
 - organic-inorganic halide perovskites 147, 178
 - organic solar cells (OSCs) 9–11, 15, 80, 210
 - organic solvents, physical and chemical properties of 173
 - oxygen-deficient carbon black (ODC) 42–43, 194, 195
 - oxygen-rich carbon black (ORC) 43, 194, 195
- p**
- parallel and series resistance effect 55–56
 - PbSe QD-based solar cells, MEG effect in 274
 - perovskite films, structural
 - characterization of 187
 - perovskite materials
 - three dimensional halide perovskites 137–142
 - two dimensional halide perovskites 142–144
 - perovskite solar cells (PSCs) 11, 13
 - cation optimization 150–151
 - charge transfer dynamics 157
 - halide optimization 151
 - halide segregation 155
 - interface engineering 155–156
 - inverted planar p-i-n structure 15
 - long-term stability of 209
 - mesoscopic structure 13–14
 - phase formation, inorganic cations
 - influence on 153–154
 - photovoltaic parameters of 271
 - regular planar n-i-p structure 15
 - solvent engineering 147–149
 - stability issues and solutions
 - back electrode 212–215
 - electron transport layer (ETL) 211

- perovskite solar cells (PSCs) (*contd.*)
 - encapsulant 215–216
 - halide perovskite light absorbing layer 216–226
 - hole transport layer 212, 213
 - substrates for 210
 - stoichiometric and non-stoichiometric compositions 151–153
 - triple-mesoscopic layer structure 14–15
 - perovskite solar modules (PSMs) 65, 66, 68, 69, 71, 72, 75–80, 82, 226, 228
 - perovskite/S20 spacer film composite 112
 - phase stability, of halide perovskites 217–218, 220
 - photocurrent density-voltage (J-V) curves, of solid state dye-sensitized solar cells 94
 - photoenergy conversion efficiency 89, 93, 96, 100
 - photoluminescence microscopy imaging 34–35
 - photo-to-current conversion efficiency spectrum 167
 - photovoltaic effect 1
 - photovoltaic parameters, of ZrO₂ based FP-MPSCs 111, 113
 - pneumatic spray coating 74
 - polyethylene terephthalate (PET) 210
 - porosity estimation 21
 - gas adsorption 21–22
 - SEM/FIB 3D nanotomography 22–23
 - power conversion efficiency (PCE) 6, 7, 9, 11, 13–15, 51, 52, 58, 69, 71, 72, 76, 79, 80, 107, 111, 113–115, 118, 119, 121, 122, 124, 127–129, 140, 143, 146, 149, 167, 169, 171, 172, 174, 177–186, 188, 190, 191, 193, 194, 198, 209, 211, 212, 214, 216, 221–227, 237–240, 252, 253, 256, 260, 270, 271, 274
 - power conversion efficiency limit, of single-junction perovskite solar cells 270
 - printable mesoscopic PSCs 169, 222
 - additive engineering 183
 - acidic additives 188
 - chloride additives 188, 190
 - functional molecular additives 183–187
 - composition engineering 178
 - A site cation 178–180
 - B-site metal cation and X-site anion 180–183
 - interface engineering 190
 - perovskite and counter electrode 193–197
 - perovskite and electron transport layer 191–193
 - photovoltaic parameters of 271
 - solvent annealing 174–178
 - solvent engineering 169–174
 - printing layer quality
 - porosity estimation 21
 - gas adsorption 21–22
 - SEM/FIB 3D nanotomography 22–23
 - sheet resistance 23–24
 - shunt resistance of unfilled cell 24
 - thickness measurement 19–20
 - ellipsometry 20–21
 - profilometry 20
 - scanning electron microscope 20
 - profilometry 20
 - pulse based TRPL 46, 47
- q**
- quantum-dots (QD) photovoltaic system, MEG effect in 274
 - quasi fermi level splitting (QFLS) 34
- r**
- Raman shift spectroscopy 26–28
 - real-time photoluminescence measurement 37–40
 - renewable energy sources 1
 - robotic mesh (RbM) 249, 250
 - roll-to-roll (R2R) production 241
 - roll-to-roll (R2R) technology 71

- room temperature processing 146
- Ruddlesden-Popper (RP) layered perovskites 142
- S**
- saturation current effect 56–57
- scanning electron microscopy (SEM) 20, 22–23, 28–32, 74, 108, 109, 112–114, 118, 120, 122–124, 127, 175, 177, 182, 196
- screen-printing method, mCPSC 7, 67, 75–78, 91–93, 95, 97, 99, 108, 118, 239–243, 247, 249, 254
 - deposition of the mesoscopic layers 248
 - ink properties 243
 - mesh characteristics 243–244
 - mesoporous TiO₂ layer 245–246
 - screen and substrate gap 244–245
- SEM/FIB 3D nanotomography 22–23
- sense connections 24
- series resistance (R_s) 19, 23, 24, 28, 55–56, 116, 117, 239, 253, 262
- sheet resistance, of thin conducting films 24
- sheet-to-sheet (S2S) production 241
- Shockley and Queisser limit 6, 270
- Shockley equation 5
- Shockley-Queisser efficiency limit 270, 271, 273
- Shockley-Queisser limit 13, 179, 273, 274
- Shockley's diode equation 50
- short-circuit current 5, 50, 179, 190
- shunt resistance of unfilled cell 24
- silicon solar cells 2–7, 44, 58, 65, 219, 238, 239, 269
- single-cation (and anion) HPs 139
- SiO₂ insulating mesoscopic layers, in FP-MPSCs 121–124
- slot-die coating 65, 67–72, 82
- soft-cover deposition 67, 79–80
- solar cell parameters
 - for carbon-based cells with and without Cu:NiOx 99
 - for standard carbon cell without and with Co₃O₄ layer 100
- solar cells, principle of 2–13
- solar energy 1, 118
- solid-state reaction method 146
- solution-based technologies
 - bar coating 72–73
 - blade coating 68–69
 - brush painting 80–82
 - chemical bath deposition 78–79
 - inkjet printing 75–76
 - screen printing 76–78
 - slot-die coating 69–72
 - soft-cover deposition 79–80
 - spin coating 67–68
 - spray coating 73–75
- solution-processable methods 269
- solvent annealing (SA) 174–179
- solvent engineering 72, 147–149, 169, 174–177
- solvent evaporation control crystallization (SECC) method 14, 175, 176
- solvothermal synthesis 146
- space charge region of diode 3
- spacer layers 90, 91, 105, 107, 108, 111, 113–120, 122–128, 131, 143
- spatially resolved steady-state photo-physical methods 33–42
- spectral response (SR) 52–54, 57, 58, 179, 181
- spin coating 7, 48, 65, 67–69, 73, 78, 82, 91, 93, 96, 118, 119, 121, 145, 156, 169, 172, 175, 191, 246–248
- Spiro-OMeTAD 15, 75, 212, 213, 225, 240, 261, 262
- spray-coated compact TiO₂ layers, AFM images of 33
- spray coating 67, 73–75, 82, 246
- spray pyrolysis 246, 247, 249
- spray-pyrolysis deposition 93
 - of compact TiO₂ layer 94
- standard vs. sheet resistance measurement 23

t

- tapping mode 32, 33
- thermal stability, of halide perovskites 216–217
- three dimensional (3D) halide perovskites 137–142
- 3-dimensional (3D) methylammonium lead iodide (MAPbI₃) perovskite 11
- time-resolved photoluminescence (TRPL) 46
 - pulsed (transient) excitation 46
 - sample preparation 49–50
 - spatially resolved measurements 50
 - steady-state excitation 46–49
- time-resolved pump-probe spectroscopy 45
- TiO₂/Al₂O₃/NiO/C based FP-MPSCs 127
- TiO₂ screen-print paste, powder-based preparation of 98
- TiO₂/ZrO₂/C triple mesoscopic layer 14, 195
- TiO₂/ZrO₂/NiO/carbon based FP-MPSCs 128, 129
- transient absorption spectroscopy (TAS) 45–46
 - of MAPbI₃ 157
- transient optoelectronic methods 42–50
- transient photocurrent (TPC) 43–44
- transient photovoltage (TPV) 43–44
- triple-mesoscopic FP-MPSCs 108
- 2D PTAMAPbI₄ perovskite 156
- 2D/3D (5-AVA)₂PbI₄ layer 184, 185
- two dimensional (2D) halide perovskites 142–144

u

- ultrasonic spray coating 74
- ultrasound-assisted synthesis, of perovskite material 147

- ultraviolet-to-near-infrared range (UV-NIR) spectroscopy 25
- UV-vis absorption spectrum of MAPbI₃ 26
- UV-vis-NIR spectroscopy 25–26

v

- vapor-assisted solution process (VASP) 145
- V_{oc} vs. light intensity measurement 54–88

w

- width of the dead area (W_d) 251
- Wuhan Cells 13

x

- X-ray diffraction (XRD) technique 25, 111–113, 120, 125, 126, 176, 189
- X-site anion 180–183

z

- ZnO-single crystal electrodes 7
- Zn₂SnO₄ anode 96
- ZrO₂ insulating mesoscopic layers, in FP-MPSCs 106
 - vs. Al₂O₃ layers 108–110
 - dark current 114, 115
 - impedance spectra 116
 - nanoparticle size and layer thickness effect 111, 113
 - Nyquist plot and Bode plot 116
 - photovoltaic performance 114
 - SEM images of 109
 - thickness effect 110
- ZrO₂ nanoparticles 108, 111, 113, 184
- ZrO₂ slurry 107, 108

