

Index

a

acousto optic Q-switching 275
 active mode-locking 275
 adsorption-desorption
 kinetics 76, 81–83
 Ag₅Au₅ alloy NPs-functionalized ZnO:Ag
 columnar 33
 Ag film coated SiNWs, FDTD simulated E
 field intensity of 193, 194
 Ag nanoparticles-based SAs 15, 249, 287
 Ag-NWs
 for solar cells 148–149
 Ag₂S-sensitized ZnO/SnO₂
 nanowires 112
 aligned NFs heterostructures, on chip
 fabrication of 89
 alizarin red S (ARS)
 photodegradation 111
 ammonia sensing characteristics, of
 ZnO-NW/RGO composites 63–65
 antimonene 280, 291–293
 Au-Ag alloy film/Si micropillars
 hybrids 195
 Au capped SiNPLs 192
 Au/Fe₂O₃/ZnO NWs sensor 36
 Au-loaded hybrid ZnO/SnO₂core-shell
 NRs sensors 35
 Au-nanorod surface plasmons 14
 AuNPs conjugated Si nanorod
 arrays 192

AuNPs functionalized Si nanorod arrays,
 FDTD simulated plasmonic hot
 spot distributions of 193
 Au NPs-functionalized ZnO NWs 28, 36
 Au–SnO₂ NFs 12, 13
 avalanche photodiode 314–318

b

band bending at heterojunctions 82
 band diagram 219–220
 biaxial SnO/ZnO hybrid nanowires 105
 Bi₂Se₃ 279, 283, 292, 295
 bismuthene 280, 293–296
 bismuth selenide (Bi₂Se₃) 283, 292, 295
 BN/GO-based PD device 321–322
 BN/GO composite layer planar structure,
 I-V characterization of 325, 326
 boron carbide nitride (B-C-N)
 nanotubes 4, 5
 Bosch process 188
 bottom-up approach 2–7, 277
 bottom-up technique 165, 334
 branching growth (BG) nanowires 136

c

carbon nanotube (CNT) 4
 arrays 2
 unzipping 59
 carbon nanotubes/SnO₂
 heterostructures 111
 catalyst patterning methods 139

- CdS/Cu₂S core-shell nanowire solar cells 16
 CdSe/ZnO solar cells 147
 CdS nanowires 141–142
 CdS NWs
 characterization 144
 chalcogenides 7, 164, 173, 175, 279, 281, 330
 heterostructured nanorods, properties of 175
 chemical enhancement 190
 chemical sensitization 30, 34, 44, 86, 99, 107
 chemical vapor deposition (CVD)
 method 60, 138, 167
 1D ZnO nanostructures
 fabrication 208
 ZnO NWs fabrication 168
 technique 277
 chemiresistive gas sensors 79
 chemisorption 39, 81–83, 85
 chemoresistive gas sensors 107, 110
 CNTs-based SA, broadband
 operation of 287
 CNTs/polymer composites
 fabrication 39
 CNTs@Sn₃O₄ hybrid nanostructures 105
 Co₃O₄-ZnSnO₃ composite arrays, sensor
 response of 262
 co-axial electrospinning 80–81, 87, 89
 complex PPy-coated SnO₂ tube-in-tube structure 110
 conducting polymer/1D metal oxide
 nanocomposites, for gas sensors 29, 36–38
 conducting polymers 36, 37, 40, 76, 77, 79, 83, 87, 91, 110
 core-shell α -Fe₂O₃@NiO hollow
 nanofiber sensors, formaldehyde sensitivity of 28
 core-shell SnO₂-coated ZnO
 nanowires 112
 cross-stacked Pt coated WO₃ NRs
 sensor 32
 cryogenic plasma etching 188
 CsPbBr₃ NCs-based LEDs 17
 CsPbX₃/ZnS QDs 14
 Cu@Cu-Ni NWs 149
 Cu nanoparticles-based SAs 287
 Cu-NWs
 for solar cell 149
 Cu₂O nanowires/rGO based hybrid, for
 NO₂ detection 65–66
 current-voltage characteristics, of
 Gd-doped ZnO NTs/p-GaN
 heterojunction 211
- d**
- detection performance, of PDs 327
 direct current (DC) sputtering 194, 247, 320
 photodetector fabrication 323
 dislocation-mediated growth
 method 139
 dissolution-precipitation process 99
 dopants 128, 131, 139, 167
 doping agents 131
 drop-casting process
 photodetector fabrication
 method 321
 dye-sensitized solar cells (DSSC), SnO₂
 material application in 114
- e**
- e-beam irradiation 85
 electric sensitization 30, 44
 electrochemical method 280
 graphene synthesis 58
 electroless etching technique 140
 electron beam (E-beam) evaporation
 photodetector fabrication 322–323
 electron transfer theory
 band diagram 219–220
 extinction estimation 220–221
 electro-optic modulator 275
 electrospinning 8, 30, 32, 34–35, 37, 71, 77, 79–81, 89, 91, 100–101, 244, 246
 single nanofiber-based gas sensors 87
 electrospun In₂O₃ nanowires 236
 E-noses 87–89
 evanescent field-type SA 291

exhaust gas safety monitoring, in
 automobiles 8–10
 extrinsic semiconductor 131

f

α -Fe₂O₃ NRs/TiO₂ nanofiber sensors 35
 Fermi level 36, 63, 81, 99, 107–108, 131,
 195, 219
 fiber lasers
 optical modulation in
 mode-locking operation 275–276
 Q-switching operation 274–275
 Fiber Solar Cells (FSCs) 98
 figure of merits, of
 photodetector 174–175
 flexible electronic devices 11, 98
 flexible organic solar cells
 (FOSCs) 148–149
 flexible room-temperature NH₃
 sensors 110
 fluorophore-SiNW hybrid FETs 197

g

GaAs NWs/polymer HSCs 135
 gas sensing
 heterostructures and heterojunctions
 effect in 108–110
 performance of 1D tin oxide-based
 hybrid nanostructures 106–108
 gas sensors 27
 based on CNTs/polymer
 nanocomposites 41
 conducting polymer/1D metal oxide
 nanocomposites for 36–38
 configurations of 79–80
 exhaust gas safety monitoring, in
 automobiles 8–10
 for environmental monitoring 11–12
 feature of 32
 health monitoring 10–11
 in food manufacturing and packing
 industries 10
 noble metal-functionalized 1D metal
 oxide semiconductors for 29–34
 operating temperature of 75

Gd-doped ZnO NTs/p-GaN LED
 device 208, 211
 germanium sulphide (GeS) 281–282
 GNPs-TiO₂ NFs 8
 graphene 169, 173, 291
 for gas sensing applications 57
 synthesis
 bottom-up approach 58
 carbon nanotubes unzipping 59
 chemical vapor deposition 60
 electrochemical method 58
 epitaxial growth on SiC 59–60
 exfoliation of graphite oxide 59
 mechanical exfoliation 58
 sonication 58–59
 top-down approach 58
 graphene-based gas sensors 57
 graphene based hybrid 1D ZnO/
 GaN LED 211
 graphene-decorated ZnO nanowires,
 sensing property of 237–238
 graphene incorporated n-ZnO NWs/p-
 GaN vertical heterojunctions, EL
 curve of 212–213
 graphene/metal oxide nanowires
 hybrid-based sensors 60–65
 for NO₂ detection 65–67
 graphene oxide synthesis 58–60
 graphene/reduced graphene oxide-based
 composites 237–243
 graphite oxide exfoliation 59

h

H₂S detection, using SnO₂ quantum wire/
 rGO based hybrids 67
 H₂S gas sensing properties, of
 CuO-functionalized ZnO
 nanofibers 35
 haze factors 148
 heterostructure based organic-inorganic
 hybrid NFs 77–79
 heterostructure based solar cells 176
 hierarchical 2D/2D nitrogen-doped
 Sn₃O₄/g-C₃N₄
 nanostructures 104

hierarchical SnO₂@rGO nanostructures 103

high-performance gas sensors 76–77, 235–236, 264

 challenges 262

hollow aluminium-doped zinc oxide (AZO) core shell NFs 83

humidity sensing performance, of WS₂-decorated ZnO nanorods 250

Hummer's method 59, 62, 65, 67, 71

hybrid Au/SnO/Ag nanostructured films 106

hybrid conducting polymer/carbon nanotube-based gas sensors 39–43

hybrid CuO NPs-decorated porous ZnO NRs 35

hybrid nanomaterials 185

hybrid nanostructures, defined 1

hybrid noble metal NPs-decorated 1D metal oxide nanostructure synthesis 30

hybrid Sn₃O₄/carbon-based nanostructures 104

hybrid SnO/ZnO nanowires 105

hybrid solar cells (HSCs) 133–135, 138

 based on inorganic semiconductor nanowires 135

hydrogen screening 7

hydrogen titanate nanowires 140

hydrothermal method 1D ZnO nanostructures synthesis 165–167

 for 1D ZnO nanorods synthesis 207

hydrothermal process 35, 114, 136, 140, 218, 221, 252, 255–256, 258

 1D ZnO nanorod 136

i

intrinsic semiconductor 130–131

ionosorption model 81

ITO/Ag-NW/ITO flexible multilayer electrode 148

l

leaky mode resonances (LMRs) 14

lengthwise growth (LG) nanowires 136

light emitting devices/diode (LEDs) 16

 GaN based hybrid 1D nanostructure for 209–212

 ZnO based hybrid 1D nanostructure for 209–212

lithography 2–3, 139, 186, 188–190, 192, 209

localized surface plasmon at Au/air interface 191

m

MB photodegradation 111

mechanical exfoliation

 graphene synthesis 58

metal assisted chemical etching (MACE), 187, 189, 192, 197

 Si nanowire fabrication 189

metal monochalcogenides (MMs) 281–282

metal organic chemical vapor deposition (MOCVD), 206–209

 1D ZnO nanostructures fabrication 209

metal oxide-based gas sensors 236

metal oxide/metal oxide heterojunctions-based gas sensors 34–36

methyl orange (MO)

 photodegradation 111

metronidazole (MN)

 photodegradation 111

micro-LEDs 16

mixed-dimensional van der Waals heterojunction photodetector 332

MnPSe₃ photodetector, Ids-Vds characteristics of 331–332

mode-locked fiber lasers

 based on 1D materials 289

 based on 2D materials 295

mode-locking operation 275–276, 289–291, 293–296

modified Hummer's method 62, 65, 67, 238, 240, 242–243

- molecular beam epitaxy (MBE)
 - process 2–5, 165
- molecular self-assembly method (MSA) 3–4
- MoO₃ nanoribbons/RGO composite,
 - hydrogen gas sensing performance of 240
- MoS₂-decorated Si nanowire, NO₂ sensing performance of 249
- MoS₂-decorated ZnO nanorods, NO₂ sensing performance of 244
- MoS₂ nano layers on SiO₂/Si substrate CVD technique 167–168
- MoS₂ nanosheets
 - CVD technique 167
 - decorated SnO₂ nanofibers, SO₂ sensing performance of 244
 - decorated ZnO nanowires array sensor 247–248
 - or SnO₂ nanotubes, gas sensing performance of 246
- multi-centre flat fibre shaped SPR device 218
- MWCNTs-doped PANI (MP)
 - nanopowders 42
- MXene
 - characteristics 284
 - general configuration of 283
 - properties 284
 - wet chemical etching process 283
 - with functional group 283
 - with nonfunctional group 283
- n**
- NaNbO₃ nanowires 145
 - synthesis 140
- nano-coaxial Co₃O₄/TiO₂ heterojunction 35
- nano-e-nose 87–89
 - fabrication 81
- nanofibers
 - adsorption-desorption kinetics 83
 - interface dependent properties 82–83
 - morphology controlled properties 83
 - physicochemical properties of 81–82
 - surface dependent properties 82
- nanofibers-based gas sensors 80
- nanofibers based nanohybrids, for gas sensing application 77
 - heterostructure based organic-inorganic hybrid NFs 77–79
- inorganic nanofibers 77
- organic nanofibers 77
- nanofibers-based sensor performance enhancement 85
- noble metal sensitisers 85–86
- UV light/high energy beam irradiation 85
- nanofiber synthesis 80
 - coaxial electrospinning 80–81
 - electrospinning 80–81
- nanohybrids-based devices 172
- nanomaterials
 - advantages 27
 - hybrid 185
- nanophotonic systems 115
- nanorods 6
 - 1D ZnO nanorod 136
 - TiO₂ nanorods 221–222
- nano-Schottky type barrier junctions 33
- nanosphere assembly patterning technique 139
- nanostructured materials 146, 163–172
 - 1D/2D, synthesis of 164
- nanostructured organic-inorganic interface, advantages of 133
- nanotechnology 1, 97–98, 205, 213, 330
- nanotubes 4
 - boron carbide nitride 5
 - carbon 2, 4
- nanowires 5
 - characterization 142–144
 - III-V nanowires 149
 - solar cells 128
- nanowire synthesis
 - catalyst patterning methods 139
 - CdS nanowires 141–142
 - chemical vapour deposition 138–139
 - NaNbO₃ NWS 140

- nanowire synthesis (*Continued*)
- Si NWs 140
 - TiO₂ nanowires 140–141
 - vapor-liquid-solid process 138
 - ZnO NWs 139–140
 - ZnS nanowire 141
- Nb₂C MXene 284
- NFs-based gas sensors 76
- on chip fabrication and direct writing of 81
- NH₃ detection, ZnO nanowires-reduced graphene oxide based hybrids for 61
- NH₃ sensing properties, of PANI-CeO₂ nanocomposite sensors 37
- NiCO₂O₄-decorated MoO₃ nanorods 259, 261
- NiMoO₄-decorated Co₃O₄ nanowire array 262
- NiO-decorated ZnO nanorods, acetone sensing performance of 255
- NiO nanosheets decorated WO₃ nanorods 256–262
- NiO/ZnO composite, sensing performance of 254
- N-methyl-2-pyrrolidone (NMP) 59, 280
- NO₂ detection, using metal oxide nanowires-reduced graphene oxide hybrids 65–67
- NO₂ sensing performance
- of MoS₂-decorated Si nanowire 249
 - of MoS₂-decorated ZnO nanorods 244
 - of MoS₂ nanosheets/SnO₂ nanotubes 246–247
 - of ZnO nanorods decorated NiO nanosheets 256
 - of SnO₂/RGO NFs 85
- noble metals
- doping with 107
 - functionalized 1D metal oxide semiconductors, for gas sensors 29–34
 - NPs-decorated 1D CTNs@conducting polymer nanohybrids 43
 - sensitisers 85–86
- NO detection, ZnO nanowires on laser scribed graphene-based sensor for 69
- NO gas sensing characteristics, of graphene-based sensors 61
- noise equivalent power (NEP), of photodetector 329
- nonlinear photonics 273, 296–297
- n-SnO₂/p-CNT composites 109
- n-SnO₂-p-Co₃O₄ composite nanofiber sensors 35
- N-type intrinsic semiconductors 131
- n-ZnO NW/p-MoS₂ nanosheet heterostructure 176
- O**
- on chip fabrication
- of aligned NFs heterostructures 89
 - of NFs based gas sensors 81
- one dimensional chalcogenide material for optoelectronic applications 175
- 1D GaTe nanowire, photocurrent responses of 327
- 1D hybrid nanomaterials 18, 28
- 1D hybrid nanostructures 2
- analyte gas molecules and detection limit 4
 - bottom up synthesis approach 3–4
 - gas sensing applications 7–8
 - nanorods 6–7
 - nanotubes 4–5
 - nanowires 5
 - optoelectronics 12–14
 - synthesis methods 4
 - top-down synthesis strategy 2–3
 - types 4
- 1D material
- defined 276
 - nanorods 277
 - nanotubes 276
 - nanowires 277
 - properties of 278
 - synthesis methods 277–278
- 1D materials-based photodetectors 330

- 1D nanomaterials 1, 8, 11, 101, 212–213, 237, 256–262, 278
- 1D nanostructured sensors 28
- 1D nanostructures 97, 205
 advantages 98
 benefits 27
- 1D n-SnO₂/p-NiO core-shell nanowires 108
- 1D semiconductor nanostructures 1, 3, 173, 185, 313
- 1D Si nanostructure hybrids
 photodetector applications 195–197
 SERS applications 190–195
- 1D Si nanostructures 185
 fabrication methods 186
 dry etching method 188
 metal assisted chemical etching 189
 vapor-liquid-solid growth 187–188
- 1D SnO₂/NiO core-shell nanowires 8
- 1D tin oxide-based composite photocatalysts 110–113
- 1D tin-oxide/TiO₂-based photocatalysts 111
- 1D/2D hybrid nanostructures-based photodetectors 332–333
- 1D ZC based UV PD, I-V characteristics of 312–313
- 1D zinc oxide crystals 312
- 1D ZnO based photodetectors, limitation of 163
- 1D ZnO nanostructures (nanowires/nanorods)
 hydrothermal method 165–167
- optical gas sensors 80
- optical modulation in fiber lasers 1D and 2D material configuration 285–286
 using 1D material-based saturable absorbers
 mode-locking operation 289–291
 Q-switching operation 286–289
 using 2D material-based saturable absorbers
 mode-locking operation 293–295
 Q-switching operation 291–292
- organic LED (OLED) 18, 149
- organic 1D nanostructures 2
- organic photovoltaics (OPVs) 134–135, 147
- organic-SiNW hybrid photodetectors 197
- organic solar cells 134, 147
- oxygen vacancy model 81
- P**
- PANI-CeO₂ nanocomposite sensors, NH₃ sensing properties of 37
- PANI/MWCNTs-based sensor 42
- PANI/ZnO nanograss 37
- paper strip@CNT-N1/1@PPy nanocomposite 42
- passive mode-locking 275
- passive Q-switching 274, 275
- PbS QD/ZnO nanowire photovoltaics 14
- Pd-CPPy-CNTs nanohybrids 43
- Pd-loaded SnO₂ nanofiber sensors 32
- Pd NPs-functionalized SnO₂ NWs sensor 30, 32
- Pd/PdO nanoparticles, catalytic effects of 107
- PdPt-functionalized α -Fe₂O₃ hollow NRs 33
- Pd-SnO₂ nanowire sensors 108
- perovskite nanocrystals 17
- photoconductive mode 195
- photodegradation, of Rhodamine B (RB) 110
- photodetector (PD) 14, 163, 311
 applications of 319–320
 based on low-dimensional semiconductors 312
 device geometries 195
 electrical characterizations 324–325
 external quantum efficiency 174
 fabrication methods 320–324
 direct current (DC) sputtering 323–324
 drop-casting process 321–322

- photodetector (PD) (*Continued*)
 electron beam (E-beam)
 evaporation 322–323
 spin coating 324
 thermal oxidation 322
 vapor phase transport
 method 320–321
 figure of merits of 174–175
 1D Si nanostructure hybrids
 for 195–197
 performance of 195
 photocurrent behavior 325
 principle of 314–315
 response time 173–174
 responsivity and external quantum
 efficiency 326–329
 responsivity of 174
 temporal response of 329
 types of 315–319
 using antimony selenide (Sb_2Se_3)
 nanosheets 313
 ZnO nanowire/graphene
 based 173–174
 photodiodes 315, 319
 avalanche 317–318
 PIN photodiode 316–317
 photoelectric effect 314, 315
 photo(electro)catalytic water splitting,
 with 1D tin oxide-based
 materials 110, 113
 photoluminescence spectroscopy 86
 photonic crystal fibers (PCFs) 285, 291
 phototransistor 195, 314, 315, 318–319
 photovoltaic mode of operation 176
 photovoltaic (PV) system 2, 12, 127, 131
 pH value
 ZnO nanowire growth 166
 physisorption 38–40, 83, 110
 PIN photodiode 314–317
 plasmonic hot spots 193
 P–N junction type solar cell 128
 p-n photodiodes 195
 poly (styrene-butadiene-styrene)/carbon
 nanotubes (SBS/CNT) hybrid fiber
 detector 11
 polystyrene nanosphere
 lithography 189, 190
 polythiophene/SWCNTs nanocomposite
 (PTh/SWCNT) for NH_3
 detection 43
 porous $\text{Au@Cr}_2\text{O}_3\text{-In}_2\text{O}_3$ NR sensor 36
 porous silicon/metal nanoparticle based
 hybrids 191
 porphyrin-SiNWs hybrids 197
 power conversion efficiency (PCE) 127,
 128, 135, 136, 148, 149
 PPy-coated 1D SnO_2 complex tubular
 nanostructures 37–38
 PPy-coated SnO_2 tube-in-tube
 nanostructures-based sensors 37
 PPy-MWCNT nanocomposites
 sensor 42
 PPy/SCCNTs nanocomposite-based
 sensors 40
 printed flexible photodetector based on
 SWCNT 331
 pristine 1D tin oxide
 nanostructures 106–107
 Pt-decorated SnO_2 -loaded SiC
 nanosheets 258–260
 Pt-functionalized WO_3 NRs 34
 Pt/ NaNbO_3 nanowires 144–145
 Pt/Pd bimetallic core-shell NPs-
 functionalized ZnO NRs 33
 Pt/PtO nanoparticles, catalytic
 effects of 107
 Pt- SnO_2 nanowire sensors 108
 P-type semiconductors 131, 209
 pulsed laser deposition (PLD)
 technique 208
- q**
- Q-factor 274–275
 Q-switched fiber lasers
 based on 1D materials 287
 based on 2D materials 294
 Q-switching 274–275, 286–289,
 291–293
 quantum confinement effects 14, 97–98,
 186, 206, 279–280

r

- Ramgir criterion 85, 91
- reactive ion etching (RIE) 139, 188
- recombination phenomenon 218
- reduced graphene oxide (rGO) 59, 61, 169
 - based e-fibers 90
 - preparation, tour method 169–170
- resistive gas sensors based on 1D nanomaterials 8
- RGO-decorated In₂O₃ nanofibers, NO₂ sensing performance of 242
- RGO-decorated TiO₂ nanotubes, hydrogen sensing performance of 242–243
- RGO-decorated ZnO nanofibers, hydrogen sensing performance of 240
- RGO-decorated ZnO nanowires, NH₃ sensing performance of 243
- RGO-decorated ZnO on AlGaN/GaN layer surface 238
- RGO-loaded CuO nanofibers, sensor response of 263
- rGO/SnO₂ nanocomposites 109
- Rhodamine B photodegradation 110
- roll-to-roll (R2R) solar cell polymer module 147
- room-temperature CO gas detection 8
- room temperature EL curve, of Gd-doped ZnO NTs/p-GaN heterojunctions 211
- room temperature gas sensors, in e-nose 87

s

- saturable absorber (SA) material 97, 278, 280, 286
- Sb-doped SnO₂ (ATO) nanowires arrays 113
- Schottky metal-semiconductor-metal (MSM) photodetector 323
- Schottky photodiodes 195
- self-assembled MoS₂/Co₃O₄ layers, NH₃ sensing performance of 243, 246, 247
- self-powered generated gas sensors 80
- semiconductor
 - axial NW heterostructures 175
 - classification of 130–131
 - devices 130
 - extrinsic 131
 - intrinsic 130–131
 - nanomaterial morphology effects 134–136
 - nanomaterials as 133–134
 - nanowires
 - morphology, advantages of 137–138
 - synthesis 138–140
- sensor response, of ZnO nanorods 236
- SERS substrate requirements 190–194
- Shockley-Queisser limit 16, 128
- Si-based photodetectors 312
- side-by-side conjugated SnO₂/TiO₂ nanofibers 110, 111
- Si double nanocone array
 - fabrication 194
- silicon nanocrystals 186
- silicon nanohole arrays 186
- silicon nano/micropyramids 186
- silicon nanowires (Si-NWs) 128, 187
 - preparation 140
 - for solar cells 145–146
- silver nanocrystal functionalized multiwalled carbon nanotubes 12
- Si micropyramid based SERS hybrid sensors 194, 195
- Si nanopillar fabrication 193
- single carbon nanotubes (SWCNT)/polypyrrole (PPy) core-shell sensor 28
- single nanofiber-based gas sensors 87
- single SiNW based SERS sensor 192
- SiNPLs/AgNWs heterojunction, photodetector properties of 196

- SiNPLs SERS sensors, FDTD simulated
 - plasmonic hot spot
 - distributions of 193
- Si pyramids based nanocermet 194
- smart food packaging 10
- SMOx gas sensor response, metallic
 - additives effect on 107
- Sn₃O₄-based hybrid
 - nanostructures 104–105
- SnO₂-based anodes 114
- SnO-based hybrid
 - nanostructures 105–106
- SnO₂-based hybrid
 - nanostructures 103–104
- SnO₂-based materials, sintering of 114, 115, 259
- SnO₂/BiOBr films 104
- SnO₂/CH₃NH₃PbI₃ photodetector 104
- SnO₂@C nanoparticles 104
- SnO₂-coated TiO₂ nanorods 111, 113
- SnO₂-coated ZnO nanorods 112
- SnO₂/g-C₃N₄ nanocomposites 262
- SnO₂-GO sensor 10
- SnO₂-In₂O₃ heterojunction 100
- SnO_{2-x}/In₂O_{3-y} nanowires 113
- SnO material synthesis
 - chemical vapor deposition 101–102
 - electrospinning technique 100–101
 - hydrothermal method 99–100
 - reactive sputtering method 102–103
- SnO₂ material synthesis
 - chemical vapor deposition 101–102
 - electrospinning technique 100–101
 - hydrothermal method 99–100
 - reactive sputtering method 102–103
- Sn₃O₄ material synthesis
 - chemical vapor deposition 101–102
 - electrospinning technique 100–101
 - hydrothermal method 99–100
 - reactive sputtering method 102–103
- SnO/nanographite microspheres
 - preparation 106
- SnO₂ nanorods, for LIB anode 114
- SnO₂ nanosheet-decorated SiC
 - nanofibers 258
- SnO₂ nanowires
 - dimensions 115
 - morphology dimensions and aspect ratio of 100
 - properties 115
 - rGO based hybrid, for NO₂
 - detection 66–67
- SnO₂/NiO-X CSNWs 8–9
- Sn₃O₄/PDINH hybrid
 - nanostructures 104
- SnO₂ quantum wire/GO nanosheets 10
- SnO₂ quantum wire/rGO based hybrid, for H₂S detection 67
- SnO/rGO nanocomposites 106
- SnO₂/RGO nanocomposite-based gas sensors 68
- SnO₂/RGO NFs, NO₂ sensing
 - properties of 85
- SnO₂/SrO nanowires 112
- SnO₂ varistor composition 115
- SnO₂/ZnO heterojunction 35, 258
- SnO₂/ZnO hierarchical nanostructured sensors 34
- solar array 132
- solar cells 16, 127–128
 - Ag-NWs for 148–149
 - Cu-NWs for 149
 - heterostructure based 176
 - nanowire application 130
 - NW-based, benefits of 138
 - Si NWs for 145
 - ZnO nanowires for 146
- solar photovoltaic systems 131–133
- sol-gel method 3–4
- sonication 172, 250
 - graphene synthesis 58–59
- SO₂ sensing performance, of MoS₂
 - nanosheets-decorated SnO₂ nanofibers 244
- spin coating 69, 148, 170, 176, 207, 320, 324
- 4-S selection criteria 85
- stretchable electronic fibers 90
- stretchable electronics 90

- successive ionic layer adsorption and reaction method (SILAR) 65, 144
 surface chemistry engineering 107
 surface enhanced Raman spectroscopy (SERS) 185–197
 enhancement mechanisms 190
 SERS applications 190–195
 surface plasmons 6, 12, 15, 148, 190–191, 196–197, 210, 217, 288
 synergistic effect 28–29, 33, 35, 38, 40, 45, 61, 79, 82, 85, 103, 109
- t**
- Te/ReS₂ heterojunction
 photodetector 332
 thermal oxidation 7, 280, 320
 photodetector fabrication method 322
 3D hierarchical Sn₃O₄-CNTs
 nanostructures 104
 tin selenide (SnS), gas sensor
 applications 281
 TiO₂-coated SnO₂ 1D
 heterostructures 111
 TiO₂ nanowires 104, 136, 142
 synthesis 140–141
 TiO₂NR/AuNP heterostructure
 amperometric current-time
 analysis 228–229
 band diagram of 219–220
 device configuration 219
 electrical characteristics 217
 electron hole pair formation 217
 electron transfer mechanism
 226–227
 electron transfer of 219
 morphology 222–224
 optical characterization 225–226
 quantum mechanical analysis 227
 TiO₂ nanorods
 amperometric measurements 222
 structural, morphological, elemental
 and optical
 characterization of 222
 synthesis 221
 X-ray diffraction pattern 224–225
- TiO₂/PANI nanocomposites, gas sensing
 properties of 28
 TiO₂@SnO₂ core-shell nanowires 111
 top-down synthesis method 1–3, 18, 164, 277
 transition metal dichalcogenides (TMDs) 173, 281–282, 292, 293, 330
 transmission-type SA 291
 two dimensional (2-D) nanostructures 205
 two-dimensional SnS₂/SnO₂
 nanoflakes 103
 2D chalcogenide materials 281–282
 2D GaTe nanosheet, photocurrent
 responses of 327
 2-dimensional materials-based
 photodetectors 330–333
 2D materials 279
 chalcogenides 281–282
 monoelements 279–280
 MXenes 283–285
 topological insulators 282–283
 2-D materials with 1-D semiconducting
 nanostructures 237
 graphene/reduced graphene oxide-
 based composites 237–243
 MoS₂-based composites 243–249
 NiO-based composites 254–256
 WS₂ based composites 249–252
 ZnO-based composite 252–254
 2D monoelements 279–280, 291–292, 294
 2D topological insulators 282–283
 2D Xenes materials 280
 type II ZnO/ZnSe core-shell
 nanostructure anti-reflection
 materials 16
- u**
- ultrasonic reaction method 106
 undoped and doped (Ni and Pd) SnO₂/
 PANI/P3HB biodegradable
 nanocomposite fibers 110
 UV light activated rGO/hollow SnO₂
 nanofibers (NFs) sensor, for NO₂
 and SO₂ gas detection 69

- UV light emitting diodes (UV LEDs) 206
 - 1D ZnO nanostructure for 206
 - practical applications 209
- UV light/high energy beam irradiation 85
- V**
- V₂O₅/SnO₂ nanowires 112
- Van der Waals hybrid structures 164
- vapor-liquid-solid (VLS) process 138
 - growth, Si NW fabrication 187–188
- vapor phase transport method
 - photodetector fabrication
 - method 320–321
- vapor-solid-solid (VSS) process
 - 139, 186
- volatile organic compounds (VOCs) 7, 33, 36, 57, 77, 80, 106
- W**
- wearable electronics, NFs based 90
- wet ball milling method 2–3
- wire on pillar 3D architecture 193
- WS₂-decorated ZnO nanorods, humidity sensing performance of 250
- X**
- X-ray lithography (XRL) 3
- Z**
- zero dimensional (0-D) nanostructures 205
- ZnO-based DSSC 136
- ZnO/CdSe/CuSCN (eta)-solar cells 146
- ZnO-decorated Zn₂SnO₄ nanowires, sensor response of 252–254
- ZnO/graphene heterostructure
 - advantage of 176
- ZnO/MoS₂ hybrid structure
 - fabrication 171–172
- ZnO nanobelt array 7
- ZnO nanorod 6
 - based LEDs device, in Ag-NPs/PMMA composite 210
 - with Sb-doped SnO₂ nanosheets 256, 258
- ZnO nanowires
 - characterization 142–143
 - graphene based H₂ sensor 67
 - graphene based
 - photodetector 173–174
 - on laser scribed graphene-based sensor, for NO detection 69
 - reduced graphene oxide based hybrids, for NH₃ detection 61–62
 - for solar cell 146–147
 - synthesis 139–141, 168
- ZnO NW/graphene foam based UV photon detector 174
- ZnO-NW/rGO composites-based sensor devices 63
- ZnO/rGO hybrid composites
 - synthesis 170–171
- ZnO-SnO₂ core-shell nanowires 108–109
- ZnO/ZnSe NW array synthesis 140
- ZnSe nanoribbon/Si p-n heterojunction system 15

