

Index

a

AC-TENG 97, 99, 100, 102, 103,
106–109
vs. and DC-TENG 106–109
active control 176, 190–193, 196, 197
active eye tracking (AET) system
245, 247
Ag nanoparticles (AgNPs) 242
air breakdown 126, 128
effect 49, 66, 80, 81, 83, 85
voltage 85, 266
air cleaning 282–287
alternating-current thin-film
electroluminescent (ACTFEL)
lamp 222
arc/spark discharge 46
atomic force microscopy (AFM) 25, 33,
81, 82, 114, 183
avalanche breakdown process 94
avalanche-type ionization 293

b

beneficial breakdown domain (BBD)
96
binary electrification layered (BEL)
TENGs 137, 138
biomedical sensing
joint movement 243–245
pulse 238–241
respiration 241–243
bipolar-CMOS-DMOS (BCD) 159
breakdown discharge effect 45, 49, 57,
65, 68–69, 74

breakdown discharge points 51–56, 71
breakdown effect 49, 51, 61, 66, 69, 72,
79–83, 85, 86, 96, 100
breakdown state 95, 96
breakdown voltage 45–48, 53–56, 65,
69, 71, 79–82, 99–101, 103, 212,
266

c

CFT mode TENG 14, 54–56, 69
charge-collecting electrode (CCE) 94,
96, 99, 100, 105–107
charge excitation mechanism
external 128–131
self-charge 130, 132–133
sliding mode TENG 133–135
charge injection methods 265–266
charge injection treatment 119
charge-shuttling-based triboelectric
nanogenerator (CS-TENG) 19,
48, 54, 65, 69, 79–83, 86, 216, 267,
268
charge-space accumulation mechanism
135–137
charge supplement channel (CSC) 267
complementary
metal–oxide–semiconductor
(CMOS) 159
contact electrification
DI water vs. insulator surfaces 115
DI water vs. SiO₂ 114
impact of material surface 36
liquid-solid interface 117

contact electrification (*contd.*)
 solid-liquid interface 116
 stress/strain 36–37
 temperature effect on 35–37
 contact electrification field-effect
 transistor (CE-FET) 175,
 181–184, 196
 contact-separation (CS) 3, 4, 26, 47, 49,
 67, 68, 71, 79, 88, 119, 145, 148,
 163, 176, 192, 195, 238, 248, 259,
 262, 264, 265, 269, 279, 290
 mode 26, 68
 continuous displacement current 118
 copper (Cu) electrode 135
 corona discharge state 95, 96
 corona polarization 119, 264
 Coulomb force 278, 281, 282
 cycle for maximum energy output
 (CMEO) 53, 56, 61, 63, 64, 69, 72,
 125, 126, 148, 149, 166, 167
 cycle of energy output (CEO) 63, 64,
 125, 148, 149
 cyclic charge 125

d

dark discharge 46
 DEDC-TENG 98, 99
 dielectric elastomer 217, 259, 260,
 268–272
 dielectric elastomer actuators (DEAs)
 217, 268
 dielectric materials 9, 14, 17, 18, 69, 72,
 79, 88, 93, 148, 273
 dielectric strength 48, 94
 dielectrophoresis (DEP) 285, 287
 direct-current TENG (DC-TENG)
 93–109
 AC-TENG *vs.* 106–109
 advanced structure design 102–103
 basic principle 94–95
via electrostatic breakdown 99–102
 for energy harvesting 103–105
 enhancing electrostatic breakdown
 99–102

improving triboelectrification
 97–99
 physical model 95–96
 for self-powered sensing 105–106
 discharge effect 45–58, 65, 68–69, 74,
 287, 292
 discharge-induced
 displacement-current-based
 fully-self-powered wireless sensing
 system 212–215
 distributed power supply 203, 204
 dry etching 262, 263, 279
 dual-capacitor enhancement system 88,
 89

e

EFR-based wireless TENG (EFR-TENG)
 209
 electric double-layer (EDL) 33–35, 196
 electric field resonance (EFR) 209
 electric potential difference (EPD) 103,
 176, 177
 electrification effect 88, 117, 145, 179,
 261
 electromagnetic generator (EMG) 72,
 117, 146, 165, 212
 electromagnetic interference (EMI) 109,
 215, 219, 225, 228
 electron avalanche 45, 46, 57, 81, 212
 electronic excitation 287–294
 electronic switch convertor
 integrated circuit 159–160
 MOSFET 161–163
 SCR and triode 163–165
 electron-withdrawing (EW) 36
 electrophoresis (EP) 285
 electrostatic adsorption 282–287
 electrostatic breakdown 83, 93, 94, 96,
 97, 99–103, 106–109
 enhancing 99–102
 electrostatic damage (ESD) 37
 electrostatic discharge 93, 287, 291
 electrostatic force optical switch (EFOS)
 215, 217

electrostatic induction 1, 69, 88,
106–109, 125, 130, 136, 175, 177,
179, 205, 206, 213, 237, 239, 245,
247, 259, 261, 277
electrostatic manipulator 260, 278–282,
294
electrostatic screening effect 117,
119
electrostatic switch 154–157
 spark switch 154–156
EM radiation generation 207
EMS 165
energy harvesting method 103, 105,
118, 145
energy management scheme
 capacitive conversion 153
 electronic discharge switch 155
 parallel switching 152–154
energy threshold 113
equivalent circuit model 2–19, 95–97,
147–149
excitatory postsynaptic current (EPSC)
194, 196
external charge excitation 128–134,
140
eye movement 238, 245–247, 254

f

ferroelectric materials 79, 80, 93, 273,
275
figure of merits (FOMS) 61, 67–69, 125,
126
figure-of-merit, TENG
 applications 74
 breakdown discharge effect 68–69
 common standard 67–68
 effective maximized energy output
 62–67
 environmental & techno-economic
 analysis 72–74
 output energy density 70–72
 piezoelectric nanogenerator 69–70
finite element method (FEM) 9, 49, 63,
125, 179
finite element simulation 84, 261

flexible organic tribotronic transistor
 (FOTT) 184, 185, 189
flexible transparent tribotronic transistor
 (FTT) 184, 185
floating-gate tribotronic transistor (FGTT)
191–193
floating self-excited sliding TENG
 (FSS-TENG) 133–135
fluorinated ethylene propylene (FEP) film
19, 29, 30, 36, 84, 103, 116, 119,
126, 137, 156, 184, 186, 192, 193,
218, 227, 246, 248, 261, 264–266,
277, 281
fractal switched capacitor converter
 (FSCC) 153, 154, 157, 158
frictional electrode (FE) contacts 94
Full Wave Rectifier (FWR) circuit 148,
155, 162, 163, 293
fully-self-powered 108, 204–215, 221,
227

g

gas's intrinsic properties 99
gesture 238, 245, 248–251, 254, 259
glow discharge 46
graphene polylactic acid (gPLA) 209
grating electrodes 281

h

harmful breakdown domain (HBD) 96
helium irradiation/implantation 264
high atmosphere pressure 80–83
high-breakdown-limit gas environments
80–83
high vacuum environment 79–80, 89, 93
high-voltage applications 38, 260
high voltage (HV) generation 48
human-machine interface (HMI)
 eye movement 245–247
 gesture 248–250
 touch/tactile 251–254
 voice/auditory 247–249
humidity 46, 86–89, 100–101, 109, 120,
159, 170, 211, 228
hybrid energy generator 120

hybrid nanogenerator 212
 hydrophobic materials 88, 89, 100, 119
 hygrothermograph 103
 hysteretic dielectric polarization 93

i

induction electrode (IE) 107
 inductively coupled plasma (ICP) etching
 186, 190, 262, 269, 273
 information sensing 176, 186–190, 196,
 197
 inhalation-driven vertical flutter
 triboelectric nanogenerator
 (IVF-TENG) 243
 integrated circuit (IC) 93, 159–160, 186
 interfacial insulating liquid 139–140
 interfacial liquid lubrication 83–86
 Internet of Things (IoT) 1, 61, 94, 145,
 175, 176, 203, 237
 intrinsic-displacement-current induced
 self-powered wireless sensing
 system 208–209
 ion generation 207, 287–294
 ion guns 119, 126
 ion irradiation 116, 263, 264
 ionized-PTFE (I-PTFE) 264, 265

j

joint movement monitoring 243, 244
 joint movement triboelectric quantization
 sensor (jmTQS) 249

k

Kapton film 85, 177, 183, 239, 264, 269,
 279
 Kapton/Kapton pair 29
 Kelvin probe force microscopy (KPFM)
 33–35, 113
 Kirchhoff's law 147

l

life-cycle assessment (LCA) 62, 72–74
 liquid lubrication-promoted TENG
 (LP-TENG) 139, 140

liquid-solid contact electrification
 32–34, 118

m

mass spectrometry 38, 58, 225, 287, 290,
 291
 material-dependent charge transfer
 29–32
 material figure of merits (FOMM) 69,
 125, 126
 Maxwell-Ampere's law 57
 Maxwell's displacement current 1, 2,
 61, 125, 145
 mechanical exfoliation method 192
 mechanical switched converter
 travel switch
 parallel switch 152
 series switch 150–151
 switch capacitor convertor
 152–154
 MEMS processing technology 186
 metal/Kapton pairs 28, 29
 metal/PEEK pairs 29
 microelectromechanical systems
 (MEMS) 155, 176, 186, 198, 268,
 278, 282, 294
 micromotion sensor based on TENG
 (msTENG) 245, 247
 micromotors 272
 working principle 273
 microplasma source 291
 MOSFET 161, 179
 switch 162
 motion-driven electroluminescence
 (MDEL) device 223
 mutual inductance 210

n

nano electrospray ionization 290
 nanofiber membrane (NM) 242
 nanoscale triboelectric gated transistors
 (NTT) 182, 183
 nanowire arrays 262, 263, 269, 278,
 287
 negated AND (NAND)gate 193

non-attached electrode-dielectric
triboelectric sensor (NEDTS)
247

no-spacer triboelectric nanogenerator
(NS-TENG) 241

N-type MOSFET (NMOS) 178–181, 193

O

organic thin film transistor (OTFT) 184,
185, 195, 196

output energy density 59, 62, 63, 70–72,
74, 81, 82

P

parallel switch 152, 159, 160, 169

Parallel Synchronous switched
Harvesting on Inductor (P-SSHI)
circuit 162, 163

Paschen's law 46–48, 53–56, 65, 79, 80,
99, 100, 140, 212, 266

performance enhancement, TENGs
charge injection methods 265–266
charge supplement 266–268
materials selection 261–262
surface modification of materials
262–265
and vacuum protection 265–266

phenolphthalein droplet 281

photon generation
radio-frequency EM-wave 56–57
visible-light 57–58

piezoelectric ceramics 272–273

piezoelectric generators 117

piezoelectric nanogenerator 69–70,
294

polarization effect 275

polyacrylamide hydrogels 252

polydimethylsiloxane (PDMS) 71, 196,
224, 239, 247, 251

polymer network liquid crystal (PNLC)
218, 219

polymethyl methacrylate (PMMA)
81–83, 156, 176, 177, 189, 208,
222

polytetrafluoroethylene (PTFE) 36, 86,
93, 179, 195, 212, 254
layer 179

power generation 1, 2, 37, 58, 133, 145,
198, 275, 277

power management
integrated circuit 159–160
MOSFET switch 161–162
silicon-controlled rectifier 163–164
transformer converter 165–166

Power-Resistance (P-R) plot 62

print circuit board (PCB) 156, 161

programmable compound prism (PCP)
217

pulse, biomedical sensing 238–245

pulse wave velocity (PWV) 239

pumping switched TENG (PSW-TENG)
211

pyroelectric generator (PENG) 69, 70,
72, 120, 294

Q

quasi-permanent electric charge 94

quenched polarization (QP) method 116

R

radio-frequency EM-wave photon
generation 56–57

reactive ion etching (RIE) 116

resistor-inductor-capacitor (RLC) 211

respiration, biomedical sensing 241–243

Rotary Charge Pumping Triboelectric
Nanogenerator (RC-TENG) 133,
134

rotary freestanding sliding TENG
(RFS-TENG) 218, 219

S

Schottky diodes 27

self-charge excitation 130–135, 140

self-charge-pumping TENG (SCP-TENG)
128, 131

self-multiplying circuit (SVMC) 130, 132

self-powered all-optical wireless
ultrasonic sensor (SAWS) 225

- self-powered pulse sensor 240
- self-powered sensing 105–106, 109, 204, 205
- self-powered ultrasensitive pulse sensor (SUPS) 239
- self-powered visualized flexible pressure sensor (SP-VFPS) 224
- self-powered wireless sensing e-sticker (SWISE) 213, 214, 228
- semi-conducting carbon nanotubes (s-CNTs) 187
- series switch 150–151, 161
- Series Synchronous switched Harvesting on Inductor (S-SSHI) circuit 162, 163
- shape-adaptive triboelectric nanogenerator (SATENG) 244
- short-range self-powered wireless sensor network (SS-WSN) 211, 212
- signal-to-noise (SNR) ratio 215, 245
- silicon-controlled rectifier (SCR) 163–165
- silver nanowires 187, 224, 269
- sliding mode TENG 63, 83, 85, 88, 95, 133–135, 139, 245
- sliding-electrification-gated NMOS (SG NMOS) 179–181
- sliding-electrification-gated tribotronics logic (SGL) 181
- smart optical modulator (SOM) system 217, 218, 269–271
- solid-liquid charging process 139
- spark switch 154–156, 159
- stress/strain 34, 36–38, 241
- surface charge density (SCD) 280
- surface-charge engineering 88, 89
- sustainable energy supply 145
 - 5G technologies 145
- switch capacitor convertor 152–154
- t**
- tactile sensors 186, 187, 189, 193, 195, 251–253, 259
- techno-economic analysis (TEA) 62, 72–74
- ternary electrification layered (TEL) 137
- ternary tribo-layer architecture 137–139
- thermionic emission equation 27
- thermionic emission method 26–29
- 3D printing technology 275
- time-varying magnetic field-based fully-self-powered wireless sensing system 209–212
- toothpick electrospray 291
- touch sensors 251–254
- transformer converter 165–168
 - for EMS 165–167
- travel switch
 - parallel switch 152
 - power management strategy 151
 - series switch 150–151
 - switch capacitor convertor 152–154
- tribo-assisted spectrometry (TAS) 38, 205, 206, 225–227, 248
- triboelectric all-textile sensor array (TATSA) 243
- triboelectric charge 4, 8, 13, 35–37, 69, 79, 83, 86, 93, 96, 97, 99, 100, 102, 103, 177–181, 183, 197, 208, 242, 243, 252, 261, 264, 265, 267, 273, 280
- triboelectric effect
 - applications 37–38
 - environmental and material effects 34–37
 - liquid-solid contact electrification 32–34
 - material-dependent charge transfer 29–32
 - thermionic emission method 26–29
- triboelectric HMI (THMI) 251
- triboelectricity 35, 38, 74, 176–181, 197, 198, 204–206, 227, 229, 241
 - modulate field effect 177–181
- triboelectric micromotor (TM) 273, 274
- triboelectric nanogenerator (TENG) 26, 37, 145
 - advancement history 146
 - application demonstration 157–159, 167

- applications 58
- breakdown discharge 47–49
- breakdown discharge points 51–56
- CFT mode 53–54
- characteristics 62–63
- contact-separation 47–49
- discharge effects in 48–49
- effective maximized energy output per cycle 65–67
- electronic switch convertor
 - integrated circuit 159
 - MOSFET 161
 - SCR and triode 163–165
- electrostatic switch 156–157
 - spark switch 154–156
- fundamental knowledge 45–48
- future direction of 168
- Maxwell's displacement current 145
- mechanical energy storage 169
- mechanical switched converter
 - travel switch 150–154
- operation cycles of 64
- parameters of 65–66
- photon generation 56–58
- theoretical equation for 147–150
- threshold air breakdown 49–50
- transformer converter
 - for EMS 165–167
- V-Q plot 63–65
- triboelectric-potential driven (TPD)
 - NMOS 178, 179
- triboelectric vector sensor (TVS) 105
- triboelectrification 37, 79, 86, 93
 - effect 145
 - and electrostatic induction 175
 - improving 97–99
- triboelectrification-induced
 - electroluminescence (TIEL) 205, 206, 220–225
- tribo-induced EM-wave generation (TIEG) 207, 208
 - discharge-induced
 - displacement-current-based
 - fully-self-powered wireless sensing system 212–215
 - intrinsic-displacement-current induced
 - self-powered wireless sensing system 208–209
 - time-varying magnetic field-based
 - fully-self-powered wireless sensing system 209–212
- tribo-induced light color control 219–220
- tribo-induced light direction control 217
- tribo-induced light intensity control 217–219
- tribo-induced light ON/OFF control 215–216
- tribo-induced light propagation tuning (TILPT)
 - tribo-induced light color control 219–220
 - tribo-induced light direction control 217
 - tribo-induced light intensity control 217–219
 - tribo-induced light ON/OFF control 215–216
- tribophotonics 38, 58, 203–229
 - characteristic 205–207
- tribotronic artificial synapse (TAS) 38, 105, 194–196, 205–207, 225–227, 247, 248
- tribotronic energy extractor (TEE) 161, 162
- tribotronics
 - for active control 190–193
 - for artificial synapse 193–196
 - for information sensing 186–190
 - structure of 184–186
 - theory of 181–183
 - tribo-potential 176–177
- tribotronic thin film transistor (TFT) 185, 186
- tribotronic transistor array (TTA) 189, 190
- tribotronic tuning diode (TTD) 190, 191
- triode 163–165

tunable optical gratings (TOG) 217, 268, 270
turn-off state 95, 96

U

UV lithography 192

V

vacuum control system 85
vacuum protection 265–266
verbal communication 247, 249
visible-light photon generation 57–58
volatile organic compounds (VOCs)
 sensing 226, 284, 287
Voltage-Current (V-I) plot 62
voltage multiplication circuit (VMC) 135
V-Q plot 19, 20, 49, 51, 53, 56, 61, 63–65, 67, 167

W

wearable electronic sensing devices 239
wireless power delivery 208, 209
wireless sensing 58, 204–221, 225, 227
wireless signal transmission 203–207, 210
 challenge 204–205

X

X-ray mappings 263, 264
XY complementary subdivision pattern (XYCSP) 252

Y

yarn-based stretchable sensor arrays (YSSA) 251



