

Index

a

- abrasive wear (AW) 10, 28, 52, 59, 90, 109, 147, 225
 - adhesive and 147
 - dimension 225
 - mechanism of 59
- acetic acid treatment (AAT) 251
- acoustic emission monitoring test 241
- acrylonitrile butadiene styrene (ABS) 221, 255
- additive manufacturing (AM)
 - of biocomposites 220
 - fabrication of 222
 - process parameters 220
 - specimen deterioration 227–228
 - wear and frictional characteristics of 228
 - wear and friction test 228
 - acoustic emission monitoring test 241
 - pin-on-disc or tribometer 239
 - pin-on-drum 239–240
 - repeated impact wear test 240
 - Rubbing test 241
 - wear behaviour 222
 - abrasive wear 224–225
 - adhesion wear 223–224
 - corrosive oxidative wear 226
 - erosion wear 225–226
 - fatigue wear 226
 - fretting wear 226
- adhesion wear 223–224
- Amonton's formula 148
- animal fiber 135

- areca sheath (AS) fiber 69
- atomic force microscopy (AFM) 89, 197

b

- bamboo fibers 141, 162–163
 - based epoxy composites 29
- banana fibers 4, 14
- benzoyl chloride treatment 259
- benzoyl peroxide treatment (BPT) 251
- betel nut fibers 7–8
- biobased composites
 - banana reinforcement 4
 - Betel nut fibers 7–8
 - Calotropis gigantea* reinforcement 5–6
 - coconut coir reinforcement 4
 - flax reinforcement 3
 - hemp reinforcement 4–5
 - Kenaf reinforcement 6–7
 - Ramie reinforcement 5
 - tribological characteristics
 - fillers on wear behavior 11
 - morphology analysis 12–14
 - reinforcement orientation on wear behavior 8–9
 - reinforcement volume fraction on wear behavior 9–10
 - surface modification on wear behavior 11–12
 - tribological characterization 2
- biocompatibility 186, 187, 189, 191, 193, 197, 205
- biocomposites 71, 187
 - additive manufacturing (AM) 220–222

- biocomposites (*contd.*)
 classification 254, 255
 natural fiber polymer composites 254–255
 natural fiber-reinforced composites 255–256
 orthopaedic applications 200–203
 friction and wear of biocomposites 203–207
 sliding wear 173–177
- biomaterials 185
 classification of
 ceramic biomaterials 193
 composite biomaterials 193–194
 metallic biomaterials 189–193
 dental applications 197
 desired properties of 188
 wear of biomaterials
 friction and technique 196–197
 wear testing methods 195–196
- bio-polymer composite
 biofiller incorporated 173–175
 synthetic/inorganic filler incorporated 175–177
- block-on-disc (BOD) machine 4, 26
 block-on-ring apparatus 84
 2-body abrasive wear 68, 225
 3-body abrasive wear 67, 225, 262
Boehmeria nivea 5
 bone/implant surfaces 201
 Borassus fruit fine fiber (BFF) 92, 264
- C**
Calotropis gigantea
 fiber-reinforced epoxy composites 28
 reinforcement 5–6
 cane fibers 251
 carbon fiber reinforced carbon (CFRC) 201
 carbon footprint 173
 carbon nanofibers (CNFs) 271
 cellulose 77
 cellulose fibers 131, 250, 253
 cellulosic natural fibers 21–23, 121, 161
 cement by-pass dust (CBPD) 68, 259
 ceramic biomaterials 193
 ceramic matrix composites (CMC) 185
 ceramic palm fiber composite 161
 chemical wear 147
 cobalt-based alloys 189, 191
 coconut coir reinforcement 4
 coconut fiber 164, 271
Cocos nucifera 164
 coefficient of friction (COF) 3, 27, 69, 86, 108, 144, 170
 composite biomaterials 193–194
 composite materials 19, 20, 29, 34, 48, 51, 65, 117, 131, 135, 185, 187
 compression molding method 40, 262
 conventional composites 60, 67, 199, 200, 219
 corn stalk fibers 12, 13
 corrosive wear 2, 90, 170, 226
 cotton fiber 137
 cotton plant 137
 crystalline polymers 131
- d**
 date palm fibers (DPF) 250, 262
 dental applications 197
 friction and wear of
 dental resins composites in vitro 199–200
 dental restorations in vivo 200
 non-metallic implants in 198
 dental resins composites in vitro 199–200
 dental restorations in vivo 200
- e**
 energy-dispersive X-ray spectroscopy (EDXS) 196
 erosion wear 225, 259
 erosive wear 70, 90, 169, 225–226
 ethylenediaminetetraacetic acid (EDTA) 253
Eulaliopsis binata fiber-reinforced epoxy composites 29
- f**
 fatigue wear 2, 90, 147, 226
 Fe-based alloys 191
 fiber reinforced plastics (FRP) 91, 201
 fiber-reinforced polymer composites (FRP) 149, 255
 fiber-reinforced polymers 187
 fibers 133, 248
 fiber volume fraction 10

- fibre cell 77
 fibre-reinforced composites 20
 fibre-reinforced polymers (FRPs) 19, 21
 tribological properties 25–33
 flax/epoxy based composites
 alkali treatment 40, 43
 compression moulding method 40
 method 40
 wear results 41–43
 wear testing 40
 flax fiber 139
 fluorocarbon base (FA) 50
 fretting wear 90, 226
 friction 142
 frictional resistance 10
 friction test method 148
- g**
- glass fiber (GF) 22, 32, 68, 149, 262
 glass-vinyl ester (GVE) composites 67
 graft copolymerization (GC) 251
 graphitic nanoplatelets (GNP) 267
- h**
- Handy lay-up method 52
 hardness 225
 hemicellulose 13, 21, 49, 77, 118, 161
 hemp fiber (HF) 4, 112, 139, 269
 high corrosion resistance 170, 189
 high-density polyethylene (HDPE)
 composites 271
 high wear resistance 187, 189, 207
 himalayan agave fiber (HAF) 262
 human body
 different polymers and composite 194
 implant material 188
 hybrid polyester-composites 50–51
 hydrophilic fibers 161, 253
 hydroxyapatite (HA) 193
- i**
- Ipomoea carnea* fibre-reinforced epoxy
 composites 28
 isocyanate treatment (IT) 251
 Izod method 240
- j**
- jute fiber (JF) 111, 112, 138, 161, 265
 jute-reinforced polymer composites 162
- k**
- Kenaf fibers 6, 7, 26, 111, 140, 270
 kinetic friction 106, 143
- l**
- lamina 3, 4, 8, 10–15, 51
 lignin 5, 23, 77, 80
 low-density polyethylene (LDPE)
 composites 267–268
- m**
- maleated coupling agents 252
 maleate polypropylene (MAPP) 264
 maleic anhydride-g-polypropylene
 (MA-g-PP) 111
 Malvaceae 6, 137, 139
 man-made fibers 22, 75, 248, 250
 metallic-based biomaterials 189
 metal matrix composites (MMC) 185
 metal oxide fillers, biocomposite
 bamboo fibre 162–163
 coconut fiber 164
 jute fiber 161–162
 oil palm fiber 160–161
 micro emulsion silicon (MS) 50
 milkweed 5
 mineral fiber 141
 mudar 5
 multi walled carbon nanotube (MWCNT)
 5, 176
Musaceae fiber (MF) 69–71
 Musa fiber 4
- n**
- nano-clay treated fiber (NC-BF) 257
 natural fiber-based PLA composite 71
 natural fiber-based VE composite 70
 natural fiber-filled composites 254
 natural fiber-filled polymer
 wear properties of 257–260
 natural fiber flax 40
 natural fiber-polymer composites
 (NFPCs) 254
 natural fiber-reinforced high-density
 polyethylene composites 267
 natural fiber-reinforced hybrid
 biocomposites 270–273

- natural fiber-reinforced low-density polyethylene composites 267–268
- natural fiber-reinforced polyamide composites 269–270
- natural fiber reinforced polyester composites 260–262
- natural fiber-reinforced polyethylene terephthalate composites 269
- natural fiber reinforced polyimide composites
 - driving forces 115–117
 - hand layup 120–121
 - materials and methods 117–118
 - natural fibres 118–119
 - production of 119
 - natural fibers/polyimides composites 121–122
 - polyimides 121
 - stratification 120
 - tribological applications of
 - natural fibers/polyimides composites 122–124
 - vacuum bagging technique 121
- natural fiber reinforced polylactic acid composites 265–267
- natural fiber reinforced polypropylene composites 263–265
- natural fiber reinforced thermoplastic composites
 - load 107
 - motion type 107
 - performance metrics from wear test 108–109
 - temperature 108
 - test duration 108
 - velocity 107–108
 - wear behaviour of composite 107
 - wear test 109–112
 - wear testing methods 105–107
- natural fiber reinforced vinyl ester composite 262–263
- natural fiber reinforcement 249
- natural fiber reinforcement polyamide composites
 - applications 149–150
 - fibers 133–134
 - friction 142–145
 - friction test methodologies 148
 - natural fibers 135–141
 - polyamide 134–135
 - polymer materials 129
 - production 141–142
 - thermoplastic composites 131
 - thermoplastic polymer matrix 132
 - thermoplastic polymers 130
 - thermosetting polymers 130
 - wear 145–147
 - wear test methodologies 148
- natural fibers (NFs) 1, 20–22, 47, 65, 70, 75, 109, 247, 248
 - advantages 124
 - biological treatment 253–254
 - categories of 78
 - chemical treatment
 - acetylation treatment 252
 - alkaline treatment 251
 - benzoylation treatment 252
 - esterification 251
 - maleated coupling agents 252
 - peroxide treatment 252
 - silane treatment 251
 - as compared to conventional reinforcing glass fiber 136
 - composites 115
 - mechanical and chemical characteristics 79
 - natural fiber reinforced polyimide composites 118–121
 - natural fiber reinforcement polyamide composites 135–141
 - natural fibre reinforced polypropylene composites 76–80
 - physical treatment 252–253
 - polyester based biocomposites 49–50
 - treatments of 250
 - tribological studies 86
- natural fibers/polyimides composites 121
- natural fibers polymer composites (NFPCs) 1, 159
- natural fibre composites 49
- natural fibre PP composites
 - wear rate and friction coefficient 87
- natural fibre-reinforced epoxy composites
 - environment and industry 23–25
 - FRP 25
 - tribological properties of 25–30
 - tribological test 30

- natural fibre-reinforced epoxy hybrid composites 30–33
- natural fibre reinforced polypropylene composites 80
- dry sand rubber wheel test 84
- friction coefficient of 86–90
- natural fibres 76–80
- pin-on-drum test 84
- polypropylene 76
- tribological properties of 83–86
- wear behaviour of 90–94
- natural fibre reinforced vinyl ester composites
- composite materials 67
- natural fiber-based PLA composite 71
- natural fiber-based VE composite 70–71
- o**
- oil palm fiber 56, 160–161
- organosilanes 251
- orthopaedic applications 200–203
- friction and wear of biocomposites 203–207
- oxidative wear 226
- p**
- palm fiber composites (PFC) 161
- palmyra palm-leaf stalk fiber (PPLSF) 260
- partially crystalline polymers 131
- pectin 13, 22, 77, 80, 250, 256
- petiole date palm fiber (PDPF) 262
- pin-on-disc type test 198
- pin on disk (POD) 56, 106, 239
- method 196
- tribometer 84
- pin-on-drum 84, 239–240
- plant-based bio-resources 66
- plant fiber 135
- polyalthia longigolia seed (PLS) 68
- polyamide
- matrix composites 132
- natural fiber reinforcement polyamide composites 134–141
- polycarbonate (PC) 255
- polyester based biocomposites
- driving forces 47–48
- handy lay-up method 52
- hybrid polyester-composites 50–51
- natural fibre composites 49–50
- natural fibres 49
- stratification 51
- tribological applications 59–60
- tribological characteristics of 53–59
- tribological tests on natural fibre 52–53
- vacuum bagging technique 52
- polyester composites 48
- polyester hybrid composites 56
- poly ether-ether ketone (PEEK) 197
- polyethylene terephthalate (PET) 255
- polyethylene terephthalate-glycol (PETG) 221
- polyimides 121
- polylactic acid (PLA) 3, 109, 110, 221, 265, 270
- polylactide/jute composites 266
- polymer-based composites 65
- polymer coating (PT) 251
- polymer composites 185
- polymeric resin 10
- polymer matrix composites (PMC) 167, 185
- polymers
- classification of 130
- wear classification 59
- polypropylene (PP) 76, 111
- polytetrafluoroethylene (PTFE) 149, 172, 203
- polyurethane/KF composite 111
- polyvinyl alcohol (PVA) 69
- potassium permanganate treatment (PPT) 251
- pressure-velocity (PV) 204
- pristine polyurethane (PU) 110
- r**
- Ramie fiber (RF) 5, 6, 112
- response surface methodology (RSM) 31, 112
- restorative dentistry 197
- Rubbing test 241
- s**
- scanning electron microscope/light microscope (SEM/LM) 196

- scanning electron microscopy (SEM) 4, 198, 241, 260, 263, 266
- semi-crystalline polymers 131
- short fiber reinforcements 133
- silane treatment (ST) 251, 257, 260, 267, 269, 272
- silk fibers 135
- sisal fiber (SF) 8, 29, 32, 50, 89, 91–93, 112
- sliding friction 144
- sliding wear 168, 169
 - in bio composites 173
 - bio-filler incorporated bio-polymer composite 173–175
 - measure wear method 170–171
 - in polymer composites 171–173
 - synthetic/inorganic filler 175–177
 - wear general aspects 168–170
- specific wear rate (SWR) 40, 41
 - vs sliding distance 42
 - vs sliding speed 42
- specific wear resistance (SWR) 263
- stainless alloys 191
- static friction 80, 143
- static vs. kinetic friction 143
- stearic acid treatment (SAT) 251
- stratification 51, 120
- subtractive manufacturing 220
- surface-to-surface friction 188
- syngonanthus nitens* 27
- synthetic fibers 19, 22, 25
- t**
- thermoplastic composites 89, 131–132
- thermoplastic polymer matrix 132–133
- thermoplastic polymers 130–131, 133, 221, 254
- thermosetting polymers 65, 67, 130
- TiO₂ nanoparticles 163
- titanium-based alloys 187, 191
- tribological effects 2
- tribological tests 29, 30, 52, 53, 256
- tribometer 2, 83, 106, 239
- tribotester 83
- tricalcium phosphate (TCP) 193
- u**
- ultra-high molecular weight polyethylene (UHMWPE) 149, 203–206
- untreated Jute fibers (UJF) 92, 111, 265
- v**
- vacuum bagging technique 52, 121
- VE composites 68–71
- VE/*Polyalthia longifolia* seed (PLS) composites 68
- vinyl ester (VE) resin 66
- w**
- wax 13, 22, 77, 80, 252, 256
- wear 145–147
 - characteristics 224
- wear and friction test
 - acoustic emission monitoring test 241
 - pin-on-disc or tribometer 239
 - pin-on-drum 239–240
 - repeated impact wear test 240
 - rubbing test 241
- wear mechanism 7, 25, 58, 71, 90, 94, 123, 162, 176
- wear of biomaterials
 - friction and technique 196–197
 - wear testing methods 195–196
- wear parameters 146
- wear rate vs. friction coefficient 150
- wear test 40
 - merits and demerits of 196
 - methodologies 148
 - methods 105–107, 195–196
- x**
- X-ray photoelectron spectroscopy (XPS) 197