

Index

a

air mass 0 (AM0) 8
 AM1.0 8
 anode fiber electrodes 214

b

bending deformation 24, 216, 217
 biscrolling method 87
 blade coating method 41–42
 Boltzmann constant 13

c

cadmium telluride (CdTe) solar cells 8
 carbon nanomaterials
 carbon nanotube 37–39
 graphene 34, 36, 37
 carbon nanotube (CNT) 37–39
 carbon nanotube fiber 75–83
 cathodic-electrodeposition 143, 145
 charges separation
 intermediate layer 185–187
 photoactive/electron transport
 materials vs., 182–185
 charge transport layers, for fiber
 perovskite solar cells 147–149
 coaxial structure
 DSSCs 105–106
 fiber-shaped polymer solar cells with
 127–129
 conducting polymers 18, 33–35, 112, 115
 conduction band 9, 16, 17, 21, 50, 80, 95,
 110

copper indium gallium selenide (CIGS)
 solar cells 8, 21
 core-sheath structure 112
 counter electrode 3, 16, 17, 50, 52, 53,
 68, 70–75, 80, 82, 85–88, 95–97,
 101–105, 109, 161, 177, 189, 191,
 193, 194, 206, 208, 218

d

detailed balance limitation 12–15
 1,8-diiodooctane (DIO) 144
 dimethyl sulfide 54
 dimethyl sulfoxide (DMSO) solvent 142
 dip-coating process 142–145, 148, 180,
 188, 189, 208, 210, 213
 direct sewing 206
 direct-spinning method 79, 88
 donor/acceptor interface 18, 46
 drift-diffusion model 12, 14–15
 dry-spinning method 3, 77, 88, 108
 DSSC-supercapacitor unit 170
 dye-sensitized solar cells (DSSCs)
 coaxial structure 105–106
 fiber-shaped 107–109
 integrated fiber-shaped 109–114
 twisting structure 97–104
 working mechanism of 16–17, 95, 96

e

electrochemical method 53, 85, 126
 electrode-spinning 146–147
 electrolyte
 infiltration 183, 184

- electrolyte (*contd.*)
 leakage 95, 104, 162
 twisting structure 104
- encapsulation
 gel electrolytes 193–196
 polymer coatings 196
 polymer tubes 193, 194
- equivalent circuit model 12, 15–16
- ethanol feedstock 79
- f**
- fiber and textile solar cells
 continuous production of 230
 performance improvement of 229–230
 potential applications of 231–232
- fiber-based integrated textiles 167–171
- fiber electrodes
 carbon based fibers 73–87
 functional fibers 87–88
 metal wires 68–71
 polymer fibers 71–73
- fiber perovskite solar cells
 cathodic-electrodeposition 145
 charge transport layers for 147–149
 dip-coating process 142–145
 electrode materials for 149
 electrode-spinning 146–147
 materials 136–139
 perovskite formation strategies 139–142
 structure and photovoltaic parameters 137
 thermal-evaporation 145–146
- fiber-shaped DSSCs 107–109
- fiber-shaped integrated device
 on nanogenerator and solar cell 165–167
 on solar cell and lithium-ion battery 164–165
 on solar cells and supercapacitors 161–164
- fiber-shaped polymer solar cells
 with coaxial structure 127–129
 with twisting structure 123–127
- fiber-shaped solar cells
 characteristics of 2
 functionalization of 2–3
 integration of 2–3
 textile solar cells on 210–211
- flexible dye-sensitized solar cells 50–53
- flexible film solar cells
 blade coating method 41–42
 overview of 31
 roll-to-roll system 45–46
 screen printing 43–45
 slot-die coating method 43
 spin-coating method 40–41
- flexible organic solar cell (OSC) 46–50
- flexible perovskite solar cells 53–56
- flexible planar type solar cells 227, 228
- flexible transparent conducting electrodes (TCEs)
 conducting polymers 33, 34, 35
 metal oxides 32–33
- g**
- galvanostatic charge–discharge 113, 166
- gamma-butyrolactone (γ -GBL) 142
- gel electrolytes 193, 195
- graphene 34–37, 39, 49, 53, 55, 73
- graphene fiber 83–87, 89, 103
- h**
- highest occupied molecular orbital (HOMO) level 16, 17, 19, 123
- hysteresis effect 22
- i**
- implantable photovoltaic solar cells 228
- implantable powering system 231
- incidence of light intensity 11
- indium tin oxide (ITO) 122
- industrial shuttle flying machines 202, 206
- integrated fiber-shaped DSSCs 109–114
- interface and device performances
 stability and influence 189–191
 structure 186, 188–189

- interfacial charge transfer
 active material/fiber electrode interface 178–182
 within fiber electrode 176–179
- interlaced fiber electrodes 211–213
- interlocking yarns 208
- k**
- Kirchhoff's law 12
- knitting process 202, 210
- l**
- layer-by-layer stacking method 36
- light illumination 9, 15, 17, 19, 21, 24, 25, 53, 151, 201, 208, 215, 222
- liquid electrolyte 17, 20, 22, 96, 104, 109, 115, 123, 137, 151, 164, 193, 195, 196, 208, 211, 218, 222, 230
- lithium-ion battery belt 167, 169
- LUMO level 16–19, 123
- m**
- Maxwell's equation 14
- metal oxides 32–33
- metal wires 68–71
- micropits 182
- multi-walled carbon nanotube (MWCNT)
 fiber 3, 79–82, 88, 97, 102, 108, 110, 112, 176–178, 189, 190, 196
- n**
- nucleation-growth theory 140
- p**
- PEDOT:PSS electrodes 34
- perovskite formation strategies 139–142
- perovskite nanocrystals 19, 189
- perovskite solar cells, working mechanism of 19–23
- photoactive/electron transport materials 182–185
- photoactive layer materials 229
- photoanode 97–101
- photoelectrochemical stability 179
- photovoltaic conversion 182
- photovoltaic conversion performance 1, 2, 74, 88, 89, 95, 98, 105, 106, 108, 112, 124, 139, 188, 196, 207, 220, 222, 230
- photovoltaic textile 115, 130, 201, 210, 222
- piezoelectric nanogenerator 166, 192
- planar-junction structure 18
- planar solar cells, development of 227–229
- plasmonic effect 205
- Poisson's equation 14
- poly(methyl methacrylate) (PMMA) 128, 196
- polyaniline (PANi) 33, 86, 112
- poly(vinyl alcohol) (PVA)-H₃PO₄ gel 161
- polymer-based dipole materials 185
- polymer coatings 196
- polymer solar cells (PSCs)
 fiber-shaped 123–129
 overview of 121–123
 textiles 129–132
 working mechanism of 18–19
 working principle 127
- polymer tubes 193, 194
- PVA/H₃PO₄ 166
- r**
- reverse saturation current 12–13
- roll-to-roll system 45–46, 57
- rotation-translation method 72, 108, 190
- s**
- sandwich configuration 105
- screen printing 40, 43–45, 57
- sewing process 202, 210
- sheet resistance vs. transmittance 38
- Shockley–Reed–Hall recombination 14
- shuttle flying process 211
- silicon solar cells, structure of 8, 10
- single substrate-based fabrication 40
- single-walled CNT (SWCNT) films 37
- slot-die coating method 40, 43, 44, 57
- smart textile sensor 210

- solar cells
 - detailed balance limitation 12–14
 - drift-diffusion model 14–15
 - efficiency limitation for 8–16
 - equivalent circuit model 15–16
 - for flexible and wearable application 22–24
 - working mechanism for 8–16
 - solar energy 7, 17, 192
 - solar simulator 8, 171
 - solid-state electrolyte 104, 197, 205, 208, 218
 - spin-coating method 40–41
 - S-Q limit 12
 - stacking textile electrodes 208–210
 - strip-shaped solar cells 206–208
 - Sun illumination 205, 206
 - superparamagnetic nanoparticle 108
- t**
- textile electrodes 208–210
 - stacking 208
 - textile solar cells
 - application of 220, 221
 - breathability of 216–218
 - components 203
 - construction substrate 203
 - encapsulation structure and materials for 218–220
 - fiber-shaped 210–211
 - incidence angle for 213–216
 - incorporation of planar solar cells 203–206
 - interlaced fiber electrodes 211–213
 - mechanics of 216–218
 - strip-shaped solar cells 206–208
 - textile electrode 208–210
 - weaving patterns for 213–216
 - textile triboelectric nanogenerator cloth (TENG-cloth) 167
 - thermal evaporation 145–146
 - thermodynamic theory 14
 - 3D hopping mechanism 80, 177
 - transportable lightweight cloth 170
 - triboelectric nanogenerators (TENGs) 113, 167
 - trifluoromethane-sulfonic acid (TFMS) 38
 - tunneling conduction (TC) 177, 178
 - twisting structure
 - counter electrode 101–104
 - electrolyte 104
 - fiber-shaped polymer solar cells with 123–127
 - photoanode 97–101
- v**
- variable range hopping (VRH) 177, 178
- w**
- wearable sensor systems 231
 - wearable solar cells
 - applications of 3–4
 - development of 1
 - interface functional of 190–193
 - weaving patterns 213–216
 - weaving process 2, 115, 129, 131, 197, 202, 210, 213, 214
 - wet-spinning method 73, 75–77, 84, 85

