

Index

a

- active mode-locked ultrafast fiber lasers 122–124
- active mode-locking 121–123
- active/nonlinear optical fiber-graphene device, for ultrahigh sensitivity sensors 23
- Ag₂Te-based nanofibers 230–231
- aggregation-induced emission (AIE) 105
- alginate–polyacrylamide hydrogel flexible waveguides 51
- all-fiber-coupled electrochemical SPR fiber-optic sensing system 85
- all-fiber Tm-doped laser 130
- all-optical modulator (AOM) 8, 12
- artificial saturable absorbers 122
- atmospheric turbulence principle 138
- axial viscosity gradient (AVG) 205, 207
- AVG breakup 206–210, 212, 215

b

- battery management system (BMS) 75
- Bi₂(Te, Se)₃-based nanofibers 226–228
- biochemical sensing, on FOFLs 110–115
- biocompatibility 47, 64, 66, 95, 96, 110, 114, 155, 162, 164–166, 168, 170, 182, 189, 192
- of wearable optical sensors 52–53
- birefringence effect 6
- black phosphorus

low-symmetry crystal structure 6

third-order nonlinearity 6

Bridgman crystal growth process 212

c

- capillary instability 29, 35, 37, 206, 207
- capillary number (Ca) 208, 209
- carbon nanofiber (CNF) 162, 185
- cell and organism analysis 113–115
- channelrhodopsin-2 (ChR2) 144, 180
- chemical vapor deposition (CVD) 8, 9, 29, 30, 34, 152–153
- clean-transfer 2D InSe photodetectors 14
- CO₂ laser processing, of silicon-core optical fibers 34
- coherent random laser 109
- color center (CV) SPE 12
- commercial silica fibers 165, 181
- common optical fibers (COF) 101–102
- compositional microstructuring 32, 35
- comprehensive integrated optical health monitoring systems 46
- conductive core heating via laser absorption 33–34
- conductive polyethylene (CPE) 162, 185
- cooling performance (COP) 225
- Coulomb interaction 4, 6
- cryo-electron microscopy (cryo-EM) method 76

- crystalline WS₂ film 11
 cyclic olefin copolymer cladding (COC) 162
- d**
 depth-dependent fiber probes 188, 191
 Dirac fermionic graphene materials 2
 direct digital manufacturing (DDM) 198
 direct optical readout 181
 dispersion managed soliton (DMS) 136, 137
 2-μm dispersion-managed soliton fiber laser 137
 dispersion-managed thulium-doped fiber (TDF) laser 135, 136
 disposable biochemical sensors 111–113
 dissipative sensing mechanism 98
 distributed Bragg reflection (DBR) cavities 96
 pulse laser structure diagram 130
 diverse thermal drawing methods 185–186
 double-crucible technique 151–152
 Drude model 80
 D-shaped fiber (DSF) 7, 8, 22
 dual-wavelength mode-locked spectrum 127
 dye-doped PDMS fiber 51
 dynamic durability 47, 51–52
- e**
 electrical conductivity 162, 226, 233
 electric-optic modulator (EOM) 12, 14
 electrochemical surface plasmon resonance (EC-SPR) method 77, 80–81
 electronic absorption 32–34
 electronic bandgap modulation 34–35
 electronic band structures 4, 5, 211
 electronics integration 181–183
 electrospinning 113, 226, 231–234
 energy level structure 119–121
 enzyme-linked immunosorbent assay (ELISA) 110
- erbium–ytterbium codoped fiber amplifier (EYDFA) 132
 extrusion method 149–150
- f**
 Fabry–Pérot (FP) cavities 95–96
 Fabry–Perot interferometer (FPI) 23, 61, 62, 76
 Faraday constant 81
 fast, high-throughput biochemical sensors 113
 fiber-based neural probes
 biocompatibility 155
 electrical properties 157–158
 mechanical properties 156–157
 optical properties 157
 fiber Bragg grating (FBG) 1, 21, 48, 62–63, 76
 fiber endface photodetectors (FPD) 14, 16
 fiber fabrication process
 double-crucible technique 151–152
 extrusion method 149–150
 high-pressure chemical vapor deposition technique 152–153
 integrated dynamic wet spinning technique 155
 laser-heated pedestal growth technique 153–154
 molten-core-in-tube method 147–148
 pressure-assisted melt filling technique 153–154
 rod-in-tube method 146–147
 stack-and-draw method 150
 thin-film rolling method 148–149
 3D printing approach 150–151
 fiber Fabry–Pérot (FFP) cavity 23, 62, 101, 106–108
 fiber microring resonator 101–105
 fiber-optic sensors 3, 9, 20–24, 53, 55, 67, 85
 fiber optofluidic lasers (FOFLs)
 cell and organism analysis 113–115
 disposable biochemical sensors 111–113

- fast, high-throughput biochemical sensors 113
- highly sensitive biochemical sensors 110–111
- figures of merit, for 2D-materials-fiber photodetectors 15
- flexible optical motion detection systems 46
- flexible thermoelectrics (FTE) 226, 231, 232
- fluorescent resonance energy transfer 22
- four-wave mixing (FWM)
- of graphene 4
 - of MoS₂, 6
- free-carrier absorption (FCA) 41
- free-carrier dispersion (FCD) 41
- 2-μm free-space data transmission
- holmium-doped active mode-locked fiber system laser 137
- free-space data transmission system 140
- free space optical (FSO)
- communication 138, 139
- 2-μm free-space optical communication 138
- g**
- galvanostatic charge and voltage holding (GCVH) methods 85
- galvanostatic intermittent titration technique (GITT) 88
- genetically encoded calcium indicators (GECIs) 180
- genetic manipulation-enabled optical approaches 180
- glass cladding 148, 150, 153, 227, 234
- glass fibers 30, 143, 150, 152, 158–161, 229–231, 234
- glassomer 200
- GO-based all-optical wavelength converter 133
- graphene
- basic properties of 2D materials 3–4
 - photothermal effect 13
- graphene-based 2D materials 2, 22
- graphene-covered-microfiber AOM device 12
- graphene-fiber sensors 21
- graphene–MoS₂–WS₂ heterostructure FPD 15, 16
- h**
- helical scaffolding fiber 165
- hetero-core fiber based sensor probes 52, 56–57
- hexagonal boron nitride (hBN) 7
- high harmonic generation (HHG) 4
- highly sensitive biochemical sensors 110–111
- high-pressure chemical vapor deposition technique 29, 152–153
- HML pulse trains 130, 131
- Ho³⁺ ion energy level structure 119, 120
- hollow-core antiresonant fiber (HC-ARF) 104
- hollow-core conjoined-tube negative-curvature fiber 2
- hollow-core fibers 20, 22, 190
- hollow core MOF (HC-MOF) 103–104
- hollow-core PBG fibers 106, 114
- hollow optical fibers 101–103, 112
- holmium-doped fiber (HDF) 119, 138, 139
- hybrid graphene-fiber-endface structure 8
- hybrid graphene-microfiber device 9
- hydrogel hybrid probes 169
- i**
- inorganic synthetic fibers
- Ag₂Te-based nanofibers 230–231
 - Bi₂(Te, Se)₃-based nanofibers 226–228
 - NaCo₂O₄-based nanofibers 232–234
 - PbTe-based nanofibers 229–230
 - SnSe-based nanofibers 231–232
- in-situ* monitoring of ion activities in battery 85–88
- in-situ* monitoring of state of charge (SOC) of battery 84–85

- in-situ* monitoring of state of health (SOH) of battery 88–90
- integrability, of optical wearable sensors 53–54
- integrated dynamic wet spinning technique 155, 168
- k**
- Kerr effect 4, 12, 17
- l**
- laser annealing/recrystallization 42
- laser dyes 95, 106, 115
- laser-heated pedestal growth technique 153–154
- laser-induced instability method 37
- laser-irradiated silicon core fiber 33
- laser processed optical fiber application capillary instabilities 35–38
compositional microstructuring 35
electronic bandgap modulation 34–35
- laser processing, of semiconductor optical fibers
conductive core heating via laser absorption 33–34
electronic absorption via the core 32–33
- light-emitting devices 10
- light sources 3, 9–13, 19, 46, 52, 65, 69, 167, 192
- liquid-core optical ring resonator (LCORR) 102
- m**
- Mach–Zehnder intensity modulator (MZM) 138, 139
- microelectromechanical system (MEMS) 23
- microfiber 7–14
sensing platforms 52
SWCNTs 131
- microstructured fiber 2, 7, 22, 150
- microstructured optical fiber (MOF) 8, 101, 103–104, 153
- mid-infrared light emission 6
- miniaturized microfibers 2
- mode broadening 97, 98
- mode-locked fiber laser active 122–124
passive 124–132
- mode-locked thulium-doped fiber laser 125, 137
- mode-locking effect 121, 122, 124
- mode locking technology 121
- mode splitting 97, 98
- molten-core-in-tube method 147–148
- monolayer MoS₂ photoluminescence quantum yield 4
valleytronics 4
- MoS₂, band structures of 4
- MoS₂/microbottle device 12
- multifunctional multimaterial fibers 2
- multiplexable feature, of sensors 54
- 2.07 μm multiwavelength AML fiber laser 123
- n**
- NaCo₂O₄-based fibers 232–234
- natural saturable absorbers 122
- Navier–Stokes equations 207, 208
- neural interfacing commercial silica fibers 181
direct optical readout 181
electronics integration 181–183
genetic manipulation-enabled optical approaches 180
- thermally drawn multifunctional fiber 183–184
- neural interfacing applications as-drawn fiber-based probes 186–187
diverse thermal drawing methods 184–185
material selection 184–185
multifunctional fibers with post processing 187–190
- tissue engineering 190–191
- neural probes glass fibers 158–161
polymer fibers 162–168

- nonlinear applications 20, 38, 39, 42
 nonlinear optical loop mirror (NALM)
 structure 122
 nonlinear optics 1, 3–6, 9, 17–20, 39
 nonlinear polarization rotation
 (NPR) 18, 122, 124–128
 nonlinear spectral sensing 22
 nonparametric process 17
 nonstretchable fiber-based
 probes 162–165
 normal-dispersion Tm-doped mode-locked fiber laser 127
 NPR-based mode-locked thulium-doped fiber laser 137
 NPR-induced birefringence filter 128
- o**
- operando monitoring of renewable energy
 in-situ monitoring of ion activities in battery 85–88
 in-situ monitoring of state of charge (SOC) of battery 84–85
 in-situ monitoring of state of health (SOH) of battery 88–90
 ultrafast and repeatable hydrogen monitoring 81–84
 optical fiber-2D-material integrations 7–9
 optical fiber integrated with graphene saturable absorber 18
 optical fiber microcavities 96, 105, 113
 optical fiber microresonators
 fiber Fabry-Pérot cavity 106–108
 fiber microring resonator 101–105
 photonic bandgap fiber
 microcavity 105–106
 random scattering 108–109
 optical fiber modulators 13
 optical fiber photodetectors 16
 optical fiber sensors 76, 77, 82, 84, 88, 95
 optical microcavity
 principle of 96–97
 sensing mechanism of 97–98
 optical microfiber ring resonator 104–105
- optical modulator 9, 12
 optical polarizer 9
 optical sensor development 45
 optical spectrum analyzer (OSA) 20, 48, 82, 133, 138, 140
 optofluidic laser
 laser emission principle 98–100
 sensing mechanism of 100–101
 optofluidic ring resonator (OFRR) 102
 optogenetic technology
 fiber-based neural probes 155–158
 fiber fabrication process 145, 155
 principle of 144–145
 output power characteristics, of actively mode-locked fiber laser 124
- p**
- parametric process 17, 19
 passively mode locked dispersion-managed thulium-doped fiber laser 136
 passively mode-locked SWP fiber laser 129
 passive mode-locked ultrafast fiber lasers 124
 hybrid mode-locked 130–132
 nonlinear amplified loop
 mirror 128–130
 nonlinear polarization rotation effect 124–128
 2D material mode locking 130
 passive mode-locking devices 121
 Paul trap 207, 208, 217
 PbTe-based fibers 229–230
 photodetectors 9, 14–16, 20, 47, 52, 55, 65, 66, 69, 138, 140, 207, 215
 photonic bandgap fiber
 microcavity 105–106
 photonic crystal fibers (PCFs) 1, 14, 146, 203, 204
 photonic crystal (PC) microcavities 96
 photonic neuromorphic computing (PNC) 203, 216, 217
 photosensitive proteins 144
 Plateau-Rayleigh instability 35

- polarimeters 8, 16
 polarimetric devices 3, 8–10
 polarimetric graphene-fiber devices 10
 polarization insensitive isolator
 (PI-ISO) 132
 polycarbonate core (PC) 162
 polydimethylsiloxane (PDMS) 162,
 167, 187
 polydimethylsiloxane (PDMS) 49
 polymer fibers 162–168
 nonstretchable fiber-based
 probes 162–165
 stretchable fiber-based
 probes 165–168
 polystyrene 151, 167
 poly-vinylidene fluoride
 (PVDF) 184, 230
 pressure-assisted melt filling
 technique 29, 153–154
 processed optical fiber-based sensing
 probes 52
 processed optical fiber based wearable
 sensing systems 46
- q**
 Q-factor 96, 100–105, 107, 108, 110, 116
 Q-switched mode-locked DSR thulium-doped fiber laser 135
 quantum dots 10, 12, 95, 106
 quantum interconnects (QuIC) 203
 quasi-distributed sensing system 54
 quasistatic cooling 211
- r**
 random lasers (RLs) 108, 109
 rapid photothermal annealing 32
 rapid thermal annealing 31–32
 reduced graphene oxide (rGO) 23, 49
 renewable-power grid 75
 resonance wavelength shift 97
 resonant condition 97
 response curve 47, 48, 50
 response time, of optical wearable system 51–52
 rod-in-tube method 146–147, 152
- s**
 saturable absorber mirrors (SESAMs) 17
 saturable absorption (SA)
 of graphene 4
 of graphene-based 2D materials 17
 of MoS₂, 6
 second harmonic generation
 (SHG) 4, 20
 Seebeck effect 225, 231
 semiconductor optical fibers
 heat treatment of 29–32
 laser processing of 32–34
 tapering of 38–42
 sensitivity, of monitoring system
 47–50
 Si–Ge alloy optical fiber 34
 silica fiber-based sensing probes 50
 silver nanowires (AgNWs) 158, 162, 187
 single-crystal Te nanowires 227
 single-mode fiber (SMF) 18, 41, 42, 56,
 61, 78, 101, 203, 204
 single-mode WGM lasing 105
 single-photon emitters (SPEs) 12
 sleeved tapering process 39
 smoke channel communication 139–141
 SnSe-based nanofibers 231–232
 solid electrolyte interphase (SEI)
 growth 76
 solitons 17, 18, 41, 125, 128, 135–137
 solvent evaporation-or entrapment-driven (SEED) 168
 SP fiber laser based on nonlinear polarization rotation 128
 spherically symmetric thermal gradient (SSTG) 211
 square-wave pulse laser structure 129
 square-wave soliton passively mode-locked fiber laser 128
 stack-and-draw method 150
 standard fiber-optics 18, 198
 stereocoiled graphene-microfiber structure 13
 stereo graphene-coil-microfiber structure, for polarization manipulation 10

- stretchable fiber-based
probes 162, 165–168
- surface plasmon polariton (SPP) 78
- surface plasmon resonance 68,
77, 80, 81
- t**
- tapered optical fiber applications
dispersion tailoring 41
mode-matched coupling 41–42
- tapering, of semiconductor optical
fibers 38–39
- test efficiency, of optofluidic laser
113
- TFBG-assisted plasmonic excitation by
thin metal film coating 78–80
- thermal annealing 29–32
- thermal drawing process (TDP) 146,
183, 184, 227
- thermally drawn multifunctional
fiber 179, 183–191
- thermocapillary effect 37
- thermoelectric cooling 225
- thermoelectric fibers, inorganic
225–235
- thin-film rolling method 148–149
- third harmonic generation (THG)
of graphene 4
of MoS₂, 5
- 3D printing approach 150–151, 202
- 3D-resonant microstructures 106
- thulium-doped fiber (TDF) 119,
131–133, 135–137
- thulium-doped fiber amplifier
(TDFA) 133
- thulium-doped fiber laser 131,
133, 135–137
- thulium–holmium codoped fiber
(THDF) 119, 138
- thulium–holmium codoped fiber
amplifiers (THDFA) 138
- tilted fiber Bragg grating (TFBG) 78
- time stability, of all-optical wavelength
conversion 134
- tissue engineering 179, 190–191
- Tm-doped mode-locking fiber laser
configuration 132
- total internal reflection (TIR) 1, 57, 97
- transition metal dichalcogenides
(TMDCs) 2–6
- transmission electron microscopy
(TEM) 31, 76
- twin detector measurement setup 131
- 2D materials
defined 2, 3
with direct electronic bandgap 10
integration to optical fiber platform 3
mode locking 130
properties 3–7
research 7
single-photon emitter applications
12
- 2D-materials-microfiber light emission
sources 11
- 2D heterostructures 7
- two-photon absorption (TPA) 6, 17, 41
- two-photon lithography 192
- u**
- ultrafast and repeatable hydrogen
monitoring 81–84
- 2μm ultrafast fiber laser communication
free space optical (FSO)
communication 137–138
- smoke channel
communication 139–141
- 2μm ultrafast fiber laser-related
technology
- pulse shaping and evolution 134–137
- wavelength conversion 132–134
- ultrashort laser pulse generation 121, 188
- v**
- valleytronics 4, 7
- very large-scale integration (VLSI)
architectural and morphological
control of 200–205
- axial fiber-structuring 205–208
- fiber-embedded functional
systems 205–208

- very large-scale integration (*Continued*)
fiber optics 197
microprocessors' design and
 fabrication 198
3D architecture of 199
- W**
waveguide-integrated-2D-materials 19
wavelength conversion signal, of
 GO-coated microfiber 134
wearable optical interrogation
 systems 46
wearable optical sensing systems 45, 46,
 55, 56, 61, 62, 69
wearable sensors, performance
- biocompatibility 52–53
integrability 53–54
linearity and range of operation 50–51
response time and dynamic
 durability 51–52
sensitivity 47–50
whispering-gallery-mode (WGM)
 cavities 95, 207, 211, 212
- Y**
Young's modulus 3, 23, 58, 156, 157,
 165, 166
- Z**
zero-angular-momentum laser 106