

Index

a

- absolute permittivity 8
- Al-disk-array/Al₂O₃/Al perfect absorber 156, 157
- Amptek “COOL-X” miniature X-ray generator 231
- applications 231
- combined output spectrum 232
- cooling phase spectrum 232
- features 231–233
- heat and cool output flux 232
- heating phase spectrum 232
- AlN films 98
- AlN pyroelectric detector 101
- artificial pyroelectric materials 28
- Au Pt-PZT-Pt pyroelectric IR detector on silicon substrate 124, 125
- auto image calibration 74

b

- Ba_{0.66}S_{r0.34}TiO₃
 - induced pyroelectric coefficient 60, 61
 - permittivity vs. temperature at various bias fields 60, 61
- barium strontium titanate (Ba_xSr_{1-x}TiO₃) 28, 60, 63, 72–75, 122
- barium titanate (BTO) ceramic-based hybrid NG 183, 198, 206, 207
- BaTiO₃ 26, 42, 43, 72, 96
- bilayer-structured pyroelectric sensor 91
- bismuth sodium titanate (BNT) based lead-free ceramics 96

BNKLB lead-free ceramic samples, for sensor applications 97

BNKT-based ceramic 97

boracite 25

breakdown field 16

BST Broadband Pyro-Electric Infrared Area Detector 74–75

c

- caesium nitrate (CsNO₃) 28
- calamine 24–25
- calcium doped strontium barium niobate ceramics, pyroelectric properties of 76
- calcium modified lead titantante (Pb_{1-x}Ca_xTiO₃, PCT) thin films 86
- calcium-modified lead titanate (PCT) thin film pyroelectric infrared (IR) detectors 86, 87
- capacitance of a parallel plate capacitor 7–9
- Carnot cycle 178–179
- ceramic based PyNG 198
 - lead-free 204–208
 - PZT based 201–204
 - self-powered flexible p-Si/n-ZnO NWs heterojunction PDs 200–201
- ZnO based pyroelectric nanogenerators 198–201
- ceramic-polymer composites 90–96
- Clausius–Mossotti relation 12

- CMOS (complementary metal-oxide-semiconductor) compatible pyroelectric detector 100–102, 127, 129, 141, 153, 156, 158 cobalt phthalocyanine 28 coefficients of thermal expansion 20 collagen 35 conductive ferroelectric domain walls (EFDWs) 45 continuous phase transitions 40 converse coefficient 38 crystal negative polarity 230 crystal positive polarity 230 cubic ABO_3 perovskite-type unit cell 77 Curie temperature 41, 56, 60, 72–74, 76, 77, 79, 98, 120, 121, 178, 211 Curie–Weiss law 46
- d**
- Debye relaxation 6
 - Debye's approximation 33
 - depolarization field 7, 10
 - deuterated and L-alanine-doped triglycine sulfate (DLaTGS) detectors 28, 66–68
 - for infrared microscopy 67
 - deuterated TGS (DTGS) 63–66, 68, 121, 158
 - dielectric(s) 1
 - capacitance of a parallel plate capacitor 7–9
 - Debye relaxation 6
 - dielectric constant 9–10
 - dielectric relaxation 5–6
 - dielectrics breakdown 15–16
 - dielectrics losses 12–13
 - electric displacement field 9
 - electric susceptibility 9–10
 - electronic polarization 3–4
 - ionic polarization 4
 - local field 10
 - molecular theory of induced charges 6
 - orientation polarization 4
 - polarization of 2–3
 - space charge polarization 4–5
 - dielectric breakdown 15, 16, 179
 - dielectric constant 4, 5, 7, 9, 46, 59, 62, 63, 65–67, 73, 74, 76, 78–86, 90, 92–95, 99, 120, 125
 - dielectric dispersion 5
 - dielectric loss angle 13–14
 - dielectric losses 12–15, 65, 76, 90, 161
 - dielectric loss index (factor) 15
 - dielectric relaxation 5–6, 94
 - dielectric strength 16
 - dielectric susceptibility 12
 - domain switching 39
 - domain wall(s) 39, 42
 - motion 43
 - nanoelectronics 45
 - double-crystal arrangement, for neutron generator 228, 229
 - dual-element PZT pyroelectric IR detector design 28, 125
- e**
- elastic compliance coefficients 20
 - electric displacement field 9–10
 - electric susceptibility 9–10, 12
 - electrocaloric effect 24
 - electromagnetic shielding hybrid NG (ES-HNG) 193
 - electrometer 23
 - electronic polarization 2–6, 32
 - electrostriction coefficients 38, 39
 - Ericsson cycle 179–180
 - Er^{3+} modified PVDF (Er-PVDF) film 187, 188
 - Eu-doped SBN 76
- f**
- Faraday cup-target setup for ion current measurement 225
 - fast high-density non-volatile random access memory (FeRAMs) 43
 - ferroelectric(s) 55–57
 - domains 39, 42–45, 205
 - hybrid focal-plane IR detector 122, 123

- lead zirconate titanate thin films 81
- ferroelectric materials 57, 178
- Curie temperature 178
 - as IR detectors, operating modes for 60–61
- ferroelectricity 39
- domain-wall motion 43
 - ferroelectric domains 42
 - phase transition 40–41
 - soft-mode 45–46
- ferromagnetism 39
- field-effect transistors (FeFETs) 43, 57, 59, 120, 121, 162
- field of dipoles inside cavity 11–12
- first-order phase transitions 40
- flexible $\text{Pb}(\text{Zr}_{0.52}\text{Ti}_{0.48})\text{O}_3$ (PZT)
- film-based hybrid
 - piezoelectric-pyroelectric NG 203
- free-standing and strain-free gallium nitride (GaN)
- temperature dependent pyroelectric coefficient of 102
- g**
- Galileo probe net flux radiometer 27, 29
- gallium nitride (GaN) 28
- based pyroelectric materials 102
 - resonators performance 155
- Gibbs free energy 6
- graphene pyroelectric bolometer 162, 163
- device architecture 163–164
 - performance 164–165
- h**
- high-grade heat 173
- high performance pyroelectric infrared (IR) detector 81, 86
- high-performance wearable pyroelectric sensor 90
- hybrid ferroelectric 1,4-diazabicyclo [2.2.2]octane perrhenate (dabcoHReO₄)nanofibre-based PyNG 205
- hybrid focal plane array detector 28, 122, 126–127
- hybrid PyNG 190, 191
- i**
- induced dipole moment 2
- induced dipoles 7
- infrared sensor based KNN/[P(VDF-TrFE)70:30] composite thick film 96
- integrated flexible hybrid energy cell 197
- integrated resonant absorber pyroelectric detector 148
- design 149
 - sensitivity 150
- ionic polarization 2, 4, 5, 32
- IR detectors, classes of 119
- IR sensor 126
- equivalent circuit of 126
- j**
- Joule heat 16
- Joule–Lenz law 12
- k**
- Kramers–Kronig relations 10
- Kundt powder patterns 24–25
- l**
- lapis electricus* 21
- lead-free ceramics 96–97
- based pyroelectric nanogenerators 204–208
- lead zirconate-lead titanate (1-x)PbZrO₃-xPbTiO₃-PZT perovskite solid solution 78
- lead zirconate titanate (PZT) 35, 42, 84, 89, 93, 94, 97, 120, 162, 182
- thin films 79
- lead zirconate titanate Pb(Zr,Ti)O₃ 42, 89
- LiNbO₃/PVDF composites for thermal/infrared sensing applications 95

- linear pyroelectric array
detector assembly 129
detector chip technology 127–129
fundamental structure of 127
PYROLINE 256 camera system
129–131
LiSO₄-doped TGS crystals 66
lithium niobate (LiNbO₃) 63, 67–72, 95,
96, 146, 158, 163, 230
lithium niobite (LN) crystals 67–72
lithium tantalate (LiTaO₃) 28, 29, 63,
67–72, 78, 80, 84, 94, 95,
102, 121, 127–131, 137, 139,
140, 146, 221, 222, 224, 226–230
crystal structure 67–68
lithium tantalate (LT)
Terahertz pyroelectric detector 71
thin films 69
Lorentz field 10, 11
Lorentz–Lorentz equation 12
Lorentz relation 11
loss of power 12, 13
low-grade heat 173, 208
low-grade thermal energy harvesting
technologies 173
low-noise un-cooled infrared radiation
detection 103
LT/PVDF nano composite film 94
Lyddane–Sachs–Teller relation 46
lyncurium 21, 22
lyngourion 21
- m**
- manganese doped lead zirconate titanate
thin films 81
material dispersion 5, 10
material figure-of-merits (FoMs) 60, 62,
66, 76, 80, 81, 83, 86,
92, 95, 96
mechanical hybrid NGs 192, 194,
197–198
medium-grade heat 173
MEMS-based hybrid plasmonic–
pyroelectric detector 158
MEMS processing techniques 154
- MEMS pyroelectric IR detector 101
miniature pyroelectric X-ray generator
“COOL-X” (battery operated)
232–233
Mn-doped 0.74Pb(Mg_{1/3}Nb_{2/3})O₃-0.26
PbTiO₃ crystals 84
Mn-doped PZT thin films 82
modified Ericsson cycle 180
modified lead titanate (PT) 85
based thick films 86
molecular theory of induced charges 6–7
multi-channel LT pyroelectric detectors
71
multi-component ferroelectric ceramic
materials 79
multi-frequency band pyroelectric sensor
104–106
multiferroics 39
multilayer Pb(Zr_{0.3}Ti_{0.7})O₃/PbTiO₃ thin
films, poling of 82
- n**
- nanowire ferroelectric polymers based
PyNG 191, 193
nature heat 173
net flux radiometer (NFR) 27, 29
Neuman’s principle 19
neutron production with pyroelectric
double-crystal assembly 227
noise equivalent of temperature difference
(NETD) 103, 122, 127, 143, 151,
152, 155
noise equivalent power (NEP) 59, 70, 80,
94, 100, 129, 136, 139, 140, 142,
144, 146–150, 164
non-polar molecule 6
- o**
- Olsen cycle 178, 180–181
one-structure-based multi-effects coupled
nanogenerator 204, 207
orientational polarization 2–4
(111) oriented Pb(Zr_xTi_{1-x})O₃ (PZT) thin
films 80

p

- packaged domain patterned LT thin film pyroelectric device 138
 $\text{Pb}_{0.88}\text{Ln}_{0.08}\text{Ti}_{0.98}\text{Mn}_{0.02}\text{O}_3$ ferroelectric ceramic system 79
 $\text{PbZr}_{0.3}\text{Ti}_{0.7}\text{O}_3$ device, voltage response experimental results of 126
 $\text{PbZrO}_3\text{-PbTiO}_3$ phase diagram 78
 PCLT-P(VDF-TrFE) nanocomposite thin films 92
 permittivity of free space 9
 perovskite-structured ferroelectric ceramics 77
 advantages 77
 modified lead titanate 85–87
 modified lead zirconate 78–85
 phenylpyridine 28
 photovoltaic-pyroelectric coupling effect based self-powered photodetector 207
 piezoelectric moduli 20, 32, 37–39
 piezoelectricity 20, 24, 27, 37–39, 57, 87, 103
 piezoelectrics 37, 125
 256 pixels LiTaO_3 linear arrays 130
 plasmonic IR detector
 fabrication and performance 158–161
 structure design 156–158
 plasmonic perfect absorber
 reflectivity, absorptivity and transmissivity characteristics of 160
 Plessey PLT522 detector on TO5 header 121
 polar molecule 5, 6, 64
 polarizability of the dielectric material 12
 polarization 11
 density 9
 of dielectrics 2–3
 polarized dielectric material 1–2
 poling 37, 44, 64, 69, 79, 81, 82, 85, 86, 90, 92–94, 132, 137, 177, 190, 201
 polycrystalline AlN thin film-based bulk micromachined pyroelectric IR sensor 101
 polymer-based PyNGs 183
 environmental conditions 183–186
 hybrid pyroelectric nanogenerators 191–198
 pyroelectric material development 186–188
 wearable PyNG 188
 polymer-based pyroelectric infrared sensor 89
 polyvinylidene fluoride (PVDF) 87, 88
 for infrared thermal sensing 88
 polymer 120
 polyvinyl fluorides 28, 87
 porous lead zirconate titanate
 ($\text{PbZr}_{0.3}\text{Ti}_{0.7}\text{O}_3$) thick films 81, 84, 126
 primary pyroelectric coefficient 20, 32, 33
 primary pyroelectricity 20, 32, 33
 PT-P (VDF-TrFE) 0-3 composites 92
 PVDF based piezoelectric and pyroelectric hybrid nanogenerator (PPNG) 191, 195–197
 PVDF nanowires–poly(dimethyl siloxane) (PDMS) composite film 89, 186, 188, 190–192, 196, 202–207
 PVDF polymer detector
 self-absorbing layer structure 140–141
 sensor array specification and performance 142–143
 sensor assembly 141–142
 PVDF-on-silicon pyroelectric sensor array 140, 142
 P(VDF-TrFE) based high performance PyNGs 185
 P(VDF-TrFE) based PyNGs 186
 P(VDF-TrFE) composite materials 95
 P(VDF-TrFE) ferroelectric copolymer films 92
 pyro-phototronic effect 106–107
 based UV sensors 107
 Pyrocam detector 72

- pyroelectric $\text{Al}_{1-x}\text{Sc}_x\text{N}$ (AlScN) thin films 99
- pyroelectric calcium lead titanate (PCT) thin films 86, 87
- pyroelectric coefficient 19, 20, 55 primary 20, 32, 33 secondary 20, 32
- pyroelectric crystal symmetry 20, 35–37, 72, 221, 222, 224, 226–231
- pyroelectric detectors element 56 theory of 57–61
- pyroelectric device configurations 120
- pyroelectric effect 19–21, 32, 33–35, 55, 56, 67, 86, 99, 102, 103, 106, 122, 143, 144, 156, 177, 183, 185, 188, 191, 192, 195–197, 210, 222, 224, 229, 230
- pyroelectric energy harvesting (PyEH) 173–211 theory of 175–177 thermodynamic cycles 178–181
- pyroelectric fusion 221 history of 221–224
- pyroelectric neutron generator 224–229
- pyroelectric X-ray generators 229–233
- pyroelectric generators (PEGs) 28, 181–182, 233 conceptual model of 176
- pyroelectric infrared detector array 84
- pyroelectric infrared sensor 80
- pyroelectric IR detector(s) 120 graphene pyroelectric bolometer 161–165
- hybrid focal plane array detector 126–127
- integrated resonant absorber pyroelectric detector 148–150
- linear array detector 127–131
- periodic domain TFLTTM detector 131–138
- plasmonic IR detector 155–161
- resonant IR detector 150–155
- TADPH polymer detector 146
- TFP polymer detector 143
- thick film detectors 120–123
- thin film detectors 123–126
- pyroelectric LiTaO_3 single-channel detectors 70
- pyroelectric materials 62 aluminum nitride 98–102 ceramic-polymer composites 90–96 gallium nitride 102–103 lead-free ceramics 96–97 organic polymers 87–90 single crystals 63 barium strontium titanate 72–75 lithium tantalate and niobate 67–72 strontium barium niobite 75–77 zinc oxide 103–107
- pyroelectric nanogenerators (PyNGs) 183 ceramic based 198–208 polymer-based 183–198 thermal nanophotonic-pyroelectric nanogenerators 208–210
- pyroelectric neutron generator (PNG) 28, 195–196, 224–229
- pyroelectric thermal detectors, advantages of 119–120
- pyroelectric X-ray generators 229–233
- pyroelectricity 19, 55 history of 21–31
- pyroelectric crystal symmetry 36–37 simple model of 33–35 theory of 32–33
- PZT based pyroelectric nanogenerators 201–204
- PZT micro/nanowire based PyNG 202
- PZT-based hybrid NG 203
- PZT-PAni/PVDF composite films 93
- PZT/PVDF-TrFE composites 93

q

- quad-wavelength detector 156–157, 159
- quantum detectors 119

- quarter cut schematic representation, of pyroelectric detector 100
- quartz 24–25, 124, 132, 151, 154
- α -quartz 21
- quartz plates 25
- r**
- rare-earth (RE) dopant effect, on SBN50 ceramics 76
- relative permittivity 1, 5, 7–10, 12, 59, 62, 92, 164
- relaxations 3–6, 45, 94, 99, 145
- remnant polarization 39, 76
- resonances 5–6, 89, 103, 151–152, 156–160
- resonant IR detector 150–151
- differential operation and detector arrays 154, 155
- GaN resonators performance 155
- IR absorbing coatings and structures 152–153
- operation principles 151–152
- rigid ion model 32
- Rochelle salt 23, 26, 39
- room temperature ultraviolet (UV) detection 105
- s**
- scanning probe microscopy (SPM) 45
- secondary pyroelectric coefficient 20, 32
- secondary pyroelectricity 20–21, 69
- second-order phase transitions 40–41, 63
- Sharp–Garn method 102
- single crystalline lead-free KNbO₃ NW/PDMS polymer composite based PyNG 204
- single-channel LT pyroelectric detector 71
- single-layer graphene (SLG) 162–164
- SiO₂-doped Ba_{0.85}Sr_{0.15}TiO₃ glass-ceramic (g-c) films 74
- soft-mode 45–46
- solar, mechanical and thermal hybrid NGs 198
- space (surface) charge polarization 3
- space charge polarization 2–5
- Spiricon Pyrocam™ III camera 72
- spontaneous polarization (P_s) 32–35, 38–39, 41–42, 55–57, 63–64, 69, 75, 85, 88, 104, 139, 176, 178, 183, 192, 210, 231
- stretchable tribo/piezo/pyroelectric hybrid NG 192
- strontium barium niobite (SBN30)/polyurethane (PU) nanocomposites, pyroelectric property of 76
- strontium barium niobite crystals 63, 75–77
- struvite 25
- t**
- TADPh film based pyroelectric detector
- design 147
 - sensitivity 147–148
- D-tartaric acid 25
- L-tartaric acid 25
- tartrate of soda and potash 23
- temperature coefficient of resistance (TCR) 161–162, 164
- tensorial pyroelectricity 21
- terahertz pyroelectric detector 70–71
- terahertz thermal detectors 139
- tertiary pyroelectric effect 21
- TGS-PVDF composite 90
- thermal detectors 70, 86, 119, 131, 139–140, 162
- thermal energy harvesting technologies 173–174
- thermal hybrid NGs 194, 198
- thermal imaging sensor 26
- thermal nanophotonic-pyroelectric nanogenerators 208–210
- thermodynamic cycles, of PyEH 178
- Carnot cycle 178–179
 - Ericsson cycle 179–180
 - Olsen cycle 180, 181

- thermoelectric coolers (TEC) 66,
225–226
- thick film detectors 120–123
- thick film transfer (TFT) technique 86
- thin film detectors 123–126, 134
- thin film lithium tantalate (TFLTTM)
pyroelectric detector 131
applications 132
attached to metalized silicon
134, 135
domain engineered 137–138
domain engineered detector 134
fabrication process 132
large aperture devices 136–137
on ceramic 135–136
poly-vinylidene fluoride polymer
detector 140–143
terahertz thermal detectors
139–140
- thin film polymer based PyNGs 184
- thin-film pyroelectric (TFP)
detector 77, 86, 143–144
sensor 123
- thin-film technology 120, 154
- TO-packaged 5-mm aperture TFLTTM
pyroelectric detector 136
- topaz plate 25
- total and specific dielectric losses 14–15
- tourmaline 21–26, 34–35
- triboelectric nanogenerators (TENGs)
192
- triboelectric-piezoelectric-pyroelectric
hybrid NG 196
- triglycine sulfate (TGS) 35, 120
crystal 63–66
- structure 63
- temperature dependence of merit
figure 64
- two-crystal system inside vacuum
chamber 226
- U**
- ultra-thin (45 µm) p-Si/n-ZnO
heterojunction PD 201
- UV nano-sensor based on *p*-Si/*n*-ZnO
NWs heterojunctions 106
- V**
- vacuum permittivity 8–9
- W**
- waste heat 173, 183, 208–209
- water vapor-driven PyNG 184–185
- wearable PyNG 188–189, 204
- wind flow driven PVDF-based PyNG
184–185
- wurtzite *n*-type GaN films, pyro-effect in
102
- wurtzite-structured ZnO NWs 106
- Z**
- zinc oxide (ZnO) 103
based pyroelectric nanogenerators
198–201
- based UV photodetectors 105
- film, for pyroelectric sensors 104
- nanowire array-P3HT film
heterojunction 197
- zone-boundary phonon 46
- zone-center phonons 46

