

Index

a

- additive-assisted crssystallization 39–40
- aluminum nitride (AlN) 118
- ambipolar transport behaviors of OSCs 56
- aminopropyl triethoxysilane (APTS) 97
- anthryl surface group 133
- attenuated-total-reflection Fourier transform infrared (ATR-FTIR) 123
- Au/TTF-TCNQ electrodes 88
- azobenzenes 72

b

- band bending, in OSCs 77
- BBL/PBZT binary semiconductor blends 46
- BC pentacene-based OFETs 94
- benzenethiol (BT) derivatives 100
- bilayer heterojunction approach 158–159
- bilayer heterojunction sensor 158
- bilayer lipid membranes (BLMs) 161
- biocompatibility of organic materials 180
- 1,2,3,4-bis(*p*-methylbenzylidene) (MDBS) 41
- 1,3:2,4-bis(3,4-dimethylbenzylidene) sorbitol (DMDBS) 41
- blade coating method 50

c

- carbon-based molecular junctions 99
- carbon electrode-molecule junctions 98
- carbon nanomaterial-based electrodes 92–97
- C₈-BTBT/C₆₀ heterojunction 60
- C₈-BTBT molecular crystals 96
- C₈-BTBT:PSS crystal films 45
- cell culture, electrochemical control of 167
- cell sensors 168–170
- charge insertion layer (CIL) 2, 7
 - chemical structures 8
 - DNA and graphene oxides as 9
 - metal oxides for 7–8
 - metal salts as 9
 - organic polymers with dipolar groups as 9
 - organic small molecules as 9
 - OSC/electrode interface 84–89
- charge-transfer (CT) interactions 65
- charge trapping-induced memory effect 69–72
- 1-chloronaphthalene additives 37
- C₁₆IDT-BT conjugated polymer binder 50
- CNT arrays 92
- co-crystal engineering 64, 68
- concave-convex interactions 64, 68
- conjugated polymer/elastomer phase separation-induced elasticity (CONPHINE) method 55

- conjugated polymer films,
microstructures of 36
- conjugated polymer semiconductors 35, 52
- covalently bonded carbon-based
single-molecule devices 98
- covalent modification methods, SAM
of dielectrics 12–14
of electrodes 12–13
- CuPc monolayer 58, 59
- Cytop, as dielectric layer 123
- d**
- dash-line lithography (DLL) approach
98
- device/brain interfaces 173
- diarylethenes (DAEs) 72, 73
- dielectric capacitance 104, 134
- dielectric constant 40, 105, 123, 160
- dielectric microstructure design
nano fabrication 116–118
roughness effect 114–116
self-assembled morphology 118–120
- dielectric surface energy control
SAM modify 106–112
surface modification with polymers
112–113
- dielectric surface passivation methods
9–11, 121–126
- 1,8-diiodooctane (DIO) 38, 39
- 2,7-dioctyl[1]-benzothieno[3,2-b][1]
benzothiophene (C₈-BTBT) 43
- diphenyl ether (DPE) 37
- dipyrrolopyridine derivative 65
- direct surface functionalization method
97
- “disorder-free” conjugated polymer
IDTBT 36
- “disorder-free” polymer semiconductors
36
- dithiocarbamate (DTC)-based molecules
12
- doping effect, of OSC channels 48
- DPP-based polymers 37, 39, 68
- DPP2T/PS composites 52
- droplet-pinned crystallization (DPC)
method 59, 60
- DTC-piperazine/piperidine-R motif 82
- DTPTP₂-TCNQ CT complexes 64
- e**
- EGOFET-based sensors 160–162
- electric double layer (EDL) 142
- electrochemical OH electron-trapping
mechanism 123
- electrocorticography (ECOG) 171
- electron injection, from metal electrode
into semiconductor 78
- energy gap 55, 105
- ExBox₂⁴⁺ 68
- f**
- feedback-controlled electroburning
process 99
- (3-pyrrolinium)(CdCl₃) ferroelectric
heterojunction 60
- flexible bioelectronics 170–174
- fluid-enhanced crystal engineering
(FLUENCE) 35
- fluid shear stress (FSS) 169
- fluorinated diF-TESADT 84
- Fowler-Nordheim (F-N) tunneling 78
- FT-FET-integrated polymer light-emitting
diode 54
- fullerene derivatives 68
- g**
- gap dielectrics 124–126
- Gaussian disorder model 128
- graphene-based pentacene OFETs 96
- graphene film vs. CNT electrode 97
- graphene, work function value of 94
- h**
- H-bonded supramolecular single-crystal
OFET 67
- heterostructured top gate/top contact
(TGTC) OFETs 96
- high boiling point solvent additives
37–39

high-*k* materials 14, 126, 131
 high-performance scalable flexible
 optoelectronics 180–181
 high-quality OSC films 180

i

insulating polymers, general
 requirements for 50
 integrated OFET-OECTs 176
 integrating memory effect 148–154
 interfacial modification methods
 covalent modification methods
 12–29
 development of 31
 noncovalent modification methods
 7–11

l

Langmuir-Blodgett (LB) technique 59,
 108
 Langmuir films 59
 Langmuir-Schaefer (LS) technique
 59
 light/cell/device interfaces 174–177
 long-range ordered single-crystal film
 59–60

m

magnetic sensor 147–148
 mean molecular area (MMA) 108
 ME coupling effect 147
 meso-diphenyl
 tetrathia[22]annulene[2,1,2,1]
 (DPTTA) 63
 metal salts 9, 87, 88
 modified diketopyrrolopyrrolethieno
 [3,2-*b*]thiophene copolymer
 (DPPT-TT)-based OFETs 88
 molecular level heterojunction 57,
 61–65
 molecular template growth (MTG)
 57
 monolayer field-effect transistor (MFET)
 157
 monolayer functionalization 156–157

multifunctional molecular-level
 heterojunctions, based on
 mechanically interlocked
 molecules (MIMs) 65
 multifunctional sensors 148, 183

n

nanoconfinement effect 50–55
 nanoimprinting lithography (NIL) 116
 naphthalene diimide derivatives (NDIs)
 156
 n-channel C₆₀ OFETs, carrier injection in
 89
N-heterocyclic carbenes (NHCs) 12
 noncovalent modification methods
 charge insertion layer at electrode
 surface 7–9
 dielectric surface passivation methods
 9–10
 nonelectrogenic cells 166–170
 non-ohmic contact 77
 nonsolvent additives 37–39
 n-type F₁₆CuPc-based organic transistors
 88

o

OCET-based, EGOFET-based sensors
 160–162
 octadecylsilanes (OTSs) 106
 odd–even effect 82
 off-center spin-coating method 49
 Ohmic contact 9, 77, 79, 86, 89, 92,
 97
 organic bioelectronics 166, 170, 171
 organic/2D heterostructures 181
 organic field-effect transistors (OFETs)
 architecture 2
 CNT composites as source/drain
 electrodes in 94
 different interfaces in 1–3
 graphene-based carbon electrodes for
 95
 interface engineering in 3–4
 interfaces in 2
 MWCNT electrodes 92

- organic field-effect transistors (OFETs) (*contd.*)
 - OECTs
 - with nonelectrogenic cells 166–170
 - sensors 165
 - organic semiconductors (OSCs) 33
 - C₅-BTBT as 71
 - heterojunctions 56
 - polymer trap blends 71
 - OSC/electrode interface
 - carrier injection characteristics 77
 - work function tuning 79
 - carbon nanomaterial-based electrodes 92–97
 - charge insertion layer modification 84–89
 - covalent bond formation at molecular level 97–100
 - polymer-based electrodes 89–92
 - SAM modification 80–84
- p**
- paraffinic triptycene 10
 - PA-SAMs 14, 20, 131, 133, 135
 - PEDOT/PSS water-based conjugated
 - π -electron bonding system 89
 - persistent photocurrent (PPC) 144
 - perylene-TCNQ system 64
 - phase separation 46
 - of multicomponent systems 45
 - of OSC/insulator polymer blends 46
 - phosphonate ester derivative-based SAM molecules 14
 - phosphonic acid (PA) 14, 20, 110, 126, 131, 136, 139
 - photochemical F-AZO
 - modification-induced modulation, of Au work function 102
 - photochromic blends, interfacial energy diagram of 73
 - photochromic molecules (PCMs) 72, 144
 - photochromism-induced switching effect 72–75
 - photo hybrid bilayer dielectric (PHBD) 144
 - photo-patternable crosslinked PSS/MWCNT composites 94
 - photoresponsive cell/device interfaces 175
 - photoresponsive dielectrics 142–144
 - P3HT crystalline nanowires 92
 - P3HT films, hole mobility of 41
 - P3HT/PCBM heterojunction 59
 - P3HT/PDMS blend 52
 - P3HT/PS blend-based transistors, FET performance of 48
 - P3HT/PS blends 48
 - P3HT/SEBS blend 52
 - P3HT, solution-based self-assembly of 40
 - P3HT/SP blend-based OFET 74
 - P3HT/SWNT composite electrodes 91
 - planar bilayer heterostructures 57–61
 - polarity, of dielectric interface 128
 - polycrystalline dinappolycrystalline dinaphtho[2,3-*b*:2',3'-*f*] thieno[3,2-*b*]thiophene (DNTT) structure fabrication 49
 - polyethylene naphthalate (PEN) 136, 141
 - polymer-based electrodes 80, 89–92
 - polymer dielectric modification 11
 - polymer encapsulation 9, 122, 124
 - polymorphism 34
 - porcine odorant-binding proteins (pOBPs) 160
 - pressure sensor 141, 145–147, 177
- q**
- quasi-1D CNT electrodes 92
 - quasi-Langmuir-Shafer (QLS) method 59
- r**
- reduced graphene oxide as contact electrodes, in BGBC pentacene transistors 97
 - remote floating gate 159–160
 - Richardson-Schottky emission 78

S

- SAM/high-*k* dielectrics 131–137
 - SAM-modified high-*k* dielectrics 14, 20, 21, 132–134
 - SAM modification of electrodes 12
 - SAM/SiO₂ dielectrics 14, 16, 126, 127, 131
 - Schottky contact 77
 - self-assembled monolayer field-effect transistors (SAMFETs) 28
 - applications 29
 - device performance 30
 - molecular structures of OSCs 29
 - molecule design for 137–139
 - morphology control of 139–141
 - N-type 29
 - organic semiconducting molecular design 28
 - self-assembly 28, 29, 40, 42, 52, 65, 68, 80, 118, 151
 - semiconductor/electrode interface 77
 - electrically stimulated switching of charge-injection barrier 100
 - installing switching effects 100–102
 - semiconductor/semiconductor interface 33
 - charge trapping-induced memory effect 69–72
 - heterojunctions 55
 - material's nucleation and morphology 37
 - blending with insulating polymers 45–50
 - blending with polymer elastomer 50–55
 - nucleating agents influence on 41–42
 - solvent additives influence on 37–41
 - template-mediated crystallization 43–45
 - molecular level 61–64
 - photochromism-induced switching effect 72–75
 - planar bilayer heterostructures 57–61
 - supramolecular arrangement 64–69
 - silane-based SAM molecules 12
 - skin-inspired electronics 177
 - SKPM 130
 - solid solution crystal, of p-type and n-type OSCs 64
 - spin-casted CuSCN 88
 - spin-coating technique 108
 - spiropyrans 72
 - spirothiopyran (SP) photoisomerization 100
 - stereoelectroencephalography (SEEG) 171
 - sulfur dioxide (SO₂) detection 156
 - supramolecular arrangement
 - of heterojunctions 64–69
 - of OSCs 64
 - suspended gate OFET (SGOFET) 145
- t**
- template-mediated crystallization (TMC) method 43–45
 - template-mediated molecular crystal seed (TMCS) method 45
 - tetrathiafulvalene-tetracyanoquinodimethane (TTF-TCNQ) co-crystals 61
 - thermal sensor 141, 145, 147
 - thermal stability 73, 103, 144, 147, 181–183
 - thiolate-gold bond 12, 80
 - thiolate-SAMs 82
 - threshold voltage 48, 50, 69, 71, 87, 91, 103, 113, 121, 130, 133, 134, 142, 144, 155, 161
 - TIPS-pentacene, contact-induced nucleation of 84
 - TIPS-pentacene thin films 35
 - top-contact (TC) OFETs 79
 - transducer, OFETs as 155
 - transparent and flexible OFET (tf-OFET) 148

(tridecafluoro-1,1,2,2,-tetrahydrooctyl)
trichlorosilane (FTS) 97

trisradical tricationic complex,
self-assembly and solid-state
semiconducting properties of
65

tris-*tert*-butyl-1,3,5-benzenetrisamide
(BTA) 41

U

UV-cross-linked PAA/PSS-MWNTs, work
function of 94

V

vertical phase separation, C₈-BTBT and PS
49

W

water-gated organic FET (WGOFET)
sensor 160

weak epitaxy growth (WEG) method 57

work function, of PEDOT/PSS 91

X

X-ray reflectivity (XRR) 138

