

Index

a

active dielectrics 40–43, 51
 aerospace electrical equipment
 epoxy resin nanocomposites 284, 285
 insulating materials
 breakdown strength reduction
 277–278
 increased dielectric loss factor
 275–276
 partial discharge and accelerated
 aging 278–279
 space charge accumulation and
 electric field distortion 276–277
 substantial drop in resistivity
 272–275
 vacuum surface flashover voltage
 279–280
 polyetherimide nanocomposites
 282–284
 polyimide nanocomposites 280–282
 polytetrafluoroethylene composites
 285–288
 strong insulating polymer dielectrics
 characteristics of polyimide
 305–307
 corona resistance life of polyimide
 304–305
 electrical tree characteristics
 301–302
 micro/nano-doped epoxy resin
 composites 302–304

strong nonlinear conductivity
 charge accumulation and electric
 field distortion 288–290
 high energy electron irradiation and
 working voltage 290–292
 nonlinear conductivity 292–295
 vacuum DC surface discharge
 incident electron beam
 characteristics 297–298
 insulation distance and electrode
 height 298–300
 effect of electron beam irradiation
 296–297
 mechanism of 296–297
 affinochromism 332
 alicyclic amine (ACA) 88
 aliphatic epoxy resins 182
 all-organic polymer composites 92–94
 polymer blends 90–92
 polymer doped with organic fillers 92
 aromatic polymer 67, 243, 244, 246, 257
 atomic layer deposition (ALD) 83, 242

b

benzocyclobutene resin 165–167
 benzoxazine resins 167, 195
 biaxial-oriented polypropylene (BOPP)
 58, 240
 bipolar charge transport processes 290
 bis(benzocyclobutene) (c-BCB) 70
 bismaleimide 194, 201, 202, 215

- bisphenol-A epoxy resins 88, 182, 229, 343
- Boltzmann constant 47, 62, 274
- boron nitride nanosheet (BNNS) 13, 71, 170, 245, 248, 280
- C**
- carbon neutrality 57, 106
- charge-discharge efficiency 58, 60, 72, 73, 94, 248
- chemical vapor deposition (CVD) 80, 83
- Clausius and Mosotti/Lorentz model 28, 30
- Clausius equation 61
- commercial high-temperature polymer 9–11
- composite materials 13–14
- conduction phenomena 38–40
- conjugated polymers 88, 324, 325, 330–334
- copper-clad laminate (CCL) 157, 181, 192, 202–203, 205
- core@shell nanofillers
inorganic shells for 79–80
organic shells for 77–79
- corona resistance 15, 304–305
- cross-linked polymer 4, 12, 87–88, 248–250, 257, 348, 350
- cyanate resin (CE) 215, 233
- cyanylated polymer (PEEK-CN) 5
- cycloaliphatic epoxy resins 182
- d**
- Debye's equations 29, 33–34
- Debye's relaxation theory 34
- 4,4-diaminodiphenyl ether (4,4'-ODA) 73, 199, 236
- dicumyl peroxide (DCP) 87
- dielectric capacitor 57–59, 61, 63, 67, 85, 94
- dielectric constant 24, 26, 33, 43, 58, 61–63, 66, 70, 73, 80, 81, 84, 89, 116, 126, 129, 139, 156, 157, 160, 161, 164, 165, 167, 168, 170, 171, 195–197, 201, 202, 206–208, 210, 211, 215–217, 219–221, 241–245, 248–250, 252, 253, 274, 275, 277, 278, 280, 282, 287, 344
- dielectric loss factor 157, 164, 270, 275–276, 280–282, 288
- dielectric permittivity 2, 23–27, 29–34, 36, 41, 42, 44–46, 170, 172
- dielectric polarizability 24–27
- dielectric polymers 58–61, 63, 65–69, 72, 75, 80, 81, 83, 87, 90, 93–95, 159, 181, 221, 240, 243, 244, 248, 257, 283, 284, 314, 336, 337, 339, 343, 345, 346, 348, 351, 352, 369
- dielectric relaxations, in polymers 43–44
- dielectrics
active dielectrics 40–43
conduction phenomena 38–40
definition of 21–22
dielectric permittivity 23–27
dielectric polarizability 24–27
dipole moment and types of dielectric materials 22–23
heat capacity 47
polarization
static electric field 24–32
time varying electric field 32–38
polymer matrix composites 45–46
thermal/heat conduction 50
- dielectric spectroscopy 32, 125–130
- differential scanning calorimetry (DSC) 5, 254
- dipole moment 22–24, 26, 27, 29, 31, 41, 44, 61, 62, 70, 88, 94, 196, 215, 275, 307
- dipole's local electric field 27–29
- dry-type bushing 228–233
- dynamic dielectric analysis (DEA) 9
- dynamic thermomechanical analysis (DMA) 5–6
- e**
- electrical conductivity 59, 63, 65, 66, 75, 76, 83, 117, 129, 137, 275, 277, 293, 295, 332
- electric dipole 22, 23, 61

- electric packaging materials 154, 157, 159
- electronic displacement polarization 61
- electronic packaging
- composite dielectrics
 - inorganic fillers 169–171
 - inorganic porous fillers 171
 - organic porous fillers 171–172
 - development of 150–152
 - high-temperature polymer dielectrics
 - benzocyclobutene resins 165–167
 - benzoxazine resins 167
 - epoxy resins 163–166
 - organic porous materials 168
 - polyaryl ether 167–168
 - polyimide 160–163
 - requirement of
 - dielectric properties 155–157
 - dynamic thermomechanical properties 157
 - moisture absorption 159
 - thermal conductivity 158–159
 - thermal expansion coefficient 157–158
 - encapsulated systems 324, 325, 333–335
 - energetic electron irradiation 280
 - energy density 46, 57–60, 72, 73, 84, 169, 248, 365, 366
 - energy storage
 - capacitors 57, 59, 62, 71, 72, 82, 86, 92, 365
 - density 60, 242, 243, 248, 257
 - parameters 60–61, 67, 68
 - engineering plastics 201, 241, 251–253, 257, 271, 366
 - EP/ZIF-8 composites 173
 - epoxy-based dielectric polymers 346
 - epoxy resin (EP) 163–165
 - curing agent 232
 - filling modification 232–233
 - molecular chain change 229–232
 - nanocomposites 284, 285
 - properties and application of 184–185
 - structure of 182–183
 - used for CCL in PCB 185–188
 - equivalent series resistance (ESR) 61
- f**
- film capacitors 59, 66, 67, 69, 88, 95, 227, 239, 240, 244, 249, 256, 257, 366
 - fire performance index (FPI) 121, 217
 - flame resistance 120, 121, 141
 - flip-chip package-on-package (PoP) 152
 - fluorinated PI 161, 163, 205
 - fluorinated polymers 4, 104, 244
 - fluorine-containing monomers 161, 162
 - Fowler–Nordheim tunneling 64, 66
 - frequency dependent dielectric permittivity 33–34
 - fusible polyimides 200
- g**
- glycidylamine epoxy resins 182
 - glycidylester epoxy resins 182
 - glycidylether epoxy resins 182
- h**
- heat capacity 4, 47–51, 159
 - heteroaromatic polymer 243, 244, 246, 257
 - high-angle annular dark field (HAADF) mode 78, 79
 - high-frequency power transformer 227–233, 256
 - high-performance polymer composites 160
 - high-temperature capacitor materials
 - all-organic polymer composites 92–94
 - polymer blends 90–92
 - polymer doped with organic fillers 92
 - conductive/semi-conductive fillers 74–76
 - core@shell nanofillers
 - inorganic shells for 79–80
 - organic shells for 77–79
 - electrical characteristics

- high-temperature capacitor materials (*contd.*)
 - dielectric breakdown strength 63–64
 - dielectric constant and dielectric loss 61–63
 - electrical conduction and charge injection 64–65
 - energy storage parameters 60–61
 - inorganic insulating fillers
 - with metal oxides 70–71
 - nitrides and fluorides 71–74
 - insulating and semi-conductive fillers 76
 - layered polymer composites
 - polymer films with inorganic layers 80–83
 - sandwich-structured nanocomposites 83–85
 - novel polymers
 - commercial high- T_g polymers 86–87
 - cross-linked polymers 87–88
 - polymers with polar groups 89–90
 - wide bandgap polymers 88–89
 - polymer/inorganic nanofiller composites 69–76
 - self-clearing abilities of 67–69
 - thermal characteristics of 65–67
 - high-temperature dielectric polymer
 - benzocyclobutene resins 165–167
 - benzoxazine resins 167
 - development
 - cost and scale-up production 367–368
 - polymer-based high temperature composites 367
 - temperature stability 365–366
 - epoxy resins 163–165
 - intrinsic high-temperature polymers 368–369
 - large-scale industrial production 370
 - organic porous materials 168
 - polyaryl ether 167–168
 - polyimide 160–163
 - polymer-based high temperature composites 369
 - polytetrafluoroethylene 240–242
 - polyvinylidene fluoride 242–243
 - high-temperature polymers
 - commercial high-temperature polymer 9–11
 - composite materials 13–14
 - development of 2–3
 - differential scanning calorimetry (DSC) 5
 - dynamic dielectric analysis (DEA) 9
 - dynamic thermomechanical analysis (DMA) 5–6
 - inorganic fillers 169–171
 - inorganic porous fillers 171
 - molecular structure modification 11–13
 - organic porous fillers 171–172
 - parameters of 3–5
 - static thermomechanical analysis (TMA) 7–8
 - thermal conductivity 8–9
 - thermogravimetric analysis (TGA) 6–7
 - high-temperature resistant dielectric material for IGBT
 - engineering plastics 252–256
 - silicone gels 251–252
 - high-temperature resistant dielectric material for capacitor
 - crosslinked polymer 248–250
 - high-temperature dielectric polymer 240–245
 - nanocomposite material 245–248
 - hollow glass microsphere (HGM) 171, 210, 214
 - 1,3-2 (4-hydroxyphenyl) amamantane diglycidyl ether (DGEBAD) 230
- i**
- ILD/IMD materials, in advanced microchips 160
 - inorganic dielectric 1

- inorganic fillers 2, 13, 14, 79, 117, 119, 159, 160, 169–171, 197, 218, 234, 241, 257, 280, 284, 367, 368
- insulating fillers 70–72
- porous fillers 171
- inorganic nanoparticles
- inorganic shells for 79–80
- organic shells for 77–79
- insulated gate bipolar transistor (IGBT) engineering plastics 252
- silicone gels 251–252
- insulating materials 39, 43, 103–106, 110, 113–119, 121, 125–140, 184, 191, 192, 251, 269, 270, 272–280, 290, 295–297, 299, 301, 304, 313, 314, 324, 337
- integrated 5G/satellite 6G communication 149, 150
- integrated circuit (IC) 149, 185, 195
- interfacial polarization 25, 45, 61, 62, 80, 89
- intrinsic high-temperature polymers 14, 368–370
- intrinsic self-healing dielectrics by reversible bonds/interactions 348–351
- k**
- Kapton® polyimide (4,4'-oxydiphenylene-pyromellitimide) 104
- l**
- layered polymer composites
- polymer films with inorganic layers 80–83
- sandwich-structured nanocomposites 83–85
- life cycle control, of biomimetic smart materials 314
- limited oxygen index (LOI) 120
- linear phenolic resins 192–194
- liquid crystal polymer (LCP)
- structure and properties of 211–213
- used for PCB 213–215
- low-density polyethylene (LDPE) 81
- m**
- Maxwell–Wagner–Sillars polarization 62
- melting interdiffusion by
- magnetic/microwave heating of nanoparticles 337–341
- metal-organic frameworks (MOFs) 171, 217
- metal oxides composite 70, 71
- microcapsule-based self-healing dielectrics 342–348
- microcapsule-based self-healing methods 344
- microcapsule/polymer composites 333
- micro-multilayer multifunctional electrical insulation (MMEI) 112, 113
- micro/nano-doped epoxy resin composites 302–304
- montmorillonite (MMT) nanosheets 81, 330, 331
- Moore's law 155
- MXene 74, 75
- n**
- nanocomposites 74
- material 245–248
- sandwich-structured 83–85
- nitrides and fluorides composites 71–74
- nitrogen-containing phenolic resins 194–195
- non-fusible and insoluble PI 199–200
- nonlinear conductivity 288–295, 315–320, 322, 323
- novel polymers
- commercial high- T_g polymers 86–87
- cross-linked polymers 87–88
- polymers with polar groups 89–90
- wide bandgap polymers 88–89
- o**
- Ohmic law 65
- Onsager model 30
- organic porous fillers 171–172
- organic porous materials 168
- orientation polarization 62, 89

p

- partial discharges 79, 109, 130–133, 233, 277–280, 302, 313, 337, 339, 342, 349
- pH-induced self-reporting technique 334
- phenolic CCL 192
- phenolic paper-based CCL 192, 196
- phenolic resins
 - properties and applications 191–196
 - structure of 188
 - synthesis of 188–191
 - thermoplastic 189–190
 - thermosetting 190–191
- 4-phenylethynylphthalic anhydride (PEPA) 87
- photochromic compounds 324–329
- photoswitchable conductive materials 325
- PI-based polymer nanocomposites 73
- plasma-enhanced chemical vapor deposition (PECVD) 83
- polarization
 - and dielectric permittivity 23–24
 - static electric field 24–32
 - time varying electric field 32–38
- polyaryl ether (PAE) 160, 167–168
- poly(aryl ether ketone) 79
- poly(aryl ether sulfone) 77, 245
- polybenzoxazine 167, 195–196
- polycarbonate (PC) 66, 243, 244
- polydiacetylenes (PDAs) 325
- polyether amine (PEA) 88
- polyetheretherketone (PEEK) 2, 66, 90, 106, 251, 254–256, 269
- 1,4-poly(ether fluoromethyl naphthalene amide) (PNFA) 90
- polyetherimide (PEI) 2, 59, 91, 112, 200, 243, 250, 255, 282–284
- polyimide (PI) 160–163
 - characteristics 197, 201
 - cross-linked structure 237–239
 - in double-sided copper laminates 203–205
 - filling modification 234–235
 - in flexible copper-clad laminate 202–203
- fusible 200–201
- nanocomposites 75, 280–282
- non-fusible and insoluble PI 199–200
- one-step method 197–198
- in rigid CCLs 201
- rigid groups 235–237
- three-step method 199
- two-step method 198–199
- polymer-based high-temperature composites 367–369
- polymer blends 90–92
- polymer matrix composites 45–46
- polymer nanocomposites 60, 67, 70–74, 76, 77, 79, 80, 94, 95, 248, 280, 338
- polymers of intrinsic microporosity (PIMs) 89
- polyoxafluoronorborene (POFNB)
 - polymers 11, 88
- polyphenylene oxide 207, 218–220
- polyphenylene sulfide (PPS) 11, 58, 214, 241, 243, 244, 251, 253, 366
- poly(phthalazinone ether ketone) (PPEK) 11, 66
- polytetrafluoroethylene (PTFE) 240–243
 - and breakdown strength measurement 287
 - composites 285–288
 - microstructure formation process 287
 - structure and properties of 207–209
 - used for PCB 209–211
- polyvinylidene fluoride (PVDF) 58, 242–243
- poly(vinylidene fluoride-co-hexafluoro propylene) (P(VDF-HFP)) 74
- Poole–Frenkel emission 65, 275
- power and electronic equipment 269, 270, 320
- power cables
 - aging and degradation 137–140
 - development and insulating materials 103–106
 - dielectric spectroscopy 125–130
 - extrusion technology 110–112

- insulating material
 - chemical resistance 122–125
 - corrosivity 121
 - electrical requirements 116
 - environmental and functional considerations 119
 - flame resistance 120–121
 - heat release 121–122
 - mechanical requirements 118–119
 - radiation resistance 122
 - recapitulation of 125
 - smoke evolution 121
 - thermal requirements 117–118
 - toxicity 121
- micro-multilayer multifunctional electrical insulation (MMEI) 112–113
- partial discharges 130–133
- space charge and DC conductivity 133–137
- wrapping technology 106–110
- power density 57, 61, 106, 158, 164, 228, 248
- PP/MgO/PP-g-mah nanocomposites 77
- printed circuit board (PCB)
 - epoxy resin 182–188
 - phenolic resins 188–197
 - polyimides 197–206
 - polymer materials 206–221
- pyromellitic dianhydride (PMDA) 9, 73

- r**
- radiation resistance 10, 122, 124, 161, 200, 242, 269, 270
- renewable energy 57, 58
- roll-to-roll processed capacitor 58

- S**
- sandwich-structured nanocomposites 83–85
- sandwich-structured PAI composite film 8
- Schottky emission 64–66, 79, 81, 88, 302, 316
- secondary electron emission avalanche (SEEA) model 296
- self-adaptive dielectrics (SADs) 314–324
- self-clearing processes 67, 69
- self-cross-linking poly(arylene ether nitriles) (PEN) 12
- self-healing dielectrics
 - expectations 336–337
 - intrinsic self-healing dielectrics by reversible bonds/interactions 348–351
 - melting interdiffusion by magnetic/microwave heating 337–341
 - microcapsule-based self-healing dielectrics 342–348
- self-reporting dielectrics (SRDs)
 - conjugated polymers 330–333
 - encapsulated systems 333–335
 - photochromic compounds 325–330
 - stimuli-response materials and sensing materials 324
- silicone gels 251–252
- silicone rubber (SiR) 269, 317, 319, 322, 323
- smoke evolution 121
- solid dielectrics 1, 35, 36, 51, 277, 278, 337
- space charge-limited current (SCLC) 65, 273, 274, 294
- space charge phenomenon 134
- space charge polarization 89
- SP photoswitchable solvatochromism 329
- static dielectric permittivity 27, 29–32
- static thermomechanical analysis (TMA) 7–8
- stimuli-response materials 324
- stored energy density 57, 58, 60
- sulfonylated polymer (PEEK-SO₂) 5
- surface flashover 279–280, 296, 298, 321
- system-in-package (SiP) design 151, 152

t

Teflon® 104, 105, 107, 108

Tefzel® 104, 112

thermal conductivity 2, 5, 8, 9, 13, 50,
51, 63, 67, 72, 75, 76, 80, 117, 118,
141, 153, 154, 158–159, 164, 169,
170, 172, 187, 205, 206, 209, 210,
241, 242, 277, 368, 370

thermal/heat conduction 50

thermal interface materials (TIMs) 153,
154, 159, 170thermally conductive and dielectric
polymer composites (TDPCs) 159thermogravimetric analysis (TGA) 6–7,
139, 231

thermoplastic phenolic resins 188–190

thermosetting phenolic resin 188–191

triallyl isocyanurate (TAIC) 87

tung oil-modified phenolic resin
192–193**v**

vacuum surface flashover 279

w

wide bandgap polymers 88–89

y

Young's modulus 63, 70, 90

