

Index

a

aa phase, orthorhombic symmetry 258
 acoustic filters 253–255
 active EC regenerator (AER) 439–441
 actuators application 158–159
 adaptive lenses (ALENS) 44
 additive manufacturing (AM) 213–216,
 500, 502–503, 513–514, 584
 AgNbO_3 (AN) 382–384, 561
 AlN thin films 255
 antiferroelectric ceramics 377–384
 AgNbO_3 -based antiferroelectric
 ceramics 382–384
 NaNbO_3 (NN) 381–382
 (Pb, La)(Zr, Sn, Ti) O_3 -based
 antiferroelectric ceramics
 380–381
 PbZrO_3 (PZ) 379–380
 application specific integrated circuit
 (ASIC) 577
 $(\text{ATHP})_2\text{PbBr}_2\text{Cl}_2$ 127–128
 Aurivillius phases 209, 219
 Aurivillius single-crystal particle 209
 avalanche breakdown 348–349

b

BaO-TiO_2 system 531
 barium strontium titanate-
 polydimethylsiloxane (BST-PDMS)
 porous foam 510, 512
 barium titanate (BT)
 atomic structure and physical origins
 75–76

ceramics 429–431
 Curie temperature 72
 high-piezoelectric BT-based ceramics
 69–71
 isovalent cations 68–69
 phase structure 67–68
 physical and structure mechanisms
 73
 piezoelectric properties of 69
 barium titanate nanoparticles (BTNPs)
 587–588
 BaTiO_3 -based ceramics 316–320,
 373–376
 $\text{Ba}(\text{Zr,Ti})\text{O}_3$ (BZT) based ceramic films
 376
 Bi atoms in BIT 168
 biaxially orientated polypropylene (BOPP)
 398–400
 biaxially oriented film preparation process
 356
 biaxially stretched dielectric polymer film
 355
 biaxial orientation process 354–355
 biaxial stretching 354–355
 Bi-based end-member mixing 149–150
 BiFeO_3 (BFO) 563
 based ceramics 325–327
 nanofilms 584
 binary relaxor-PT ceramics 219
 $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$ based ceramics 320–323,
 372–373
 $(\text{Bi}_2\text{O}_2)^{2+}(\text{A}_{m-1}\text{B}_m\text{O}_{3m+1})^{2-}$ 167

- biomedical applications, piezoelectric materials
 - bone/tissue regeneration 584–587
 - cancer therapy 590–592
 - implantable energy harvesters
 - self-powered systems 574–577
 - ultrasonic wireless-powered systems 577–580
 - neural stimulation 587–590
 - ultrasound imaging transducers 581–584
 - biomolecular materials 459–460
 - biosensing
 - biomedical pressure sensing 474
 - physical health monitoring 468–473
 - prosthetic devices 474–476
 - $\text{Bi}_{12}\text{PbO}_{19}$ (BP) compound 146
 - BiScO_3 - PbTiO_3 piezoelectric ceramics
 - actuators application 158–159
 - characteristics of
 - phase diagram of 143
 - preparation methods of 143–147
 - commercialization of 141
 - development of 141
 - energy harvester application IEEE 159–161
 - grain size effect 153–156
 - grain size of 141
 - MPB
 - A-site and B-site doping 148–149
 - Bi-based end-member mixing 149–150
 - Pb-based compound treatment 151–153
 - perspectives for 139–140
 - phase diagram of 142–143
 - preparation methods 141
 - sintering processing 145–147
 - synthetic method 144–145
 - research diagram of 139
 - transducers application 156–158
- bismuth ferrite
 - crystal structure 96–98
 - domain configuration 98–102
 - electrical properties
 - electro-strain 105
 - energy storage property 105–106
 - ferroelectricity 104–105
 - piezoelectricity 102–104
- bismuth-layered templates 212
- bismuth layer-structured ferroelectrics (BLSFs) 167, 192, 231
- bismuth oxide 167
- bismuth-oxygen layer 169
- bismuth titanate compound ($\text{Bi}_4\text{Ti}_3\text{O}_{12}$, BIT) 167
- $\text{Bi}_4\text{Ti}_3\text{O}_{12}$ (BIT)
 - based flexible yarn-based piezoelectric nanogenerator (FY-PNG) 531
 - crystal structure and phase transition of 168–170
 - electrical properties of 189, 191
 - complex impedance and electrical modulus analysis 183
 - dielectric relaxation process 186
 - ion-pair modification 186
 - microstructural components 188
 - $\text{Nb}^{5+}/\text{Ta}^{5+}/\text{Ce}^{3+}$ co-doped 187
 - potential application of 182
 - resistivity of 185
 - fabrications of
 - preparation process based on external field 172
 - preparation process based on templates 175–177
 - ferroelectric domain structure of ceramics 179–181
 - crystal 178–179
 - space group analysis of 177–178
 - high-temperature applications based on 192–195
 - irradiation effect on 192
 - mechanical fatigue behavior of 191
 - synthesis of 170–172
 - thermal depoling behavior of 191–192
- $\text{Bi}_4\text{Ti}_{2.98}(\text{WNB})_{0.01}\text{O}_{12}$ 188, 191
- blended Polymers 389–391
- BNNS 397–399
- BNT-8BA ferroelectric ceramics 560

- BNT-based ceramics 90, 93, 95, 225, 231, 315, 320, 322, 323, 432, 433
- BNT-based material systems 86
- BNT-BT textured ceramics 225, 228
- bone/tissue regeneration 574, 584–587
- breakdown mechanisms 348
- electromechanical breakdown 349–350
 - intrinsic breakdown 348–349
 - partial discharge breakdown 350
 - thermal breakdown 350
- breakdown voltage down strength 348
- Bridgman method 66, 271
- BS-PT binary phase diagram 141
- BT-based ceramics, piezoelectrics 228
- BT@SO/PVDF nanocomposite 394
- bulk ceramics 424
- barium titanate 429–431
 - BNT 431–433
 - ferroelectric-ferroelectric phase transition 428
 - first-order and second-order phase transitions 428
 - KNN 433
 - PMN-xPT 434–435
 - preparation process 428
 - properties 429
 - PST 435
 - PZT 433–434
- burnt-out polymer spheres method (BURPS) 500–502
- c**
- calcium barium zirconate titanate (BCZT) 375, 396, 498, 505, 525, 527
- cancer therapy 590–592
- cancer treatment 455, 464, 476–479, 591, 592
- capacitive micromachined ultrasonic transducers (cMUT) 254, 255
- carbon-polyvinylidene fluoride-barium titanate (C-PVDF-BTO) porous composite 510, 512
- ceramic preparation methods 175, 177
- CMOS (complementary metal–oxide–semiconductor) platform 253
- $[C(NH_2)_3][ClO_4]$ (guanidinium perchlorate) 121
- composite dielectric materials
- core-shell-filled nanocomposites 398
 - high-temperature nanocomposites 398–400
 - 0D-filled nanocomposites 394–395
 - 1D-filled nanocomposites 395–396
 - 2D-filled nanocomposites 396–398
- constant temperature growth 273
- conventional biaxially oriented equipment 355
- converse piezoelectric effect 1, 3–4, 6, 129, 313, 495
- copolymerization of PVDF 387
- co-precipitation method 171, 174
- core-shell-filled nanocomposites 398
- core-shell structure 61, 375, 377, 463, 464
- c phase, tetragonal symmetry 258
- crystal classes 10, 11, 14, 23, 25
- crystal growth of KNN and KTN single crystals 271–274
- crystalline phases, of KNN thin films 261
- crystallographically oriented ceramics 201
- crystallographically textured ceramics 201
- CTFE 330, 387, 388
- Curie-Weiss law 295
- Czochralski method 117, 271
- d**
- DC resistivity of BIT-based components 187
- degassing and co-firing 352
- D–E hysteresis loops of linear and nonlinear dielectrics 343
- depolarization phenomenon 86–89, 560
- depolarization temperature 86, 88, 89, 99, 106, 148, 153, 225, 320

- dielectric capacitors 341, 342, 393, 400–402, 561
- dielectric ceramics 342, 353, 354, 365
- dielectric dispersion 36, 183, 186, 317
- dielectric energy storage materials
 - applications 356–357
 - breakdown mechanisms 348
 - key parameters of 342–345
 - MLCCs 351, 354
 - organic thin film capacitors 354–356
 - polarization mechanisms 345–347
- dielectric materials, energy storage 342
- dielectric organic materials 342
- N,N*-Dimethylformamide (DMF) solvent 385
- Dion–Jacobson compounds 209
- dipolar polarization (P_d) 345–347
- direct electrical stimulations 587
- direct ink writing (DIW) 502, 503
- direct piezoelectric effect 1, 3, 5, 261–263, 495, 496
- direct writing AM 214, 215
- discharging density 344
- disease treatment
 - cancer 476–479
 - oral care 479
 - organs and tissues regeneration 476
- domain wall (DW) 98
 - domain structure vs. electrical properties 99–102
 - domain walls conductivity vs. electrical properties 102
 - motion 28–30
- e**
- Einstein summation rule 5
- electrical breakdown problems 566–567
- electrical response, of BFO-BT
 - ferroelectric ceramics 563
- electrical stimulation therapy 539–542
- electric energy storage 341
- electric-field-controlled two-dimensional optical beam scanner 307–308
- electroactive piezoelectric phase 499
- electrocaloric effect (ECE)
 - adiabatic entropy change and temperature change 424
- AER 439, 440
- bulk ceramics 424
- disadvantages 441
- ferroelectric ceramics
 - bulk ceramics 428–435
 - ceramic films 424–428
 - MLCs 436–438
- heat transfer stages 443
- liquid pumping systems 443
- refrigeration 423, 438
- rings 442
- solid-state coolers 441
- electromechanical breakdown 348–350
- electromechanical breakdown strength (E_{em}) 350
- electromechanical coupling properties of piezoelectric materials 467, 487
- electron backscatter diffraction (EBSD) technique 208, 209
- electronic breakdown 348, 349
- electronic breakdown strength 348
- electronic polarization (P_e) 345–347
- electron microprobe analysis (EMPA) 274
- electro-optic effect of KTN crystal 292–294, 302–304
- electrostatic dielectric capacitors 393
- electro-strain 89–94, 105, 106, 286–291
- electrostrictive effect 311
 - applications 333–334
 - characterization of 312–314
 - fundamentals and history 311–312
 - lead-free piezoelectric ceramics 316–327
 - in piezoelectric materials
 - ferroelectric polymers 329–330
 - hybrid perovskite ferroelectrics 332–333
 - lead-based ferroelectrics 327–329
 - molecular ferroelectrics 330–332
 - optimization of electrostrictive strain 316
- electrostrictive polymers 333

- electrostrictive strain 322, 350
 - optimization of 316
 - temperature-stable 316
 - electrowinning 281
 - energy harvesters 237
 - application IEEE 159, 160
 - textured piezoceramics 237–239
 - energy harvesting 479, 487
 - flexibility 538–539
 - porous piezoelectric materials 496, 508–510
 - energy storage density, definition of 342
 - energy storage efficiency 343, 357, 363, 368
 - energy storage performance
 - of dielectric materials 344
 - of PZ-based AFE materials 380
 - energy storage properties
 - of high-entropy RFE ceramics 377–378
 - of high-temperature dielectrics 392–393
 - of NN-based dielectric materials 382
 - of PLZST-based antiferroelectric materials 381
 - of polymer blends 391
 - epoxy resin 161, 499, 514
 - equal-diameter growth of KTN crystal 277–278
 - Ewald sphere 17, 18, 20
 - explosive driven ferroelectric generator design 563–567
 - extrinsic and domain-wall motion
 - mechanisms of piezoelectricity 28–30
 - extrinsic microstructural characteristics 201
- f**
- fabrication of piezo-bioelectronic device
 - structure design 0D, 460–461
 - FEG pulsed power generation 567–569
 - ferroelastic switching 117, 118
 - ferroelectric ceramics
 - bulk ceramics 428–435
 - ceramic films 424–428
 - MLCs 436–438
 - ferroelectric generators (FEGs) 553, 554, 563–567
 - ferroelectric materials 553
 - applications
 - electrical breakdown problems 566–567
 - explosive driven ferroelectric generator design 563–566
 - FEG pulsed power generation 567–569
 - lead-free ferroelectric compounds 558, 561–563
 - lead zirconate titanate 554
 - PZST 556–558
 - PZT 52/48 557–558
 - PZT 95/5 554–556
 - ferroelectrics@polymer matrix composites 123
 - ferroelectrics 23
 - phase 170
 - polarization of BLSFs materials 170
 - polymers 329–330, 384–388
 - properties of $K_{1-x}Na_xNbO_3$ Crystals 285, 287
 - film capacitor 341, 342, 354–356, 394, 399
 - first law of thermodynamics 4
 - flexibility
 - development 521
 - electrical stimulation therapy 539–542
 - electromechanical conversion 521
 - energy harvesting 538–539
 - inorganic piezoelectric material 523–531
 - organic matrix 522
 - organic piezoelectric materials
 - bio-based materials 533–534
 - molecular ferroelectrics 534–535
 - organic-inorganic hybrid lead halide 533
 - PVDF 532
 - power supply 521

- flexibility (*contd.*)
 sensors 535–538
 working mechanism 522–523
- flexible molecular ferroelectrics 122
- fluorenyl polyester (FDAPE) 393
- flux method 36, 66, 271
- force-electrical effect 553
- freeze-casting method 504
- freeze-cast porous PZT ceramics 509, 510
- functional defects 257
- g**
- gel casting 500–502
- glass ceramics 365, 369–371
- gradient refractive index (GRIN) optical devices 304–305
- grain-oriented ceramics 201
- graphene nanoplatelet-loaded polydimethylsiloxane (GNPs-PDMS) patch 578
- guided bone regeneration (GBR) therapy 585
- h**
- heat treatment technology 172
- Hermann–Mauguin symbol 14
- heterostrain 93, 94
- hierarchically interconnected piezoceramic textile (HIPT) 526
- high-energy ball milling method 145, 172
- high-entropy relaxor ferroelectric ceramics 377, 378
- high-frequency array transducers 583
- high-performance piezoelectric biomaterials 587
- high-piezoelectric properties of KNN materials 269
- high-temperature BiScO₃-PbTiO₃ piezoelectric ceramics 139–162
- high-temperature nanocomposites 398–400
- high-temperature piezoelectric ultrasonic transducer (HTUT) 193
- high-temperature stability considerations 392–393
- hot forging (HF) 172, 175, 176, 195
- hot-pressing (HP) 144, 172, 175, 195, 231, 381, 531
- human epidermal growth factor type 2 receptor (HER2) 464, 465
- hybrid perovskite [(CH₃)₄N]MnCl₃ 116
- hybrid perovskite ferroelectrics 332–333
- hydrofluorocarbons (HFCs) 423
- hydrogel-based composites 126
- hydrothermal method 171, 172, 174
- hysteresis loop, defined 23
- i**
- ice template method 504
- ImClO₄@BC hydrogel composites 126
- imidazolium perchlorate (ImClO₄) 119, 120, 124, 126, 535
- implantable acoustic energy transfer and communication device (AECD) 578
- implantable energy harvesters
 self-powered systems 574–577
 ultrasonic wireless-powered systems 577–580
- inner electrodes preparation 352
- inorganic-based laser lift-off (ILLO) 458, 468
- inorganic bio-piezoelectric materials 455
- inorganic dielectric materials
 antiferroelectric ceramics 377–379, 384
 liner dielectric ceramics 365–371
 relaxor ferroelectric ceramics 371–377
- inorganic piezoelectric materials 456, 458
 BaO-TiO₂ system 531
 bismuth layer-structure 531
 FY-PNG 531
 hot-pressing process 531
 perovskite-structured materials
 components 523
 dipping method 526

- HIPT 526
 - (K,Na)NbO₃-based (KNN-based) 525
 - lead 523
 - nano-sized grains 526
 - 1D BaTiO₃ materials 525
 - PZT 524
 - self-assembled technology 525
 - stretchability and mechanical durability 525
 - thin film 527
 - 3D framework 527
 - two/three-dimensional 525
 - 2D piezoelectric materials 529–531
 - wurtzite-type materials 527–529
 - interface engineering 376, 394, 400
 - interfacial polarization (P_{int}) 96, 126, 132, 345, 347, 390, 398
 - intravascular photoacoustic (IVPA) transducer 582
 - intrinsic breakdown 348–349
 - intrinsic crystallographic characteristics 201
 - ionic polarization (P_i) 345–347
 - ionization and displacement effects 192
- k**
- Kerr effect (quadratic electro-optic effect) 292
 - (K, Na)NbO₃ (KNN)
 - based ceramics 323–324
 - thin films 259–261
 - K_{0.5}Na_{0.5}NbO₃ (KNN)-based ferroelectric ceramics 58, 66, 377, 433
 - KNN-based ceramics 51–65, 222–225, 323, 324
 - KNN 1-3 composites for ultrasound imaging transducers 582–583
 - KNN single crystals
 - crystal growth of 271–274
 - dielectric properties of 281–282
 - giant electro-strain of 286–291
 - high-piezoelectric properties of 269
 - piezoelectric and ferroelectric properties of 282–286
 - segregation effect of 274–277
 - structure of 278–281
 - top-seeded solution crystal growth 270–271
 - K15 sensor 193
 - KTN single crystals
 - crystal growth of 271–274
 - electro-optic effect of 292–294
 - electro-optic modulation devices based on
 - electric-field-controlled two-dimensional optical beam scanner 307
 - GRIN optical devices 304
 - photorefractive effect 306
 - equal-diameter growth of 277–278
 - near Curie temperature 295–298
 - structure origin of electro-optic effect in
 - linear electro-optic effect and ferroelectric domains structure 298–301
 - quadratic electro-optic effect and polar nano-regions 301–304
 - top-seeded solution crystal growth 270–271
- l**
- lamination 352
 - Landau free energy simulation 75, 76
 - large electro-strain 90–91
 - large-scale industrial production of dielectric films 354
 - lattice parameter of BIT 169
 - lattice parameters of K_{1-x}Na_xNbO₃ Crystals 279–280
 - Laue classes 8, 14
 - layer-wise slurry AM 214
 - LCR digital bridge impedance meter 281
 - lead-based ceramics 40, 71–73, 314, 315, 327–329, 562, 563
 - lead-based ferroelectrics
 - lead-based ceramics 327–329
 - lead-based single crystals 327
 - lead-based piezoelectric materials 467
 - adaptive lenses (ALENS) 44

- lead-based piezoelectric materials (*contd.*)
 - challenges and prospects 46–47
 - electro-optic modulator 43
 - lead-based relaxor ferroelectrics 35–36
 - lead zirconate titanate, PZT 33–35
 - local structure heterogeneity to boost piezoelectricity 36–37
 - medical ultrasonic transducer 43
 - piezoelectric metamaterials 42–43
 - solid-state crystal growth (SSCG) 41–42
 - texture technology (templated grain growth) 37–41
 - underwater acoustic transducer 43
 - lead-based piezoelectrics 36, 43–46, 219–222, 467
 - lead-based relaxor ferroelectrics 35–36
 - lead-based single crystals 66, 308, 327
 - lead-free based piezoelectrics 222
 - BNT-based ceramics 225–228
 - BT-based ceramics 228–231
 - KNN-based ceramics 222–225
 - lead-free ferroelectric compounds
 - AgNbO₃ 561–562
 - BiFeO₃ 563
 - NBT 558–561
 - lead-free linear array ultrasonic transducer 583
 - lead-free perovskite piezoelectric materials
 - bismuth ferrite 96–106
 - sodium bismuth titanate 85–96
 - lead-free piezoelectric ceramics
 - BaTiO₃-based ceramics 316–320
 - BiFeO₃-based ceramics 325–327
 - (Bi_{0.5}Na_{0.5})TiO₃-based ceramics 320–323
 - (K, Na)NbO₃-based ceramics 323–324
 - NaNbO₃-based ceramics 324–325
 - lead-free textured ceramics 222, 234, 235
 - lead magnesium niobate (PMN) 434, 435, 498
 - lead zirconate titanate (PZT) 33–35, 312, 455, 498, 553, 554, 556–558
 - Lepidocrocite compounds 209
 - liner dielectric ceramics
 - glass ceramics 369–371
 - SrTiO₃ based ceramics 367–369
 - TiO₂ based ceramics 365–367
 - liquid phase sintering (LPS) 103, 146
 - Lotgering coefficient of ceramics 175
 - Lotgering method 207
 - LPFM 180
- m**
- machine direction (MD) 208, 355
 - magnetic field orientation technology 175
 - magnetic slip casting 213, 214
 - March–Dollase texture model 208
 - mask-image-projection-based stereolithography (MIP-SLA) method 584
 - maximum polarization (P_{\max}) 95, 353, 363, 386, 396, 505
 - Maxwell–Wagner–Sillars polarization 347
 - Maxwell–Wagner space charge relaxation model 183
 - medical ultrasonic transducers 43, 46, 581
 - metal-free organic perovskite molecular ferroelectrics 120
 - micro-displacement actuators 311, 312, 334
 - mm-scale flexible LF-PUEH device design 486–487
 - molecular ferroelectrics, piezoelectricity 330
 - in composites 122–126
 - crystalline thin films 119–120
 - in crystals 116–118
 - in molecular solid solutions 126–127
 - nanoparticles 127–128
 - in plastic polycrystals 120–122
 - molecular solid solutions 126–127, 129
 - molten salt method 171, 174, 175, 195, 531
 - molten salt synthesis (MSS) 212
 - Moore’s law 253

- morphotropic phase boundary (MPB)
 30–31, 35, 53, 126, 139, 557
 A-site and B-site doping 148–149
 Bi-based end-member mixing
 149–150
 Pb-based compound treatment
 151–153
- morphotropic phases 30–31, 34, 35, 53,
 62, 85, 126, 139, 256, 258, 325, 371,
 428, 459
- multilayer ceramic capacitors (MLCCs)
 351
 degreasing and co-firing 352
 external electrode printing, packaging,
 and testing 352–354
 inner electrodes preparation 352
 lamination 352
 preparation of casting slurry 351
 tape-casting process 351–352
- multi-layer ceramics (MLCs) 436–438,
 440, 442–444
- multiple of a random distribution (MRD)
 207
- n**
- NaNbO₃-based antiferroelectric ceramics
 381–382
- NaNbO₃-based ceramics 324–325
- NaNbO₃-like perovskite 52
- nano-scale domains 60, 296, 324
- NBT-8BA ceramics 560, 561
- necking process 271, 273
- Neumann principle 6–9
- neural stimulation 541, 574, 587–590
- neuromodulation 483
- nonferroelectric polymers 388–391
 energy storage properties 389
- non-perovskite structured templates
 209, 211–212
- non-reactive polymer phase 499
- o**
- 1D-filled nanocomposites 395–396
- 1D piezo-bioelectronic nanomaterials
 461, 462
- optical indicatrix 292, 293
- oral care 479
- organic bio-piezoelectric materials 455
- organic dielectric materials
 polymer-based dielectrics for energy
 storage 384–391
- organic piezoelectric materials
 bio-based materials 533–534
 molecular ferroelectrics 534–535
 organic-inorganic hybrid lead halide
 533
 PVDF 532
- organic thin film capacitors 354–356
- organs and tissues regeneration 476
- orientation distribution function (ODF)
 207, 208
- orientation polarization 346
- orthorhombic-tetragonal (O–T) phase
 boundary 53
- Ostwald ripening process 202, 203
- O–T phase transition temperature 54
- 4,4'-oxydianiline (ODN) 392
- p**
- paraelectric phase 28, 69, 117, 121, 169,
 170, 177, 269, 274, 281, 292, 302,
 314, 315, 317, 324, 327, 426, 428,
 429, 431, 434, 435
- partial discharge breakdown 348–350
- PATP-modified BCT-BZT NFs 396
- Pb-based compound treatment
 151–153
- Pb-based relaxor ferroelectric ceramics
 371–372
- (Pb, La)(Zr, Sn, Ti)O₃-based
 antiferroelectric ceramics
 380–381
- PbZrO₃-based antiferroelectric ceramics
 379–380
- Pb(Zr,Ti)O₃ thin films 258–259
- PDMS-based composites 123–125
- perovskite-layered structured (PLS)
 compounds 233
- perovskite platelets 211

- perovskite-structured piezoelectric materials
 - components 523
 - dipping method 526
 - HIPT 526
 - (K,Na)NbO₃-based (KNN-based) 525
 - lead 523
 - nano-sized grains 526
 - 1D BaTiO₃ materials 525
 - PZT 524
 - self-assembled technology 525
 - stretchability and mechanical durability 525
 - thin film 527
 - 3D framework 527
 - two/three-dimensional 525
- PFM-aided characterization and design 128–131
- phase boundaries vs. piezoelectricity 85–86
- phase boundary engineering 53–56
- phase-separation methods 499
- phase transition process 71, 168, 270, 562
- photoacoustic and piezo-ultrasound
 - hybrid-induced lead-free energy harvester for 3D twining wireless multifunctional implants 578–579
- photodynamic-acoustodynamic hybrid therapy 592
- photorefractive effect 306
- physical vapor deposition (PVD) method 355
- piezo-bioelectronic device
 - applications 487–488
 - biomolecular materials 459–460
 - biosensing 468
 - biomedical pressure sensing 474
 - physical health monitoring 468–473
 - prosthetic devices 474–476
 - disease treatment
 - cancer 476–479
 - oral care 479
 - organs and tissues regeneration 476
 - energy harvesting 479–487
 - fabrication of 460–467
 - inorganic ceramics 456–458
 - polymers 458–459
 - properties of 456, 457
- piezo-bioelectronic device fabrication
 - modification and packaging 464–467
 - structure design
 - 1D 461–462
 - 2D shape 462–463
 - 3D 463–464
- piezocaloric effect 5
- piezo-catalysis
 - definition of 590
 - for nondestructive tooth whitening 479, 480
- piezocatalytic therapy in vivo 480, 491
- piezocatalytic tumor therapy 590, 591
- piezoelectric actuators 45, 158, 235–237, 329, 333
- piezoelectric coefficients
 - Cartesian coordinate system 9–10
 - center of inversion 8
 - mirror plane 8–9
 - Neumann principle 7–9
 - simplified definitions of
 - converse piezoelectric effect 3–4
 - direct and converse piezoelectric coefficients 4–5
 - direct piezoelectric effect 3
 - typical values of 5
 - space symmetry groups 10–14
 - tensors of 5–6, 14
 - voigt/matrix notation for piezoelectric coefficient 6–7
- piezoelectric composites 158, 459, 497–499, 576
 - preparation 576
- piezoelectric effect, direct 495
- piezoelectric energy harvesters (PEHs) 122, 123, 126, 238, 456, 479, 481, 574
- piezoelectricity 1
 - bismuth ferrite

- BF-BT solid solution 103
- BF-ions 103, 104
- molecular ferroelectrics 116–128
- by third-rank tensor
 - tensor of piezoelectric coefficients 5–6
 - voigt/matrix notation for
 - piezoelectric coefficient 6–7
- piezoelectric metamaterials 42–43, 46, 47, 593
- piezoelectric micro-displacement
 - actuators 311
- piezoelectric micromachined ultrasonic transducers (pMUT) 254, 255
- piezoelectric properties 53
 - phase boundary engineering 53–56
 - physical mechanisms 58–61
 - structural heterogeneity 61–62
 - texturing 56–57
- piezoelectrics-based energy harvesters (PEHs) 122, 123, 126, 574
- piezoelectric sensors, BIT 194
- piezoelectric thin films 255
 - applications of 253–255
 - direct piezoelectric effect 261–263
 - (K,Na)NbO₃ (KNN) 259–261
 - novel science of new material phases 255
 - Pb(Zr,Ti)O₃ thin films 258–259
 - reverse piezoelectric effect 263
- plasticity, definition 121
- plastic molecular ferroelectric
 - [C(NH₂)₃]ClO₄ 121–123, 125
- plastic polycrystals 120–122
- PMN-PT ferroelectric 44, 327
- PMN-xPT-based bulk ceramics 434–435
- Pockels effect (linear electro-optic effect) 292
- polarization-electric field (P-E) 23, 27, 184, 505–506
 - loops 505
- polarization mechanisms 342, 345–347, 401
- polar nano-regions (PNRs) 35, 60, 61, 295, 298, 301–304, 316, 317, 324, 367, 372, 377
- poled ferroelectric materials 553
- poling process 88, 299, 311, 495, 505, 553
- polycrystalline ferroelectric ceramics 24–26
- polycrystalline synthesis 272
- polydimethylsiloxane (PDMS) 44, 123, 126, 128, 467, 474, 478, 499, 503, 510, 522, 527, 531, 539, 576, 578
- polyimide 392
- polymer-based capacitors 399
- polymer-based dielectric composite films 393, 394
- polymer-based dielectrics for energy storage
 - blended polymers 389–391
 - ferroelectric polymers 384–388
 - high-temperature stability
 - considerations in 392–393
 - nonferroelectric polymers 388–389
 - size consideration in 391–392
- polymer based piezoelectric biosensors 471
- polymorphic phase boundary, in KNN system 260
- polyurethane (PU) 125, 334, 458, 525, 534
- polyvinylidene difluoride (PVDF) 130, 384, 390, 499, 500, 521, 522, 531, 532, 585
 - copolymerization of PVDF 387
 - organic piezoelectric materials
- porous piezoelectric materials
 - acoustic impedance 496
 - advantages 497
 - biomedical 511–513
 - catalysis 510, 512
 - ceramics 498
 - classification 497
 - composites 499
 - direct piezoelectric effect 495, 496
 - disadvantages 495
 - energy harvesting 496, 508–510

- porous piezoelectric materials (*contd.*)
- energy storage 513–514
 - fabrication techniques 497
 - additive manufacturing 502–503
 - BURPS 500–501
 - freeze-casting method 504
 - gel casting 501, 502
 - replica template method 503–504
 - hydrostatic voltage coefficient 496
 - modelling and characterization
 - dielectric and piezoelectric properties 506–507
 - electric field distribution 505
 - mechanical properties 507
 - polarization-electric field loops 505–506
 - parameters 495
 - phases 497
 - poling process 495
 - polymers 499
 - sensors 510
 - thin film 500
- porous piezoelectric polymers 499
- potassium sodium niobate (KNN) 51
- based single crystals 66
 - based thin films 65
 - ceramics
 - emerging phenomena 63
 - piezoelectric properties 53–62
 - synthesis of 51–53
 - temperature stability 62–63
- power density, ceramic capacitors 344
- precision positioning technology 311
- Press & Folding (P&F) technique 386
- printed circuit board (PCB) 590
- pseudo-perovskite 167, 209, 231
- PST-based bulk ceramics 435
- PU-based composites 125–26
- PVDF/HHE piezoelectric nanofibers 471
- P(VDF-TrFE) copolymers 458, 459
- P(VDF-TrFE-CTFE) compositions 388
- pyro-catalysis for tooth whitening 481
- pyromellitic dianhydride (PMDA) 392
- PZT-based bulk ceramics 433–434
- q**
- quadratic electrostriction and piezoelectricity 26–28
- quinuclidinium-related compounds 122
- r**
- radio frequency (RF) wireless communications 253
- reactive oxygen radicals 477
- reactive oxygen species (ROS) 461, 477–481, 487, 590, 591
- reactive templated grain growth (RTGG) 203, 228, 231
- recoverable energy storage density (W_{rec}) 363
- refraction index ellipsoid 292
- refrigeration 33, 78, 423, 424, 428, 434, 438, 443, 444
- regenerative engineering 476
- relaxor ferroelectric ceramics 371
- BaTiO₃ (BT) 373, 376
 - Bi_{0.5}Na_{0.5}TiO₃ based ceramics 372–373
 - high-entropy relaxor ferroelectric ceramics 377, 378
 - Pb-based relaxor ferroelectric ceramics 371–372
- relaxor ferroelectrics 36
- single crystals 5
- relaxor-antiferroelectrics (RAFE) 364
- relaxor-PT textured ceramics 233
- remnant polarization (P_r) 69, 85, 99, 145, 225, 311, 320, 322, 363, 386, 387, 401, 505, 506, 553, 562, 568
- replica template method 503–504
- Restriction of Hazardous Substances Directive (RoHS) 51
- reverse piezoelectric effect 261–263
- Ruddlesden–Popper compounds 209
- s**
- sacrificial template method 500
- SbSI ceramics 201

- scandium lead tantalite (PST) 435, 438–440, 442, 444
- Schottky barrier 103, 401, 465
- seed-free solid-state crystal growth (SFSSCG) method 66, 582
- segregation effect of KNN and KTN crystals 274–278
- segregation phenomenon of single crystal 272
- self-powered gustation electronic skin 475
- self-powered photodynamic therapy (s-PDT) system 463
- self-powered piezoelectric sensors 126, 468
- self-powered systems 521, 574–577
- self-powered wireless data transmission 484
- sequential biaxial orientation 355
- shock-induced depolarization and repolarization of PZST ferroelectric ceramics 557
- shock wave depolarization of PZT 52/48 557
- shoulder placement process 273
- simultaneous biaxial orientation 355
- single crystal X-ray diffraction
 angular displacement of Bragg peaks 20
 in BiB_3O_6 20–23
 geometry of 17–18
 strain and rotation in the real and reciprocal space 18–20
- sintering
 densification and texture evolution 216–219
 processing 145–148
- sodium bismuth titanate (BNT) 431
 BNT-based materials 95–96
 depolarization phenomenon 86–89
 depolarization temperature T_d vs. piezoelectricity d_{33} 89
 electro-strain 91–94
 large electro-strain 90–91
 phase boundaries vs. piezoelectricity 85–86
- sol-gel method 65, 89, 144, 145, 155, 171, 174, 368, 371, 427, 500, 526
- solidly mounted resonators (SMR) 254, 255
- solid-state conversion of single crystals 41
- solid-state crystal growth (SSCG) 41–42, 66, 582
- solid-state single-crystal growth 41
- solution combustion synthesis 172, 174
- sonodynamic therapy 461, 591
- spark plasma sintering (SPS) 52, 141, 172, 175, 176, 231, 366, 429, 431
- speech recognition 475, 476
- SrTiO_3 based ceramics 367–369
- SSR method 170, 171
- strain engineering 256, 261
- stress-induced ferroelectric (FE) to antiferroelectric (AFE) phase transition 562
- structural health monitoring (SHM) 192
- surface acoustic wave (SAW) resonators 254, 255
- synergistic chemotherapy-piezoelectric therapy 591
- t**
- tape-casting process 213, 214, 351
- temperature stability 345
 high-temperature stability considerations 392–393
 KNN-based ceramics 62–63
- temperature-stable electrostrictive strain 316
- template-assisted methods 499, 526
- templated grain growth (TGG) 146, 175, 202, 207
 reactive 203, 228, 231
 technology 38
- tensor of piezoelectric coefficients 5–6, 9

- ternary lead-based textured ceramics
 - 40
 - tert-butyl alcohol 502
 - tetrodotoxin (TTX) 588
 - textured ceramics 201
 - BNT-BT 225, 228
 - crystallographically 201
 - textured perovskite-structured
 - piezoelectrics
 - lead-based piezoelectrics 219–222
 - lead-free based piezoelectrics 222–231
 - with other structures 231–233
 - textured piezoceramics
 - device applications
 - energy harvesters 237–239
 - piezoelectric actuators 235–237
 - ultrasonic transducers 233–235
 - enhancing electrical properties 219–233
 - fundamental basis for 202
 - high-performance electronic applications 201
 - phase via Ostwald ripening process 202
 - template selection and synthesis
 - non-perovskite structured templates 211–212
 - perovskite-structured templates 209–211
 - template alignments and inducing texture 212–216
 - templated grain growth (TGG) 202–207
 - texture analysis 207–09
 - texture engineering 201, 202, 237
 - texture technology (templated grain growth) 37–41
 - thermal breakdown 348–350
 - thin-film bulk acoustic resonators (FBAR) 254, 255
 - 3D piezo-bioelectronic materials 463
 - 3D printing 47, 502, 584, 593
 - TiO₂ based ceramics 365–367
 - Ti-O bond lengths 169
 - tissue engineering 584, 587
 - topochemical conversion (TMC) 209–211
 - top-seeded solution crystal growth 270–271
 - top-seeded solution growth method (TSSG) 66, 270, 271, 274, 275, 308
 - traditional solid-state sintering method 172
 - trans-gauche conformation 385
 - transducers application 156–158
 - transverse direction (TD) 355
 - transverse impact depolarization
 - high-voltage experiment 557
 - Tungsten bronze (TB)
 - family 231
 - structured templates 212
 - 2D-filled nanocomposites 396–398
 - 2D piezo-bioelectronic nanomaterials 462
 - two-layer PMN-PT implantable system for powering cardiac pacemaker 575
 - two-phase piezoelectric composites 498
 - two-step sintering (TSS) method 53, 141, 144–146, 155, 353, 429, 431, 434
- U**
- ultrasonic energy transfer (UET) 577
 - ultrasonic nondestructive inspection (UNDE) 192
 - ultrasonic transducers 43, 46, 86, 156–157, 193, 201, 233–235, 255, 581–584
 - ultrasonic transfer method 578
 - ultrasonic wireless-powered systems 577–580
 - ultrasound bio-microscopy (UBM) images 582
 - ultrasound imaging transducers 581–584, 592
 - unit cells (UC) PbTiO₃ thin films 256

V

vacuum dielectric constant 342
VPFM signal 179

W

wearable smart devices 521
Weibull distribution 348
wurtzite-type materials 527, 528

Z

0D-filled nanocomposites 394
0D piezoelectric bioelectronic materials
461
ZnO@microporous organic polymer
synthesis 464–465

