

Index

a

active mechanical haptics 431–449
 adherends 345–347, 349, 351–354,
 356–363
 adhesive failure 143, 352, 357–358
 American Society for Testing and
 Materials (ASTM) 347
 Archie's porosity-resistivity model 393
 artificial electronic skin 235, 244
 atomic layer deposition (ALD) 465
 atom-transfer radical polymerization
 (ATRP) 75
 augmented reality (AR) 431
 auxetic material 246

b

biaxially stretching 270
 biomedical devices 20, 269, 286, 287
 block copolymers 148, 159
 Bluetooth module 341
 Brownian diffusion 13
 buckling modes 184–186, 193, 194, 279,
 282, 293, 296
 bulk dissipation model 10, 11
 bulk hysteretic dissipation 9–11
 burst pressure tests 347

c

cable-driven method 432, 434
 capacitive tactile sensors 399–401
 with engineered dielectrics 401–408
 with engineered electrodes 408–413
 stretchable 413–415

carbon black/polyurethane porous
 nanocomposite 393
 carbon nanotube (CNT)/PDMS composite
 382
 catechol chemistry 351
 chemical energy harvesters 22–23
 chemical vapor deposition (CVD) 40,
 98
 circular arc-shaped cut line 432
 classical affine and phantom network
 theories 7
 classical Lake–Thomas theory 8
 CNFs/water/PDMS emulsion 396
 cohesive failure 352, 357–358
 colorless polyimide (CPI) 211, 222
 complementary metal-oxide-
 semiconductor (CMOS) 275
 compression-induced constrained
 buckle-delamination 298
 compression-induced spontaneous
 buckle-delamination 298, 299
 compression-induced wrinkling 293,
 297, 298
 computer-aided design (CAD) 211
 conducting polymers 16, 148, 151
 conductive elastic spheres 379
 conductive polypyrrole 246
 constriction resistance 379–383, 388,
 389, 395
 continuous wave (CW) laser 213
 conventional conductive materials 16
 copper–gold core–shell nanowires
 (CuAuNWs) 215

- crack onset strain (COS) 141, 149, 152, 154
- critical load 293, 331
- crystallinity 40, 97, 147–148, 150
- curved origami
- active tuning 437–438
 - body-centered stepping device 444–447
 - closed-loop design and system integration 438–440
 - definition 432
 - design 434
 - elastic deformation 434
 - geometric modeling 434–436
 - haptic perceptions 434
 - in-hand haptic device 440–443
 - mechanics modeling 436–437
 - plasticity 433
 - principle 433
 - stiffness perception via active pressing 443–444
 - stiffness tuning via 432–434
 - whole-body stiffness perceptions 447–448
- curvilinear substrate designs strategy 272
- d**
- defect-free ideal network 10
- defect-network fracture model 10
- delamination states design 279–281
- dielectric elastomers (DE) membrane 274
- dip-coated with silver nanowire (AgNW) 383
- dipole–dipole interaction 351
- direct ink write (DIW) 71, 72
- direct LM casting 73
- displacement function 321–325, 327, 338
- double cantilever beam (DCB) test 142, 143
- DPP-based semiconducting polymers 149
- dry adhesion 346, 361, 362
- dynamic mechanical analysis (DMA) 143, 144
- e**
- effective conductive path model 385, 386, 389, 390, 392
- effective medium theory (EMT) 74, 76, 79, 407
- effective Young's modulus 79–81, 102, 339, 401, 407
- elastic deformation 273, 434
- elastic modulus 6–9, 15, 37, 80, 89–91, 93, 95–98, 100, 103, 107, 108, 110, 113, 117–120, 124, 127, 128, 149, 156, 180, 194, 198, 297, 345, 363, 383, 389
- elastomer fiber mat sensors 243
- elastomer substrate designs
- curvilinear substrate designs 272
 - engineered planar 270–271
- electrical dissolution rate, for conductors 460
- electrical permittivity 74, 76, 79
- electric/magnetic-field-assisted loading strategy 274
- electrochemical hydrogel biosensors 4, 5, 18, 19
- electrohydrodynamic (EHD) 235, 239
- electrokinetic mechanical energy harvesters 22
- electromechanical coupling 78–80, 82
- electron accepting polymers 140
- electron accepting small molecule conductors 140
- electronic skins (e-skins) 37, 157, 159, 235, 244–246, 303–305, 343, 373
- electrospinning 235–254, 304
- empirical expression 408, 457
- encapsulation layers 153, 458, 461–464, 466
- energy balance 90

- engineered planar substrate designs 270–271
- equi-biaxial stress 121
- equilibrium equations 321
- Eshelby's theory 80, 81
- Euclidean space 321
- Euler buckling 180, 279
- Eutectic gallium-indium (EGaIn) 69, 70
- f**
- fabricated stretchable transistors 150
- fatigue 360–361
- fatigue-resistant hydrogels 12
- fatigue threshold 6, 7, 9, 11–12, 360, 361
- film on air (FOA) tensile tests 141
- film-on-water (FOW) tensile test technique 141, 142
- film thickness 153–155, 174, 297, 387, 390
- fingertip modulus sensor (FMS) 337–340
- finite deformation theory 175
- finite element analysis (FEA) 57, 79, 156, 178, 184, 267, 333, 382
- finite element method (FEM) 78, 123, 434
- flexible biobattery
 - chemical energy harvesters 22–23
 - thermal energy harvesters 23
- flexible electronic devices, protective strain isolation structure design 195–202
- strain limited structure design 193–195
- flexible electronic robots 286
- flexible electronics 4, 88, 89, 103, 173, 174, 177, 178, 181, 185, 186, 189–202, 235, 243, 251, 252, 254, 265–287
- flexible hybrid response tactile sensors 415–417
- flexible hydrogel biobattery
 - chemical energy harvesters 22–23
 - mechanical energy harvesters 21–22
 - thermal energy harvesters 23
- flexible OLEDs 155–158
- flexible sensors 235, 243, 244, 284, 287, 395
- fluorescence recovery after bleaching (FRAP) 12
- force–displacement relation 432, 433, 437, 438, 443, 449
- force-softness bimodal sensor (FSS) 328–336
- four-point bend (FPB) test 142, 143
- fractocohesive length 358–359
- fracture mechanics 82, 358
- fracture toughness 5–11, 14, 15, 47, 50, 89, 90, 116, 117, 119, 120, 122, 127, 143, 145, 151, 153, 246
- frame structures 275, 278
- g**
- Ga-based alloys 69, 75
- Ga-based liquid metals 69–71
- gallium-indium-tin (Galinstan) 69
- gold cyanide (AuCN) 212
- graphene, indentation and mechanical behavior 100
- Griffith bond cleavage 353
- h**
- helical design 189–190
- Hertz normal contact theory 380
- hexagonal boron nitride (*h*-BN) 88
- high precision manufacturing
 - EHD printing 239–243
 - inkjet printing 236–239
- high-resolution electron energy loss spectroscopy (HREELS) 125
- host–guest interaction 351
- hydrogel-based electronic materials 14
- hydrogel bioelectronic device 4
- hydrogel-tissue adhesives 349
- hydrogel-2D material interfaces 20
- hydrogen gas detection 302

i

- indentation tests 6, 7, 98, 99, 102, 103, 105, 109, 120
- indium tin oxide (ITO) 155
- inkjet printing 74, 76, 208, 209, 236–239
- inorganic electronic devices 195
- in-situ* hydrogel bioelectronics 3
 - components 5
 - defined 5
 - electrochemical biosensors
 - hydrogel-2D material interfaces 20
 - selective transport design 19–20
 - extreme properties
 - elastic modulus 6–8
 - fatigue threshold 11–12
 - fracture toughness 8–11
 - mass transport 12–14
 - flexible biobattery
 - chemical energy harvesters 22–23
 - mechanical energy harvesters 21–22
 - thermal energy harvesters 23
 - stretchable hydrogel conductors
 - multiscale orthogonal design 14–15
 - orthogonal design implementations 15–18
- in situ* tensile testing 116, 117, 119, 120, 122
- interfacial adhesion, in mechanics-guided assembly
 - controlled interface delamination 281
 - delamination states design 279–281
- interlocked micro-domes (or hemispheres) arrays 382
- Internet of Things 158, 173
- intrinsic adhesion energy 359
- intrinsic fracture energy 8, 10–12
- Irwin–Orowan dissipation 354
- island–bridge structure
 - design 177
 - fractal-inspired interconnection 186–188
 - serpentine interconnection 180–186
 - straight interconnection 178–180

j

- Jacobi cosine amplitude functions 299

k

- Kirigami design strategy 267
- Kirigami-inspired design 192
- Kirigami substrate design 270, 271
- Kuhn monomers 9, 12

l

- Lake–Thomas chain scission 353
- Lake–Thomas theory 8, 12
- laser-based fabrication 207–226
- laser fabrication 207, 208, 211–225
- laser-induced graphene (LIG) 217
- laser-induced hydrothermal growth 209, 210, 223–225
- laser irradiation 209, 215, 217
- laser pyrolysis 223, 224
- lateral tensile strain 376
- linear strips 90
- liquid metal based electronics
 - Ga-based liquid metals 69–71
 - Ga-based LM electronics 71
 - LM-coated thin-film metal traces 73–74
- mechanics and modeling
 - LM-polymer composites 79
 - microfluidic LM pressure sensor 77–78
 - microfluidic LM strain gauge 76–77
- relevant literature 71
- LM architectures 71
 - LM-polymer composites 74–75
 - printable LM-based inks 76
- liquid metals (LMs) 16, 69
- LM architectures
 - LM-coated thin-film metal traces 73–74
 - LM-polymer composites 74–75
 - microfluidic LM channels 71
 - printable LM-based inks 76
- LM-polymer composites
 - effective Young’s modulus 80–81
 - electromechanical coupling 79–80

- electrical permittivity and thermal conductivity 79
- loading conditions strategy
 - electric/magnetic-field-assisted loading strategy 274
 - mechanical loading strategy 272–274
- loading-path controlled assembly
 - reconfigurable cross-shaped structures 282
 - reconfigurable structures harnessing interface mechanics 282–283
- Lorentz forces 273, 274
- low-dimensional materials 87

- m**
- magnesium (Mg) 454
- magnesium oxide (MgO) 454
- magnetoelastic sensors 376
- Maxwell forces 274
- mechanical energy harvesters 21–22
- mechanical loading strategy 272–274
- mechanics-guided 3D assembly
 - elastomer substrate designs
 - curvilinear substrate designs 272
 - engineered planar 270–271
 - fundamental aspects 265
 - loading conditions strategy
 - electric/magnetic-field-assisted loading strategy 274
 - mechanical loading strategy 272–274
- mechanics modeling and analyses
 - interfacial adhesion 279–281
 - loading-path controlled assembly 282–283
- 2D precursor designs
 - buckling analysis of 275–279
 - multilayer and multilevel design strategy 267–269
 - origami/Kirigami design strategy 267
 - spatial stiffness control 269–270
- microfluidic LM channels 71–72, 76, 82
- microfluidic LM pressure sensor 77–78
- microfluidic LM strain gauge 76–77
- micro-pyramid dielectric patterns 401
- microscale inorganic light-emitting diodes (μ -ILEDs) 306
- minimal potential energy 437
- Miura origami 432–437
- mode of diffusion 13
- modern electronics 453
- monocrystalline silicon nanomembranes 455
- multilayer and multilevel design strategy 267–269

- n**
- near-crack dissipation 9, 11
- negative Poisson's ratio (auxetic) materials 246
- network elasticity 4, 9, 13, 14, 20
- non-stretchable materials 294, 300

- o**
- optical sensors 376
- organic conductors 139, 140, 150
- organic electrochemical transistors (OECTs) 139, 158
- organic electronic materials
 - applications 156–159
 - common devices 139
 - design
 - additives and blends 150–151
 - backbone and side-chain structure 146–147
 - block copolymers 148
 - crosslinking and hydrogen bonding 148–150
 - film thickness 153–155
 - interfaces 155–156
 - molecular weight 145–146
 - neutral axis and ultrathin devices 153
 - organic photovoltaic considerations 152
 - regioregularity and crystallinity 147–148
 - stretchable device architecture 156
- intrinsic properties 140

- organic electronic materials (*contd.*)
 - mechanical characterization methods
 - fracture toughness 143
 - tensile tests 141–142
 - stress strain curve 142
 - thermomechanical behavior
 - 143–145
 - organic photodetectors 139
 - organic photovoltaic (OPV) 139, 152
 - organic semiconductor films 141, 151
 - organic thin film 141, 251, 453
 - origami-inspired design 190–192
 - Origami/Kirigami design strategy 267

- P**
 - partial differential equation (PDE) 78
 - PDMS micro-domes spray-coated with
 - carbon-black PDMS (CPDMS) 383
 - percolation scaling law 387
 - permittivity of vacuum 377, 399, 405, 417
 - phosphate-buffered saline (PBS) 455, 456, 460
 - photoplethysmogram (PPG) 209
 - piezoelectric and triboelectric sensors 374
 - piezoelectric microsystem 306
 - piezoresistive pressure sensors 329, 335, 396
 - piezoresistivity of nanocomposites 385
 - π - π stack 351
 - planar stretchable and flexible structures
 - island-bridge structure design 177–188
 - three-dimensional flexible electronic structures 189–193
 - wave/wrinkle structure design 174–177
 - plasticity 38–40, 43, 44, 53, 58, 59, 267, 268, 432, 433
 - P(NDI2OD-T2) 145, 146, 152
 - Poisson's ratio 78, 105, 121, 125, 126, 174, 180, 182, 185, 194, 246, 278, 297, 331, 339, 381, 387, 408
 - polydimethylsiloxane (PDMS) 49, 71, 113, 141, 174, 213, 223, 237, 279
 - poly(3,4-ethylenedioxythiophene)
 - polystyrene sulfonate (PEDOT:PSS) 16, 215
 - poly(3,4-ethylenedioxythiophene)
 - polystyrene sulfonate (PEDOT:PSS) 302
 - poly(3,4-ethylenedioxythiophene):
 - poly(styrene sulfonate) (PEDOT:PSS) 215
 - polyethylene terephthalate (PET) 217, 243, 267
 - poly(3-hexylthiophene) (P3HT)
 - nanofibers 251
 - polymer networks 3–17, 20, 345, 346, 349–353, 356, 357, 360, 363
 - polyurethane acrylate (PUA) 215
 - polyurethane foams 392
 - polyvinylidene fluoride (PVDF) 215, 222, 304
 - porous material, mass density of 459
 - Pouillet's law 77, 79, 82
 - pressure-sensitivity trade-off 377, 378
 - printable LM-based inks 76
 - printed circuit board (PCB) 71, 334, 335
 - printing-based deposition methods 72–73

- r**
 - Raman spectroscopy 109, 110, 122, 123, 126
 - reaction constant 454, 457, 459–463
 - reactive diffusion equation 457, 462, 463
 - reconfigurable cross-shaped structures 282
 - regioregularity (RR) 146–148
 - resistive-capacitive hybrid response
 - tactile sensors
 - flexible 415–417
 - stretchable 417–418
 - resistive tactile sensors
 - bulk conductive nanocomposites 385–392
 - microstructured contact 379–385

- porous conductive materials 392–397
- stretchable resistive tactile sensors 397–399
- Rheology test 7
- S**
- scalar function 323
- scanning electron microscopy (SEM) 40, 89, 185, 276
- semiconducting materials, hydrolysis 455–457
- semiconductor-grade monocrystalline silicon 453
- semi-infinite solid
 - elastic solid with displacement function 321–325
 - revolution indenter 325–327
 - spherical indenter 327–328
- separator polymerized high internal phase emulsions (polyHIPEs) 303
- shear elastic modulus 6–8
- silicic acid (Si(OH)₄) 453, 455
- silicon nanomembranes, dissolution rate 455
- silicon nitrides 461
- silicon oxides 461, 464
- silver nanoparticle (AgNP) 211, 218, 220, 222, 236
- simple linear-chain model 110
- small molecule acceptor (SMA) 148, 152
- soft electronic devices 207, 225
- soft heating device 220
- soft lithography techniques 71
- soft resistive and capacitive tactile sensors 376–420
- spatial stiffness control 2D precursor, 269
- spherical indentation method
 - human body features
 - force-softness sensor 329–334
 - identification application 336
 - tactile glove 334–335
 - semi-infinite solid
 - elastic solid with displacement function 321–325
 - revolution indenter 325–327
 - spherical indenter 327–328
 - swollen tissues softness
 - fingertip modulus sensor 338
 - softness measurement 340–343
- stiff material 156, 357
- straight ribbons 2D precursors, 275–277
- strain–displacement relations 322
- strain insensitivity 397–399, 413, 415–417
- strain isolation method 196
- strain isolation structure design 195–202
- strain limited structure design 193–195
- stress–displacement relations 322, 323, 326
- stress–strain relations 95, 322
- stretch interference 377, 378, 397–399, 413, 415, 417, 419
- stretchable adhesion 361
- stretchable capacitive tactile sensors 413–415
- stretchable electronics 37, 235
 - application
 - optoelectronic devices 252–254
 - organic field-effect transistors 248–252
 - strain and pressure sensor 247–248
 - high precision manufacturing
 - EHD printing 239–243
 - inkjet printing 236–239
 - operating parameters 241
 - stretchable nanofiber mats 243–244
 - stretchable yarns and fabrics 244–247
- stretchable fiber-like sensors 246
- stretchable hybrid response tactile sensor (SHRTS) 416–418
- stretchable hydrogel conductors 14
 - electrically conductive fillers 14
 - interfacial design 18
 - multiscale orthogonal design 14–15
 - orthogonal design implementations 15–18
 - serpentine structural design 18
- stretchable nanofiber mats 243–244

- stretchable OLEDs 156
- stretchable resistive tactile sensors 397–399
- styrene–isoprene–styrene (SIS) 76
- surface initiated ATRP (SI-ATRP) 75
- t**
- tactile sensors
 - bottlenecks of soft resistive 376–378
 - capacitive 376–378, 399–415
 - overview of 373–376
 - resistive 378–399
 - resistive–capacitive hybrid response 415–418
- Taylor expansion 328
- tension-induced buckling
 - in kirigami structures 300
 - in serpentine structures 299
- texture analyzer (TA) 340, 341
- thermal conductivity 74, 76, 79
- thermal energy harvesters 20, 22, 23
- thermal oxide dissolution rate 455
- thermo-galvanic effect 23
- thermos-diffusion effect 23
- thicker films 141
- thin film/substrate system 275, 279–281
- three-dimensional flexible electronic structures
 - helical design 189–190
 - kirigami-inspired design 192–193
 - origami-inspired design 190–192
- 3D flexible electronics 265
 - biomedical devices 286
 - fabrication methods 265
 - flexible robotics 286–287
 - flexible sensors 284
 - tunable electromagnetic devices 284–285
- 3D helical structures 189, 271, 277, 278
- T-peel tests 8
- transient electronics 453
 - characteristics 453
 - development 453
 - device with bi-layered structures 461
 - dissolution behavior 454
 - model of reactive diffusion 457–461
 - semiconducting materials 455–457
 - transient metals 460
- transient electrophysiology sensor 467
- transition-metal dichalcogenides (TMDs) 87
- transparent conducting electrodes (TCE) 155
- triboelectric nanogenerators (TEENGs) 21
- tunable electromagnetic devices 284–285, 287
- tunneling resistance 379–385, 388, 389, 392, 418
- 2D curved ribbons 275, 278–279
- two-dimensional (2D) materials
 - AFM-enabled nanoindentation 93–95
 - bulge test
 - depressurize inside and form a concave deflection, in film 121–122
 - depressurize outside and form a convex deflection, in film 122–123
 - dry-transfer technique 113–115
 - electrostatic force triggered drum structure 124–125
 - graphene 87
 - in situ* characterization techniques 89
 - mechanical stability 89
 - mechanical testing
 - black phosphor 107–108
 - graphene 95–101, 115
 - graphene oxide 101–103
 - h*-BN 105–107, 118–120
 - MoS₂ 103
 - MoSe₂ 117–118
 - rebar graphene 117
 - WSe₂ 103–105
 - micromechanical devices, with push–pull mechanism 112–113
 - micro-/nano-mechanical devices 111–120
 - nanoindentation method 90–93

- phonon dispersion measurement 125–126
 - piezoelectric tube-driven testing 120–121
 - properties and potential uses 88
 - SEM, *in situ* indentation 108–110
 - thermal actuated micromechanical devices 111–112
 - two-dimensional (2D) transition-metal dichalcogenides 87
 - 2D flexible electronics 265
 - 2D precursor designs
 - multilayer and multilevel design strategy 267–269
 - Origami/Kirigami design strategy 267
 - spatial stiffness control 269–270
 - 2D precursors buckling analysis
 - frame structures 278
 - helical structures 277–278
 - straight ribbons 275–277
 - 2D curved ribbons 278–279
- V**
- van der Waals forces 87, 155
 - vertical interconnect accesses (VIAs) 211
 - virtual reality (VR) 208, 213, 220, 431
- W**
- wave/wrinkle structure 174–178, 180
 - wet adhesion
 - adhesive islands 354–356
 - bridging polymers 356–357
 - bulk modification 356
 - catechol chemistry 351
 - characterization 346–347
 - combination of topologies 352
 - combined methods 357
 - covalent bonds 349
 - dipole–dipole interaction 351
 - direct attachment 354
 - dissipation 352–354
 - dynamic covalent bonds 349
 - Griffith bond cleavage 353
 - host–guest interaction 351
 - hydrogen bond 350
 - hydrophobic interaction 350
 - ionic bonds 349
 - Irwin–Orowan dissipation 354
 - Lake–Thomas chain scission 353
 - macroscopic mechanical interlock 351
 - molecular topology 351–352
 - π – π stack 351
 - principles for 347–349
 - static covalent bonds 349
 - stress deconcentration 354
 - surface initiation 356
 - surface modification 356
 - topological adhesion 357
 - topology of connection 351–352
 - wet interfaces
 - adhesive failure and cohesive failure 357–358
 - fatigue 360–361
 - fractocohesive length-and size-dependency 358–359
 - rate dependency 359–360
 - stretchable adhesion 361
 - wet materials 345, 346, 362
 - wireless control and power (WCP) module 306
 - wrinkling and buckling
 - healthcare applications
 - biological interfaces 308–310
 - biosensors 306–308
 - mechanical instability 294
 - strategy of 294
 - stretchability
 - compression-induced constrained buckle-delamination 298
 - compression-induced spontaneous buckle-delamination 298–299
 - compression-induced wrinkling 297–298
 - structural designs for 294–296
 - tension-induced buckling in kirigami structures 300
 - tension-induced buckling in serpentine structures 299

wrinkling and buckling (*contd.*)

stretchable devices

batteries 302–304

electronic skin 305

sensors 300–302

solar cells 304, 305

supercapacitors 304, 305

yYoung's modulus 40, 45, 50, 78–81, 87,
96, 97, 100–103, 105, 115, 121, 123,
125, 127, 141, 159, 181, 277, 278,
297, 299, 329–334, 336–343, 379,
381, 386–389, 401, 405–407,
410–412, 418, 419, 436