

Contents

List of Figures *xvii*

List of Tables *xxiii*

Preface *xxvii*

1	Introduction	<i>1</i>
1.1	Background	<i>1</i>
1.1.1	Global Mission of Achieving Carbon Neutrality	<i>1</i>
1.1.2	Global Passion for Promoting Energy Transition	<i>3</i>
1.1.3	Global Status of Developing Hybrid Energy Systems	<i>5</i>
1.2	Hybrid Energy Systems	<i>8</i>
1.2.1	Definition	<i>8</i>
1.2.2	Classification	<i>9</i>
1.2.3	Advantages	<i>12</i>
1.3	Chapter Organization	<i>13</i>
	References	<i>16</i>
2	Industrial Decarbonization-Oriented Deployment of Hybrid Wind-Solar-Storage System	<i>21</i>
2.1	Background Review	<i>22</i>
2.2	Main Issue Description	<i>24</i>
2.2.1	System Schematic	<i>24</i>
2.2.2	Decarbonization Datasets	<i>24</i>
2.2.3	Optimization Scheme	<i>26</i>
2.3	Mathematical Modeling	<i>27</i>
2.3.1	Notations	<i>27</i>
2.3.2	Decarbonized Deployment	<i>29</i>
2.3.2.1	To Reduce the Total Electricity Utilization Costs	<i>29</i>
2.3.2.2	To Promote the Installed Capacity of Wind and Solar Power	<i>29</i>
2.3.2.3	To Accelerate Decarbonization and Control Pollution Emissions	<i>30</i>
2.3.2.4	Wind Power Output	<i>30</i>
2.3.2.5	Solar Power Output	<i>31</i>
2.3.2.6	Operation of Battery Storage System	<i>31</i>
2.3.2.7	Compensation of Wind, Solar, and Storage Resources	<i>32</i>

2.3.2.8	Electricity Supply and Demand Balance	32
2.3.2.9	Available Area for New Energy Installation	33
2.3.3	Global Model	33
2.3.4	Model Solving	35
2.4	Case Study	35
2.4.1	Case Description	37
2.4.2	Data Collection	37
2.4.3	Calculation Results and Analysis	39
2.4.3.1	Optimal Configurations Results	39
2.4.3.2	Economic Performance and Self-Sufficiency Ratio	42
2.4.3.3	Regional Decarbonization Potential	43
2.5	Comprehensive Discussions	43
2.5.1	Scenario Simulation	43
2.5.2	Management Recommendations	44
	References	45
3	Sustainable Operation-Oriented Deployment of Hybrid Wind-Solar-Storage System	51
3.1	Background Review	52
3.2	Main Issue Description	54
3.2.1	System Schematic	54
3.2.2	Operation Strategy	55
3.2.3	Optimization Scheme	56
3.3	Mathematical Modeling	57
3.3.1	Notations	57
3.3.2	Sustainable Deployment	58
3.3.2.1	Economic Sustainability: Minimize the Levelized Cost of Electricity	58
3.3.2.2	Technical Sustainability: Maximize Self-Sufficiency Ratio	60
3.3.2.3	Environmental Sustainability: Minimize Carbon Emissions	60
3.3.2.4	Social Sustainability: Maximize Job Creation	60
3.3.2.5	Output of Solar Power	61
3.3.2.6	Output of Wind Power	61
3.3.2.7	Balance of Battery Storage System	62
3.3.2.8	Balance of Demand and Supply	62
3.3.2.9	Key Operation Constraints	62
3.3.3	Global Model	63
3.3.4	Model Solving	64
3.4	Case Study	65
3.4.1	Case Description	65
3.4.2	Data Collection	66
3.4.3	Calculation Results and Analysis	67
3.4.3.1	Results Under Different Scenarios	67
3.4.4	Results of Energy Balance	69

3.4.4.1	Influence of Electricity Price	69
3.4.4.2	Influence of Natural Resources	70
3.5	Comprehensive Discussion	71
3.5.1	Related Propositions	71
3.5.2	Management Recommendations	72
	References	73
4	Disaster Resilience-Oriented Deployment of Hybrid Wind-Solar-Storage-Gas System	79
4.1	Background Review	80
4.2	Main Issue Description	81
4.2.1	System Schematic	81
4.2.2	Resilience Characterization	82
4.2.3	Optimization Scheme	83
4.3	Mathematical Modeling	85
4.3.1	Notations	85
4.3.2	Resilient Deployment	87
4.3.2.1	The Upper-Level Decision Maker: To Maximize the Use of Clean Energy	87
4.3.2.2	To Minimize the Total Annual Power Costs	87
4.3.2.3	To Minimize Carbon Emissions	88
4.3.2.4	To Maximize Power System Resilience	88
4.3.2.5	Clean Energy Use Restrictions	89
4.3.2.6	Installation Area Restriction	89
4.3.2.7	PV Panel Operation	89
4.3.2.8	Energy Storage System Operation	90
4.3.2.9	Battery State Restrictions	90
4.3.2.10	Gas Turbine Operation	90
4.3.2.11	Power Supply and Demand Balance	91
4.3.3	Global Model	91
4.3.4	Model Solving	92
4.4	Case Study	93
4.4.1	Case Description	94
4.4.2	Data Collection	94
4.4.3	Calculation Results and Analysis	95
4.4.3.1	Maximum Resilience Emission Results	97
4.4.3.2	Comparison of Different Scenarios	98
4.4.3.3	Operation Under Normal Modes	98
4.4.3.4	Operation Under Extreme Disasters	101
4.4.3.5	Influence of Changing Market Prices	104
4.5	Comprehensive Discussion	105
4.5.1	Related Propositions	105
4.5.2	Management Recommendations	106
	References	107

5 Bi-level Emission Quota Allocation Toward Coal and Biomass Co-combustion 113

- 5.1 Background Review 113
- 5.2 Main Issues' Description 115
 - 5.2.1 System Schematic 116
 - 5.2.2 Uncertain Decision-Making Environment 116
 - 5.2.3 Bi-level Decision-Making Structure 116
- 5.3 Modeling 118
 - 5.3.1 Notations 118
 - 5.3.2 Perspective from the Local Authority 119
 - 5.3.2.1 To Maximize the Revenue 119
 - 5.3.2.2 To Minimize the Total Carbon Emissions 119
 - 5.3.2.3 Limitations on Each CPP's Carbon Emissions 119
 - 5.3.2.4 Guarantee of Power Supply 120
 - 5.3.2.5 Gap Between the Assigned Emission Quota and the Actual Emissions 120
 - 5.3.3 Perspective from the CPPs 120
 - 5.3.3.1 To Maximize Profits of Electricity Generation 120
 - 5.3.3.2 Combustion Efficiency 121
 - 5.3.3.3 Fuel Quantity Requirements 121
 - 5.3.3.4 Fuel Qualities' Requirements 121
 - 5.3.3.5 Blending Ratio Limitation of Biomass 122
 - 5.3.3.6 Responsibility to Ensure Power Supply 122
 - 5.3.3.7 Emissions Quota Constraints 122
 - 5.3.3.8 Dynamic Fuel Storage 123
 - 5.3.3.9 Logistic Constraint on Fuel Storage 123
 - 5.3.3.10 Limitation of Warehousing Ability 123
- 5.3.4 Global Model 123
- 5.3.5 Model Solving 125
- 5.4 Case Study 125
 - 5.4.1 Case Description 125
 - 5.4.2 Data Collection 128
 - 5.4.3 Results Under Different Scenarios 128
- 5.5 Discussion 132
 - 5.5.1 Propositions and Analyses 132
 - 5.5.2 Policy Implications 137
- References 139

6 Bi-Level Emission Quota Allocation Toward Coal and Municipal Solid Waste Co-combustion 143

- 6.1 Background Review 144
- 6.2 Main Issue Description 145
 - 6.2.1 System Schematic 145
 - 6.2.2 Uncertain Decision-Making 146
 - 6.2.3 Bi-Level Relationship 147

6.3	Modeling	148
6.3.1	Notations	149
6.3.2	Modeling Description for Regional Authority	150
6.3.2.1	To Maximize Revenue	150
6.3.2.2	Emission Quota Limitation	150
6.3.2.3	Total Emissions Limitation	151
6.3.2.4	Power Supply and Demand Risk	151
6.3.3	Modeling Description for Each IPP	151
6.3.3.1	To Maximize Profits	151
6.3.3.2	Available Capacity Limitations of Power Plants	152
6.3.3.3	Quality Requirements of Fuels	152
6.3.3.4	Combustion Technical Requirements	153
6.3.4	Global Model	153
6.3.5	Solution Approach	154
6.4	Case Study	157
6.4.1	Case Presentation	157
6.4.2	Data Collection	157
6.4.3	Calculation Results	161
6.4.4	Results of Different Scenarios	161
6.4.4.1	S0: Baseline Scenario, $\alpha = 1$	161
6.4.4.2	S1: Initial Curb Scenario, $\alpha = 0.9$	163
6.4.4.3	S2: Moderate Curb Scenario, $\alpha = 0.9$	163
6.4.4.4	S3: Serious Curb Scenario, $\alpha = 0.85$	163
6.4.4.5	S4: Vigorous Curb Scenario, $\alpha = 0.8$	164
6.4.4.6	S5: Maximal Limitation Scenario, $\alpha = 0.75$	164
6.4.5	Scenario Results Comparison	164
6.4.5.1	Comparison of Total Carbon Emissions at Each Power Plant	164
6.4.5.2	Carbon Emissions from Different Fuels at Each Power Plant	165
6.4.5.3	Comparison of Revenue, Costs, and Profits at Each Power Plant	167
6.4.5.4	Influence of Subsidy Variation on Profits Trend	167
6.5	Comprehensive Discussion	169
6.5.1	Policy Implications	169
6.5.2	Industrial Management Recommendations	171
	References	171
7	Bi-level Multi-objective Emission Quota Allocation Toward Coal and Sewage Co-combustion	175
7.1	Background Review	176
7.2	Main Issue Description	177
7.2.1	System Schematic	177
7.2.2	Uncertain Decision Environment	177
7.2.3	Optimization Scheme	178
7.3	Modeling	180
7.3.1	Notations	180
7.3.2	Allocation Scheme for the Authority	181

7.3.2.1	Maximizing Economic Benefits	181
7.3.2.2	Minimizing Carbon Emission Intensity	181
7.3.2.3	Maximizing Sludge Utilization	182
7.3.2.4	Benchmark Allocation Method	182
7.3.2.5	The Control of Carbon Emission	182
7.3.2.6	Power Supply and Demand Balance	183
7.3.2.7	Bounds of Quotas	183
7.3.3	Strategy for Coal-Fired Plants	183
7.3.3.1	Maximizing Profits	183
7.3.3.2	Quality Requirements on Fuel	184
7.3.3.3	Restrictions on Pollutant Emission	184
7.3.3.4	Available Quantities of Fuel	185
7.3.4	Global Model	185
7.3.5	Model Solving	185
7.4	Case Study	187
7.4.1	Case Description	187
7.4.2	Data Collection	187
7.4.3	Calculation Results	191
7.4.3.1	Analysis Under Different Objective Weights	191
7.4.4	Scenario Analysis	192
7.4.4.1	Scenario 1: Results Under Different Levels of Carbon Emission Reductions	194
7.4.4.2	Scenario 2: Results Under Different Carbon Emission Intensity Reduction Targets	195
7.5	Comprehensive Discussion	196
7.5.1	Model Comparison	197
7.5.2	Policy Implications	198
	References	199
8	Reliable–Economical Scheduling of Hybrid Solar–Hydro System	203
8.1	Background Review	204
8.2	Key Problem Statement	206
8.2.1	System Description	206
8.2.2	Trade-Off Between Reliable and Economical Power Supply	207
8.2.3	Handling Renewable Energy Uncertainties	208
8.3	Modeling	209
8.3.1	Notations	209
8.3.2	Hybrid System’s Reliability and Economy Equilibrium	210
8.3.2.1	Maximize Power Supply Reliability	210
8.3.2.2	Maximize Electricity Sales Revenue	211
8.3.3	Constraints of the Hybrid System	211
8.3.3.1	Photovoltaic Power Plant’s Output	211
8.3.3.2	Accessible Photovoltaic Arrays	212
8.3.3.3	Solar Power Output Limitation	212

8.3.3.4	Hydro Turbine Output	213
8.3.3.5	Limitation on Available Water	213
8.3.3.6	Dynamic Water Inventory	213
8.3.3.7	Limit on the Ability of Power Transmission	214
8.3.3.8	Limit on the Stability of Power Transmission	214
8.3.4	Global Model	214
8.3.5	Model Solving	216
8.4	Case Study	217
8.4.1	Case Description	217
8.4.2	Data Collection	219
8.4.3	Calculation Results	220
8.4.3.1	Technical Output Analysis	223
8.4.3.2	Power Output Ratio Analysis	224
8.4.3.3	Hourly Power Output Analysis	225
8.4.3.4	Economic Benefits Analysis	225
8.5	Discussion	228
8.5.1	Comparative Study	228
8.5.2	Related Propositions	229
8.5.3	Management Recommendations	231
	References	232
9	Reliable–Economic Equilibrium-Based Short-Term Scheduling of Hybrid Solar–Wind–Gas System	237
9.1	Background Review	238
9.2	Key Problem Statement	239
9.2.1	System Description	240
9.2.2	Resolving Renewable Energy Uncertainties	240
9.2.3	Achieving Reliable-Economic Equilibrium	242
9.3	Modeling	243
9.3.1	Notations	243
9.3.2	To Guarantee Economic Benefits and Reliability	244
9.3.2.1	To Maximize Total Income	244
9.3.2.2	To Minimize the Deviation of Power Supply and Demand	245
9.3.3	Constraints of System Components	245
9.3.3.1	Output of Solar Power Plants	245
9.3.3.2	Solar Power Output Limitation	246
9.3.3.3	Power Output of Wind Farm	246
9.3.3.4	Wind Power Output Limitation	246
9.3.3.5	Output of Natural Gas Power Plants	247
9.3.3.6	Operation Limitations of Natural Gas Turbines	247
9.3.3.7	System Spinning Reserve	247
9.3.4	Global Model	247
9.3.5	Mathematical Solving	249
9.3.5.1	Transforming the Multi-Objective Model Using ε -Constraint Method	249

9.3.5.2	Select the Optimal Solution Using Fuzzy Satisfying Method	249
9.4	Case Study	250
9.4.1	Case Description	250
9.4.2	Data Collection	251
9.5	Calculation Results and Analysis	255
9.5.1	Optimal Solutions	255
9.5.2	Economic Benefits Analysis	255
9.5.3	System Reliability Analysis	257
9.6	Comprehensive Discussion	260
9.6.1	Related Propositions	260
9.6.2	Comparative Study	262
9.6.3	Management Recommendations	263
	References	264
10	Reliable–Economical–Social Equilibrium-Based Scheduling of Hybrid Solar–Wind–Hydro System	269
10.1	Background Review	269
10.2	Key Problem Statement	271
10.2.1	System Description	271
10.2.2	Multi-objective Decision-Making Problem	272
10.2.3	Seasonal and Daily Uncertainties	273
10.3	Modeling	274
10.3.1	Notations	274
10.3.2	Four Main Goals Considered for the Hybrid System	275
10.3.2.1	Maximizing Complementary Rate	275
10.3.2.2	Maximizing Power Supply Reliability	276
10.3.2.3	Minimizing New Energy Curtailments	277
10.3.2.4	Maximizing Yearly Power Supply Profits	277
10.3.3	Constraints of the Hybrid System	277
10.3.3.1	New Energy Output Limitation	277
10.3.3.2	Hydropower Output Limitation	278
10.3.3.3	Water Flow Limitation	278
10.3.3.4	Water Volume Limitation	278
10.3.3.5	Transmission Capacity Limitation	279
10.3.4	Global Model	279
10.3.5	Model Solving	280
10.4	Case Study	281
10.4.1	Case Description	281
10.4.2	Data Collection	283
10.5	Results	284
10.5.1	Complementary Rates of New Energies	286
10.5.2	Results Under Different Reliability and Complementarity Rates	288
10.5.3	Results Under Different New Energy Curtailment Rates	290

10.5.4	Comparison of Different Systems	293
10.6	Discussion	293
10.6.1	Core Findings	295
10.6.2	Management Recommendations	296
	References	297
11	Optimal RPS Implementation Strategy Considering Both Power Suppliers and Users	301
11.1	Background Review	301
11.2	Key Problem Statement	303
11.2.1	Decision Process Description	303
11.2.2	Power User Classifications	304
11.2.3	Multi-Objectives of Demand and Supply Sides	304
11.3	Modeling	305
11.3.1	Assumptions	305
11.3.2	Notations	305
11.3.3	Objectives	306
11.3.3.1	To Minimize the Electricity Tariff Variations	307
11.3.3.2	To Minimize Total Costs	307
11.3.3.3	To Maximize RPS	308
11.3.4	Provincial Power Constraints	308
11.3.4.1	Power Generation and Consumption Balance	308
11.3.4.2	Power Sale Limitations	309
11.3.4.3	Power Transmission Limitations	309
11.3.4.4	RPS and Non-hydro RPS Target Limitations	309
11.3.5	Global Model	310
11.3.6	Model Solving	311
11.4	Case Study	314
11.4.1	Case Description	314
11.4.2	Data Collection	314
11.4.3	Calculation Results	317
11.4.3.1	Details of Power Consumption for Three Groups of Users	317
11.4.3.2	Details of Guangdong Province's Power Schedule	318
11.4.3.3	Three Key Findings From the Results Analysis	318
11.5	Discussion	319
11.5.1	Comparison With the Existing Schedule	319
11.5.1.1	Comparison of Power Tariff and Policy Acceptance	320
11.5.1.2	Generation Costs and CO ₂ Emissions	320
11.5.2	Scenario Analysis	322
11.5.2.1	RE Consumption Proportion Results	323
11.5.2.2	Power Tariff Results	324
11.5.2.3	Generation Cost and CO ₂ Emission Results	325
11.5.3	Key Finding	326
	References	327

12	Optimal RPS Implementation Strategy Considering Equity and Economy Equilibrium	331
12.1	Introduction	331
12.2	Key Problem Statement	333
12.2.1	Bi-Level Relationship	333
12.2.2	Equity and Economy Trade-Off	334
12.3	Modeling	335
12.3.1	Notations	335
12.3.2	Central Government's Equity Concern	336
12.3.2.1	Equitable Allocation	336
12.3.2.2	Renewable Energy Consumption Ratio	337
12.3.3	The Provincial Government's Economic Concern	337
12.3.3.1	The Balance of Renewable Electricity Generation and Trading	338
12.3.3.2	The Balance of Power Supply and Demand	338
12.3.3.3	Limitation of Generation Capacity	338
12.3.3.4	Limitation of Transmission Capacity	339
12.3.4	Global Model	339
12.3.5	Model-Solving Approach	340
12.4	Case Study	341
12.4.1	Case Description	341
12.4.2	Data Collection	341
12.4.3	Calculation Results	345
12.4.3.1	Generation and Trading Results for Individual Provinces	345
12.4.3.2	The Minimum and Maximum RPS that can be Achieved for Individual Provinces	347
12.4.3.3	Results of Central Government Considering Allocation Equity	348
12.5	Discussions	348
12.5.1	Trade-offs Between Equity and Economy	348
12.5.1.1	Comparison of Integrated Scores	351
12.5.1.2	Comparison of Maximum Equity Parameter	351
12.5.1.3	Comparison of the Cost-Change Rate	351
12.5.1.4	Comparison of Generation Strategy	354
12.5.2	Key Findings	354
	References	355
13	Optimal RPS Implementation Strategy Considering Emission Trade and Green Certificate Trade	359
13.1	Introduction	359
13.2	Key Problem Statement	361
13.2.1	Integration of the TGC and CET Policies	361
13.2.2	Interaction of Power Generation and Trading	363
13.3	Modeling	364
13.3.1	Assumptions	364
13.3.2	Notations	365
13.3.3	Power Generation and Trading Objectives	366

13.3.3.1	Economic Performance	366
13.3.3.2	Environmental Protection	367
13.3.4	Generation and Trading Constraints	367
13.3.4.1	Renewable Power Generation Capacity Limitation	367
13.3.4.2	Traditional Power Generation Capacity Limitation	367
13.3.4.3	Power Demand and Supply Balance	368
13.3.4.4	Power Transmission Limitation	368
13.3.4.5	Power Trading Constraints	368
13.3.4.6	TGC Trading Constraints	368
13.3.4.7	CET Trading Constraints	368
13.3.4.8	RPS-Bundled TGC Consumption	369
13.3.4.9	CET Quota Constraints	369
13.3.5	Global Model	369
13.3.6	Model Solving	370
13.3.6.1	Model Transformation Process	371
13.3.6.2	Applying Fuzzy Satisfying Approach to Select the Optimal Solution	372
13.4	Case Study	372
13.4.1	Case Description	372
13.4.2	Data Collection	374
13.4.2.1	Technical Generation Parameters	374
13.4.2.2	Policy-Related Parameters	375
13.4.3	Calculation Results and Analysis	375
13.4.3.1	Results of Power Generation and Trading	375
13.4.3.2	Results of Economic–Environmental Trade-Offs	378
13.5	Discussion	378
13.5.1	Scenario Analyses	378
13.5.1.1	Scenario Settings	379
13.5.1.2	Economic and Environmental Trade-Offs Under Different Scenario	379
13.5.1.3	Power Generation Results Under Different Scenarios	380
13.5.1.4	Power Trading Results Under Different Scenarios	380
13.5.2	Key Findings	381
	References	382
14	Emerging Hybrid Energy Storage Systems	387
	References	394
	Index	395

