

Index

a

activated carbon fabric (ACT) 79
 AMTEC 155
 electrodes for 171, 173
 working fluids for 169–170
 anion thermal diffusion 203
 arc spraying 37

b

β'' -alumina 155
 β'' -alumina solid electrolyte 163
 battery type thermal battery 197
 Bi_2Te_3 4, 25–28, 37, 60, 116, 120, 130, 131
 Boltzmann constant 11, 147
 bridging effect 27
 Butler–Volmer equation 159

c

carbon cloth 79
 carbon nanotubes
 conductive polymer composites 57–58
 carbon nanotube yarns (CNTY) 133
 carbon neutrality 155
 carbon textile 79
 Carnot-related efficiency 16
 cathode/electrolyte interface 159
 cathode pressure drop 160
 coherent nanostructures 30, 31
 cold-end compensation 88, 90
 compensation bridge 90
 concentrated solar power (CSP) 43
 conductive polymer composites 57–58

conjugated polymer

 n-type organic TE materials
 53–55
 p-type organic TE materials 50–52
 conversion efficiency 15–18
 copper hexacyanoferrate (CuHCF) 182,
 187, 201
 cyclodextrin (CD) 76

d

deep eutectic solvent (DES) 77
 drop-cast technique 62
 dual-stage sodium 163–169, 172

e

Eastman entropy 70, 74
 of transfer 147
 Ecoflex 117
 edge functional graphene (EFG) 80
 electrical conductivity 13–14
 electric double layer capacitive (EDLC)
 9
 electrochemical cycle 178
 electrochemical deposition/stripping
 196
 electrochemical impedance spectroscopy
 (EIS) 72
 electrodes 79–82
 for AMTEC 171, 173
 law 96
 electrode transition layer 39–40
 electrolytes 77–78

- electronic thermoelectric devices
 application and service performance 40–41
 Bi_2Te_3 25–28
 electrode connection technology 39
 and interface structure 39–40
 manufacturing process of 36–38
 PbX ($X=\text{S}, \text{Se}, \text{Te}$) compound 28–31
 Peltier effect 22–23
 performance and optimization method of 33–36
 Seebeck effect 21–22
 selection of electrode material 39
 SiGe alloy 31–33
 single-stage/multi-stage device
 structure design 38–39
 thermoelectric material/electrode transition layer 39–40
 Thomson effect 23–24
 endothermic effect 6
 equivalent series resistance (ESR) 79
- f**
 Faradaic process 10
 Faraday constant 9, 166
 filler factor 113
 filler material 113, 114, 118
 finite element method 38
 floating catalyst chemical vapour
 deposition (FCCVD) method 131
 four-probe method 14
- g**
 gas-liquid interface 160
 gelation process 148, 149
 gel-based electrolyte 83
 Gibbs free energy 8, 71, 83
 Gouy–Chapman–Stern theory 68
- h**
 Hagen–Poiseuille law 160
 Harman method 107–108
 heat absorption 22
 heat dissipation effect 117
 hopping transport model 47
 hybrid ion systems (HICs)
 mechanisms 196–200
 thermally regenerative electrochemical
 cycles (TRECs) 200–202
- i**
 inorganic material 116–121
 inorganic-organic superlattices 60
 inorganic semiconductor nanomaterials
 inorganic-organic superlattices 60
 interface optimization 59–60
 interface optimization 59–60
 intermediate conductor, law of 95
 intermediate temperature, law of 96
 isobaric liquid heating 157
 isobaric vapor cooling 157
 isothermal ion expansion 157
- k**
 KC200GT 189, 190
 Kelvin’s relationship 21
 Knudsen flow 160, 161
- l**
 liquid-based thermocells
 electrodes 79–82
 electrolyte 77–78
 redox couple 74–77
 liquid electrolytes 1
 liquid thermocells (LTCs) 1, 4, 195
 lithium-ion battery (LIB) 195
 lithium-ion thermal charging cell (LITC)
 196
 Lorenz constant 46
 low-grade heat harvesting
 charge transport 46, 49
 conversion efficiency 15–18
 electrical conductivity 13–14
 history of 2–4
 Peltier effect 6
 power density 18
 Seebeck coefficient 13
 Seebeck effect 5
 thermal conductivity 14–15
 thermal transport 45, 46

- thermodiffusion effect 8–9
 - thermoextraction effect 10–11
 - thermoelectric effect 9–10
 - Thomson effect 6–8
- m**
- mass transfer resistance 79, 159, 160
 - mean conductor, law of 95
 - metal-organic complex
 - n-type organic TE materials 52–55
 - p-type organic TE materials 50–52
 - multi-stage device structure design
 - 38–39
- n**
- nickel hexacyanoferrate (NiHCF) cathode
 - 183
 - non-coherent nanostructures 31
 - non-steady-state method 15
 - n-type organic TE materials 52
 - conjugated polymer 53–54
 - metal-organic complex 54
 - organic small molecules 54–55
 - n-type thermoelectric material 21
 - NWPU 124
- o**
- Ohm's law 73
 - open-circuit voltage (OCV) 9, 130, 158,
 - 162, 178
 - organic-inorganic composite material
 - 128–133
 - organic polymer material 121–128
 - organic rankine cycle (ORC) 195
 - organic small molecules
 - n-type organic TE materials 52–55
 - p-type organic TE materials
 - 50–52
- p**
- PbX (X=S, Se, Te) compound 28–31
 - PEDOT, PSS
 - dedoping of 56–57
 - secondary doping of 56
 - sequential treatments of 57
 - Peltier effect 2
 - electronic thermoelectric devices of
 - 22–23
 - low-grade heat harvesting 6
 - photovoltaics (PV) 43, 157
 - phthalocyanine (Pc) 51
 - π -shaped connection 82
 - Planck constant 11
 - p/n type conversion 203–205
 - polyethyleneimine (PEI) 123
 - polythiophene (PTh) 50
 - power density 18
 - p-type organic TE materials
 - conjugated polymer 50–51
 - metal-organic complex 51–55
 - organic small molecules 51–52
 - p-type thermoelectric material 21
 - PV module 189
 - pyrogen cell 143, 144
- r**
- redox couple 74–77
 - refractory metal coatings 171
 - roll-to-roll (R2R) printing 122
- s**
- Seebeck coefficient 4, 7, 13–16, 24, 26–28
 - Seebeck effect 2
 - electronic thermoelectric devices of
 - 21–24
 - low-grade heat harvesting 5
 - and Soret effect 137
 - semi-coherent nanostructures 30, 31
 - silicon-germanium (SiGe) alloy 31–33
 - single/double-walled carbon nanotubes
 - (S/DWCNTs) 57
 - single-stage device structure design
 - 38–39
 - single-stage sodium 158–163
 - sodium cations 159
 - sodium heat engine 155
 - solid-state thermoelectric (s-TE) 1, 141,
 - 146, 152
 - Soret effect 4, 70, 72, 137, 139, 146, 147,
 - 150, 212

- steady-state method 14
- Stefan-Boltzmann constant 166
- t**
- temperature coefficient 71, 83, 178, 179, 182–187, 191
- temperature-entropy (T-S) diagram 167
- temperature gradient 8, 10, 45, 68, 88, 91, 98, 140, 141
- thermosensitive thermocells
 - conversion efficiency and output power 105–107
 - electrode connected technology of 99–101
 - electrode material selection 99–101
 - Harman method 107–108
 - interface structure of 104–105
 - structure of 101–104
- thermal conductivity 12–17, 24–26, 30–32, 39, 45–47, 106–108, 113–118
- thermal conversion effect 150
- thermal diffusion effect 137, 145, 150, 198
- thermal-electric module 38
- thermal electrochemical converter
 - dual-stage sodium 163–169
 - single-stage sodium 158–163
- thermal electrode 88
 - materials 96–98
- thermal energy 137
- thermal load matching 113–115
- thermally charged capacitors (TCCs) 200
- thermally charged hybrid supercapacitor (TCHS) 197
- thermal regenerative electrochemical cycle (TREC) 178, 200–202
 - combination of 186–190
 - progresses of 180–186
- thermal transpiration 159
- thermocells
 - capacitance cycle 73
 - design 68–74
 - direct and indirect 82–85
- thermocouple 60, 88, 91, 96–98, 150, 210
- thermodiffusion 4
 - cell 141–143
 - effect 8–9, 145
- thermodynamic constraints 172
- thermodynamic cycle 157, 167, 178
- thermodynamic principle 2
- thermoelectric battery 41, 152, 178
- thermoelectric (TE) devices 3
 - construction 60–62
 - functionalization 62–64
- thermoelectric effect 43, 88, 91
- thermoelectric generators (TEGs) 40, 141, 189
- thermoelectric ionogels
 - application of 149–151
 - basic performance 139–141
 - preparation of 145–149
 - thermodiffusion cell 141–143
 - thermogalvanic and thermodiffusion effect 145
 - thermogalvanic effect 143–145
- thermoelectric material 39–40
- thermoelectric motive force 88, 89, 91
- thermoelectric power generation 38, 41, 100, 103, 108, 140
- thermoelectric refrigeration technology 41
- thermoelectrochemical cells
 - device integration and applications 207–210
 - engineering designs for 203
 - functional designs 205–207
 - p/n type conversion 203–205
- thermoelectrochemical system 4
- thermoextraction 4
 - effect 10–11
- thermogalvanic cells (TGCs) 200
- thermogalvanic effect 9–10, 143–145
- thermosensitive thermocells
 - cold-end compensation of 90
 - electrode law 96
 - hot end temperature of 93–94
 - law of intermediate conductor 95
 - law of intermediate temperature 96
 - law of mean conductor 95

- measurement conditions of 90–91
 - system design of 94–95
 - for thermal electrode materials 96–98
 - working principle of 88–93
- thermoelectricity 9, 82, 141
- Thomson effect 2
- electronic thermoelectric devices of 23–24
 - low-grade heat harvesting 6–8
- two-probe method 14
- V**
- van der Waals force 25
 - variable range hopping (VRH) model 47
- W**
- waste heat cogeneration 111
 - wearables devices
 - filler material 113, 114
 - inorganic material 116–121
 - lateral heat flow and substrates
 - effecting 115–116
 - organic-inorganic composite material 128–133
 - organic polymer material 121–128
 - thermal load matching 113–115
- wearable sensors 113
- Wiedemann–Franz law 45, 46
- Y**
- Y-shaped structure 35
- Z**
- zinc ion thermal charging cell (ZTCC) 4, 195, 201
 - zinc ion thermoelectric chemical batteries (ZTEC) 198
 - zinc ion thermoelectric chemical supercapacitors (ZTES) 198
 - ZT value 12, 21, 24, 26, 32, 84, 107, 206

