

Index

a

ab initio molecular dynamics (AIMD) 217–218
 acidic additive 135–136
 additives-based perovskite composites as absorbers
 additives-based wide-bandgap perovskite composites 162–164
 2D-3D based narrow-bandgap perovskite composites 166–167
 2D-3D based wide-bandgap perovskite composites 164–166
 additives-based wide-bandgap perovskite composites 162–164
 Ag electrodes based PSCs 56
 alkali halide doping strategy 110
 all-inorganic halide perovskites 10
 alloy structure in A, B or X site 31–33
 Arrhenius equation 15
 ascorbic acid (AA) 136, 137
 A-site alloying method 157
 atomic force microscopy (AFM) 110, 111, 212
 atomic-layer-deposition (ALD) 77, 228
 Auger recombination 22, 151
 average visible transmittance (AVT) 20, 21
 versus PCE 20, 105

b

Boltzmann constant 15, 205
 Brønsted proton acceptors 56

B-site alloy-based composites 160–161
 building integrated photovoltaics (BIPV) 20, 104, 200

c

capacitance–voltage (C–V) measurements 210
 carbon additives-based perovskite composites 142–146
 carbon-based composites
 ETL materials 81–82
 HTL materials 82–83
 for interfacial layer 84–85
 carbon, graphene, defined 105–110
 carbon nanoparticles (CNPs) 106, 107, 120
 carbon nanotube (CNT) films 28, 35
 carbon QD based composites 120, 122
 carbon quantum dots (CQDs) 82
 cell-to-module (CTM) 117, 193
 ceramic-matrix composites (CMCs) 27, 28
 charge recombination layer (CRL) 155, 156
 charge transport layers (CTLs) 2, 16, 18, 19, 46, 50, 52, 83, 105, 154, 173
 CIGS tandems perovskite 156
 coarse-grained simulations 217
 composite-based charge transport layers 34–35, 173–178
 composite-based electrodes 35–36
 composite-based perovskite active layer (PAL) 96

- composite-based perovskite films
 - characterization
 - chemical interactions 215–217
 - devices characterization, carrier mobility and dynamics 218–220
 - electrical properties 209–211
 - four-point probe method 209–210
 - growth dynamics of 205–207
 - heterogeneity 211–215
 - optical properties 207–209
 - simulations 217–218
 - stability characterization 222
 - trap densities 220–222
 - experimental techniques 220
 - SCLC method 221–222
 - theoretical and computational approaches 220–221
 - composite-based perovskite solar cells (CPSCs) 30, 75
 - development strategy 2
 - fabrication strategy for 3–5
 - interface engineering 4
 - composite functional materials
 - advantages of 30–31
 - classification of 28
 - development
 - alloy structure in A, B or X site 31–33
 - charge transport layers 34–35
 - composite-based electrodes 35–36
 - composite perovskites 33–34
 - properties of 27–30
 - composite materials, defined 27
 - composite perovskites 33–34
 - composites-based buffer layers 178–179
 - composites-based charge transport layers 173
 - electron transport layers in tandems 176–178
 - hole transport layers in tandems 173–176
 - composites-based hole transport layers in tandems 173–176
 - composites-based interconnection layers 167
 - in all perovskite tandems 170–171
 - in perovskite/organic tandems 171–173
 - in perovskite/Si tandems 167–170
 - composites-based interfacial layers in tandems
 - composites-based buffer layers 178–179
 - composites-based passivation layer 179–180
 - conduction band offset (CBO) 179
 - conductive atomic force microscopy (C-AFM) 167, 212–213
 - control crystallization by chemical interaction 124
 - crystalline silicon solar cells 1
 - C60 pyrrolidine tris-acid (CPTA) 72
 - current–voltage (I–V) measurements 210, 220
 - Czochralski (CZ) silicon 153
- d**
- deep level optical spectroscopy (DLOS) 220
 - deep level transient spectroscopy (DLTS) 220
 - density functional theory (DFT) 43, 57, 99, 100, 104, 174, 175, 217, 219, 220
 - density of states (DOS) 100, 220, 221
 - deposition methods 154, 158, 190, 191, 226, 228
 - device encapsulation, robust design 62–63
 - device heterointerface instability 52
 - efficiency loss induced by 58–60
 - heterointerface defects of
 - perovskite/ETL 52–54
 - perovskite/HTL 54–56
 - interaction with metal electrodes 56–58
 - differential scanning calorimetry (DSC) 217
 - dimethylformamide (DMF) 14, 167, 217, 228

dimethyl sulfoxide (DMSO) 14, 46, 99,
100, 164, 167, 206, 217, 228
Dion–Jacobson (DJ) 2D perovskites
11–12
disability adjusted life years (DALYs)
228
dye sensitized solar cells (DSSCs) 51

e

electrochemical impedance spectroscopy
(EIS) 79, 109, 217, 219
electron transport layer (ETL) 3, 18, 30,
34, 72
carbon-based composites 81–85
inorganic-based composites with metal
and metal oxide 76–81
organic-based composites 71–76
in tandems 176–178
electron transport materials (ETMs) 52,
72, 84, 176
energy conversion
efficiency improvement 22–23
energy gap 21–22
interface defects 22
external quantum efficiency (EQE) 144,
159, 220

f

facilitate strain release, heterostructure
interfaces 124, 126–127
flexible perovskite solar cells (F-PSCs)
19–20, 170
4-fluorophenethylamine (FPEAI)
166–167
4-fluoro-phenethylammonium chloride
(4F-PEACl) 179
2-(4-fluorophenyl)ethylamine
hydroiodide (F-PEAI) 164
2-(4-fluorophenyl)ethylammonium iodide
(FPEAI) 215
focused-ion-beam (FIB) technique 211
formamidine sulfinic acid (FSA)
163–164
formamidinium iodide (FAI) 9, 46, 52,
137, 140, 154, 158, 229

Fourier transform infrared spectroscopy
(FTIR) 110, 216
Frenkel defects 44, 45, 110
full width at half maximum (FWHM)
21, 96

g

gallic acid (GA) 135
 γ -valerolactone (GVL) 229
geometric filling factor (GFF) 117, 193,
194, 199
glass-glass vacuum laminated
encapsulation 189–190
global electricity 1
grain boundaries (GBs) 2, 3, 13, 19,
44–46, 60, 93, 96, 99–101, 104, 110,
115, 118, 124, 140, 141, 166, 187,
188, 207, 211, 213
graphene oxide/polyaniline (G-PANI)
nanocomposites 82
graphene quantum dots (GQDs) 33, 79,
81
grazing incidence wide-angle X-ray
scattering (GIWAXS) 118, 124,
166, 213–215
grazing incidence X-ray diffraction
(GIXRD) 126, 215
green production technology 228–229

h

hailde perovskite thin films 49
Hall effect 209, 220
heat-induced perovskite degradation 44
heterogeneity of composite-based films
211–215
heterointerface defects of perovskite
ETL 52–54
HTL 54–56
heterointerfaces instability, efficiency loss
induced by 58–60
heterojunction solar cells 19
highest occupied molecular orbital
(HOMO) 140
high resolution transmission electron
microscopy (HR-TEM) 211–212

Hoke effect 43
hole-conductor free (HCF) 17, 19, 103
hole/electron-transport-free simple structure 19
hole transport layer (HTL) 3, 34, 54, 83, 144
carbon-based composites 82
inorganic-based composites with metal and metal oxide 79
organic-based composites 72
hole transport materials (HTMs) 18, 19, 35, 54, 63, 72, 74, 75, 133, 134
hybrid perovskites and solar cells (PSC)
low-dimensional perovskites 10–13
perovskite crystal growth 14–16
single-crystal perovskites 13–14
three-dimensional perovskites 7–10
working principles 16–17
hydrazine additive 134–135
hydrazinium iodide (HAI) 135
hypophosphorous acid (HPA) 135

i

IEC 61215 norm 186
indene-C60 bisadduct (ICBA) 176
inorganic additives-based perovskite composites 103
acidic additive 135–136
alkali halide addtives 110–112
carbon, grapheme 105–110
hydrazine additive 134–135
metal oxides 103–104
semitransparent PSCs with metal oxide-based composites 104–105
 SnCl_2 additive 134
 SnF_2 additive 133–134
inorganic-based composites with metal and metal oxide
ETL materials 76–79
HTL materials 79, 81
inorganic composite-based perovskites 157
instability problems
device encapsulation robust design 62–63

device structures design 60, 62
perovskite composites development 60
interaction with metal electrodes 56–58
interconnection layer (ICL) 153–156, 167, 168, 172
interface defects 2, 22, 46, 54, 83, 115
interface engineering 3, 4, 22, 60, 72, 104, 105, 186, 226
interfacial layer, carbon-based composites 84–85
internal encapsulation 52, 102, 187–189, 196
internet of things (IoT) systems 198
ions migration of perovskites 50–51
isopropyl alcohol (IPA) 118

k

Kelvin probe force microscopy (KPFM) 53, 219

l

large-volume amines (LVAs) 142
lead-based perovskites 7–8
lead-tin mixed perovskites 8–9
levelized cost of energy (LCOE) 191
Lewis base additives 137, 140
Lewis electron acceptors 56
light-emitting diodes (LEDs) 13, 207, 209
light-harvesting material 1
liquid-phase transmission electron microscopy (TEM) 206
lithium bis(trifluoromethanesulfonyl)-imide (Li-TFSI) 76
low-dimensional (LD) perovskites 10
3D heterostructure perovskite composites 114
0D-3D composites 118–119
1D-3D composites 118
2D-3D composites 114–118
Dion-Jacobson (DJ) 2D perovskites 11–12
one-/zero-dimensional (1D/0D) perovskites 12–13

Ruddlesden–Popper (RP) 2D
perovskites 10–11

m

MAPbI₃ degradation 42, 53
materials instability
 device efficiency loss induced by
 51–52
 heat-induced perovskite degradation
 44
 ions migration 50–51
 moisture-induced perovskite
 degradation 41–42
 perovskite film surface/buried
 interfaces 46–48
 photo-induced perovskite degradation
 42–44
 point defects induced perovskite
 degradation 44–45
 strain-induced perovskite lattice
 distortion 48–50
matrix material-based composites 27
maximum power point tracking (MPPT)
 60, 222
metal electrodes interaction 56–58
metal halide perovskites (MHPs) 16,
 31–33, 110, 162, 231
metal-matrix composites (MMCs) 28
metal oxides 19, 72, 75, 79, 103–104
methylammonium chloride (MACl) 44,
 79, 158, 159
methylammonium iodide (MAI) 9, 41,
 44, 52, 56, 137, 205
micro-computed tomography (micro-CT)
 213
moisture-induced perovskite degradation
 41–42
molecular electrostatic potential (MEP)
 217, 218
Monte Carlo simulations 217, 219
Mott–Gurney law 211
multi-cation based perovskite
 compositions 93
multi-junction solar cells 9, 158, 178
multiple single-junction cells 151

n

n-i-p based traditional structure 18
nitrogen-doped graphene oxide (N_xGO)
 144, 145
N,N-dimethylformamide (DMF) 99

o

oleylammonium iodide (OAmI) 114,
 115, 213
1D-3D composites 118
one-/zero-dimensional (1D/0D)
 perovskites 12–13
organic additives-based perovskite
 composites 93, 137
 organic ammonium halides 93–96
 organic small molecules 96–99
 polymer based materials 99–102
organic ammonium halides 93–96
organic-based composites
 ETL materials 71–72
 HTL materials 72–76
organic small molecules 96–99
oxygen-induced photodegradation 43

p

Pb-based perovskites 7, 8, 119
2,2'-(perfluoronaphthalene-2,6-diylidene)-
 dimalononitrile (F6-TCNNQ)
 162
perovskite alloy-based composites as
 absorbers 156
 A-site alloy-based composites 157
 B-site alloy-based composites 160–161
 X-site alloy-based composites 158–160
perovskite-based devices
 device heterointerface instability
 52
 efficiency loss induced by 58–60
 heterointerface defects of
 perovskite/ETL 52–54
 heterointerface defects of
 perovskite/HTL 54–56
 interaction with metal electrodes
 56–58
 instability problems 60

- perovskite-based devices (*contd.*)
 - device encapsulation robust design 62–63
 - device structures design 60, 62
 - perovskite composites development 60
- materials instability
 - device efficiency loss induced by 51–52
 - heat-induced perovskite degradation 44
 - ions migration 50–51
 - moisture-induced perovskite degradation 41–42
 - perovskite film surface/buried interfaces 46–48
 - photo-induced perovskite degradation 42–44
 - point defects induced perovskite degradation 44–45
 - strain-induced perovskite lattice distortion 48–50
- perovskite-based tandems
 - all perovskite tandems 154–155
 - perovskite/CIGS tandems 156
 - perovskite/organic tandems 155–156
 - perovskite/Si tandems 152–154
- perovskite composites development 60
- perovskite crystal growth, dynamics of 14–16
- perovskite crystal lattice 45
- perovskite/ETL heterointerface defects 52–54
- perovskite film surface/buried interfaces 46–48
- perovskite/HTL heterointerface defects 54–56
- perovskite materials 2, 7–16, 33, 41, 52, 156, 192, 196
- perovskite/organic tandems 155–156
- perovskite quantum dots (PQDs) 120–121
- perovskite/Si tandems 152–154, 164, 167–170, 176, 179, 198
- perovskite solar cells (PSCs) 1
 - configurations of
 - flexible perovskite solar cells 19–20
 - hole/electron-transport-free simple structure 19
 - n-i-p based traditional structure 18
 - p-i-n based inverted structure 18
 - semitransparent perovskite solar cells 20
 - current status of 185–186
 - cyclic utilization of lead components 231
 - energy conversion
 - efficiency improvement 22–23
 - energy gap 21–22
 - interface defects 22
 - fabrication process of modules 192–193
 - future research 226–231
 - green production technology 228–230
 - market prospect 196–199
 - module quality assessment 194
 - module structure design 193–194
 - perspectives of composites-based 225–226
 - power conversion efficiencies 74
 - scalable fabrication methods
 - deposition methods 190–192
 - high-quality perovskite films 192
 - scale-up processing technology 226–228
 - solar modules production efficiency and stability improvement 196
 - recent advances in efficiency of modules 194–196
 - stability issues 186
 - evaluation standards 186–187
 - external encapsulation 189–190
 - internal encapsulation 187–189
 - toxicity issues of lead in modules 200
 - working principles 16–17
- perovskite solar modules (PSMs) 185, 226
 - GCL 197
 - IEC 61215 test 188

(6,6)-phenyl-C61-butyric acid methyl (PCBM) 71
 phenylethylammonium iodide (PEAI) 114
 photo-induced perovskite degradation 42–44
 photoluminescence (PL) 11, 13, 43, 79, 119, 120, 194
 photoluminescence spectroscopy 208
 p-i-n based inverted structure 18
 planar heterojunction (PHJ) 16, 71, 84
 planar n-i-p perovskite solar cells 73
 PMMA-based composite perovskite film 49
 point defects induced perovskite degradation 44–45
 poly(9-vinylcarbazole) (PVK) 49, 76
 poly(ethylene-co-vinyl acetate) (EVA) 141–142
 polycrystalline perovskite films 14, 45, 48, 60, 93, 99, 100, 187, 212
 polycrystalline perovskites 13, 19
 Polyethylene Terephthalate (PET) 226
 polymeric Lewis base 99, 100
 polymer-matrix composites (PMCs) 27, 28, 30
 polymer polymethyl methacrylate (PMMA) 99, 211
 polymethyl methacrylate (PMMA), HR-TEM technique 99
 power conversion efficiency (PCE) 1, 35, 71, 133, 151, 226
 lower 9
 4-pyrene oxy butylamine (PYBA) 124

q

quantum dot additives-based perovskite composites 119
 carbon QD based composites 120, 122
 perovskite QD based composites 120
 quasi-Fermi levels (QFLs) 16, 120

r

reduced film strain by composites-based perovskites

control crystallization by chemical interaction 124
 facilitate strain release by heterostructure interfaces 124, 126–127
 reduce lattice strain by compositional design 122
 reduced graphene oxide (rGO) 83
 reduce lattice strain by compositional design 122
 robust design, device encapsulation 62–63
 Ruddlesden–Popper (RP) 2D perovskites 10–11

S

scalable fabrication methods
 deposition methods 190–192
 high-quality perovskite films 192
 scanning electron microscopy (SEM) 21, 42, 110, 159, 179, 211
 Schottky defects 44, 45, 110
 selected area electron diffraction (SAED) 207
 self-assembled monolayers (SAMs) 79, 154, 156, 157, 167, 170
 self-assembled organic nanocomposites (SAONs) 72
 semitransparent perovskite solar cells 20
 semitransparent PSCs with metal oxide-based composites 104–105
 sequential interface engineering (SIE) strategy 179
 Shockley–Quisser (S–Q) 9, 21, 116
 silicon-based solar cells 1
 silicon heterojunction (SHJ)-bottom cells 153
 single-crystal perovskites 2, 13, 14, 45, 60
 single-junction c-Si solar cells 151
 single-junction solar cells 9, 21, 151, 161, 164, 173, 177
 single-walled carbon nanotubes (SWNTs) 82
 Si tandems perovskite 167–170

- slot-die coating method 191
- SnCl_2 additive 134
- SnF_2 additive 133–134
- Sn-PSCs, structures and additives 138
- Sn-PS solar cells 145
- solar modules production
 - efficiency and stability improvement 196
 - recent advances in efficiency of modules 194–196
- solar spectrum 23, 151
- solid-state nuclear magnetic resonance (NMR) spectroscopy 216
- space-charge-limited current (SCLC) 210, 220–222
- Spiro-OMeTAD oxidation process 76
- strain-induced perovskite lattice distortion 48–50
- Stranski–Krastanov mechanisms 205
- t**
- tandem solar cells (TSCs) 151
 - additives-based perovskite composites as absorbers 161–167
 - composites-based charge transport layers 173–178
 - composites-based interconnection layers 167–173
 - composites-based interfacial layers in tandems 178–180
 - perovskite alloy-based composites as absorbers 156–161
 - perovskite-based tandems 151
 - all perovskite tandems 154–155
 - perovskite/CIGS tandems 156
 - perovskite/organic tandems 155–156
 - perovskite/Si tandems 152–154
- 4-tert-butylpyridine (TBP) 76
- 4-(tert-butyl)pyridinium bis(trifluoromethanesulfonyl)imide (BPTFSI) 76
- thermal admittance spectroscopy (TAS) 218, 220
- thermally stimulated capacitance (TSC) techniques 155, 164, 170–172, 220
- thermogravimetric analysis (TGA) 217
- thin-film solar cells 1, 62
- 3D crystal perovskites 10
- three-dimensional perovskites
 - all inorganic perovskites 10
 - lead-based perovskites 7–8
 - lead-tin mixed perovskites 8–9
 - tin-based perovskites 9–10
- time-of-flight secondary ion mass spectrometry (TOF-SIMS) 173, 222
- time-resolved mass spectrometry technique 56
- time-resolved photoluminescence (TRPL) 79, 218
- tin-based perovskites 9–10
- TiO_2 -reduced graphene oxide (T/RGO) 81–82
- transient absorption spectroscopy (TAS) 218, 220
- transmission electron microscopy (TEM) 100, 205, 206, 211, 213
- transparent conductive oxide (TCO) 19, 20, 152, 156, 167, 192, 194, 231
- 2,2,2-trifluoroethylamine hydrochloride (TFEACl) 135
- 1,1,1-trifluoroethyl ammonium iodide (FEAI) 96
- trimethylamine (TMA) 140
- triphenylamine (TPA) 74–75, 84
- tris(2,4,6-trimethyl-3-(pyridine-3-yl)-phenyl)borane (3TPYMB) 71
- 2D-3D based narrow-bandgap perovskite composites 166–167
- 2D-3D based wide-bandgap perovskite composites 164–166
- 2D-3D composites 114–118
- 2D perovskites
 - Dion-Jacobson (DJ) 11–12
 - Ruddlesden–Popper (RP) 10–11

V

- van der Waals gap 10–12
- Volmer–Weber growth model 207
- Volmer–Weber mechanisms 205

W

- wide-bandgap (WBG)
 - absorber materials 152
 - perovskite modules 116, 199
 - perovskite precursors 115, 162, 164

X

- X-ray diffraction (XRD) 42, 48, 96, 112, 120, 133, 140, 164, 205
- X-ray photoelectron spectroscopy (XPS) 42, 98, 107, 110, 170, 213, 216
- X-site alloy-based composites 156, 158–160

Z

- 0D–3D composites, 118–119





