

Index

a

acrylonitrile-butadienestyrene (ABS)
34–39, 46, 47, 49, 51, 53, 54, 56,
71, 72, 76, 78, 79, 86, 87, 98–107,
112, 113, 117, 122, 135, 136, 138,
453, 455

acrylonitrile–styrene-acrylate (ASA)
34, 36, 37, 39, 46, 57, 73, 76, 77

Additive and Modular Enabled Rotor
blades and Integrated
Composites Assembly
(AMERICA) project 138

additive friction stir deposition (AFSD)
287, 288

additive manufacturing (AM) 1–24,
29–59, 69–87, 93–124, 129–150,
155–171, 177–192, 199–221,
227–242, 245–264, 285–287,
301–341, 439–468

Additive Manufacturing Integrated
Energy (AMIE) project
132–133

additives 38, 39, 45, 50–52, 54, 57, 58,
80, 160, 182, 187, 188, 191, 212,
213, 231

admixture 182, 185

aggregates 161, 167–169, 181–183,
187, 189, 213

AI Build company 17

alginate 189

Apis CorTM 165, 235, 248, 399

Arc-DED 282–285

Arevo's technology 12

art and design 245, 246, 251, 409

artificial intelligence (AI) 237, 240,
397, 416–425

artificial reefs 245–247

as-deposited microstructure 306–309

ASTM F3637–23 360

autoclave molds 38, 39, 108, 111, 115,
123

automated fiber placement (AFP)
process 10–11

b

Belotti group 6

big area additive manufacturing
(BAAMTM) 8, 9, 11, 14, 20, 48,
49, 97, 109, 111, 112, 129, 135,
140, 147, 453, 455

technology 5, 132, 453

binder jetting (BJ) 93, 161, 162,
271–273, 358, 407, 452, 463

bio-based materials 41–47

bio-based plastics 41, 42

biochar 186

BioHome3D 44, 46

biomimetic artificial reefs 246–247

bioplastics 41, 42

biopolymeric stabilizers 189

biopolymers 189

Blue Gantry 1–5, 12, 15, 17–20

Large Format Additive Manufacturing: Polymers, Metals, and Ceramics, First Edition.

Edited by Daniel M. Nieto, Daniel M. Sánchez, Ahmed A. Hassen, Eric MacDonald, and Sergio I. Molina
© 2026 WILEY-VCH GmbH. All rights reserved, including rights for text and data mining and training
of artificial intelligence technologies or similar technologies. Published 2026 by WILEY-VCH GmbH.

- bricks 157, 179, 188
- buildability 184–186, 192, 202, 203, 208, 213–216, 231, 232, 240, 263
- Building Information Modeling (BIM) 167, 467
- C**
- cable-driven printers 24
- cable-driven systems 236
- carboxymethyl cellulose (CMC) 187
- caulking gun 202, 210–212
- CEAD (Delft, Netherlands) 14
- cement 155–171, 177–192, 199–221, 245–264
- cement-based materials 163, 180–187, 202, 219, 221, 245
 - artificial reefs 246–247
 - buildings 248–250
 - opportunities 255–258
 - urban furniture 247–248
 - versatility 246
- cementitious 181–188, 227–242, 463–468
- cementitious materials LFAM 463
 - cementitious material bead extrusion 464–465
 - chemical process 466
 - deposition of extruded beads 465
 - extrusion head delivery 464
 - mechanical deformations 467
 - mixing of wet and dry ingredients 464
 - physical process 466–467
 - service life of produced structure 466
 - solidification 465–466
- cementitious mortar 187, 262, 263
- civil construction 156–159, 161, 168, 169, 178–180
 - energy consumption 157
- clay-based materials 158–170, 177, 180–192
 - art and design 251
 - opportunities 255–258
 - structures 251–252
- coarse aggregate binding (CAB) 161
- COBOD™ 166, 167, 235, 248
- coefficient of thermal expansion (CTE) 34–36, 38, 39, 42, 43, 50, 82, 83, 115, 117, 118
- cold spray additive manufacturing (CSAM) 285–287
 - advantages 285
 - challenges 286
- cold spray 3D printing 285
- commodity polymers 34, 117
- compression molding molds 115, 116, 123
- computational fluid dynamics (CFD)
 - model 460, 464, 465
- concrete 180–189
- concrete casting molds 116, 123
- Concrete Choreography project 250
- concrete facade panels
 - in Heydar Aliyev Centre 255
 - in Vhils' panels 255
- concrete printing (CP) methodology 164, 168
- construction LFAM 199–201
 - building finishing up 241–242
 - components 227, 229–237
 - custom nature of 227–228
 - economic drivers 229
 - environmental impacts 229
 - equipment removal, structure curing, and site restoration 241
 - foundation 230
 - material delivery system 232
 - materials 230–232
 - motion system 234
 - operation 239–240
 - permit 238–239
 - quality control and quality assurance 240–241
 - reinforcement 232–233
 - site preparation 239
 - social drivers 228–229
 - structural design 237–238
- Construction 4.0 200, 201, 221

construction industry 44, 112,
 156–159, 187, 192, 200, 201, 221,
 227–230, 251, 253, 284, 399–400,
 467
 Construction Management 227
 construction waste 157
 continuous fiber 3D printing (CF3D)
 12
 continuum-scale model 452
 Contour Crafting™ (CC) concept 164,
 165, 168
 coordinate measuring machines (CMM)
 444, 446
 corrosion behavior 324–326
 cryogenic mechanical properties 322
d
 DED technologies 274–277, 400
 Delta Wasp 3MT 5
 deposition process 301–303
 as-deposited microstructure
 306–309
 postprocess heat treatment 309–311
 ferrous alloys 311–315
 non-ferrous alloys 315–317
 solidification 303–306
 Design for Additive Manufacturing
 (DfAM) 32, 141, 420, 422, 423
 diffraction-based methods 449
 Digimat-AM tool 460
 digital tectonics 254
 digital twin, multiscale numerical
 modeling for 460–462
 directed energy deposition (DED) 271,
 272, 274–278, 301, 302, 422
 arc-DED 282–285
 EB-DED 281–282
 L-DED 278–281
 machines 12
 direct writing (DW) 29
 discrete element approaches 467
 dissolvable materials 48–49
 distortion 34, 35, 71, 83, 110, 114, 115,
 283, 285, 357, 367, 380, 382, 420,
 422, 423, 440–444

compensation 444
 in Hybrid Additive and Subtractive
 Manufacturing 449–451
 interactive control 444–446
 measurement techniques 446
 Dive Technology 135
 double-wire arc-DED 285
 D-Shape system 161, 162
 dynamic open time 202, 208
e
 EAAD 251, 253
 earth 158, 168, 169, 178, 179, 188–192
 EB-DED 281–282
 elastic limit 201
 electric arc 276, 282, 283, 302, 354, 358
 Electroimpact's Scalable Composite
 Robotic Additive Manufacturing
 (SCRAM) system 11
 electron backscatter diffraction (EBSD)
 332, 333, 340, 370–372, 383
 electron beam additive manufacturing
 (EBAM) 158, 281
 energy applications 137–138
 ER70S-6 welding wire 322
 extrudability 182–185, 202, 203, 208,
 211, 212, 216, 231, 232, 240, 262,
 263
 extrusion-based technologies 163
 extrusion deposition-based additive
 manufacturing (EDAM) 29, 46,
 453, 454, 456, 459, 462, 463

f
 facade applications 252–255
 facade concrete panels 253
 FE analysis 458, 460
 ferrous alloys 311–315
 fiber reinforcement 11, 12, 21, 30, 36,
 42, 47, 118
 finite element method (FEM) 378,
 444, 446, 455, 467
 finite element method (FEM)-based
 numerical simulation 444, 455
 flowability 70, 73, 183, 358

- flue-gas desulfurization (FGD) gypsum 212
- foamed materials 50
- 45-degree belt printers 22–23
- fossil fuel-derived polymers 47
- freeform following printers 23–24
- friction-based AM 272, 274, 275, 287, 290
 - benefits 287–289
 - challenges 289
- functionally graded materials (FMG) 276, 420
- fused filament fabrication (FFF) 1, 2, 18, 29, 30, 34, 38, 39, 53–55, 59, 69, 78, 87, 141, 147
- fused granulate fabrication (FGF) 29, 46, 69
- fused pellet modeling (FPM) 1
- g**
 - gantry-based printing system 248
 - gantry motion systems 234–236
 - geometrical design considerations 143–144
 - contour configuration and filling 147–148
 - minimum wall thicknesses and slim elements 144–145
 - overhang areas and bridges 145–147
 - geomaterials 231, 463
 - GMAW-based Arc-DED technology 284
 - grain shape 364–371
 - grain size 364–371
 - Grasshopper software 257
 - GTAW-based Arc-DED technology 284
- h**
 - Hall-Petch effect 364
 - high-temperature autoclave tooling 108
 - high-temperature Dahltram I-350 carbon fiber resin 108
 - hole-drilling 449
 - human evolution 155, 228
 - Human Machine Interface (HMI) software 15, 16
 - Hybrid Arc-DED 285
 - hybrid manufacturing 331
 - humidity of build chamber 334–336
 - for localized microstructure control 336–338
 - 316L fabricated 331–334
- i**
 - ICON™ 166, 235, 248
 - inert carrier gas 302
 - infinite printer 169
 - infrared (IR) thermography 442
 - in situ 3D concrete printing technology 248
 - integrated thermo-mechanical phase transformation model 448
 - interactive distortion control in wire-arc DED 445
 - interior design and furniture 138–141
 - interpass temperature 302, 305–307, 314
 - International Labor Organization 156
- j**
 - JuggerBot 3D Tradesman P3-44 9–10, 18
- k**
 - keyhole-induced pores 356, 357
- l**
 - lack of fusion (LOF) 278, 324, 355, 356, 358, 359
 - Laminated Object Manufacturing (LOM) 273
 - Large Format Additive Manufacturing (LFAM) 69
 - admixture 182
 - aerospace 130–131
 - aggregates 182
 - anechoic chambers and wall panels 150

- anisotropy 31
- architecture 131–134
- as-deposited microstructure 306–309
- automotive 130
- buildability 184
- build table 14
- for cement-and clay-based materials
 - processing 158–170
- cement-based materials 180–192, 245–250
 - opportunities 255–258
- cement-based printable materials 201
- with cementitious materials 192
- chemical composition 377–379
- clay-based materials 187–192, 250–251
 - art and design 251
 - opportunities 255–258
 - structures 251–252
- co-extrusion of wires 11–12
- compressed air-assisted process 170
- in construction 227–229
- continuous fiber printing 12
- corrosion behavior 324–326
- cost efficiency, industrialization, and market adoption 18–21
- cryogenic mechanical properties 322
- deposition process 301–303
- design considerations
 - deposition nozzle 142–143
 - geometrical 143–148
 - layer configuration and resolution of printed parts 141–142
 - layer time dependence 143
- dimensional and tolerance control in 379–383
- energy applications 137–138
- extrudability 183–184
- extrusion-based methods 163–169, 182
- facade applications 252–255
- facade component manufacturing
 - challenges 258
- facade panel fabrication
 - project definition 259
 - 3D model design 260
 - 3D print test and validation 261–264
- ferrous alloys 311–315
- FFF systems 1, 2
- filament-based feedstock 3–4
- flowability 183
- furniture and interiors 150
- grain size and shape 364–371
- heated enclosures 9–10
- high-temperature mechanical properties 318–322
- hybrid, combined technology 327–331
- improving layer adhesion 14–15
- integration of automated fiber placement 10–11
- interior design and furniture 138–141
- machining and post-processing 7
- machining strategies 121–123
- market adoption 20–21
- material drying, conveyance and control systems 6–7
- multi-materials printing 7–8
- non-ferrous materials 315–317
- open-time 184
- optimal motion platform for 21–24
- ORNL 2–3
- ORNL's Blue Gantry system 4
- oxidation resistance 326–327
- phases 361–363
- pick and place system 8–9
- polymers
 - development of 57–59
 - dissolvable materials 48–49
 - foamed materials 50
 - magnetic materials 48
 - nano-additivated materials 50–51
 - sustainable and bio-based materials 41–47

- Large Format Additive Manufacturing (LFAM) (*contd.*)
 - thermoplastics and thermoplastic composites 32–40
 - thermosets polymers and reactive chemistries 40–41
 - post-process heat treatment 309–311
 - powder bed and material jetting 159–163
 - printability 182
 - printability window 183
 - release agents and mold coating 121
 - room-temperature mechanical properties 317–318, 322
 - slicing software and printing algorithms 15–18
 - smart molding 150
 - solidification 303–306
 - thermokinetics 309
 - thixotropy 184
 - 3D printing 170–171
 - topological optimization 148–149
 - wind tunnels 150
- large format additive manufacturing (LFAM) with metallic materials
 - advantages 269–270
 - aerospace industry 394–397
 - artificial intelligence 416–424
 - artistic and creative applications 409–410
 - automotive industry 397–398
 - challenges 271
 - construction industry 399–400
 - marine industry 402–406
 - molds 410–412
 - oil and gas industry 406–408
 - other industrial applications 413–416
 - process workflow 274–275
 - railway industry 401–402
 - sports equipment 412–413
 - technology classification 271–274
- large-scale extrusion 3D printing technology 167
- large-scale wire-DED challenges 440
- laser cladding 279, 401
- laser-DED (L-DED) 276, 278, 283, 285, 289, 290, 302, 303, 307–310, 393, 395, 396, 400, 407
 - disadvantage 279
 - laser powder-based DED 279–280
 - laser wire based-DED 280–281
 - process parameters 278
 - recycling and reusing powder 280
- laser displacement sensors (LDS) 444
- laser metal deposition (LMD) 278, 366
- laser powder-based DED 279–280
- laser welding 356, 357
- laser wire based-DED technology 280–281
- layer-by-layer bottom-up method 380
- life cycle assessment (LCA) 187
- m**
 - machine-tool-based systems 289
 - magnetic materials 48
 - Magnum Venus Products (MVP) 8, 9, 97
 - MakerBot Replicator 2–4, 18
 - marine applications 36, 134–137
 - Massachusetts Institute of Technology (MIT) 159
 - mass balance approach 378
 - material extrusion (ME) 69–70, 94, 183, 201, 233, 271–273, 398, 452, 461
 - polymers and polymer-based composites 74
 - mechanical properties of 74–79
 - microstructural analysis of 84–87
 - rheology of 70–74
 - thermal and thermomechanical properties of 79–83
 - mean-field homogenization methods 460
 - Melt Flow Index (MFI) 54, 73, 74, 76
 - metal additive manufacturing (MAM) 271–273

digital design for distortion and residual stress control 440
 distortion and interactive control 444–446
 residual stress manipulation 446–449
 thermal sensors 440–444
 tool path planning 440–444
 transition 439–440
 metal arc welding (MAW) 302, 303, 307, 308
 metal casting 439
 metal LFAM powder-fed processes 353–354
 Metallic LFAM solutions 289–291
 metallographic analysis 360–361
 molds and dies 93–124
 autoclave molds 115
 compression molding molds 115
 concrete casting molds 116
 design and operation requirements 113–114
 final parts materials 118–120
 large format additive manufacturing of 96–113
 material selection criteria 116–118
 need for 95–96
 out-of-autoclave (OOA) molds 114
 stamping dies 115–116
 trim tools and fixtures 114
 vacuum-assisted resin transfer molding and lay-up tooling 114
 motion system
 cable-driven systems 236
 gantry motion systems 234–236
 process control software 236–237
 robotic motion systems 236
 MUD Frontiers project 188–189
 multiagent printing 23, 24
 multi-material printing 8, 24, 30, 459
 multiscale numerical modeling, for digital twin 460–462

n

nano 43, 50–51, 84, 182, 185, 188, 209, 371
 natural fabrics 190
 Navantia's 3D Cabins project 6
 neutron diffraction (ND) methods 446, 447, 449, 450, 452
 nonferrous materials 315–317
 nozzle design 280
 nucleation 182, 304, 306, 312, 334, 361, 362, 364, 377
 numerical modeling and simulation 376–377

o

Oak Ridge National Laboratory (ORNL)
 1–5, 12, 15–20, 43, 45, 48, 50, 94, 97, 98, 109, 111–113, 129, 132–135, 137, 138, 236, 410, 411, 414–416, 453
 BAAM technology 132
 Blue Gantry 2–5, 18–20
 off-site applications 248–250
 OpenFOAM 460, 461
 optical fiber sensor (OFS) 444, 446
 optical microscopy 84, 355, 370, 371, 383
 Optionally Manned Technology Demonstrator (OMTD) 134, 135
 original equipment manufacturer (OEM) 15
 out-of-autoclave (OOA) molds 114, 123
 oxidation resistance 326–327

p

parametric design methodology 246, 249, 251, 252, 259, 264
 pastry bag method 211
 PAW-based arc-DED process 284
 physics-based 1D heat transfer model 455
 plastic viscosity 201, 209

- polyacid lactic (PLA) 38, 41–47, 49, 51, 53, 71, 73, 76, 79, 84, 117, 121, 122, 140
 - polycaprolactone (PCL) 42, 71
 - polyetherimide (PEI or Ultem®) 39, 54, 71, 72, 104, 123
 - polymer LFAM 29, 141
 - advancements and challenges 452–454
 - challenges and opportunities 462
 - EDAM process modeling and simulations 454
 - fiber orientation 458–460
 - layer deposition time optimization 456–458
 - multiscale numerical modeling for digital twin 460–462
 - temperature history, deformation and residual stress 455–456
 - polymers and polymer-based composites 69–70
 - mechanical properties of 74–79
 - microstructural analysis of 84–87
 - rheology of 70–74
 - thermal and thermomechanical properties of 79–83
 - polypropylene (PP) fibers 185, 186
 - polyphenylene sulfide (PPS) 34–36, 38, 56, 79, 101, 108–110, 117
 - polyvinyl alcohol (PVA) fibers 186, 213, 215
 - pore closure 311
 - porosity 355–360
 - porosity characterization 360–361
 - potentiodynamic polarization analysis 324, 325
 - powder bed-based systems 161
 - powder bed fusion (PBF) 272–273, 301, 302, 316, 357–358, 379, 381, 393, 394
 - tool path planning for 441–442
 - powder feeder 162, 302
 - power-based L-DED 280
 - pozzolanic 178, 182
 - precipitation hardened (PH) steels 314, 365
 - prefabrication 248–250, 252, 254, 255, 259
 - printability 39, 42, 49, 51, 101, 116, 163, 177, 180–182, 184, 186, 188, 189, 192, 210, 240, 424
 - printability window 183
 - process control software 230, 236–237
 - programmable logic controllers (PLCs) 2, 16
 - pumpability 183, 203, 208, 231, 232, 240
 - pumping system 162, 168, 183, 184, 211, 237, 239
- r**
- Rabiowitsch equation 70
 - Radiolaria Pavilion 163
 - raw earth 169, 189
 - reactive additive manufacturing (RAM)
 - thermoset LFAM platforms 8
 - reduced strain closure (RSC) fiber orientation diffusion model 458
 - residual stress 9, 31, 34, 40, 43, 71, 76, 271, 278, 283, 302, 311, 327, 355, 357, 359, 367, 371–377
 - in Hybrid Additive and Subtractive Manufacturing 449–451
 - manipulation 446–449
 - rheometers 71, 73, 202, 206, 208–210
 - Robotic Fabrication Laboratory (RFL) 250
 - robotic machining 7
 - robotic motion systems 236
 - robotic systems 12, 21, 24, 190, 201, 221, 236, 289
 - Roman innovation 178
- s**
- selective binder (cement) activation (SCA) 160
 - selective paste intrusion (SPI) 160

- semi-crystalline polymer 33
- Sequential Quadratic Programming (SQP) method 458
- setting time 182, 186, 202, 203, 211–214
- shape retention test 214, 215
- sheet-based FSAM 273, 287, 288
- sheet lamination 271–274, 287, 452
- Sheet Molding Compound (SMC) composites 109, 110
- shell or hollow concept 31
- Shotcrete 3D printing technique 170
- solidification, in LFAM 303–306
- solidification rate 369
- solid-state welding technologies 274
- stamping dies 111, 115–116
- static-dynamic open time 208
- strain relaxation-based methods 449
- structures, LFAM 251–252
- Studio RAP 251
- sugarcane bagasse ash (SCBA) 187
- superabsorbent polymers (SAPs), 186
- Super Discovery Max 6
- sustainable and bio-based materials 41
- Sustainable Development Goals (SDGs) 199, 200
- t**
- Tandem or twin Arc-DED 285
- Technology and Clay (TECLA) 169
- tectonics 254
- thermal distortion, 283, 285, 367, 423, 455, 456
- thermal sensors 440–444
- thermal-structural coupling methods 374
- thermocouples 417, 443, 444
- thermokinetics process 303
- thixotropy 184, 186, 201, 240, 473
- 3D concrete printing (3DCP) 246, 250, 253
- 3D laser scanner 444, 446
- 3D printing 158–160, 200
 - buildability 203
 - cementitious mortars 187
 - in civil engineering 186
 - in construction 200
 - current challenges 201
 - density 210
 - engineered cementitious composites 208
 - extrudability 203
 - flow table method 204
 - hardened mechanical properties 218–220
 - with land-based mortars 191
 - mechanical behavior 204
 - open time 208
 - pastry bag and caulking gun 210–211
 - powder bed 160
 - requirements 203
 - rheometer testing 208–210
 - setting time 211–214
 - shape retention test 214–215
 - slump test 205
 - squeezing test 206–207
 - using mortar/concrete 185
 - using robotic systems 190
 - V-funnel test 207
 - visual inspection 215–218
- 3D Systems EXT Titan 10
- Tim Womer & Associates 5
- titanium alloys 285, 366, 367, 378, 420
- tolerance control, in LFAM 380
- top-down approach 452
- track-mounted printers 22
- traditional 3D printing methods 2
- trim tools and fixtures 100, 114, 117
- u**
- ultra-high performance concrete (UHPC) 185, 464
- ultrasonic additive manufacturing (UAM) 273
- ultrasonic testing (US) 360
- urban furniture 245, 247–248

V

vacuum-assisted resin transfer molding
(VARTM) 97
and lay-up tooling 114
Vanke Pavilion 255, 257

W

wall building machine 159
WASP™ 5, 168, 169, 190, 251, 261
Web of Science 97, 328
WinSun™ 165, 166
wire-additive welding 317
wire arc additive manufacturing
(WAAM) 158, 282, 358, 381

wire arc-based LFAM (WA-LFAM)
311
wire-arc directed energy deposition
(WA-DED) 302, 307, 393
wire-based L-DED 280, 281
wire direct energy deposition
(wire-DED) 439

X

X-ray computed tomography (XCT)
86, 360, 371, 383
X-ray diffraction 355, 374
X-ray methods 449















