

Index

a

- ABX₃ and hybridized ABX₃ type materials 107–110
- active matrix organic light-emitting diodes (AMOLEDs) 7
- additive engineering 117
- Ag₂S@SiO₂ quantum dots 89
- 2-(2-(2-aminoethoxy)acetic acid (AEAA) 86
- 5-aminopentanoic acid (5AVA) 85, 96
- amplified spontaneous emission (ASE) 334–338, 343
- annealing 70, 96, 113, 117, 120, 131, 140, 151–153, 171, 190, 209, 325
- antimony-based metal halide materials 241
- antisolvent method 190
- A-site metal ion doping 208–210
- Auger process 146, 147
- Auger recombination 20, 24, 296, 318, 334, 335, 337
- augmented/virtual reality (AR/VR) 7

b

- bimetallic cationic halide perovskites materials 243–247
- 9,10-bis(*N*-benzimidazole)anthracene (BBIA) 292
- bismuth-based metal halide materials 238–240
- blue light-emitting layers preparation nano-microcrystalline precursors 191

- three-dimensional and quasi-two-dimensional perovskite films 190–191
 - blue light perovskite materials 218–220
 - blue perovskite light emitting diodes
 - blue-shift strategy 171–175
 - interface engineering 193–195
 - optimization of device stability 195–199
 - passivation of film defects 191–192
 - selection and optimization of hole and electron injection layers 192–193
 - technology development of 169–170
 - blue-shift strategy 171–175, 178, 179, 199, 200
 - Boltzmann constant 333
 - B-site metal ion doping 208, 210–212
- ### **c**
- cationic hybridized perovskites 110
 - charge injection layers (CILs) 285
 - charge transport layer (CTL) 118–120, 155, 285, 295, 323, 324
 - charge transport materials in PeLED 288–290
 - charge transport of metal halide perovskite materials 286–288
 - Cl/Br mixed halide perovskite material 231
 - colloidal synthesis methods 214, 221–223

- colloidal undoped and double doped
 - Cs₂AgInCl₆ nanocrystals 263–265
- conjugated polymeric electrolytes (CPEs) 304, 324, 325
- copper-based metal halide materials 241–243
- core-shell ZnO/ZnS nanoparticle 291
- crystal engineering 130, 150–151, 161
- CsPbBr₃ QDs 55, 148
- CsPbBr₃ quantum dot perovskite LED device 141
- CsPbBr₃ quantum dots 130, 131, 134, 141–143, 160, 189
- CsPbI₃ 42, 44, 55, 66, 69, 103, 105–110, 114–116, 120, 214–216, 220, 221, 274, 275

- d**
- device stability 20, 131, 160, 161, 195–199, 231, 290, 313, 318, 324, 326
- diamine passivation molecule 96
- didodecyldimethylammonium bromide (DDAB) 42, 142, 143, 149, 150, 184, 185
- dodecyl dimethyl ammonium ion (DDA⁺) 185
- doped organic electron transport materials 293–294
- doping 9, 13, 19, 87, 90, 91, 93, 95, 107, 110, 113–114, 120, 121, 131, 172, 174, 181–183, 186–188, 195, 199, 205–225, 237, 239, 245, 247–249, 251, 257, 261, 267, 270, 273, 276, 277, 280, 292, 294, 296, 300, 301, 305, 307, 320, 323, 324, 326, 327
- double HTLs with PVK and TFB 302–303
- double perovskites 91, 107, 110–111, 120, 214, 243, 245, 247, 249, 265, 267
- down-conversion 257–261, 277, 336
- down-conversion luminescence 336
- down-conversion method 257–261

- e**
- efficiency roll-off 132, 146, 147, 153, 161, 169, 195, 196, 199, 217, 292, 318–328
- electron and hole transport materials
 - charge transport materials in PeLED 288–290
 - charge transport of metal halide perovskite materials 286–288
- electron injection layer modulation 325–328
- electron-phonon coupling effect (EPI) 179
- electron transport materials in PeLEDs
 - doped organic electron transport materials 293–294
 - inorganically doped electron transport materials 292
 - inorganic oxides electron transport materials 290–291
 - organic-inorganic hybrid electron transport materials 294
 - organic monolayer electron transport materials 292
 - organic multilayer electron transport materials 292–293
- europium-based metal halide materials 243
- exciton
 - definition of 2–3
 - self-trapping 3–4
- exotic excitation 3
- external quantum efficiencies (EQEs) 11–16, 18–21, 25, 42, 83–86, 88–91, 93–99, 103–105, 115, 118–120, 129–132, 134–137, 140–158, 160, 161, 170, 177–179, 181, 183, 185, 188, 192, 215–217, 219, 220, 255, 256, 258, 261, 263, 264, 274, 279, 281, 282, 291–293, 297, 299–304, 306, 307, 317, 319, 322–324, 327

- f**
- Frenkel excitons 2
- full electroluminescent PeLEDs

- sky-blue perovskite light emitting diodes 266–270
 - yellow perovskite light emitting diodes 261–266
- g**
- gas-solid interactions 119–120
 - Goldschmidt tolerance factor 36, 87, 207, 221, 236
 - green light perovskite materials 216
 - organic-inorganic hybrid perovskite materials 136–137
 - pure inorganic perovskite materials 134–136
 - synthesis of 137–140
 - green perovskite light emitting diodes
 - aspects of materials 146–147
 - aspects of the device structure 147
 - crystal engineering 150–151
 - history 129–132
 - ligand engineering 147–150
 - nanocrystalline green perovskite light emitting diodes 142, 144, 146
 - optimization of device structure 155–158
 - other properties of 158–161
 - passivation engineering 153–155
 - quantum dot 141–143
 - quasi-2D Ruddlesden-Popper green perovskite light emitting diodes 145–146
 - structure of 140
 - surface engineering 151–153
- h**
- halide perovskite quantum dots/nanocrystals 40, 42–44
 - halide perovskites 35, 49, 53, 70–74, 84, 86–89, 94, 98, 99, 106, 196, 211, 212, 214, 313, 335
 - charge transport of 286–288
 - colloidal 220
 - crystal structure 1–2
 - crystal structure and possible defects 319
 - exciton effects 2–4
 - factors influencing the efficiency of 16–23
 - heterophase 274
 - layered 36–40
 - lead 221
 - for light-emitting diodes 36
 - luminescence properties 7–16
 - non-lead metal 231–251
 - quantum dots/nanocrystals 40, 42–44
 - size effect 5–7
 - sources of instability 313–317
 - two-dimensional phase precursors 260
 - zero-dimensional Sn-doped 261–263
 - halogenated perovskites 3, 91, 134, 205, 208, 210, 214, 218, 224, 225, 248
 - heterogeneous perovskites 110, 133
 - high temperature solid-state synthesis method 220, 223–224
 - hole injection layer modulation 323–325
 - hole transport materials in PeLEDs 286, 294–295
- i**
- impurity doping 205
 - inorganically doped electron transport materials 292
 - inorganic oxides electron transport materials 290–291
 - insulator-perovskite-insulator (IPI) structure 156
 - interface engineering 191–195, 327
 - interfacial passivation 120
 - intrinsic bimolecular recombination constant 15
 - intrinsic self-trapped exciton 3
 - ion exchange method 67–68, 121, 220–221
- j**
- Joule heating 20, 158, 160, 300, 319, 327

l

- large-area perovskite films
 - non-template method 75–76
 - printing method 71–72
 - spin coating 69–70
 - spraying method 74–75
 - template method 75
 - vacuum thermal vapour deposition method 70–71
 - vapour phase deposition method 71–74
- laser
 - of perovskite films 337–339
 - of perovskite nanocrystals or quantum dots 343–344
 - of perovskite nanoplates and microplates 341–343
 - of perovskite nanowires 339–341
 - physics principles of 333–337
- laser etching method 68–69
- layered halide perovskite materials 36–40
- layered organometallic halide perovskites 94
- lead-free blue perovskite materials 232
- lead-free metal halide emitters 231
- ligand-assisted redeposition (LARP) 137–139, 160
- ligand-assisted-precipitation (LARP) 45, 60–67, 234, 235
- ligand engineering 45, 91, 103, 132, 251, 323
- light extraction efficiency (LEE) 85, 98, 281
- LMPT method 185
- low-dimensional metal-halide perovskites (2D perovskites) 335
- luminescence properties of perovskite materials
 - non-radiative combination mechanisms at surfaces and interfaces 13–16
 - photon generation 8–10
 - photophysical processes and efficiency calculations 10–13
 - luminescence quantum yield 35, 83, 84, 103, 137, 169, 215, 223, 231, 265, 299, 334, 338

m

- MAPbBr₃ colloidal nanocrystals 142
- mechanochemical method 46–47
- metal halide double perovskites 110, 111
- metal halide perovskites (MHPs) 286
 - charge transport of 286–288
 - crystal structure of 1–2
 - exciton effects 2–4
 - factors influencing the efficiency of 16–23
 - luminescence properties 7–16
 - non-lead 231–251
 - size effect 5–7
 - sources of instability 313–317
- metal ion doping effect
 - A-site metal ion doping 208–210
 - blue light perovskite materials 218–220
 - B-site metal ion doping 210–212
 - colloidal synthesis methods 221–223
 - green light perovskite materials 216–218
 - high temperature solid-state synthesis method 223–224
 - near-infrared optical perovskite materials 212–214
 - post-synthetic ion exchange method 220–221
 - red light perovskite materials 214–216
 - thermal injection method 223
- methylamine lead iodide (MAPbI₃) 86–88
- micro/mini-LEDs 255
- microwave method 49–50
- mixed-phase quasi-two-dimensional perovskites 12
- molecular passivation 88, 95–96
- multi-quantum wells (MQWs) structure 87, 94–95, 115, 116, 172, 173, 318, 322

n

nanocrystalline green perovskite light emitting diodes 142, 144, 146

nanocrystal pegging (NCP) 142, 144, 150

nanocrystals

- blue light perovskite 183
- CdSe 49
- colloidal undoped and double-doped $\text{Cs}_2\text{AgInCl}_6$ 263–264
- CsPbX_3 9, 10
- halide perovskite quantum dots 40, 42–44
- laser of perovskite 343–344
- Mn-doped CsPbCl_3 51
- monodisperse 53
- quantum dot materials 183
- semiconductor 5
- synthesis of 111–112

nano-microcrystalline precursors 191

nanostructured CsPbX_3 14

near infrared (NIR) 20, 83, 171, 199, 212, 213, 261, 340

near-infrared light-emitting diodes (NIR LEDs) 83, 99, 212, 213

near-infrared optical perovskite materials 212–214

near-infrared perovskite light-emitting devices 205

- device structure optimization 96–98
- methylamine lead iodide (MAPbI_3) 86–88
- molecular passivation 95–96
- multi-quantum well structure 94–95
- near-infrared wavelength adjustment 91–93
- NIR-emitting materials based on perovskite 88–90
- progress in 84–86

near-infrared wavelength adjustment 91, 93

NIR-emitting materials based on perovskite 88–90

$\text{N,N}'$ -bis(1-naphthyl)- $\text{N,N}'$ -bis(phenylbenzidine) (NPB) interlayers 98

non-lead metal halide perovskite materials

- antimony-based metal halide materials 241–242
- bimetallic cationic halide perovskites materials 243, 245–247
- bismuth-based metal halide materials 238–240
- copper-based metal halide materials 241–245
- development history of 231–234
- doping 248–249
- europium-based metal halide materials 243, 245
- preparation of 234–236
- selection of solvents and undesirable solvents 248
- surface passivation 247–248
- tin-based perovskites Materials 236–239

non-radiative Shockley Read-Hall composite 15

non-template method 75–76

N -(2-bromoethyl)-1,3-propanediamine dihydrobromide (NPA^{2+}) 181

o

octahedral factor 36, 107–110, 114, 210–212

octanoic acid (OTAc) 58, 60, 61, 142, 184

1D perovskite nanowires 335

one-photon absorption and emission 336

organic-inorganic hybrid electron transport materials 294

organic-inorganic hybrid perovskite materials 110, 134, 136–137

organic monolayer electron transport materials 292

organic multilayer electron transport materials 292–293

Osher-Stark effect 318

p

- passivation engineering 153–155
- passivation of film defects 191–192
- PEA₂Cs_{n-1}Pb_nBr_{3n+1} perovskite films 158
- PEDOT+PSS
 - after methanol treatment 297–298
 - TB(MA) instead of 299
- perovskite blue light emitting materials
 - nanocrystals/quantum dot materials 183
 - with a quasi-two-dimensional structure 175–182
- perovskite encapsulated quantum dot structures 89
- perovskite light-emitting diodes (PeLEDs) 6
 - device performance development of 20–23
 - device structure of 16–17
 - electron injection layer modulation 325–328
 - extrinsic instability of 315–317
 - factors affecting efficiency roll-off 318–322
 - hole injection layer modulation 323–325
 - intrinsic instability of 314–315
 - perovskite structure modulation 322–323
 - physical parameters of 18–19
 - stability analysis of 317–318
- perovskite materials
 - applications of 35
 - commercial prospects of 43–46
 - crystal structure of 1–2
 - exciton effects 2–4
 - factors influencing the efficiency of 16–23
 - halide perovskite quantum dots/nanocrystals 40, 42–44
 - layered halide 36–41
 - luminescence properties of 7–16
 - size effect of 5–7
 - 3D halide perovskite materials for light-emitting diodes 36–37
- perovskite nanomaterials
 - ion exchange method 67–68
 - laser etching method 68–69
 - ligand-assisted-precipitation (LARP) 60–67
 - mechanochemical method 46–47
 - microwave method 49–51
 - solvent heat method 50–52
 - thermal injection method 51–60
 - ultrasonic method 47–48
- perovskite nanowires (NWs) 335, 339–341
- perovskite-organic coupling white light-emitting diodes (POC-WLEDs) 278–280
- perovskite red light-emitting diodes
 - development history of 103–105
 - device structure and common materials 117–118
 - gas-solid interactions 119–120
 - interfacial passivation 120
 - light extraction technology 119
 - polymer-assisted films 120
 - thermal annealing 120
- (110) perovskite with corrugated inorganic layers 271–273
- (001) perovskite with flat inorganic layers 274
- phenylbutylamine cation (PBA⁺) 179
- phonons 6, 11, 15
- photoluminescence (PL) 13, 24, 35, 40, 43, 53, 69, 83, 96, 103, 134, 137, 157, 169, 176, 177, 210, 213–215, 217, 220, 223, 231, 245, 248, 257, 260, 261, 265, 267, 271–274, 276, 277, 291, 299, 303, 313, 322, 323, 336
- photoluminescence quantum efficiency (PLQE) 157, 261, 273, 274, 322, 323
- photoluminescence quantum yield (PLQY) 35, 38–40, 45, 55, 66, 74, 76, 83, 91–94, 103, 116, 137, 139, 140, 148, 150, 160, 169, 177, 186,

- 187, 215, 216, 219, 223, 231, 232, 235, 239, 245, 257, 259, 261, 263–266, 269, 272, 276, 280, 299, 319, 338, 343
- polaritons 3, 4, 281, 341
- poly[(9, 9-di-*n*-octylfluorenyl-2, 7-diyl)-alt-(4, 4'-(*N*-[4-*n*-butyl]phenyl)-diphenylamine)] (TFB) 16
- polyfluorenylbenzene anion-conjugated polyelectrolytes with counter ions 303–305
- polymer-assisted films 120
- poly(3,4-ethylenedioxythiophene): polystyrene sulfonate (PEDOT+PSS) 98
- poly(3,4-ethylenedioxythiophene): poly(styrenesulfonate) transport material 286
- post-synthetic ion exchange method 220–221
- printing method 71, 72
- PSS-doped Na 300
- pure inorganic perovskite materials 134–136
- PVK blended with PBD 301–302
- PVK-doped NiO_x 300
- PVK doped PTAA 300–301
- PVK-doped TPD, TCTA 296–297
- q**
- quantum dot green perovskite light emitting diodes 141–142
- quantum dot perovskite light emitting diodes 300–301
- quantum dots in perovskite (QDiP) 85, 90
- quasi-2D BA₂(CsPbBr)_{3*n*-1}PbBr₄ perovskite materials 146
- quasi-2D films 112
- quasi-two-dimensional perovskite crystals (2D/quasi-2D perovskites) 172, 304
- quasi-2D Ruddlesden-Popper green perovskite light emitting diodes 145–146
- quasi-2D structured PEA₂(MA)_{*n*-1}Pb_{*n*}Br_{3*n*+1} perovskite materials 146
- r**
- radiative emission quantum yield 334
- Rashba-type energy band splitting 9
- red emission perovskite materials ABX₃ and hybridized ABX₃ type materials 107–110
- additive engineering 117
- CsPbI₃ 105–107
- doping 113–114
- double perovskites 110–111
- energy level regulation 119
- ligand engineering 115–117
- multiple quantum-wells structure 115–116
- nanocrystals 111–112
- quasi-2D films 112–113
- surface passivation 114–115
- red light perovskite materials 103, 105, 107, 109, 113, 114, 120, 121, 214–216
- Rydberg constant 3
- s**
- Sb³⁺-doped Cs₂ZrCl₆ crystals 269
- self-assembly process 129, 172
- self-trapped excitons 3, 4, 237, 238, 245, 247, 257, 271–278
- self-trapping excitons 3–4
- Shockley-Read-Hall (SRH) complex constants 13
- single white light perovskite materials (110) perovskite with corrugated inorganic layers 271–273
- (001) perovskite with flat inorganic layers 274
- self-trapped excitons 274–278
- sky-blue perovskite light emitting diodes 266–270
- solvent atmosphere treatment 176, 190
- solvent heat method 50–51

- spin coating 46, 69–70, 76, 137–140, 150, 159, 171, 190, 236, 241, 291, 296, 297, 343
 - spraying method 74–75
 - surface engineering 151–153, 220
 - surface modification of nanostructures 184–186
 - surface passivation 12–14, 66, 113–115, 120, 121, 130, 150–153, 161, 205, 210, 225, 241, 247–248, 251, 304
- t**
- template method 75, 339
 - tetraoctylammonium bromide (TOAB) 55, 142, 143, 150
 - thermal annealing 120, 131, 153
 - thermal injection method 40, 42, 44, 51–60, 111, 112, 121, 134, 137–139, 141, 191, 223, 234, 235
 - thermally activated delayed fluorescence (TADF) 84
 - thiocyanate (SCN) 320, 323
 - three-body Auger recombination constant 334
 - 3D perovskite-based light-emitting diodes 103
 - 3D halide perovskite materials for light-emitting diodes 36
 - three-dimensional and quasi-two-dimensional perovskite films 190–191
 - three-dimensional perovskite material 129
- tin-based perovskites materials 236–238
 - tolerance factor 107, 109, 110, 133, 209–211
 - trioctylphosphine oxide (TOPO) 14, 15, 153, 154
 - 2,4,6-tris[3-(diphenylphosphinyl)phenyl]-1,3,5-triazine 285, 293
- u**
- ultrasonic method 45, 47–48
 - unbalanced charge injection 196, 319
 - Urbach energy 12
- v**
- vacuum thermal vapour deposition method 70–71
 - vapour phase deposition method 71–74
- w**
- Wannier excitons 2
 - white perovskite light-emitting diodes (WPeLEDs)
 - background of 255–257
 - down-conversion method 257–261
- y**
- yellow perovskite light emitting diodes 261–266
- z**
- 0D perovskite nanocrystals 335
 - zero-dimensional Sn-doped halide perovskites 261–263