

Index

a

- Adsorbed rigid water film in the water-filled pore region behind the meniscus 46
 - theoretical estimation method using a surface-energy approach 46
 - vapor pressure dependent adsorbed volume behind the meniscus 49
- Adsorbed rigid water films on the interface muscovite mica and calcite to water
 - influence of the solute concentration of electrolyte solutions 53
 - investigations using pure water and electrolyte solutions 53
 - investigations using various experimental techniques 50
 - results of international studies using AFM and MD simulations 50
- Adsorption and desorption isotherms 182
 - ads/des-isotherms of selected ceramic brick products 182
 - ads/des-isotherms of selected sand-lime bricks 182
- Adsorption and desorption isotherms of reference mortar REF 151
 - analytical regression function used for ads/desorption 152
- Adsorption/desorption and scanning isotherms 189
- Adsorption film thicknesses due to relative humidity of air: Theoretical estimation 38
 - comparison experiment and calculation result 39
 - influence of surface curvature and pore type 40
 - modeling for non-porous surfaces using disjoining pressure plus BET 39
 - on non-porous surfaces 38
- Adsorption isotherms of the material REF via φ and p_{cap} 25
- Air-pores in cement-bound materials 161
 - influence of specimen shape on water uptake into air voids 167
 - influence on sorption isotherms 175
 - smallest existence limit radius for manufacturing-related air voids 164
 - theoretical examination of behavior and durability 161
- Air-porosity-content of the materials used 142
- Air-voids content of concrete 141
 - content and pore diameter distribution in material REF 140
 - pore diameter distribution in a Michigan highway concrete 141
 - SEM images of inner surface of air voids of air entraining agent 141

- Applicability of theoretical modeling on cement-bound material possessing fiber structure 75
 - adsorbed films in the water-filled pore region on fibrous CSH 76
 - calculations of the radius dependent inner pore surface 76
 - liquid uptake and storage 76
 - the “menisci” span in the irregular pores between the particles 75
 - related properties determined from theoretical considerations 75
 - results of pore analyses of MIP 77
- Atomic Force Microscopy AFM and MD simulations on adsorbed rigid water films 52
- Attainable degree of hydration 92
 - modeling the dependence on water/cement ratio 92
 - sealed or water saturated storage 92
- b**
- Book content: short description xi
- c**
- Calculations to porosity, degree of hydration and the material densities 78
- Capillary condensation 13
 - derivation Kelvin equation 13
 - distribution depending on pore radii $r_R(\varphi)$ and r_R 36
 - equations considering the modified Kelvin-equation 36
 - modified Kelvin-equation $r_R(\varphi)$ for real pore radius r_R 37
 - relationship radius/relative humidity 15
- Capillary pressure 11, 12
 - cause of fluid transport and rise height 12
 - in cylindrical pores and in slit pores 11
- Capillary water absorption depending on initial water content and time 232
 - influence of initial saturation on the shape of imbibition curve 233, 234
 - influence of initial saturation on the slope of the imbibition curves 234
 - studies on the behavior of HCP and concrete 232
 - water imbibition curves of UHPC 235
- Capillary water uptake after drying from saturation state 169
 - limited rewetting water content 170
 - possible water content due to the material age and the drying procedure 173
- Carbonation behavior of the test specimens 137
 - phenolphthalein tests 137
- Carbonation: Influence on moisture storage and transport 212
 - experimental results on HPCI and HPCIII from Auroy et al. 213
- Cavitation in the pore system during drying 215
 - boiling point resp. vapour pressure curves below 100 °C 216
 - comparison of boiling point curves from Clausius–Clapeyron and from Magnus 216
 - effective water-pressure curve in the pores of HCP 217

- pore radii affected with cavitation onset at 80 °C and at 20 °C 217
 - practical influence of cavitation in concrete 219
- Cavitation in the system water/vapor 21
- Concrete data for the experimental investigations 134
- Course of scanning isotherms
 - calculated scannings to measured ads/des-isotherms of HCPIII 202

d

- Desorption isotherms: dependence on initial storage conditions 199
 - second desorption isotherm of HCPI 200
 - second desorption isotherm of material REF after sealed curing 201
 - second desorption isotherm of REF after sealed curing: measured and calculated 202
 - second desorption isotherm schematic for CEMIII related materials 201
- Drying methods and influence of drying 144
 - comparison of drying at 40 °C/1 mbar or 40 °C-silica-gel on the adsorption-isotherms 147
 - desiccator salt solutions 147
 - moisture equilibrium according to EN ISO 12571 146
 - possible influence on capillary water uptake 148
 - possible influence on MIP pore distribution 149
- Drying of ceramic bricks, calcium silicate products and porous concrete 297
 - applicability of concrete drying modeling 297
 - influence of boundary conditions 304
 - influence of wall thickness on drying 299
 - modeling one-side drying of wall panels of different thickness 302

f

- Floating water droplets 19
 - application of Kelvin equation 19
 - in vapor saturated air 19

h

- Hardening related material properties calculated with Powers/Hansen 82
 - calculation of densities ρ_{wet} , ρ_{humid} and ρ_{dry} 84
 - chemical shrinkage and autogenous shrinkage 84
 - pore fractions of gel pores and capillary pores 82
 - total porosity of the concrete after standard drying 81
- Hydration kinetics 93
 - calculation of regression curves 93
 - dependence of storage conditions 95
 - example of development of phase composition with degree of hydration 98
 - experimental results on HCP of CEMI and CEMIII/A 94

- Hydration-related system parameters required by the method of Powers/Hansen 81, 86
 - chemical shrinkage prediction and comparison with experiment 87
 - coefficient k_{phys} for estimating the physically bound water 90
 - determination of the characteristic value k_{gel} 89
 - experimental investigations on the maximum water binding W_{chem0} 86
 - parameters W_{chem0} , k_{chem} , k_{gel} , k_{phys} and m 81, 86
 - volume-reduction coefficient k_{chem} 87
 - water fraction W_{chem0} required for hydration 87
- Hysteresis influence on water content distributions 266
 - assessment of calculations with one sorption isotherm only 270
 - comparison when using the adsorption or the desorption isotherm 268, 269
 - nonuniform redistribution after one side water uptake 266
 - scanning behavior on distribution in a selected VE 266
- Hysteretic moisture storage behavior 150
 - adsorption and desorption isotherms of reference mortar ref 151
 - causes of differences between adsorption and desorption 153
 - questions with respect to modeling of storage and transport 155

i

- Initial composition parameters: Calculation considering air pore volume and additives 78
- Inner surface of porous material 30
- Inner surface of porous material determined using the sorption isotherm 24
 - total surface determined by BET method 26
 - total surface determined by the method of Adolphs and Setzer 29
- Ion concentrations in the pore solution of HCP 56

k

- Kelvin equation 16
 - extent of validity 16
 - modified Kelvin-equation $r_R(\varphi)$ for real pore radius r_R 37

l

- Liquid absorption in material pores 10
 - adhesion works and potential energy 10
 - basic equations 10
 - capillary rise via the adhesion works 10
- Long-term moisture storage tests on slice-shaped specimens 158
 - question of dissolution of portlandite during water storage 160
 - tendency to complete filling of air-pores 158

m

- Meniscus formation
 - contact angle as a function of liquid uptake or liquid release 59
 - influence of adsorption films 56

- influence of the pore radius on the meniscus shape 17
- partial wetting and total wetting 57
- shape as a function of the contact angle 17
- Meniscus in pores 17
 - Young–Laplace equation 17
- MIP curve as a storage function at elevated temperature 229
- MIP results on porosity of the considered materials 136
- Modeling of capillary transport 251
 - calculated distribution curves of absorbed water into prisms 262
 - dependence of the liquid water transport properties on water saturation degree 254
 - equivalent action time 262
 - impact of drying and wetting on the morphology 256
 - modeling time dependence of permeability on initial saturation 259
 - moisture content jumps 258
 - possible reduction of the permeability due to conversion 258
 - time functions 260
 - time influence on capillary transport 258
 - transport properties as a function of pore size distribution 253
 - water content-dependent time root independent slope 252
 - water content-dependent water transport coefficients 253
 - water content zones defined 253
 - water distribution curves from one side water imbibition 251
 - water uptake curves: experimental and calculated 262
- Modeling of drying by evaporation 282
 - influence of boundary conditions 287
 - influence of salt precipitation on the evaporation behavior 289
 - influence of surface treatment on drying behavior 293
 - modeling of dynamic deposition on drying behavior 293
 - modeling of steady-state deposit on evaporation 293
 - new formulation of evaporation at concrete surfaces 283
 - results of evaporation measurements and comparison with experiments 285
 - results of 1-side and 2-sides evaporation 287, 295
 - saturation parameters used in modeling 284
- Moisture storage function 30
 - the net moisture storage function 31
- Moisture transport
 - base modeling 122
 - structure of the simulation program 128

p

- Pore-micro-structure development of hydrating Portland cement grains 69
- Pore-micro-structure development of UHPC 73
 - high resolution images of the fiber-like CSH morphology of fibers a few nm thick 73
 - high resolution images of the morphology with pores from chemical shrinkage 73
 - SEM overview images of the UHPC structure 73

- Pore-micro-structure of Portland cement clinker before grinding 68
 - crystallized granular structure with main phases C_3S (Alite), C_2S (Belite), and C_3A 68
- Pore size dependent distribution of the inner surface 30
 - application of the method to the material REF 33
 - basic equations using the net moisture storage function 33
 - distribution within material REF via φ and r_R 34
 - pore shape parameter for the material REF 34
- Pore structure of selected materials 65
 - groups of MIP cumulative pore volume curves of ceramic bricks 66
 - structure of selected ceramic bricks 65
 - structure of the synthetic material MCM-41 65
- Primary and secondary desorption isotherms 190
 - reversibility of structural changes 190

r

- Remarks on morphology in cement-bound material
 - the fraction of closed pores in a pore system 76

s

- Salt contents in pore solution: Influence on moisture storage 230
- Salt precipitation on concrete surfaces 289
 - influence of storage conditions 291
 - IR spectroscopic analysis of the deposit 289
- Scanning isotherms 263
 - alternative experimental determination of the slope 209
 - comparison of adsorp-scannings starting from 1st and 2nd desorp isotherm 203
 - comparison of scannings from Saeidpour et al. with proposed modeling 204
 - comparison of scannings from Wu/Johannesson/Geiker with modeling proposed 205
 - comparison of scannings from Zh. Zhang et al. with modeling proposed 206
 - illustration of the possible scanning behavior depending on saturation level 264
 - master scanning isotherm 264
 - modeled as slope fan for mortar REF 264
 - modeling the course of scanning isotherms 192
 - parameters resp. dependencies used for modeling the course 192
 - results of modeling and experiments on material REF 194
 - results of modeling and experiments on sealed cured CEMI-concrete 195
 - set of measured ads/des-scannings of HCPI from de Burgh and Foster 198
 - special redistribution behavior of nonuniform initial distributions 265
- Sealed hardened test specimens 178
 - MIP results in comparison to water storage hydration 180
 - water storage and capillary imbibition curves 180
 - water uptake and storage behavior 178
- Self-Sealing 236

- base curve (echo train intensity decay) of an NMR measurement on HCP 237
- calculations from Franke on pores closed by molecule adsorption 241
- conclusions from NMR analysis and computational results 236
- description of cause by Rucker-Gramm 241
- evidence of change in water structure with decreasing pore sizes by NMR 241
- NMR results from Schulte-Holthausen/Raupach on time-dependent interlayer closure 243
- results of studies on the causes 239
- Solubility of gases in water 19
 - Henry's law 19
- Sorption isotherms 185
 - adsorption and desorption isotherms of HCP and concrete 185
 - adsorption and desorption isotherms of HCPII and HCPIII $W/C = 0.40/0.60$ 186
 - adsorption and desorption isotherms of mortar MIII $W/C = 0.40/0.60$ 185
 - adsorption/desorption and scanning isotherms from Baroghel-Bouny on HCP/concrete 189
 - adsorption/desorption and scanning isotherms of sealed hardened concrete CEMI 189
 - conversion of given isotherms: comparison of deduced isoth MIII to measured isoth MIII 207
 - conversion of given isotherms to other mixtures 207
 - conversion with consideration of various W/C -values and hydration degrees 207
 - regression curves using Franke equation 152
 - regression curves using Pickett equation 226
 - regression curves using VanGenuchten equation 223
- Sorption isotherms: Dependence on temperature 220
 - computational modeling 224
 - control tests at 40 and 60 °C of Franke on REF 221
 - desorption-enthalpy curves for different temperature ranges via RH 224, 226
 - investigations on HCP at 23°C to 80 °C of de Burgh et al. 223
 - prediction of the temperature dependent course of desorption 226
 - results at 30 and 80° C of Poyet et al. on concrete 220
 - results at 70 °C of Hundt/Kantelberg on water-stored HCP 220
- Sorptive vapour storage on material surfaces 22
 - on flat non-porous surfaces 23
- Spreading of liquids on solid surfaces 7
 - specific interfacial energy 7
- Storage behavior under changing boundary conditions with respect to air-pore content 155
 - results of long-term tests on slice-shaped specimens 156
 - the structure related pore volume fractions 156
- Surface energetic principles: Introduction 1
- Surface energies of solid surfaces 9
 - determination of the energy values 9
- Surface energy and surface tension 3

- Surface energy/tension of water 3
 - of aqueous salt solutions 6
 - dependence on temperature and relative humidity 6
 - measuring by a Wilhelmy-plate test 5
 - measuring by the bracket-method 5
 - water molecules orientation at the liquid surface 4

t

- Transport coefficients 103
 - comment on use of diffusivity or permeability 112
 - hydraulic external pressure 107
 - influence of salinity and temperature on fluid transport 108
 - temperature influence on capillary transport 105
- Transport coefficients, definitions 103
 - diffusivity d_{w0} [m^2/s] 103
 - hydraulic conductivity k_f [m/s] 103
 - intrinsic permeability [m^2] 103
 - permeability k_l [m^2] 103
 - transport coefficient d_k [s] 103
 - transport coefficient $ksat0$ [s] 103
- Transport coefficients, measurement methods and assessment 113
 - coefficients measured via electrical conductivity 114
 - determination of diffusivity [m^2/s] via NMR 118
 - diffusivity and permeability coefficients for concrete 112
 - diffusivity [m^2/s] and permeability [m^2] via capillary sorptivity 118
 - hydraulic conductivity [m/s] measured via hydraulic pressure 113
 - prediction of permeability [m^2] according to Katz-Thompson 115
 - relative diffusivity modeled from morphology resp. structure data 121
 - transport parameters from reverse calculations 121
- Transport potential capillary pressure 104
- Transport potential Diffusivity 110

v

- Validity of the Kelvin equation 16
- Vapor transfer: influence on realistic modeling of drying 279
 - calculated evaporation curves with conventional coefficients 281
 - comparison of experimental and conventionally calculated evaporation curves 281
 - experimental and calculated evaporation curves with various boundaries 279
 - modified vapor transfer coefficients 281
- Vapor transport 270
 - dependence of vapor transport coefficient from saturation 275
 - measurement error possible with wet-cup method 272
 - measurement of diffusion coefficients with dry-cup method 272
 - measurement of diffusion coefficients with wet-cup method 272
 - measurement of vapor diffusion coefficients 271

- modeling of vapor transport within the material 274, 279
- vapor diffusion coefficient 271
- vapor diffusion resistance number 271
- Vapor transport through wall elements 277
 - dependence from transfer coefficient 277
 - resulting moisture distribution inside of a concrete wall 277
 - vapor transfer coefficients 277
- Volume of adsorbed water in non-saturated material state 44
 - using net water storage function 45
 - within the not yet filled pore region 44
- Volume of the internal adsorbed water films
 - modeling of the distribution via r_R resp. φ 36
- W**
- Water content change in mortar REF slices via various storage conditions 137
- Water molecule adsorption on non-porous surfaces 23
 - experimental results on HCP and concrete 24
 - sorption isotherms from Badmann and from Franke 24
 - water-layer thickness via relative humidity 23
- Water rise in a capillary 12
 - influence of capillary condensation 13
- Water storage functions for different building materials: Overview 182

