Contents

Preface xi

1 Surface Energetic Principles for Moisture Storage in Porous Materials 1

- 1.1 Introduction 1
- 1.2 Surface Energy and Spreading of Liquids on Solid Surfaces 3
 - 1.2.1 Explanations on Surface Energy and Surface Tension 3
 - 1.2.2 Dependence of Surface Energy of Water on Temperature, on Relative Humidity of Air, and for Aqueous Salt Solutions 6
 - 1.2.3 Spreading of Liquids on a Solid Surface 7
 - 1.2.4 Determining the Surface Energies of Solid Surfaces 9
- 1.3 Basic Equations for Liquid Absorption in Material Pores 10
 - 1.3.1 Liquid Absorption in Pores by Effect of Surface Energies 10
 - 1.3.1.1 Derivation of the Capillary Rise via the Adhesion Works and the Potential Energy in Capillaries *10*

۱v

- 1.3.1.2 Capillary Pressure in Cylindrical Pores and in Slit Pores *11*
- 1.3.1.3 Capillary Pressure as a Cause of Fluid Transport and Rise Height in a Capillary Pore 12
- 1.3.2 Pore Filling by Capillary Condensation 13
 - 1.3.2.1 Extent of Validity of the Kelvin Equation 16
- 1.3.3 Saturation Vapor Pressure at the Surface of Convex Shapes 16
- 1.3.4 Explanations of the Young–Laplace Equation for Stress on Curved Fluid Surfaces *17*
- 1.3.5 Application of Kelvin Equation to Floating Droplets 19
- 1.3.6 Solubility of Gases in Water 19
- 1.3.7 Cavitation in the System Water/Vapor 21
- 1.4 Sorptive Storage on Material Surfaces and on the Inner Surface of Pore Systems *22*
 - 1.4.1 Preliminaries 22
 - 1.4.2 Measured Surface Sorption of Water Vapor on Flat Nonporous Surfaces 23

- 1.4.3 Use of Water Vapor Sorption Isotherms to Determine the Value of the Internal Surface Area 24
 - 1.4.3.1 Total Internal Surface Determined Using BET Method 25
 - 1.4.3.2 Total Internal Surface Determined by the Method of Adolphs and Setzer 29
- 1.4.4 Calculation of the Pore Size-Dependent Distribution of the Inner Surface Using the Moisture Storage Function 30
 - 1.4.4.1 Determination of the Net Sorptive Storage Function 31
 - 1.4.4.2 Basic Equation for the Pore Size-Dependent Distribution of the Inner Surface 33
 - 1.4.4.3 Application of the Basic Equations with Regard to the Material REF 33
 - 1.4.4.4 Calibration of the Pore Shape Parameter and Calculation of the Internal Surface Distribution of the Material REF 34
 - 1.4.4.5 Distribution of the Volume of the Internal Adsorbed Water Films *36*
- 1.4.5 Equations for Capillary Condensation Considering Adsorbed Liquid Films 37
- 1.4.6 Modeling of Adsorption Film Thicknesses 38
 - 1.4.6.1 Modeling of Vapor Adsorption on Flat Nonporous Surfaces 38
 - 1.4.6.2 Modeling of Sorption Film Thicknesses in Cylindrical Pores with Influence of Surface Curvature on the Thicknesses of Adsorbed Films 40
 - 1.4.6.3 Volume of Adsorbed Water in the Not-yet-water-filled Pore Area 44
 - 1.4.6.4 Film Thicknesses Due to Adsorption in the Water-filled Pore Region Behind the Meniscus, Estimation Using a Surface Energy Approach 45
 - 1.4.6.5 Volume of Aadsorbed Water Molecules on the Inner Surface in the Water-filled Pore Area 49
- 1.4.7 Molecular Simulations and Experimental Investigations on the Dimension of Adsorbed Film Thicknesses (International Research Results) 50
- 1.4.8 Influence of Adsorption Films on Meniscus Formation and on Capillary Pressure in Capillary Pores 56

References 59

2 Real Pore Structure and Calculation Methods for Composition Parameters 65

- 2.1 Illustration of the Pore Structure of Selected Materials 65
 - 2.1.1 Pore Structure of the Synthetic Material MCM-41 and Selected Ceramic Bricks 65
 - 2.1.2 Results on the Pore-microstructure of Cement-Bound Materials 68

- 2.1.3 Applicability of Theoretical Modeling to Cement-Bound Material Possessing the Morphology Shown 74
- 2.2 Calculations on Porosity, Degree of Hydration, and Material Densities 77
 - 2.2.1 Calculations of Initial Composition Parameters of Concretes 78
 - 2.2.2 Required Hydration-Related System Parameters for the Method of Powers/Hansen *81*
 - 2.2.3 Total Porosity of the Hardened Cement Paste or Concrete After Standard Drying *81*
 - 2.2.4 Pore Fractions of Gel and Capillary Pores in the Total Pore Volume V_{pores} 82
 - 2.2.5 Chemical Shrinkage of the Hydrating Cement Product 83
 - 2.2.6 Calculation of the Densities ρ_{wet} , ρ_{humid} , and ρ_{dry} 84
 - 2.2.7 Definition of the System Parameters for the Powers/Hansen Method 86
 - 2.2.7.1 Water Fraction *Wchem*⁰ Required for Hydration of Cement Clinker *86*
 - 2.2.7.2 Volume-Reduction Coefficient k_{chem} and Chemical Shrinkage of the Hydrating Cement Product 87
 - 2.2.7.3 Definition of the Characteristic Value k_{gel} to Calculate the Gel Pore Volume 88
 - 2.2.7.4 Coefficient k_{phys} for Estimating the Physically Bound Water and the Necessary Water–Cement Value 90
 - 2.2.8 Dependence of the Attainable Degree of Hydration on the Water/Cement Ratio *91*
 - 2.2.9 Equations to Describe Hydration Kinetics 93
 - 2.2.10 Comparison of a Predicted and Measured Composition of a Cement Paste as a Function of the Degree of Hydration 96

References 98

3 Basic Equations for the Description of Moisture Transport *103*

- 3.1 Moisture Flows at the Volume Element 103
 - 3.1.1 Capillary Pressure as Transport Potential 104
 - 3.1.2 Consideration of the Temperature Influence on the Capillary Transport Coefficients 105
 - 3.1.3 Note on the Difference Between Capillary Pressure and Hydraulic External Pressure *106*
 - 3.1.4 Influence of Salinity and Temperature on Fluid Transport Coefficients *108*
 - 3.1.5 Diffusivity as Transport Coefficient for Water Saturation as Driving Potential *110*
 - 3.1.6 Comments on the Issue of Moisture Transport Modeling Based on Diffusivity or Permeability *111*
 - 3.1.7 Diffusivity and Permeability Coefficients for Mortars and Concrete 112
 - 3.1.8 Methods for Determining the Transport Parameters 113

- viii Contents
- 3.1.8.1 Measurement of the Hydraulic Conductivity [m/s] via Hydraulic Pressure *113*
- 3.1.8.2 Transport Coefficients by Measurements of the Electrical Conductivity *114*
- 3.1.8.3 Prediction of Permeability [m²] According to Katz–Thompson 115
- 3.1.8.4 Determination of Diffusivity [m²/**s**] via NMR According to Krus and Rucker-Gramm 118
- 3.1.8.5 Diffusivity [m²/**s**] and Permeability [m²] via Capillary Sorptivity *118*
- 3.1.8.6 Transport Parameters from Reverse Calculations 120
- 3.1.8.7 Relative Diffusivity Modeled from Morphology resp. Structure Data 121
- 3.2 Base Modeling of Moisture Transport 122
- 3.3 Structure of the Simulation Program *128* References *129*

4 Experimental Investigations with Regard to the Modeling of Moisture Transport in Mortars and Concrete 133

- 4.1 Preliminary Remarks on Moisture Storage 133
- 4.2 Concrete Data for the Experimental Investigations 134
- 4.3 Data on Porosity of the Considered Materials and Influence of Treatments on Porosity 135
 - 4.3.1 MIP Results for Pore Size Distribution and Pore Volume 135
 - 4.3.2 Control of the Carbonation Behavior of the Test Specimens 137
 - 4.3.3 Air-Porosity Content of the Materials Used 140
 - 4.3.4 Drying Methods and Influence of Drying 143
 - 4.3.4.1 Drying Methods 143
 - 4.3.4.2 Possible Influence of Drying on Capillary Water Uptake 147
- 4.4 Hysteretic Moisture Storage Behavior as Important Issue with Respect to Modeling 150
 - 4.4.1 Adsorption and Desorption Isotherms of the CEMI Reference Material 150
 - 4.4.2 Causes of Differences Between Adsorption and Desorption Isotherms 152
 - 4.4.3 Questions with Respect to Modeling of Storage and Transport Processes 155
- 4.5 Water Storage Behavior Under Changing Moisture Boundary Conditions with Consideration of the Air-Pore Content 155
 - 4.5.1 Illustration of the Structure-Related Pore Volume Fractions in Relation to the Total Storage Capacity 155
 - 4.5.2 Long-Term Moisture Storage Behavior of Slice-Shaped Test Specimens 156

- 4.5.3 On the Question of Dissolution of Portlandite from Slice-Shaped Test Specimens During Water Storage 159
- 4.5.4 Behavior and Durability of Air-Pores in Cement-Bound Materials *161*
- 4.5.5 Influence of Test Specimen Shape on Water Uptake into Air Voids 167
- 4.5.6 Capillary Water Uptake After Drying 169
- 4.5.7 Over-hygroscopic Range in Cement Mortar and Concrete 171
- 4.5.8 Air-Pore Influence on Sorption Isotherms 175
- 4.5.9 Water Storage Behavior of Initially Sealed Hardened Test Specimens 178
- 4.6 Adsorption and Desorption Isotherms 182
 - 4.6.1 Overview of Storage Functions for Different Building Materials 182
 - 4.6.2 Sorption Isotherms and Scanning Isotherms of Hardened Cement Paste and Concrete 185
 - 4.6.3 Primary and Secondary Desorption Isotherms, Reversibility of Structural Changes 190
 - 4.6.4 Modeling the Course of Scanning Isotherms 192
 - 4.6.5 Dependence of Desorption Isotherms on Initial Storage Conditions 198
 - 4.6.6 Using Given Isotherms for Other Concrete Compositions 207
 - 4.6.7 Alternative Experimental Determination of the Slope of Scanning Isotherms 208
 - 4.6.8 Influence of Carbonation on Moisture Storage and Transport Behavior *212*
 - 4.6.9 Cavitation in the Pore System During Desorption or Drying 215
 - 4.6.10 Dependence of Sorption Isotherms on Temperature 220
 - 4.6.11 MIP Curve as a Boundary Storage Function at Elevated Temperature 228
 - 4.6.12 Influence of Salt Contents on Moisture Storage 230
- 4.7 Results on Capillary Water Absorption Depending on Initial Water Content and Time 231
 - 4.7.1 Experimental Studies on the Behavior of HCP and Concrete 231
 - 4.7.2 Self-Sealing: Conclusions from NMR Analysis and Computational Results 235

References 243

5 Modeling of Moisture Transport Taking into Account Sorption Hysteresis and Time-Dependent Material Changes 251

- 5.1 Preliminaries 251
- 5.2 Modeling of Capillary Transport 251
 - 5.2.1 Water Content Dependence of the Water Transport Coefficients 251

x Contents

- 5.2.2 Water Content- and Time-Dependence of the Transport Coefficients 256
- 5.2.3 Computational Modeling of Scanning Isotherms and Hysteretic Moisture Transport 262
- 5.2.4 Examples of the Hysteresis Influence on Water Content Distributions *266*
- 5.3 Modeling of Vapor Transport and Drying by Evaporation of Concrete 270
 - 5.3.1 Definition and Measurement of Vapor Diffusion Resistance, Influence of Experimental Boundary Conditions on Nominal Measurand 270
 - 5.3.2 Modeling of Vapor Transport Within the Material 274
 - 5.3.3 Importance of Vapor Transfer Coefficient for Vapor Transport Through Wall Elements 276
 - 5.3.4 Influence of Vapor Transfer on Realistic Modeling of Drying Based on Experimental Results 278
 - 5.3.5 Implementation of Modified Vapor Transfer Coefficients 281
 - 5.3.6 Realistic Modeling of Drying by Evaporation 282
 - 5.3.7 Modeling the Influence of Salt Precipitation on the Evaporation Behavior of Concrete Surfaces 288
 - 5.3.7.1 Measurement Results on the Sources and on the Effect of Salt Precipitation 288
 - 5.3.7.2 Consideration of Steady-State and Dynamic Salt Precipitation on Evaporation Rate 291
 - 5.3.7.3 Comparison of Results from One-Sided and Two-Sided Evaporation 295
- 5.4 Realistic Modeling of Drying by Evaporation for Ceramic Bricks, Calcium Silicate Products, and Porous Concrete 297 References 305

Bibliography 307

Index 331