

Index

a

- accelerated corrosion test 454
- adhesion recovery mechanisms 40–43
- adhesion strength 15, 18, 200, 230, 393
- aggregation-induced emission (AIE)-based self-reporting coatings 17
- antagonistic effects 154
- anticorrosion coating, 2 *see also* corrosion protection coatings
- atmospheric corrosion monitor (ACM) technique 446
 - accelerated corrosion test 454
 - alternating wet–dry environment 463–471
- atmospheric exposure test 447–448
- atomic force microscopy (AFM) 14, 15, 256, 449
- Auger electron spectroscopy (AES) 449

b

- biological bionics 17, 393
- bisphenol A diglycidyl ether (DGEBA) 78, 93, 112, 157, 309, 312, 453

c

- carbon dots (CDs)
 - corrosion inhibition 256
 - electrochemical analysis 258–261
- Ce(NO₃)₃-EVA microcapsules 31
- cetyltrimethylammonium bromide (CTAB) 92, 94–97, 156, 176, 178
- CNTs/epoxy resin superhydrophobic coating 402

- anti-icing properties 404, 405, 407, 408, 410
- electrochemical impedance spectroscopy (EIS) 405
- mechanical durability 409–411
- surface characterization 404–406
- surface hydrophobicity 406, 409, 410
- CNTs/LDH/VO₃⁻-epoxy coating
 - corrosion protection mechanism 434–435
 - electrochemical analysis 427
 - superhydrophobic property 431–432
 - water contact angle measurement 427
- coating adhesion 2, 8, 42, 43, 63, 487, 489
- confocal laser scanning microscopy (CLSM) 14, 15, 79, 113, 132, 167, 172, 185, 256, 310, 313, 314, 336, 337, 342, 351, 352, 354, 359, 367, 368, 406, 415, 420, 455, 463, 464, 475
- constant phase element (CPE) 37, 232, 267
- corrosion inhibitors 45
 - loading and releasing test 45
 - release process from coatings 49–50
 - synergistic effect 153–155
- corrosion protection coatings 1
 - atmospheric corrosion monitor technique 449–450
 - atmospheric exposure test 447–448
 - electrochemical methods 448

corrosion protection coatings (*contd.*)
 salt spray test 446–447
 smart self-healing coatings 5–16
 smart self-reporting coatings 16–17
 superhydrophobic coatings 17–19
 wet–dry alternating cycle test 447
 crystal violet lactone (CVL) 306

d

DCF@PU/UF-EP coatings
 dual self-reporting and self-healing
 mechanisms 318–320
 self-healing performance 310,
 316–319
 self-reporting performance 310,
 313–316
 DMA test 309, 312

e

EIS measurements, Ce(NO₃)₃-EVA
 microcapsule contained coatings
 34, 35
 electrochemical impedance spectroscopy
 (EIS) 15, 76, 158, 405, 445, 448
 electrochemical noise method 448
 energy dispersive spectrum (EDS)
 analysis 14
 environmentally friendly self-healing
 coatings 487–488
 extrinsic self-healing coatings
 based on corrosion inhibitors 11–14
 based on defect filling 10–11
 extrinsic self-reporting polymers 305

f

Fe₃O₄-2MBT photothermal composite
 fillers
 epoxy coatings
 corrosion protection and
 photothermal properties of
 126–127
 corrosion resistance 134–135
 Fe₃O₄ hollow nanoparticles, composition
 and structural characterization of
 127–128

Fourier transform infrared (FTIR) spectra
 252, 428–430
 of blank epoxy, PCL, PCL/8HQ coating
 61, 62
 of CDs and CDs–SSA 263, 264
 of DCF, EPA, and ruptured DCF@PU/
 UF microcapsules 310, 311
 EVA and Ce(NO₃)₃-EVA microspheres
 32, 33
 of Fe₃O₄/2-MBT nanoparticles 128,
 129
 of Fe₃O₄ nanoparticles 128, 129
 of GO-LDH samples 222
 of MBT-BTA@mSiO₂ and BTA@mSiO₂
 159, 161
 of 2-MBT molecules 128, 129
 of nSiO₂ before and after KH560
 modification 397
 of Phen and UF/Phen microcapsules
 283, 284
 of TA-MSNs 344, 345
 of TiN-BTA@MSN and TiN@MSN
 samples 95, 96
 of UF microcapsules 283, 284

g

galvanic corrosion sensors 450–452
 GO–CeO₂/epoxy coatings
 dispersion properties 84–85
 mechanical properties 85–86
 photothermal conversion properties of
 86–87
 self-healing properties 87–89
 graphene oxide-layered double hydroxide
 (GO-LDH) composites
 chemical structure characterization
 220–221
 coating preparation 219–220
 corrosion inhibition evaluation
 226–228
 corrosion inhibitor release analysis
 225–226
 electrochemical measurement 221
 morphology characterization 220
 neutral salt spray test 221

- structure and morphology analysis 221–225
 - waterborne epoxy coatings 227–242
- h**
- 1*H*-Benzotriazole (BTA) corrosion inhibitors 155
 - hydrolysis 4
- i**
- immersion test 447, 455, 462, 470, 475
 - intrinsic self-healing coatings 5
 - based on dynamic bonds 6
 - based on shape memory effect 6–9
 - ion exchange activated self-healing coating, using GO-LDH fillers *see* graphene oxide-layered double hydroxide (GO-LDH) composites
- l**
- linear scanning voltammetry 8
 - localized electrochemical impedance spectroscopy (LEIS) 15
 - low-temperature self-healing coatings 487
- m**
- macroscopic electrochemical tests 45, 53
 - of self-healing coatings 54–57
 - magnetic stirring 31, 92, 176, 282, 370, 426
 - marine corrosion 486–488
 - MBT-BTA@mSiO₂/epoxy coatings
 - long-term protective performance of 173–176
 - electrochemical performance 170, 171
 - surface morphology analysis 170, 172
 - MBT-BTA@mSiO₂ nanocapsules
 - corrosion inhibition performance 167–169
 - corrosion inhibitor release behavior 157
 - inhibitor loading capacity 162–163
 - morphology and structure
 - characterization 158–162
 - one-step synthesis method 155
 - mechanically responsive self-reporting coating 322
 - metal ion-responsive self-reporting coatings 251
 - based on carbon dots (*see* carbon dots (CDs))
 - based on UF/Phen microcapsules 279
 - corrosion sensing 291–292
 - electrochemical analysis of self-healing coating 288–291
 - self-reporting and self-healing mechanism 292–294
 - thermal performance and shape memory effect 287–288
 - microscopic electrochemical tests 46
 - of self-healing coatings 57–60
 - modified nano SiO₂/epoxy resin superhydrophobic coating
 - hydrophobic property 396
 - mechanical durability and stability analysis 396–397
 - nSiO₂ characterization 397–398
 - nSiO₂ modification 395–396
 - stability and anti-icing ability of 401–402
 - molecular dynamic simulations 30, 32, 63
 - multiple self-healing mechanisms 38–40
- n**
- natural polyphenols 331, 382
 - neutral salt spray test 221
 - nuclear corrosion 488–489
 - Nyquist diagrams 106, 119, 121, 130, 131, 134–136, 227, 228–230, 237, 259, 266, 318, 355, 362, 363, 376, 377, 380, 412, 455, 456, 460, 466
- o**
- oil gas corrosion 489–490
 - open circuit potential (OCP) 452
 - CNTs/epoxy composite coating 411

- open circuit potential (OCP) (*contd.*)
 of PANI/BTA nanocapsule coatings
 193, 194
 of Q235 steel 264, 265
- optical microscopy (OM) 14
- organic coatings 154, 445
- outdoor exposure conditions, ACM sensor
 471–475
- oxygen and water permeability tests
 15–16
- p**
- PANI/BTA nanocapsules
 epoxy coating
 contact angle analysis 193
 corrosion monitoring 198–199
 electrochemical analysis 193–196
 mechanical properties 200
 self-healing mechanism 200–201
 SMP performance 196
 preparation and characterization of
 189–190
 self-healing coating performance test
 190–192
 self-healing coatings preparation 190
- PCL/8HQ microcapsules 44
 corrosion inhibitor release process
 48–49
- PCL@TiN photothermal composites
 composite microspheres preparation
 110–112
 epoxy/PT coating
 corrosion resistance and self-healing
 property 113
 outdoor application performance
 121, 123
 photothermal conversion property
 113, 118–120
 photothermal-induced water
 evaporation 121, 122
 morphological and structural
 characterization 112–116
 PCL microspheres preparation 110
 photothermal conversion performance
 112, 115–117
- phase-locked amplifier 15, 46
- phenolphthalein (PhPh) 252
- pH-responsive self-reporting coatings
 252–253
- Phen–urea–formaldehyde resin
 (UF/Phen) microcapsule coatings
 corrosion sensing 291–292
 electrochemical analysis of self-healing
 coating 288–291
 self-reporting and self-healing
 mechanism 292–294
 thermal performance and shape
 memory effect 287–288
- photo-oxygen degradation 4
- photoradical polymerization 17
- photothermal effect
 of epoxy/PT coating 113
 rGO@MS-P-BTA containing coatings
 183–185
 of TiN-BTA@MSN 101–103
- photothermally activated self-healing
 coating
 based on Fe₃O₄-MBT photothermal
 filler (*see* Fe₃O₄-2MBT
 photothermal composite fillers)
 based on GO-CeO₂ fillers (*see*
 GO-CeO₂ composites)
 based on PCL@TiN photothermal filler
 (*see* PCL@TiN photothermal
 composites)
 based on TiN-BTA@MSN
 photothermal filler (*see*
 TiN-BTA@MSN photothermal
 composite fillers)
- pH responsive self-healing coatings
 based on rGO@MS-P-BTA,
 microcapsules preparation,
 177–178 (*see also* rGO@MS-P-BTA
 microcapsules)
 electrochemical measurements 158
- MBT-BTA@mSiO₂ nanocapsules
 corrosion inhibition performance
 167–169
 corrosion inhibitor release behavior
 157

- inhibitor loading capacity 162–163
 - morphology and structure
 - characterization 158–162
 - release behavior 163, 164, 166
 - pH-responsive material 202
 - pH-sensitive type self-reporting
 - coatings 16
 - polyaniline with sulfosalicylic acid
 - (PANI-SSA) 253–254
 - polypyrrole (PPy) 202
 - potentiodynamic polarization test 15
- r**
- redox-responsive self-healing coatings
 - 202
 - based on PANI/BTA nanocapsules
 - (see PANI/BTA nanocapsules)
 - rGO@MS-P-BTA microcapsules
 - corrosion protection mechanism
 - 187–188
 - electrochemical performance
 - 184–186
 - morphology and structure of 178–182
 - pH-controlled corrosion inhibitor
 - release 181–182
 - photothermal effect 183–185
- s**
- salt spray test 88, 191, 217, 221, 227, 242, 252, 283, 337, 446–447
 - scanning electrochemical microscopy
 - (SECM) 15, 32, 120, 122
 - EVA microcapsules coatings 38, 39
 - results for healed coating
 - with 10 wt% PCL/8HQ microspheres
 - 59–60
 - with 10 wt% pure PCL microspheres
 - 59
 - results for scratched coating
 - with 10 wt% PCL/8HQ microspheres
 - 57–59
 - with 10 wt% pure PCL microspheres
 - 57, 58
 - scanning electron microscopy (SEM) 14, 31, 449
 - GO, LDH, and GO-LDH microstructure
 - 223, 224
 - nSiO₂/epoxy resin composite coating
 - morphology 398
 - UF/Phen microcapsules morphology
 - and particle size 282
 - scanning Kelvin probe (SKP) 15, 448
 - scanning tunneling microscope (STM)
 - 449
 - scanning vibrating electrode technique
 - (SVET) 15
 - self-healing coatings 251
 - extrinsic (see extrinsic self-healing coatings)
 - intrinsic (see intrinsic self-healing coatings)
 - in marine corrosion 486–488
 - in nuclear corrosion 488–489
 - in oil gas corrosion 489–490
 - shape memory effect 6–9, 30, 33, 38, 44, 50, 51, 53, 54, 57, 60, 63, 89, 103, 110, 117, 133, 134, 137, 138, 183–185, 187, 188, 196–198, 201–202, 291, 295, 307, 310, 317, 319, 320, 394, 413–415, 418, 421, 432, 434–436
 - shape memory epoxy polymer (SMEP)
 - coatings 306
 - shape memory polymers (SMPs) 6, 109, 183
 - shielding effect 2
 - SiO₂-CNT hybrid/epoxy shape memory
 - coating
 - electrochemical analysis 415
 - electrothermal performance test
 - 415
 - glass transition temperature (T_g) test
 - 415
 - mechanical durability 421–422
 - surface characterization 415
 - surface hydrophobicity 416–418
 - surface mechanical durability 415
 - smart self-reporting coatings 490–491
 - spiropyran 305
 - Stober method 155, 156, 201, 395

- sulfosalicylic acid–modified carbon dots (CDs–SSA)
 CDs–SSA based epoxy coatings
 fluorescence quenching effect 278
 self-healing effect 278
 self-reporting and self-healing properties 276–279
 corrosion inhibition and corrosion sensitivity 256–257
 corrosion sensitivity 274–276
 self-reporting performance of coatings 257
 surface corrosion morphology characterization 269–274
 superhydrophobic coatings 17–19, 491–493
- t**
- tannic acid (TA)
 chemical structure 332, 333
 chromogenic properties 338, 339
 coloration test 333–334
 corrosion inhibition performance 334, 339–343
 tannic acid (TA)-mesoporous silica nanocontainers (TA-MSNs)
 coatings
 aging-resistant property 337
 coloration properties 337
 self-healing property 337
 coloration properties 349–350
 corrosion inhibition performance of 350–352
 radical scavenging activity of 352–353
 release behavior 347–349
 tannic acid (TA)-MSNs/epoxy coating
 aging resistance 368–369
 corrosion resistance 354–362
 self-reporting property 353–354
 tea polyphenol (TP) 369, 370
 templating agents 154
 1,1,2,2-tetraphenylethylene (TPE)
 microcapsules 305–306
 thermal failure 4
 thermally activated self-healing coatings
 adhesion recovery mechanisms 40–43
 Ce(NO₃)₃-EVA microcapsules
 preparation 31
 cerium oleate dispersant preparation 30–31
 corrosion inhibitor loading and releasing test 45
 corrosion resistance and adhesion strength restoration 29, 30
 electrochemical analysis 34–38
 focused ion beam microscopy 45
 healing mechanisms 34, 35
 macroscopic electrochemical tests 54–57
 microscopic electrochemical tests 57–60
 molecular dynamics simulations 32
 multiple self-healing mechanisms 38–40
 PCL/8HQ microcapsules
 characterization 46–50
 self-healing tests 31–32
 single emulsification–solvent volatilization method 43
 thermal properties 33, 34
 TiN–BTA@MSN photothermal composite fillers
 coating preparation 93
 corrosion inhibition properties 93, 101–102
 epoxy/TBS coating
 corrosion protection 94, 105–106
 photothermal conversion property 93–94, 103–105
 inhibitor release behavior 92–93, 98–101
 morphology and structure
 characterization 92, 94–98
 photothermal conversion performance 92, 98
 TP-MSNs based anti-aging coating,
 oxidation resistance of 371–376
 TP-MSNs-loaded coatings
 aging resistance 378–381
 corrosion resistance 376–378

- transmission electron microscope (TEM)
220, 449
- u**
- UV-Vis absorption spectra 373
of BTA@mSiO₂ and MBT-BTA@mSiO₂
163, 165
of CDs and CDs-SSA 263, 264
complexation of Fe²⁺ and Phen 291
of MBT 164, 165
of rGO@MS-P-BTA solution 178
- w**
- waterborne epoxy coatings with
GO-LDH-V
barrier and self-healing performance
227–238
EDS spectrum analysis 238–239
electron probe microanalysis 238
SERS analysis 239, 240
water contact angle (WCA) 18, 269, 337,
369, 371, 378, 379, 395, 396, 406,
409, 411, 415–421, 431–432
of nSiO₂/epoxy resin composite coating
399, 400
of PANI/BTA coatings 190, 193
of Q235 carbon steel surface 256, 269,
271
water–oil–water solvent evaporation
method 30, 31
Wenzel's theory 193
wet–dry alternating cycle test 447
ACM measurement 467–471
corrosion morphology 463–465
electrochemical analysis 465–467
- x**
- X-ray diffraction (XRD) 449
X-ray photoelectron spectroscopy (XPS)
220, 256, 427, 449
- y**
- Young's modulus 15, 411
- z**
- zeta potential analyzer 178, 427

