

Index

a

absorber layer 94–95, 99–101, 229
 active-matrix liquid crystal displays (AMLCDs) 147
 active-MMI SLED
 field patterns and fiber coupling efficiency 208–213
 high power and low wall-plug consumption 205–207
 merit and results of 202–205
 self-imaging consideration 200–201
 spectrum and ripple analysis 207–208
 wide spectrum consideration 201–202
 active multimode interference (active-MMI) 203
 aerospace 242
 amplified spontaneous emission (ASE) 195, 201, 205, 210
 anti-reflection (AR) coatings 195, 196, 198, 203
 antisite defect 23
 asymmetric double split rings (aDSRs) 312
 atmospheric-pressure CVD (APCVD) 51
 atomic force microscopy (AFM) 236, 291, 294, 304, 322
 atomic layer deposition (ALD) 52, 53, 150, 285
 Auger coefficient 22
 Auger recombination 21, 22, 157–158, 224, 226, 233
 Auger recombination rate 21
 avalanche photodiode (APD) 262–263

b

band-to-band recombination 19–21, 152, 158
 band-to-local-energy-level recombination 153–154
 base-collector (BC) junctions 109, 113, 118
 base-emitter (BE) junctions 118
 benzocyclobutene (BCB) polymer 203
 biasing modes 111
 bipolar junction transistors (BJTs) 5, 37, 38, 107, 119
 bipolar transistors 107
 biasing modes 111
 circuit configurations 111–112
 device structures and working principles 108–111
 field-effect transistor 119
 junction FETs 126–131
 metal-oxide-semiconductor 120–126
 metal-semiconductor FETs 131–137
 modulation-doped FETs 137–141
 heterojunction bipolar transistors 117–118
 NPN and PNP BJTs 113–117
 thin-film transistors 142
 device structures and characterizations 142–147
 emerging applications 148–150
 representative materials and devices 147–148

- bismuth based halide perovskite X-ray detector 277–278
- Bloch function 34
- blue GaN LED 181–183
- Bohr radius 25
- Boltzmann distribution 17, 18
- Boltzmann's constant 146, 154
- Born–Oppenheimer approximation 32
- boron-doped silicon (B_{Si}) 25
- brain-inspired computing 149
- Bravais lattice vector 7–9, 11, 12, 14, 33, 34
- bright-state prehistory effect 260
- Brillouin zone (BZ) 34, 35, 288, 289
- building-integrated photovoltaics (BIPV) 243
- bulk-heterojunction (BHJ) 284, 320
- C**
- cadmium chalcogenide nanocrystals 161
- cadmium telluride (CdTe) solar cells 228
- cadmium zinc telluride (CZT) 280
- carrier transport
 - band-to-band transitions 19–21
 - drift current and diffusion current 14–17
 - Einstein relation 16, 17
 - electrons and holes 14
 - lifetime and mean-free-path 15
 - multiple scattering mechanisms 16
 - Shockley-Read-Hall statistics 20–21
 - thermal-equilibrium condition 19
 - trap-assisted recombination 21
- cathode-ray tube (CRT) 142
- charge-coupled device (CCD) sensors 265
- chemical beam epitaxy (CBE) 58
- chemically amplified resists (CARs) 88–89
- chemically assisted ion-beam etching (CAIBE) 198
- chemical vapor deposition (CVD) 51, 148, 205, 228, 287, 298, 302
- chip fabrication 175
- classic semiconductors 164
- coefficient of thermal expansion (CTE) 97
- color rendering index (CRI) 190
- common base configuration (CBC) 111, 112
- common collector configuration (CCC) 112, 113
- common emitter configuration (CEC) 112, 113
- communications sector, solar cells 243
- complementary
 - metal-oxide-semiconductor (CMOS) 282
- conduction band minimum (CBM) 152, 153, 164, 187
- contact angle measurement 235
- conventional sputtering 56
- copper-based halide perovskite X-ray detector 278
- copper-based halide perovskites 279
- copper gallium selenide (CGS) 227
- copper indium gallium selenide (CIGS) solar cells 227
- correlated color temperature (CCT) 190, 191
- Coulomb attraction 24
- crystalline silicon (c-Si)
 - atomic and band structures 236–237
 - properties of 238
 - synthesis method 239
- cubic close-packed (CCP) atoms 13
- CuInGaSe solar cell 227–228
- current on/off ratio (I_{ON}/I_{OFF}) 145
- cutoff mode 111
- Czochralski (CZ) growth 54, 239
- d**
- dark current 259, 262, 265
- dark-state prehistory effect 260
- depletion mode operation 123
- detectivity (D) 266
- diketopyrrolopyrrole (DPP)-based polymers 284
- N,N*-dimethylformamide 239
- Dirac equation 289
- Dirac fermions 301
- direct sonication synthesis 296–297
- direct-type X-ray detectors 274–278
- donor–acceptor pair recombination 154

- dopant atoms 25–27
- doping process
 - bipolar junction transistor 22
 - boron-doped silicon (B_{Si}) 25
 - Brillouin zone 34, 35
 - diffusion 25–27
 - diode 22
 - dopant atoms 27
 - electrically active defects 23
 - electrostatic modulation 36
 - ion implantation 29–31
 - mechanism 24, 26
 - phosphorus-doped silicon (P_{Si}) 25
 - point defects 22–25
 - surface dopants 28–29
- double-heterojunction LEDs 165–167
- double-heterostructure (DH) design 202
- Drude model 15
- dry etching 95, 177, 196
- dye-sensitized solar cells (DSSCs) 320–321
- dynamic random-access memory (DRAM) nodes 85
- e**
 - E-beam evaporation 56–57
 - Einstein relation 16–18
 - electrically active defects 23
 - electric vehicles (EVs) 242
 - electrochemical exfoliation 296
 - electron beam deposition (EBD) 228
 - electron-beam physical vapor deposition (EBPVD) 56–57
 - electron-hole pairs (EHPs) 220, 226, 273
 - electronic transport mechanism 301–302
 - electron transport layers (ETLs) 284, 321
 - electron volt (eV) 152, 249
 - emitter-base junction 111
 - energy band theory
 - atomic ions 31–32
 - Born–Oppenheimer or adiabatic approximation 32
 - ion–ion interactions 32
 - one-electron potential $V(r)$ 33
 - reciprocal lattice vector 34–35
 - Schrödinger equation 33
 - energy resolution (ER) 280
 - enhancement mode operation 123
 - epitaxial growth 57–60, 164, 173, 174, 185, 271, 287, 294, 297–298
 - epitaxial thin films 51, 59
 - etching 66, 84, 88, 179
 - excimer laser annealing (ELA) 147
 - exciton recombination 71, 155
 - excitons 71
 - external quantum efficiency (EQE) 167, 184, 187, 188, 192, 223, 267, 316
 - extreme ultraviolet (EUV) lithography
 - equipment 83, 86–88
 - light source and exposure system 85–86
 - mask materials and designs for
 - absorber layer 99–101
 - mask fabrication process 95–96
 - mask substrate 96–98
 - ML mirror layer 98–99
 - Moore’s law 83
 - research 85
 - resist development
 - metal-based nanoparticles resist 91–94
 - molecular glass resist 89–91
 - polymer-based chemically amplified resists 88–89
 - extrinsic photoconduction 251–252
- f**
 - face-centered cubic (FCC) 237
 - far-field patterns (FFP) 209
 - Fermi–Dirac statistics 39
 - fiber optic gyroscopes (FOGs) 199
 - Fick’s laws of diffusion 27
 - field-effect transistor (FET) 119, 287, 300, 306
 - antennas 308–311
 - application of 304–314
 - electronic transport mechanism 301–302
 - graphene nanoribbon 304
 - junction FETs 126–131
 - memory 307–308
 - metal-oxide-semiconductor 120–126
 - metal-semiconductor FETs 131–137

- field-effect transistor (FET) (*contd.*)
 - modulation-doped FETs 137–141
 - sensors 306–307
 - terahertz modulators 311–314
 - fill factor (FF) 223, 224
 - flexible and wearable electronics 148–149
 - floating-zone (FZ) growth 54
 - fluorescence spectroscopy 235
 - Förster resonance energy transfer (FRET) 187
 - forward active mode 111
 - Fourier transform infrared (FTIR) spectroscopy 76, 235
 - four probe measurement 60–64
 - Frank–Van der Merwe (FVM) growth mode 171
 - free excitons 155, 160
 - Frenkel pair 23
 - full width at half maximum (FWHM) 161, 164, 168, 192, 208, 280
 - functionalized multi-walled carbon nanotubes (f-MWNTs) 320
- g**
- GaAs_{1-x}P_x 160
 - gallium arsenide (GaAs) 159
 - gallium nitride (GaN) 160, 180
 - gallium phosphide (GaP) 159
 - gamma-ray detectors 279–280
 - GaN-based white LEDs 190–191
 - GaN LEDs
 - blue GaN LED 181–183
 - green and UV 183–186
 - nitrides structure and basic properties 180–181
 - Gaussian distribution function 29
 - graphene
 - antenna modulation 310
 - chemical and biological properties 293–294
 - crystal structure 287
 - electronic properties 289–291
 - mechanical properties 291–292
 - optical properties 291
 - preparation methods 294
 - CVD growth 298–299
 - direct sonication synthesis 296–297
 - electrochemical exfoliation 296
 - epitaxial growth 297–298
 - mechanical exfoliation 294, 296
 - thermal properties 292–293
 - graphene-based devices 300–301
 - FET
 - application of 304–314
 - device structure of 302–304
 - electronic transport mechanism 301–302
 - graphene nanoribbon 304
 - future of 324–325
 - graphene nanoelectromechanical systems 321–324
 - type-I two-terminal devices 314–315
 - type-II two-terminal devices 316–321
 - graphene-based field-effect transistors 302–304
 - graphene nanoribbon FETs 304
 - graphene nanoribbons (GNRs) 304
 - green light-emitting diodes (LEDs) 184
 - II–VI Group semiconductors 160–161
 - III–V Group semiconductors 158–160
 - Group V atoms 23
- h**
- Hall coefficient 65, 66
 - Hall effect measurement 64–67
 - Hermann–Mauguin notation 9
 - heterojunction back-contact solar cells (HBC) 227
 - heterojunction bipolar transistors (HBTs) 117–118
 - heterojunction solar cells 222, 241
 - heterojunction with intrinsic thin-layer cell (HIT) 227
 - hexamethyldisilazane (HMDS) 178
 - high-energy pulsed laser beam 57
 - highest occupied molecular orbital (HOMO) 187
 - high-spatial-frequency roughness (HSFR) 97
 - hole transport layers (HTLs) 187, 321
 - homojunction LEDs 164
 - homojunction solar cell 221
 - hysteresis factor 223, 225

i

illuminance (E) 170
 implantable electronics 150
 incident-photon-to-current conversion
 efficiency (IPCE) 223
 indirect-type X-ray detectors 278
 indium gallium arsenide (InGaAs) 282
 indium tin oxide (ITO) 284
 inductively coupled plasma (ICP) 177
 infrared (IR) photodetectors 271
 inorganic halide perovskites (IHPs) 192
 inorganic metal halide perovskite (IMHP)
 162
 insulated-gate FETs (IGFETs) 120
 integrated circuits (ICs) 1, 5, 56, 85, 108,
 119, 126, 130, 137
 interdigital electrodes 164
 interdigitated back-contact cell (IBC)
 227
 interface-charge-separation solar cells
 216
 interfacial engineering 188, 222, 230
 internal quantum efficiency (IQE) 167,
 188, 267
 Internet of Things (IoT) 149
 interstitial defect 23
 intrinsic graphene 301, 304, 318
 intrinsic photoconduction 251
 isoelectronic center recombination 156

j

Jahn-Teller distortion 164
 junction-charge-separating solar cells
 216
 junction field-effect transistors (JFETs)
 120, 126
 junction gate field-effect transistors
 (JUGFETs) 126

k

Kerr effects 324
 Kirchhoff's current law 110
 Kronecker delta 10

l

Lambertian distribution 168
 laser diodes (LDs) 52, 57, 195

layer-by-layer deposition 59
 lead-based halide perovskites 279
 lead-based perovskites 276
 light emitting diodes (LEDs) 167, 195,
 287
 chips manufacture 175
 evaporation 175
 packaging 179–180
 photolithography and etching
 177–179
 sputtering 176–177
 efficiency of 167
 emitting materials growth 171–174
 optical properties of 167–170
 principle and structure of 164–167
 light extraction efficiency 168
 lighting tools, historical development of
 152
 line width roughness and line edge
 roughness (LWR/LER) 90
 liquid crystal displays (LCDs) 142, 147
 liquid-phase epitaxy (LPE) 57, 171, 174
 lowest unoccupied molecular orbital
 (LUMO) 187
 low-pressure CVD (LPCVD) 51
 low-temperature poly-Si (LTPS) 147
 luminance (L) 170
 luminescent semiconductors 158–164
 luminescent spectra 167–168
 luminous flux 170, 258
 luminous intensity 170

m

magnetron sputtering 56, 176, 177, 228,
 229
 mask defects 101, 102
 mask fabrication process 95–96
 mask shadowing effect 102–103
 mask substrate 96–98
 maximum power point (MPPT) 224
 mechanical exfoliation 294
 MESFETs vs. MOSFETs 136
 mesoporous perovskite cells 232
 metal-based nanoparticles 91–94
 metal halide perovskites (MHPs) 187
 metal halides 162

- metal–insulator–semiconductor
 - photodiode 262
 - metal–organic chemical vapor deposition (MOCVD) 51, 58, 171, 172, 228
 - metal–organic molecular beam epitaxy (MOMBE) 58
 - metal–organic VPE (MOVPE) 58
 - metal–oxide–semiconductor FET (MOSFET) 69, 119, 120, 122, 126
 - metal–semiconductor FETs (MESFETs) 120, 131
 - metal–semiconductor–metal
 - photodetectors (MSM-PDs) 280–281
 - advancements and applications 282
 - design consideration 282
 - microelectromechanical systems (MEMS) 321–322
 - middle-spatial-frequency roughness (MSFR) 97
 - ML mirror layer 98–99
 - mobility (μ) 146
 - modulation-doped field-effect transistors (MODFETs) 137
 - modulation transfer function (MTF) 275
 - molecular beam epitaxy (MBE) 58, 171, 173, 228
 - molecular glass resist 89–91
 - Moore’s law 83
 - Mueller matrix ellipsometry 235
 - multi-mode interference effect 202
 - multi-mode interferometer (MMI) 199, 202, 211
 - multi-phonon process 157
 - multiple quantum wells (MQWs) 183, 185, 201, 203, 208
- n**
- nanoelectromechanical systems (NEMS) 301, 321–322
 - near-field patterns (NFP) 209
 - neuromorphic computing 149
 - noise in photodetectors 268
 - nonradiative recombination process
 - Auger recombination 157–158
 - multi-phonon process 157
 - non-telecentric nature of EUV lithography 98
 - NPN bipolar junction transistor 37, 113, 114
 - n*-type silicon-based solar cells 226
 - nucleation-growth model 171
- o**
- Ohmic contacts 117, 132, 138, 141, 176, 224
 - Ohm’s Law 116
 - one-dimensional band dispersion 37
 - one-electron potential $V(r)$ 33
 - one-step method, perovskite solar cells 239–240
 - open-circuit voltage (V_{oc}) 224
 - operating point 115
 - optical coherence tomography (OCT) systems 201
 - optoelectronic materials
 - chemical method
 - anti-solvent method 50
 - atomic layer deposition (ALD) 52, 53
 - ball-milling process yields MAPbI_3 48
 - CVD reactors 51
 - hot-injection method 49
 - solid/liquid phase chemical synthesis 48–51
 - solution-based methods 51
 - solvent evaporation method 50
 - temperature-decreasing method 49
 - temperature gradient technique 50
 - vapor phase chemical synthesis 51–53
 - electrical properties characterization
 - C–V and I–V measurements 67–70
 - four probe measurement 60–64
 - Hall effect measurement 64–67
 - epitaxy growth 57–60
 - optical properties characterization
 - Fourier transform infrared spectrum (FTIR) spectroscopy 76–78
 - photoluminescence spectrum 70–73

- ultraviolet-visible absorption
 - spectrum 74–76
 - X-ray photoelectron energy spectrum
 - 78, 80–81
 - physical method
 - Czochralski (CZ) growth 54
 - EBPVD systems 57
 - floating-zone (FZ) growth 54
 - high-energy pulsed laser beam 57
 - melt growth techniques 54–55
 - physical vapor transport (PVT) 55
 - sputtering 55
 - vapor phase physical deposition
 - 55–57
 - organic light-emitting diodes (OLEDs)
 - 142, 147, 162, 186
 - organic materials 162
 - organic photomultiplication detectors
 - (OPMDs) 283
 - advancements and applications
 - 284–285
 - design consideration 283–284
 - organic solar cells (OSCs) 230, 320
 - oxide semiconductors 1, 147
- p**
- passivated emitter rear cell (PERC) 226
 - pattern collapse 88, 102
 - perovskite-based white LEDs 191–192
 - perovskite gamma-ray detectors 279
 - perovskite LEDs
 - efficiency enhancement
 - carrier dynamics modulation
 - 187–188
 - interfacial engineering 188
 - structure and progress 186–187
 - perovskite photodetectors 269–271
 - gamma-ray detectors 279–280
 - infrared detectors 271–272
 - ultraviolet light detectors 272–273
 - visible light detectors 272
 - X-ray detectors 273–279
 - perovskite solar cells 321
 - carrier transport 233–234
 - crystal structure of perovskite materials
 - 231–232
 - device structure 232–233
 - one-step method 239–240
 - primary characterization instrument
 - 234–236
 - two-step method 240–241
 - vapor-deposition method 241
 - phenylethylammonium iodide (PEAI)
 - 278
 - phosphors 162
 - phosphorus-doped silicon (P_{Si}) 25
 - photoconduction effect 251–252
 - photoconductive type
 - current–voltage characteristics 257
 - photoconduction effect 251–252
 - photoelectric characteristics 257–258
 - photoresistor theory 252–257
 - prehistory effect 260
 - sensitivity and gain 258–259
 - photoconductors 251
 - photodetectors 249, 316
 - detection mechanism 250
 - general metrics 265–269
 - perovskite 269–280
 - photoconductive type 251
 - photodiode type 261–263
 - photomultiplier tube 264–265
 - photovoltaic type 263–264
 - principle of 249
 - wavelength sensitivity 250
 - photodiode type
 - avalanche photodiode 262–263
 - metal–insulator–semiconductor 262
 - PIN photodiode 263
 - PN junction photodiode 261
 - Schottky barrier photodiode 261–262
 - photolithography process 178
 - photoluminescence quantum yields
 - (PLQYs) 161, 191
 - photoluminescence spectrum 70
 - photomultiplier tubes (PMTs) 264, 283, 284
 - photoresist coating 178
 - photoresistor 251
 - band structure 253
 - geometric parameters 254
 - structure 253, 254
 - photoresistor theory 252–257
 - photoresist stripping 179

- photovoltaic cells, types of 245
- photovoltaic effect 220
- photovoltaic photodetector 263
- photovoltaic power generation 215, 220
- photovoltaic power station 243–244
- physical vapor deposition (PVD) 175, 176, 228
- physical vapor transport (PVT) 55
- PIN photodiode 263
- Planck's constant 154, 291, 316
- plasma-enhanced ALD (PEALD) 53
- plasma-enhanced CVD (PECVD) 51
- plastic solar cells 230
- PN junction 108
 - avalanche breakdown mechanisms 45
 - emission 165
 - n*-type and *p*-type 39
 - photodiode 261
 - properties of 38
 - p*-type and *n*-type 37, 38
 - quasi-Fermi levels 41
 - reverse bias 44
 - Shockley equation 40, 43
 - temperature influences 42
 - thermal excitation 45
 - tunneling breakdown 45
- PNP BJTs 113
- PNP transistor 116
- point defects 22–25
- Poisson equations 39
- polydimethylsiloxane (PDMS) 284
- polyethylene terephthalate (PET) 284
- polymer-based chemically amplified resists 88–89
- polymer solar cells 230
- poly(methyl methacrylate) (PMMA) 299
- post-exposure bake (PEB) 179
- power conversion efficiency (PCE) 223, 224, 226, 320
- prehistory effect 260
- primitive vectors 7, 8
- p*-type back surface field (BSF) 226
- pulsed laser deposition (PLD) 57, 228

- q**
- quantum-confined Stark effect (QCSE) 182
- quantum dots (QDs) 319

- quantum efficiency (QE) 267
- quiescent point (Q-point) 115

- r**
- radiant flux 170
- radiative recombination of
 - non-equilibrium carriers 151
 - band-to-band recombination 152–153
 - band-to-local-energy-level recombination 153–154
 - donor–acceptor pair recombination 154
 - exciton recombination 155
 - isoelectronic center recombination 156
- radio frequency devices 305
- radio frequency identification devices (RFIDs) 147
- radioluminescence (RL) 278
- rapid thermal annealing (RTA) 26, 30
- reciprocal lattice vectors 10–11, 288
- reflection high-energy electron diffraction (RHEED) 59
- responsivity (R) 266
- reverse active mode 111
- Rydberg constant 154, 155

- s**
- saturation mode 111
- scanning electron microscopy (SEM) 234, 322
- scanning photocurrent microscopy (SPCM) 317
- Schottky barrier photodiode 261, 281
- Schottky gate contact modulates 139
- Schottky gate electrode 134
- Schottky junction 67, 131, 319, 320
- Schottky solar cells 222, 319–320
- Schrödinger equation 33, 155
- self-trapped exciton (STE) 164, 192
- semiconductor
 - carrier transport
 - band-to-band transitions 19–21
 - drift current and diffusion current 14–17
 - Einstein relation 16–17
 - electrons and holes 14
 - lifetime and mean-free-path 15

- multiple scattering mechanisms 16
- Shockley-Read-Hall statistics
 - 20–21
- thermal-equilibrium condition 19
- trap-assisted recombination 21
- crystal structure and types of
 - binary AB compounds 12
 - body-centered cubic (bcc) lattice 7
 - Bravais lattice 7–9
 - bulk crystal 7
 - common semiconductor crystal structures 11–14
 - crystal lattice 7
 - CsPbBr₃ 13–14
 - face-centered cubic (fcc) lattice 7–8
 - lattice and crystal systems 6–9
 - Miller indices 9–11
 - polycrystalline solids 6
 - primitive unit cell 7–8
 - reciprocal lattice 9–11
 - single-crystalline forms 6
 - unit cell of the crystal 7
 - wurtzite crystal structure 12–13
 - zincblende lattice 12–13
- definition of 1
- examples of 1
- properties of
 - atomic bonding 2–3
 - carrier concentration 5
 - charge carrier transport 5
 - covalent bonding 3, 4
 - doping 4
 - external modulation effect 3–6
 - photon excitation 6
 - strain effect 5
- semiconductor luminescence
 - luminescent semiconductors 158–164
 - nonradiative recombination process 157–158
 - radiative recombination of non-equilibrium carriers 151–156
- Shockley ideal diode equation 40, 42, 43
- Shockley-Read-Hall (SRH) recombination 19–21, 42, 233
- Shockley-Read-Hall statistics 20
- short circuit current density (J_{sc}) 223
- signal-to-noise ratio (SNR) 265, 266
- silicon carbide (SiC) 162, 297
- silicon quantum dots (Si QDs) 318
- single-layer graphene 308
- Si solar cell 225
 - crystalline silicon
 - atomic and band structures 236–237
 - properties of 238
 - synthesis method 239
- slope efficiency 204
- Snell's law 169
- solar cells
 - advantages of 216–217
 - applications of
 - aerospace 242
 - solar-powered vehicles 242–243
 - basic principles
 - parameters of 223–225
 - photovoltaic effect 220
 - solar spectrum and irradiance 217–219
 - structure 221–222
 - crystalline silicon (c-Si)
 - atomic and band structures of 236–237
 - properties of 238
 - synthesis method of 239
 - definition of 215–216
 - overview of 215
 - perovskite solar cells
 - one-step method 239–240
 - two-step method 240–241
 - vapor-deposition method 241
 - in renewable energy 216–217
 - types
 - CdTe solar cell 228–230
 - CuInGaSe 227–228
 - organic solar cells 230–231
 - perovskite solar cells 231–236
 - silicon 225–227
- solar irradiance 218
- solar-powered vehicles 242
- solar radiation 217
- solar spectrum 217
- solid-phase epitaxy (SPE) 57
- space charge region (SCR) 264

sputtering 55
 Stokes-shifted emission 192
 Stranski–Krastanov growth mode 172
 stretchable electronics 150
 substitutional defects 23, 24
 subthreshold swing (SS) 145–146
 superluminescent light-emitting diodes (SLEDs) 195, 196, 202, 211
 surface-mount devices (SMD) 179

t

Tauc plot 76
 ternary or quaternary III-V compounds 58
 thermal conductivity 293
 thermoelectric coolers (TECs) 205
 thin-film transistors (TFTs) 142
 device structures and characterizations 142–147
 emerging applications 148–150
 representative materials and devices 147–148
 threshold voltage (V_{TH}) 145
 transconductance 130, 135
 transition metal dichalcogenides (TMDs) 148, 318
 transportation infrastructure 243
 turn-on voltage (V_{ON}) 145
 two-dimensional electron gas (2DEG) 137
 two-dimensional (2D) semiconductors 148
 type-I two-terminal devices 314–315
 type-II two-terminal devices 316–321

u

ultraviolet light detectors 272–273
 ultraviolet–visible absorption spectrum 74

ultraviolet–visible spectroscopy (UV–Vis) 234
 unit cell of the crystal 7
 UV GaN LED 183–186

v

valence band maximum (VBM) 152, 153, 187
 van der Waals interactions 3, 236
 vapor-assisted solution method 241–242
 vapor-phase epitaxy (VPE) 51, 57
 visible light photodetectors 272
 Volmer–Weber mode 171

w

wavelength-division multiplexing (WDM) systems 199–201
 white light-emitting diodes (WLEDs) 190
 GaN-based white LEDs 190–191
 perovskite-based white LEDs 191–192

x

X-ray detectors 273–274
 direct-type X-ray detectors 274–278
 indirect-type X-ray detectors 278–279
 X-ray diffraction (XRD) 234, 241
 X-ray photoelectron spectroscopy (XPS) 78, 80–81

y

Young's modulus 292

z

zinc oxide (ZnO) 160
 zinc sulphur (ZnS) 160
 zinc telluride (ZnTe) 160