

Index

Note: Page numbers in *italics* and **bold** refers to figures and tables respectively.

a

acid residual, as pollutant 184–185
active equalization 64, 65
aggregation method
 of encapsulation 38
 material 38–39
 model 38
air cooling structure 66, 67
air separation. *see* pneumatic separation
all-life cycling assessments 222–224
artificial intelligence (AI) 42, 50, 163,
 191, 211
automation 205

b

backup power systems 69
ball milling 92, 133, 221
battery 212
 classification of 12–17, **17–18**
 core structure of 11–12, 12
 cylindrical cell 12–14, 13
 demands analysis of battery assembly
 process 19
 factors influencing selection of shape
 structure 18
 pouch cell/lithium-ion polymer
 cell 15–17
 prismatic cell/square cell 14–15

 battery cell collection
 aggregation method of
 encapsulation 38
 material aggregation method
 38–39
 model aggregation method 38
 Battery Directive 7
 battery leasing model 58
 battery management systems (BMS) 68,
 213, 226
 battery pack disassembly
 CMP structure 37
 CTP structure 37–38
 battery recycling 189. *see also* direct
 regeneration recycling;
 hydrometallurgical recycling;
 metallurgical recycling;
 pyrometallurgical recycling
 demands for industry 189–192, 192
 demands for technologies 192–196,
 197
 Brightway2 202–203

c

capacitor-based circuits 64, 65
Carbon Border Adjustment Mechanism
 (CBAM) 2, 58, 201
carbon oxides, as pollutant 182

- cascaded utilization 213–214, 226
 - application scenarios 68–69, **70**
 - economic benefits 57
 - energy-storage batteries recycling 2
 - equalization technology 64–66, 64
 - low-carbon transition
 - cornerstone 57–58
 - resource efficiency 57–58
 - resource recycling 57
 - retired LIBs, sorting of 59–60, 59
 - safety compliance 58–59
 - safety management development
 - needs 68
 - safety management technology
 - 66–67
 - sorting and reconfiguration
 - 60–63, 61
 - systemic necessity 58–59
 - Cell-Module-Pack (CMP) structure
 - battery pack 37
 - Cell-to-Chassis (CTC) technology 18
 - Cell-to-Pack (CTP) structure battery
 - pack 18, 37–38
 - charged fragmentation 40–41
 - chemical degradation 38
 - chemical discharge method 33–36, 34
 - analysis and shortcomings 35
 - development requirements of 36
 - directions for 36, 36
 - chemical testing methods 22, 22
 - scanning electron microscopy (SEM) 23
 - in situ characterization
 - technique 23–24
 - x-ray diffraction (XRD) 22–23
 - Circular Economy Action Plan 7
 - clean recycling processes 195–196
 - Clerici solution 50
 - closed-loop economy development 205
 - closed loop of resources 19
 - closed-loop recycling 70–71, 85, 115, 225
 - computed tomography (CT) 20
 - conductive powder short-circuit discharge
 - method 33
 - constant current charge and discharge
 - testing 25
 - cooling water, as pollutant 183, 186
 - corrosive gases, as pollutant 186
 - cross-field technology collaboration 205, 205
 - cryogenic crushing 41
 - cyclic voltammetry (CV) 24–25
 - cylindrical cell **17–18**
 - advantages and disadvantage 13–14
 - architectural feature 13
 - manufacturing process
 - characteristics 13
 - models and evolution 12, 13
- d**
- data-driven detection method 28
 - degraded recycling, pollution prevention
 - in. *see* pollution prevention
 - demands analysis of battery assembly
 - process 19
 - density functional theory (DFT) 165
 - design for recycling 19
 - detection accuracy
 - improving 29–30
 - insufficient 26–27
 - detection efficiency
 - improving 30–31
 - lack of 27–28
 - detection technologies 211
 - accuracy 26–27
 - comparison and analysis 26–31
 - development vision 29–31
 - efficiency 27–28
 - historical data 28–29
 - differential capacity analysis (dQ/dV analysis) 26

direct regeneration recycling 129, 218–222
 disadvantages of 194
 pollution prevention 186–188, 188, 195
 spent cathode materials 129–158, 168–170
 spent graphite anode 158–168, 170–171
 disassembly
 CMP structure battery pack 37
 CTP structure battery pack 37–38
 design 19
 dry crushing 39–40, **42**
 dual carbon 129, 193, 195, 198
 dust, pollutant 183, 188
 dynamic LCA (dLCA) 198, 198, 200

e

echelon utilization. *see* cascaded utilization
 eddy current separation technology 46–47, 47
 eFootprint 204
 electric arc furnace 76
 electric vehicles (EVs) 58
 electrochemical approach 89–90, 89
 electrochemical impedance spectroscopy (EIS) 25, 57
 electrochemical intercalation method 154–155
 electrochemical regeneration technology 152–153
 electrochemical testing methods 24, 24
 constant current charge and discharge testing 25
 cyclic voltammetry (CV) 24–25
 differential capacity analysis (dQ/dV analysis) 26
 electrochemical impedance spectroscopy (EIS) 25

electromagnetic separation 45–48, 46–48
 electronic load discharge method 33
 electrostatic fragmentation **42**
 electrostatic separation 45–46, 46, 50
 encapsulation, aggregation method of 38
 energy-saving feedback discharge 32
 energy storage systems (ESS) 57, 68–69, **70**
 EoL LIBs recycling processes 7–8
 equalization technology 64–65, 64
 EU’s “New Battery Regulation” 4, 58, 108
 extended producer responsibility (EPR) 179

f

flotation separation 48–49
 fluorinated gases, as pollutants 181, 187
 fragmentation 39–40
 charged 40–41
 comparison of methods **42–43**
 dry crushing 39–40, **42**
 electrostatic **42**
 freeze-fracture **43**
 freezing crushing 41
 wet crushing 39–40, **42**
 freeze-fracture **43**
 freezing crushing 41

g

GaBi 203–204
 global LIBs recycling industry 4–5
 gravity separation 50
 GREET model 203

h

heavy metal-containing slags, as pollutant 182–183
 high-temperature graphitization repair technology 164–168, 166

high-temperature phase conversion 89, 90–91

hydrometallurgical extraction

- electrochemical approach 89–90, 89
- high-temperature phase conversion 89, 90–91
- hydrometallurgical recovery. *see* hydrometallurgical recovery
- hydrometallurgical recycling. *see* hydrometallurgical recycling
- mechanochemical approach 91–111, 93
- oxidative leaching 87–89, 89

hydrometallurgical recovery 216–218

- iron phosphorus residue 91–94, 93
- solid-state batteries 111–112, 112
- ternary cathode materials 110–111

hydrometallurgical recycling 86, 123, 226

- for cathode materials from spent LIBs 114–115
- disadvantages of 193–194
- iron phosphorus residue 91–94, 93
- LCO 95–99
- LFP battery 86–87, 87, 94–95
- pollution prevention 181, 183–186, 187, 189, 195
- solid-state batteries 112–113
- ternary battery 99–110, 101–102, 103, 105, 107, 109

i

impure black mass, as pollutant 188

impurity removal repair

- technology 159–160, 160

inductor-based circuits 64, 65

infrared thermal imaging technology 22

in situ characterization technique 23–24

intelligentization 205

ion-imprinted polymers (IIPs) 117

iron phosphorus residue 91–94, 93

j

jet milling 133

k

K-means clustering 60–62, 61

l

leachate as pollutant 183, 186

leaching residues, as pollutant 185

leaching-separation-purification 95

life cycle assessment (LCA) 197, 222–224

- cross-field technology
 - collaboration 205, 205
- current status of 197, 198
- data integration and
 - standardization 204–205
- degraded lithium-ion battery
 - recycling 197–205
- development trends of 204–205
- dynamic LCA 198, 198, 200
- intelligentization and automation 205
- life cycle impact assessment 197, 198, 199–200
- life cycle inventory 197–199, 198
- life cycle optimization and closed-loop
 - economy development 205
- multi-region input-output LCA 198, 198, 200–201
- social LCA 198, 198, 201

life cycle impact assessment (LCIA) 197, 198, 199–200

life cycle inventory (LCI) 197–199, 198

life cycle optimization 205

liquid cooling 66, 67

liquid-phase regeneration

- lithium cobalt oxide 146–149, 148
- lithium iron phosphate 144–146, 145
- nickel cobalt manganese oxide 149–151, 150

lithium cobalt oxide (LCO) 168–169, 177

- hydrometallurgical recycling
 - for 95–99
 - liquid-phase regeneration of 146–149, 148
 - metallurgical recycling 119–121
 - novel restoration 154–157, 154
 - pyrometallurgical recycling
 - 77–82, 79
 - solid-state regeneration 136–139, 138
 - spent LCO 136, 219–220
 - lithium iron phosphate (LFP) 1–2, 168, 177. *see also* spent LFP
 - hydrometallurgical recycling in 86–87, 87, 94–95
 - liquid-phase regeneration of 144–146, 145
 - metallurgical recycling 116–117
 - novel restoration 151–153, 152
 - pyrometallurgical extraction 75–77, 77
 - solid-state regeneration of 130–136, 131, 132, 134
 - lithium lock effect 75
 - lithium manganese oxide (LMO) 29
 - live reconfiguration 63
 - Lorentz force 46–47
 - loss of active material (LAM) 29
 - loss of lithium inventory (LLI) 29
 - low-speed EVs (LSEVs) 69
 - low-temperature degradation 38
 - low-temperature repair technology
 - 158–164, 161, 162
 - impurity removal 159–160, 160
 - molten salt 160–161
 - surface coating 161–162, 162
- m**
- magnetic separation 47–48, 48, 50
 - material aggregation method 38–39
 - material sorting
 - electromagnetic separation 45–48, 46–48
 - flotation 48–49, 49
 - other sorting methods 50–52
 - pneumatic separation 44–45, 45
 - screening 43–44, 44
 - mean squared error (MSE) 62
 - mechanochemical approach
 - iron phosphorus residue 91–94, 93
 - lithium cobalt oxide 95–99
 - lithium iron phosphate 94–95
 - ternary battery 99–110, 101–102, 103, 105, 107, 109
 - ternary cathode materials 110–111
 - mesh-structured switched-capacitor equalizer (MSSCE) 65
 - metal impurities, as pollutant 188
 - metallurgical extraction
 - hydrometallurgical extraction. *see* hydrometallurgical extraction
 - metallurgical recycling 116–122
 - pyrometallurgical extraction. *see* pyrometallurgical extraction
 - metallurgical recycling. *see also*
 - hydrometallurgical recovery;
 - pyrometallurgical recovery
 - LCO batteries 119–121
 - LFP batteries 116–117
 - solid-state battery 121–122
 - ternary LIB 118–119
 - microwave-assisted hydrothermal synthesis technology 155
 - model aggregation method 38
 - molten salt method 154–156
 - molten salt repair technology
 - 160–161
 - multi-energy conversion platform 36
 - multi-region input-output LCA (MRIO-LCA) 198, 198, 200–201
- n**
- nickel cobalt aluminum oxide (NCA) 177

- nickel cobalt manganese oxide (NCM) 23, 169, 177
- liquid-phase regeneration of 149–151, 150
- pyrometallurgical recovery technology 82
- solid-state regeneration of 139–144, 140–142
- spent NCM regeneration 220–222
- nitrogen oxides, as pollutant 182
- nondestructive testing 20–21
- novel restoration
 - lithium cobalt oxide 154–157, 154
 - lithium iron phosphate 151–153, 152
 - ternary materials 157–158, 158
- O**
- one-step solid-state sintering regeneration strategy 132
- openLCA 202
- organic extracts, as pollutant 185
- oxidative leaching 87–89, 89
- oxide-based solid-state batteries 83
- P**
- PACK packages 212
- passive equalization 64, 65
- physical discharge 32–33, 32
- physical exfoliation techniques 133
- physical load discharge 32
- physical testing methods 21
 - computed tomography (CT) 20
 - infrared thermal imaging technology 22
 - ultrasonic testing (UT) 20–21
- pneumatic separation 44–45, 45
- pollution prevention 177, 222–224
 - battery recycling demands 192–196, 192, 197
 - battery recycling industry demands 189–192, 192
 - degraded battery recycling 178–180, 179
 - degraded lithium-ion battery recycling 177–196
 - direct regeneration recycling 186–188, 188
 - hydrometallurgical recycling 181, 183–186, 187, 189, 195
 - pyrometallurgical recycling 180–183, 181, 184, 189
 - status and strategies 178–180
- polychlorinated dibenzo-p-dioxins (PCDDs) 182, 187
- polyvinylidene fluoride (PVDF) 180
- polyvinylpyrrolidone (PVP) 135
- pouch cell/lithium-ion polymer cell 17–18
 - advantages and disadvantage 16–17
 - manufacturing process feature 16
 - models and evolution 15–16
 - structural feature 16
- pretreatment 211–213
 - battery structure and classification 11–19
 - detection and evaluation 20–31
 - disassembly and crushing 38–42
 - material sorting 43–52
 - safe discharge 31–36, 31
- prismatic cell/square cell 17–18
 - advantages and disadvantage 15
 - manufacturing process characteristics 15
 - models and evolution 14
 - structural characteristics 14–15
- PSILCA database 203
- pyrometallurgical extraction 75. *see also*
 - pyrometallurgical recovery;
 - pyrometallurgical recycling
- pyrometallurgical recovery 214–216
 - lithium iron phosphate 75–77, 77
 - nickel cobalt manganese oxide 82
 - ternary batteries recycling 80–82
- pyrometallurgical recycling
 - demand for 122–123

- disadvantages of 193
 - limitations 79–82
 - lithium cobalt oxide 77–82, 79
 - lithium iron phosphate 75–77, 77
 - pollutants and pollution prevention
 - strategies in 180–183, 181, 184, 189
 - solid-state batteries recycling 82–86
- r**
- reconfiguration 60–61
 - development requirements for 63
 - technical analysis of 62
 - reduction roasting process 104, 105
 - regenerated LCO (R-LCO) 147
 - regenerated LFP (RLFP) 130
 - remaining useful life (RUL) 27
 - residual battery capacity 36
 - resistive load discharge 33
 - retired LIBs, sorting of 59–60, 59
- s**
- safe discharge 31, 31
 - chemical discharge method.
 - see* chemical discharge method
 - physical discharge method
 - 32–33, 32
 - safety assurance 58
 - safety automatic discharge control
 - system 36
 - safety compliance 58
 - safety management technology 66–67
 - scanning electron microscopy (SEM) 23
 - screening 43–44, 44
 - SimaPro 201–202
 - sludges, as pollutant 185–186
 - social LCA (S-LCA) 198, 198, 201
 - solid electrolyte interphase (SEI) 130
 - solid-state battery
 - hydrometallurgical recovery 111–112, 112
 - hydrometallurgical recycling
 - 112–113
 - metallurgical recycling 121–122
 - pyrometallurgical recycling in 82–86
 - solid-state regeneration 129–130
 - lithium cobalt oxide 136–139, 138
 - lithium iron phosphate 130–136, 131, 132, 134
 - NCM cathodes 139–144, 140–142
 - sorting 60–61. *see also* material sorting
 - development requirements for 63
 - retired LIBs 59–60
 - technical analysis of 62
 - spent cathode materials 168–170
 - advanced repair technology 151–158
 - direct regeneration of 129–158
 - liquid-phase regeneration
 - technology 144–151
 - novel restoration 151–158
 - solid-state regeneration
 - technology 129–144
 - spent graphite anode 170–171
 - direct regeneration of 158–168
 - high-temperature graphitization repair
 - technology 164–168
 - low-temperature repair technology
 - 158–164, 161, 162
 - spent LCO (SLCO) 136, 219–220
 - spent LFP 76, 88, 90, 135, 152, 218–219
 - spent lithium-ion batteries (LIBs) 1, 26–31
 - full-chain recycling process 5–6, 5
 - global industrialization landscape of
 - recycling 4–5
 - global progress in recycling 6–8, 6
 - high-value recycling 5–6, 5
 - production volume and
 - distribution 1–2, 2
 - pyrometallurgical recycling targeting
 - cathode from 85–86
 - recycling 3–8, 225
 - strategic significance of recycling
 - 3–4, 3

spent NCM regeneration 220–222
 State of Health (SOH) 27
 storage state of charge (SOC) 26
 sulfation roasting process 106
 support vector machine (SVM)
 60, 61, 62
 surface coating repair technology
 161–162, 162

t

ternary batteries
 hydrometallurgical recycling 99–110,
 101–102, 103, 105, 107, **109**
 metallurgical recycling 118–119
 novel repair technologies 157–158,
 158
 pyrometallurgical recovery in
 80–82
 ternary cathode materials 110–111
 Tesla's Megapack ESS 57

thermal management system (TMS)
 66–67, 67
 transformer-based circuits 64, 65

u

ultrasonic cavitation technology 154–156
 ultrasonic testing (UT) 20–21
 US Environmental Protection Agency
 (EPA) 110

v

volatile gases, as pollutant 186
 volatile organic compounds
 (VOCs) 181–182, 187

w

wastewater, as pollutant 183, 185–187
 wet crushing 39–40, **42**

x

x-ray diffraction (XRD) 22–23

