а

 α DFB lasers $102{-}103$ amplified spontaneous emission (ASE) 11, 12, 24

b

Bloch mode device 70, 71 Bragg mirrors 33

С

carrier density pulsation (CDP) 266 carrier heating (CH) 266 chemically assisted ion-beam etching (CAIBE) 111 III-V compact lasers integrated onto silicon (SOI) 195-197 - heterogeneously integrated edge-emitting laser diodes 204-205 – DFB and tunable lasers 209–211 -- Fabry-Perot lasers 205-207 – heat sinking strategies for heterogeneously integrated lasers 212-213 - - mode-locked lasers 207 – proposed novel laser architectures 211-212 – racetrack resonator lasers 207, 208 - membrane bonding on SOI 197-199 - - adhesive bonding 199-201 -- direct bonding 201, 202-203 -- substrate removal 203, 204 microdisk and microring lasers 213 214-215 - - dynamic operation and switching 219-225 - - microdisk lasers design 215-217 -- static operation 217-219

composite gain waveguide (CGW) 4

composite metallo-dielectric-gain resonators 4–5

 – composite gain-dielectric-metal 3D resonators 7–9

 composite gain-dielectric-metal waveguides 5–7

continuous wave (CW) operation via nonradiative recombination reduction 66–74

coupled-cavity waveguide (CCW) 101–102 coupled mode theory (CMT) 78

d

density matrix 259, 260, 269 distributed Bragg reflector lasers 209 distributed feedback (DFB)-like photonic crystal waveguide lasers 100-102 distributed feedback lasers 209 DVS-BCB (divinylsiloxane-bisbenzocyclobutene) 199-200 dynamic operation and switching - all-optical set-reset flip-flop 219-220 - direct modulation 219 - gating and wavelength conversion 221-222 - microwave photonic filter 224, 225 - narrowband optical isolation and reflection sensitivity of microdisk lasers 222, 223-224 - phase modulation 224

е

edge-emitting PhC lasers 77 electrical injection 93, 94, 96, 97, 99, 100, 102, 125, 135 electrically pumped subwavelength metallo-dielectric lasers 13 – cavity design and modeling 13–17

Edited by Richard M. De La Rue, Siyuan Yu, and Jean-Michel Lourtioz.

© 2014 Wiley-VCH Verlag GmbH & Co. KGaA. Published 2014 by Wiley-VCH Verlag GmbH & Co. KGaA.

Compact Semiconductor Lasers, First Edition.

electrically pumped subwavelength metallo-dielectric lasers (*contd.*)
– fabrication 17–18
– measurements and discussion 18–20
emission statistics 58
etching 10, 13, 17, 18, 20, 234, 240–242, 245, 248. See also vertical cavity surface-emitting lasers (VCSELs)
exchange Bragg coupling laser structure 211

f

Fabry-Perot lasers 205–207 3D finite-difference time-domain (FDTD) calculations 157 Finite Element Method 157 focused ion beam etching (FIBE) 283 285–287, 290, 292, 294 four-wave mixing (FWM) 259–260

g

graded photonic heterostructure (GPH) 129

h

heat sinking - comparison between membrane and bonded PhC laser 69, 70-71 higher thermal conductivity 73–74 - through substrate 72-73 heterogeneously integrated edge-emitting laser diodes 204-205 - DFB and tunable lasers 209-211 - Fabry-Perot lasers 205-207 heat sinking strategies for heterogeneously integrated lasers 212-213 - mode-locked lasers 207 proposed novel laser architectures 211-212 racetrack resonator lasers 207, 208 heterogeneously integrated multiwavelength laser 210, 211

i

inductively coupled plasma (ICP) etching 111 injection-locked ring lasers 219 InP-Based PhC fine processing 68

I

laser diodes and quantum cascade lasers and photonic crystal lasers 91–92

 mid-infrared and terahertz (THz) quantum cascade lasers 112–114

 – microdisk quantum cascade lasers 114–116 - - surface emission and small modal volumes 116, 117-131 - - THz QC lasers with truly subwavelength dimensions 131-135 - near-infrared and visible laser diodes 93 -- microcavity lasers 93-98 – nonradiative carrier recombination in photonic crystal laser diodes 109-112 - - photonic crystal surface-emitting lasers (PCSELs) 106-109 – waveguide lasers in substrate approach 98 - 106lasing region 24 light cone 38 light-current (L-I) curves 274-275 linear rate equation model 52-53

m

membrane device 70, 71 micro/nano cavity based PhC lasers 36 - lasers based on 2D PhC cavities 36-44 - lasers based on 3D PhC cavities 44-46 microcavity lasers 93-98 microdisk 232 - and microring lasers 213, 214-215 – dynamic operation and switching 219-225 – microdisk lasers design 215–217 -- static operation 217-219 microdisk quantum cascade lasers - at mid-infrared wavelength 114-115 - THz waves 115-116 microwave photonic filter 224 225 mid-infrared and terahertz (THz) quantum cascade lasers 112-114 - microdisk quantum cascade lasers 114-116 - surface emission and small modal volumes 116, 117-131 - THz QC lasers with truly subwavelength dimensions 131-135 mid-infrared quantum cascade lasers - with deeply etched photonic crystal structures 116, 117-121 - terahertz (THz) 2D photonic crystal quantum-cascade (QC) lasers 123-131 - with thin metallic photonic crystal layer 121-123 mode coupling 259, 278, 294 mode-locked lasers 207 multimode analysis 259, 260

n

nanoscale metallo-dielectric coherent light sources 1-4 - composite metallo-dielectric-gain resonators - unidirectional SRL 284-287 4 - 5 – composite gain-dielectric-metal 3D resonators 7-9 – composite gain-dielectric-metal waveguides 5-7 - electrically pumped subwavelength metallo-dielectric lasers 13 – – cavity design and modeling 13–17 -- fabrication 17-18 – – measurements and discussion 18–20 subwavelength metallo-dielectric lasers experimental validations for operation at room-temperature 9-10 - - characterization and testing 11-13 - - fabrication processes 10-11 thresholdless nanoscale coaxial lasers 20 - 22 – characterization and discussion 23. 24 - 27- - design and fabrication 22-23 near-infrared and visible laser diodes 93 - microcavity lasers 93-98 nonradiative carrier recombination in photonic crystal laser diodes 109-112 - photonic crystal surface-emitting lasers (PCSELs) 106-109 waveguide lasers in substrate approach 98-106 nonlinear gain 259, 266, 271, 279 nonlinearity, in semiconductor microring lasers 257-260 - general formalism – fundamental equations 260–265 – generalized equations in matrix form 270-272 – third order susceptibility and polarization 265 - 270- numerical results, for microring lasers 272 - 274- - experimental results for racetrack shaped SRLs 281-283 – lasing direction hysteresis 277, 278 - 280 – L–I characteristics 274–275 – temporal dynamics and lasing spectra 275 - 277- numerical results, for unidirectional microring lasers 283

 – feedback strength impact on unidirectional SRL operation 287-293 nonradiative carrier losses 240-242 nonradiative carrier recombination in photonic crystal laser diodes 109-112 non-radiative lifetime 55

- optical bistability 259
- optical feedback 271, 283 287, 289 291, 292 294

out-coupling, through surface emission directionality control 75-76

passive optical waveguides through epitaxial regrowth 78-80 III-V PhC lasers heterogeneously integrated onto SOI waveguides circuitry 80-82 photoluminescence region 24 photonic band-gaps (PBGs) 33, 35, 181-185 photonic crystal lasers. See also individual entries 33-34 - characteristics 52 -- dynamics 60-65 - - rate equation model and PhC laser parameters 52-55 - - stationary regime in PhC lasers 55-60 - design and fabrication 35-36 - - micro/nano cavity based PhC lasers 36 - 46- - slow-light based PhC lasers 46-52 - isssues to be solved and partially solved 65 - - continuous wave (CW) operation via nonradiative recombination reduction 66 - 74- - interfacing and power issues 74-82 photonic crystal surface-emitting lasers (PCSELs) 106-109 photonic integrated circuits (PICs) 195, 196, 226, 231, 257 photonic modes 3 photon lifetime and active volume 53-54 plane-wave admittance method (PWAM) 158-166 plane-wave effective-index method 157 plasma-enhanced chemical vapor deposition (PECVD) 10, 17 pump-probe spatiotemporally resolved thermo-reflectance technique 70 Purcell factor 21, 29, 54

а

quantum dots 66–67 quantum electrodynamic (QED) effects 21–22 quantum wells (QWs) 67, 68–69, 149, 151, 168, 182–184 quantum wires 67

r

racetrack geometry microring lasers 249–251 racetrack resonator lasers 207, 208 radiative lifetime and spontaneous emission factor 54–55 rate-equation model 25–27 – and PhC laser parameters 52–55 reactive ion etching (RIE)-lag effects in small SRL devices 248–249 resonator mirrors 211–212 ridge waveguide lasers with photonic crystal mirrors 103–106 ring laser 232–50. *See also* individual entries ring-resonator based tunable laser 210

S

sampled grating DBR lasers 209, 210 scanning electron microscope (SEM) 13, 17-21, 23, 94, 97, 101, 104, 107, 109, 115-118, 121, 125, 126, 132, 134, 218, 220, 244, 245, 248-250, 281, 282, 288, 289. See also photonic crystal lasers Schawlow-Townes formula (modified) 60 semiconductor ring lasers (SRLs) 231. See also nonlinearity, in semiconductor microring lasers - bending loss 238-240 historical review of contributions to research on devices 232-235 - junction heating in small devices 246-247 - microring and microdisk lasers with point couplers 242-245 - nonradiative carrier losses 240-242 racetrack geometry microring lasers 249-251 reactive ion etching (RIE)-lag effects in small devices 248-249 - waveguide design 235, 236-237 single mode and high side mode suppression ratio (SMSR) 233 slow-light based PhC lasers 46 - 2D PhC DFB -like lasers – for in-plane emission 47–50 -- for surface emission 50-52 spatially diagonal transition 113

spectral hole burning (SHB) 266 spin-on-glasses (SOGs) 199 split-ring resonator (SRR) 133, 134 stable unidirectional SRL 286 surface emission and small modal volumes - mid-infrared quantum cascade lasers – with deeply etched photonic crystal structures 116, 117-121 - - terahertz (THz) 2D photonic crystal quantum-cascade (QC) lasers 123, 125 - 131- - with thin metallic photonic crystal layer 121-123 surface-emitting QC lasers 120 surface passivation of improved efficiency, in PhC lasers 68, 69 surface plasmon polariton (SPP) 3

t

tapered fibers 76-77 terahertz (THz) - 2D photonic crystal quantum-cascade (QC) lasers 123, 125-131 - QC lasers with truly subwavelength dimensions 131-135 threshold current 237, 241, 243, 245, 247, 250, 252, 253 threshold gain for 3D resonators 5 thresholdless lasers 57 thresholdless nanoscale coaxial lasers 20-22 - characterization and discussion 23-27 design and fabrication 22–23 top and bottom-emitting photonic-crystal VCSELs 170-173 transverse modes 149, 151, 152, 154, 156 185 - 187two-mode model 258-259

V

Vernier effect 104
vertical cavity surface-emitting lasers (VCSELs) 92, 106, 149–155
enhanced fundamental mode operation 173–177
highly birefringent and dichroic 177–181
numerical methods for modeling 156–157
photonic crystal depth impact on threshold characteristics 166–169
plane-wave admittance method (PWAM)

- 158–166
- top and bottom-emitting 170-173
- with true photonic bandgap 181-185
- vertical outgassing channels (VOCs) 203

W

wafer scale testing 231, 257 waveguide lasers in substrate approach 98-100– α DFB lasers 102–103 distributed feedback (DFB)-like photonic crystal waveguide lasers 100–102
ridge waveguide lasers with photonic crystal mirrors 103–106
wire cavity laser 41–42