

Index

a

- absorbing layers 139
- acousto-optic modulator (AOM) 136, 218
- adiabatic compression 85
- adiabatic tapers 199, 200
- air-clad photonic crystal fibers 16
- aluminosilicate glass 239
- amplified spontaneous emission (ASE) 40, 42, 53, 157, 158, 218, 220, 222, 225, 227
 - beam quality 222
 - front-end 41
 - generation process 41
 - output power 225
 - suppression 49, 226
- amplifier fiber 28
- amplitude modulation 146
- angular power distribution 182
- annealing 159
- AOM. *See* acousto-optic modulator (AOM)
- AOM control pulse 220
- Ar-ion lasers 137
- ASE. *See* amplified spontaneous emission (ASE)

b

- bandwidths 161
 - limitation 138
 - limited gain 136
- beam combining 38, 271
 - high average power CW spectral 49
 - high-power coherent 227
 - methods 47
- beam quality 27–29, 44, 51, 54, 188, 214, 221, 242, 271
 - degradation 51
- beam shaping 33, 216
- beam splitter 103, 118, 120
 - polarizing 122, 124, 126
- Beers law 8

- bending diameter
 - polarizing window, dependence of 19
- birefringent filter 103
- bismuth-doped materials 272
- boron-doped silica (BS) 18
- Bragg gratings 2, 252
- Bragg reflector 138
- breathing dynamics 163
- Brillouin gain 25
 - bandwidth 42
 - coefficient 43
 - reduction 222
 - spectrum 228
- Brillouin scattering 25, 52, 241
 - stimulated 207, 227, 258
- BS. *See* boron-doped silica (BS)

c

- carbon-based absorbers 140–142
- carbon nanotubes 141, 145
- carrier envelope phase (CEP) 66
- cascade lasing 235
- cavity dispersion 103
- Čerenkov radiation 79
- CFBGs. *See* chirped fiber Bragg gratings (CFBGs)
- chalcogenide glasses 236, 256, 257, 262
- chirally-coupled core (CCC) fibers 124–125
- chirped fiber Bragg gratings (CFBGs) 138, 161–164
 - dispersion management
 - in thulium/holmium-doped mode-locked fiber laser 163–164
 - in ytterbium-doped mode-locked fiber laser 161–163
- chirped-pulse amplification (CPA) 127–129
- cladding diameter 162
 - pump 44
- cladding mode stripper (CMS) 223

- cleaving, microscopic image
 - hackle zone 32
 - mirror zone 32
 - mist zone 32
 - coherent beam combining 227
 - CO₂ laser splicing 34
 - compression
 - autocorrelation and spectrum after 162
 - of down-chirped pulses 162, 163
 - of up-chirped pulse 162
 - continuous wave (CW) 63, 135
 - high-power amplifier 177
 - conventional optical fibers. *See* photonic crystal fibers (PCFs)
 - conversion efficiency (CE)
 - curve 81
 - core-size scaling 120–121
 - counter-propagation laser scheme 207
 - cryogenically-cooled fluoride glass 236
 - cubic Ginzburg–Landau equation (CGLE) 99
 - chirped hyperbolic-secant solution 99–100
 - cubic-quintic Ginzburg–Landau equation (CQGLE) 100, 103–105, 115
 - CW-amplifier beam quality, measurement 29
 - CW fiber laser 26, 215
 - spectral broadening of 28
 - CW radiation 27
 - CW-seed 28
 - CW spectral beam technique 52
- d**
- decay times 159
 - deep-UV radiation band 88
 - design guidelines 110
 - determine
 - desired net GVD 110
 - spectral filter bandwidth 110, 111
 - experimental confirmation 112–114
 - optimizing nonlinear phase shift 111
 - dichroic filter 38
 - dichromatic coating 36
 - dispersion
 - compensation 138
 - in laser cavity 138
 - management techniques 2, 147, 149, 161, 163, 164
 - based on photonic bandgap fibers 164–168
 - parameters 138
 - positive 147
 - third-order 143
 - dispersion-managed soliton 98
 - dispersive-wave (DW) 80
 - generation 78
 - phase matching topology 85
 - radiation shifting 81
 - dissipative soliton fiber lasers 99, 103, 105, 107
 - asymmetric 165, 167
 - chirped pulses 99
 - diffractive 104
 - flat-top 114
 - nonlinearity 98
 - periodic 99, 138
 - slowly moving 128
 - distributed Bragg reflector (DBR) 139
 - Doppler-shifting 25
 - double-clad fiber (DCF) 121–122, 218, 223, 271
 - gain media based 218
 - large mode area (LMA)
 - use of 218
 - longitudinal profile of 219
 - quasi-CW regime 219
 - double clad fiber design 9
 - double clad pumping 2
 - double-clad pumping schemes 184
 - DW. *See* dispersive-wave (DW)
 - Dy³⁺-doped ZBLAN glass, absorption spectrum of 254
- e**
- electromagnetic spectrum 235
 - emission wavelength, output power 237
 - endcapped fiber 34
 - energy extraction 226
 - erbium-doped fiber 136
 - erbium-doped fiber amplifiers (EDFAs) 136
 - for telecommunication networks 9
 - erbium-doped microstructured fiber
 - end-face, SEM image 261
 - Er³⁺-doped fluoride fiber lasers
 - maximum output power 251
 - Er³⁺-doped fluoride glass fiber lasers 251
 - Er³⁺-doped fluoride system 252
 - Er³⁺-doped silicate glass fiber laser 240
 - Er³⁺-doped ZBLAN fiber laser 250
 - Er³⁺ ion, high-power fluoride glass based fiber lasers 249
 - Er³⁺ transition 239
 - etched fiber surface realization, illustration of 37
 - excited-state absorption (ESA) 250, 252
 - external cavity diode laser (ECDL) 38, 49, 53

f

fabrication techniques 160, 241
 Fabry–Perot cavity 140
 fast Fourier transform (FFT) 66
 feedback
 – loop 48
 – mechanism 224
 – parasitic 207
 femtosecond laser 98, 130, 168, 258
 fiber amplifier pumped, schematic setup
 of 38
 fiber amplifiers 37
 – beam quality degradation 51
 – laser process 19
 – mode-instability 42, 51
 – polarization control of 50
 – state-of-the-art 52
 fiber Bragg gratings (FBGs) 40, 138, 258
 – chirped 2, 4
 – low-reflection (LR) 225
 fiber coating 31
 fiber core, waveguide properties of 10
 fiber laser cavity 160
 – propagating signal and pump powers 21
 fiber laser systems 32, 271
 – absorption parameters 46
 – assembly of 31
 – beam quality of 45
 – design of 26
 – dispersion characteristics 2
 – modeling aspects of 2
 – power depending on 30
 – power/pulse energy in 14
 – splicing process, image of 31
 – unabsorbed pump power 46
 fibers core refractive index profile, influence
 on 24
 fiber's cross section
 – thermal loads 23
 fibers heat transfer
 – thermo-optical properties of 22
 filter
 – birefringent 120, 122, 126, 128
 – dichroic 206
 – interference filter (IF) 141
 – spatial 201–203
 – spectral 104, 106, 107, 119, 222
 – discrete action of 146
 finite element method (FEM)
 – method 71
 – SEM images of 70
 fluoride fiber laser 248
 Fourier transformation 211
 four-wave mixing (FWM) 75, 87

 – scattering process 87
 Fresnel reflection 45, 256
 fundamental mode (FM) 2, 11, 15, 30, 188,
 202, 203, 213
 – effective index 13
 – HOMs 15
 – preserves 187
 – during propagation in T-DCF 194
 – SBS threshold for 50
 – stable 53
 fused silica
 – block spliced 34
 – ytterbium-ion, energy level model 20
 FWHM bandwidth 40, 53

g

GaAs/AlAs Bragg mirror 142
 GaAs technology 139
 gain
 – dispersion 148
 – dynamics 144
 – fiber 136–137
 – guiding solitons 148
 – medium 158
 – parameter 144
 – rate equation 145
 Gaussian approximation 215
 Gaussian beam 27
 Gaussian mode 11
 Gaussian pulses 74
 Gaussian shape 214, 227
 Ge-doped silica 65
 GeGaSb fibers 257
 generalized nonlinear Schrödinger equation
 (GNLSE) 71–73
 GeO₂-based core fibers 259
 germanate glass fiber 258, 259
 giant-chirp oscillators (GCO) 127–130
 – autocorrelation of amplified 129
 – potential utility of 129
 – pulse measured by detector 129
 – spectrum 129
 Ginzburg–Landau equation 142
 Gires–Tournois interferometer (GTI) 137
 graphene, as saturable absorber 142
 group velocity dispersion (GVD) 2, 65, 77, 97,
 101, 136, 137
 – changed sign of dispersion 89
 – determined by the fiber lengths 110
 – fiber 148
 – group velocity and 65
 – versus laser performance 111
 – measured round-trip 167
 – nonlinearity balances 2

- and nonlinear phase accumulation 97
- parabolic self-similar pulse propagation in fibre 148
- profile of a small-core PCF 77
- round-trip, of laser cavity 167
- varied by increasing length of first segment of SMF 109

h

- higher-order modes (HOMs) 12
 - filter 30, 124, 125
- high-power Er³⁺-doped fluoride fiber lasers
 - bottlenecking mitigation schemes, schematic diagrams of 250
- high-power fiber amplifier
 - characteristic for 38
 - three-dimensional analysis of 30
- high-power fiber laser systems 35, 37, 177
 - beam combining methods 47
 - pulsed SBC 52–54
 - spectral beam combining 49–52
 - convenient process 37
 - double clad fiber design 8–11
 - fiber components
 - endcaps 33–34
 - fiber preparation 31–33
 - mode-stripper 37
 - pump coupler 34–37
 - narrow linewidth CW amplification 37–38
 - ASE sources, SBS suppression capability 42–43
 - broadened single-frequency diode laser 38–39
 - emission source 39–42
 - polarization control 16–19
 - principles of 8
 - pump core design 15–16
 - special fibers, large core design 11
 - motivation 11–12
 - photonic crystal fibers, core design 12–15
 - tandem pumping 43–47
 - temporal overlap beam 54
 - high-power narrow linewidth fiber amplifier
 - power output characteristic for 39
- high rare-earth ion solubility 254
- Ho³⁺-doped aluminosilicate glass
 - absorption spectrum 244
- Ho³⁺-doped fluoride fiber lasers, schematic diagrams of 253
- holographic reflection grating 49
- hydrofluoric acid (HF) 37

i

- ⁴I_{13/2} → ⁴I_{15/2} transition
 - fluorescence, measured spectra 239
 - power scaling of 240
- index fiber
 - geometrical parameters for 12
- instability
 - modulation 27, 28, 63, 75
 - pulsing 224
 - temporal 225–227
- ion irradiation 159, 160
- IR band 82
- isotropic fibers 16

k

- Kerr effect 27, 30, 139

l

- large mode area (LMA) fibers 11, 43, 44, 46, 177
 - amplifier, output characteristics of 47
 - mode, analysis of 200
- large-pitch photonic crystal fiber (LPF) 15
- laser-based fiber preparation
 - application examples of 33
- laser-based heat source 32
- laser cavities
 - to create short fiber laser cavities 258
 - with large normal dispersion 2
 - with larger positive dispersion 148
 - master-equation, used to model 99, 102
- laser fibers, nonlinear effects
 - inelastic scattering 25–26
 - mode instabilities 27–30
 - propagation and rate equation description 19–22
 - self-phase modulation 27
 - thermo-optical effects 22–25
- laser parameters, variation of 107
 - group-velocity dispersion 109
 - nonlinear phase shifts 107–109
 - spectral filter bandwidth 109
- laser performance 183
- laser radiation 218, 242
- lasers
 - mode-locked 104, 145
 - output characteristics of 216
 - solid-state 135
 - via adjustments to waveplates 104
 - waveguide geometry of 135
- lattice reformation 159
- light propagation 177
 - spectrum of 211, 212

Littrow angle 49
 Littrow configuration 50
 Littrow illumination 53
 long-wavelength fiber lasers efficiency
 – survey of power 237–239
 Lorentzian gain shape 106
 Lorentzian pump beam 217

m

Mach–Zehnder interferometer 69
 Marcuse equation 11
 meridional rays 178
 metal–organic chemical vapor deposition
 (MOVPE) 140
 Michelson interferometer 42
 microstructured optical fibers (MOFs)
 – tellurite glass 261
 microstructure fiber technology 272
 mid-infrared band 272
 mid-infrared fiber lasers pump 239
 mode-coupling measurements
 – experimental setup for 211
 mode-instability 51
 mode-locked fiber lasers 142, 147
 – dispersion management
 – on chirped fiber Bragg gratings 161
 – mode-locking 271
 – technique 136
 – without GVD/SPM 158
 – Yb-doped mode-locked fiber laser
 – experimental set-up 162
 mode-locked oscillators 136
 mode-stripper, illustration of 37
 modified chemical vapor deposition
 (MCVD) 246
 modulation instability (MI) 75
 molecular beam epitaxy (MBE) 140
 monolithic all-glass pump combiner
 scheme 36
 MOPA setup, schematic drawing of 48
 multiple-quantum-well (MQW)
 structure 139
 Multi-pump photon absorption process
 – energy levels, schematic of 243

n

narrow linewidth source, spectral broadening
 of 39
 Nd-doped fiber 8
 Nd:YAG lasers 63
 neodymium 136
 neodymium (Nd)-doped crown glass 8
 neodymium-doped fiber lasers 138

non-hexagonal fiber design 15
 nonlinear effects
 – classical 30
 – in fibers 27
 – in laser fibers 19
 nonlinear interference 97
 nonlinear polarization evolution (NPE) 103,
 112–114, 118, 120
 nonlinear processes
 – in glass-core fibers 66
 – in photonic crystal fibers (PCFs) 66–69
 nonlinear Schrödinger equation (NLSE)
 142, 143
 – modified 143
 normal-dispersion lasers 2, 103, 105, 116,
 130, 148
 numerical optimization of laser
 systems 154–157

o

optical absorption 142
 optical communications 1, 147
 – networks 136
 optical damage threshold 142
 optical fiber 72
 – pulse propagating in 73
 optical fibers
 – development of 7
 – glass fabrication 245
 – modeling nonlinear pulse propagation
 – envelope equations 73–74
 – unidirectional field equation 71–73
 optical Kerr effect 139
 optical spectrum analyzer (OSA) 201
 – spectral composition of 52
 output coupling 136

p

paraxial ray pump absorption 181
 Pb-free alkali germanate glass 256
 phase-matching (PM) 85
 phase modulations 146
 Phonon energy 246
 photonic bandgap (PBG) fiber 138
 photonic crystal fiber 22, 64, 122–123
 – effective cladding index of 13
 – geometrical parameters for 12
 – index-matched stress applying
 elements 18
 photonic crystal fiber amplifiers,
 polarized 48
 photonic crystal fibers (PCFs) 1, 2, 12, 64,
 271

- amplifier fiber
- beam quality, measurement 29
- coupling efficiency 45
- output characteristics of 46
- use of 88
- ASE filter 53
- cross-section of polarizing large-mode-area 19
- effective indices n_{eff} 13
- experimental supercontinuum generation 76
- group velocity dispersion (GVD) profile 77
- modal properties of 12
- partial collapsing of 33
- realizations of double clad 17
- structure, SEM of 83
- supercontinuum generation 64
 - dispersion in 69–71
 - nonlinear processes 66–69
 - properties, calculating 65–66
 - tapers 64–65
- supercontinuum sources 63–89
- ultrafast pumped supercontinuum sources
 - axially varying fiber, soliton dynamics 86
 - dispersive-wave generation 78–79
 - extreme SCG 88–89
 - initial dynamics and solitons 77–78
 - intrapulse FWM 86–87
 - intrapulse Raman scattering 79–81
 - multiple ZDWs 82–85
 - power dependence 81–82
 - soliton blue shift 87–88
 - supercontinuum generation, regimes of 74–77
 - supercontinuum, shape of 81–82
 - taper transitions 85–88
 - third ZDW 68, 84–85
 - wavelength tuning 82
- photonic crystal tellurite fibers 261
- physical limits 114
 - area theorem 114–117
 - pulse duration 119–120
 - pulse energy 117–118
- plasma chemical vapor deposition (PCVD) method 216
- Poincaré mapping 143
- polarization rotation 97
 - nonlinear 139
- power-dependent thermal lens 271
- power scalability 272
- power scaling 3, 271
- propagation equation 19
 - pulsed beam combining setup
 - single fiber amplifier chain, experimental setup of 53
 - pulsed fiber lasers, classification of 146–149
 - pulses
 - chirped 104
 - duration 101, 145, 147, 161
 - dechirped 104
 - increase 106
 - dynamics 147
 - effective saturation energy 144
 - energy 100–101, 144, 147
 - evolutions 148
 - intensity 72
 - interferometric autocorrelation 104
 - multiple, in cavity 103
 - in normal GVD regime 102
 - propagation 84, 143, 148, 162
 - within a general fiber 105
 - in passive and active fibers 146
 - shaping 104, 106, 147
 - solutions categorized by 102
 - splitting 148
 - temporal evolution 105
 - transform-limited 147
 - ultrafast, pulse generation 144
 - pump absorption 182, 205
 - pump beam apertures
 - output characteristics of laser 216
 - two-dimensional intensity distribution of 217
 - pump cladding 35
 - pump conversion efficiency 197, 205, 206
 - deterioration of 214
 - vs. absorbed pump power 197
 - pump coupling schemes 35
 - pumping fiber lasers 245
 - pump intensity 185
 - angular 190
 - Lorentzian angular distribution 190
 - pump laser technology 63
 - pump power
 - amplifier 225
 - vs. launched 223
 - core/cladding area ratio 193
 - distribution of 194
 - longitudinal distribution of 196
 - near-paraxial fraction of 186
 - optical power 52
 - output power
 - and backward power *versus* launched 224
 - pulse energy 220
 - and peak power *vs.* absorbed 220

pump radiation 37, 193, 215
 – propagating, absorption of 184, 185

q

Q-switched fiber lasers 142
 Q-switched laser setup
 – schematic of 219
 Q-switched operation 222, 252
 Q-switched T-DCF laser
 – optical spectra of 221
 quantum-confined semiconductor
 absorbers 139–140
 quintic nonlinear absorption coefficient 102

r

Raman amplification 3, 79
 – advantage of 3
 Raman cross section 258
 Raman effect 72
 Raman fiber lasers, mode-locked 3
 Raman gain coefficients 25, 241, 257
 Raman scattering 52, 73, 74, 143, 241
 – processes 241
 Raman–soliton continuum 76
 Raman soliton self-frequency shift 63
 Raman wavelength 25
 rare-earth doped fiber 143
 rare earth doping, accessible wavelengths
 by 9
 rare-earth ion doped fluoride glasses
 – fundamental laser parameters of 248
 rare-earth ion doped silicate glasses
 – fundamental laser parameters of 240
 rare earth transitions
 – emission spectra of 248
 Rayleigh scattering 207, 246
 – signal light 40
 refractive index 138
 – profile, schematic representation of 10
 relative intensity noise (RIN)
 – semiconductor lasers 4
 relaxation-oscillation-free flat spectral noise
 density 4
 resonant absorber 160
 resonant radiation 79
 resonator 136, 143

s

saturable absorbers 139
 – artificial 139
 – non-artificial 139
 saturable gain 136
 SBS-induced pulse breakdown 221
 SBS mitigation 226

SBS suppression capability 42
 SBS threshold 50
 scalar Helmholtz equation 10
 seed signal 49
 self-phase modulation (SPM) 63, 69, 74, 97,
 136, 137
 – normal dispersion region 74
 self-pulsing operation 208
 semiconductor disk laser (SDL) 4, 158, 159
 – relative intensity noise (RIN) of 4
 semiconductor saturable absorber mirror
 (SESAM) 126, 139
 – engineering and control 157–161
 – monolithic, design of 140
 – quantum dot (QD) based 140, 145
 seven-hole-missing photonic crystal fiber
 – modal characteristics of 14
 short to mid-infrared fiber lasers, material
 properties of glasses 255
 shortwave infrared fiber lasers
 – employing fluoride glass 248–249
 – employing silicate glass 239–240
 shortwave infrared fiber lasers employing
 silicate glass 239
 – chalcogenide fiber lasers 256–257
 – Dy³⁺-doped fluoride fiber lasers
 systems 253–254
 – Er³⁺-doped fluoride glass fiber lasers
 249–252
 – Er³⁺-doped silicate glass fiber laser
 240–241
 – fiber lasers, exotic glasses 254
 – germanate fiber lasers 257–259
 – Ho³⁺-doped fluoride glass fiber lasers
 252–253
 – Ho³⁺-doped silicate glass fiber lasers
 244–245
 – laser performance 238
 – rare-earth ions, energy level diagrams
 of 238
 – tellurite fiber lasers 259–261
 – Tm³⁺-doped silicate glass fiber lasers
 241–244
 shortwave infrared transitions, fluorescence
 spectra of 249
 shortwave to midwave infrared
 photonics 235
 – electromagnetic spectrum 235
 – fiber lasers 235
 – – employing fluoride glass 247
 – infrared fiber fabrication 245–247
 SIF technique 71
 signal propagation 186
 silica glass 71

- molar refractive index changes 10
 - silicate glass fiber fabrication 246
 - similariton fiber lasers approach 98
 - simplified modeling approach 149–154
 - simulations 105
 - temporal evolution 105–107
 - single-frequency (SF) laser diode 42
 - single longitudinal mode (SLM) 258
 - single-mode fibers (SMFs) 97, 103, 106, 107, 112, 119, 120, 125, 126, 206
 - single-mode pump laser diode (SM-LD1) 40
 - single-walled carbon nanotubes (SWCNTs) 141
 - diameter distribution, of product 141
 - film, SEM micrograph 141
 - saturable absorber 141
 - slope efficiency measurements 206
 - solid core index-guided photonic crystal fiber 138
 - solid-state lasers 98
 - soliton–Raman continuum 63
 - solitons
 - area theorem 147
 - dissipative 103, 148
 - fiber lasers 97
 - optical 147
 - propagation constant 74
 - self-frequency shift 79
 - spectral bandwidths 239
 - spectral beam combination (SBC) 48
 - CW and pulsed sources 54
 - setup 50
 - spectral broadening
 - power dependence 81
 - pump wavelength dependence 82
 - spectral evolution 107
 - SPM broadening 89
 - stability
 - environmental 125–127
 - plausible mechanisms for 103
 - Stark splitting 20, 239
 - in fluoride glass 249
 - Stefan–Boltzmann law 22
 - step-index double clad fiber
 - schematic comparison of 16
 - step index fiber (SIF) 13, 14
 - approximation 66
 - beam quality, measurement 29
 - effective indices n_{eff} 13
 - simulated overlap of the LP₁₁ mode 24
 - undisturbed index profile of 24
 - stimulated Brillouin scattering (SBS) 25, 207, 219, 227, 258
 - stimulated Raman scattering (SRS) 25
 - Stokes field
 - pump power 25
 - Stokes limit 245
 - efficiency 245
 - Stokes shift 25
 - Stokes wave 26
 - stress-applying parts (SAP)
 - well-known technique of 17
 - stress-induced birefringence 17
 - supercontinuum generation (SCG) 2, 63
 - supercontinuum (SC) mechanism 81
 - SWIR spectrum 4
- t**
- tandem pumped fiber amplifier, schematic setup for 44
 - taper coil radius 211
 - tapered double-clad fiber (T-DCF) 177
 - active tapered fiber, parameters of 183
 - core–cladding ratio, and dopant concentration profile 191–192
 - longitudinal shape of 187–191
 - tapering ratio 184–187
 - active tapered fiber, ray optic model of 178–183
 - amplification of CW signal 227
 - amplifier 226, 227
 - amplifier, output characteristics of 228
 - angular power distribution 182
 - broadband radiation, emission spectrum of 211
 - characteristics 181
 - cladding 181, 184
 - coiling radius 213
 - conceptual axial profiles 187
 - counter-propagating scheme 204, 212
 - counter-propagation tapered fiber laser 209
 - diameter 218
 - emission propagating 199
 - end-face image for 180
 - experiment
 - beam quality 214–215
 - mode-coupling measurements 210–214
 - pump absorption 205–206
 - pump conversion efficiency 206–207
 - self-pulsing threshold 207–210
 - fiber lasers 192
 - high-power laser
 - experimental setup for 215
 - lasers/amplifiers 199
 - actively Q-switched tapered fiber laser 218–223

- high-power fiber laser 215–218
 - high power, high gain CW amplifier 223–227
 - laser schemes, characterization 206
 - lasers, comparison of 192
 - contrast and beam quality 198–204
 - launching efficiency 204–205
 - slope efficiency, pump absorption, and power distribution 192–198
 - launching efficiency coefficients 204
 - linear taper, angle of 178
 - longitudinal profile 187, 190
 - Lorentzian angular distribution 190
 - meridional ray angle 189
 - mode coupling characterization 200–203
 - narrow bandwidth amplifier 227–229
 - near-field distribution of 215
 - normalized vignetting length 181
 - optimal length of 198
 - parabolic shapes of 190
 - parameters of 183
 - population inversion distribution 196
 - power density, cavity length 197
 - pulsed amplifier, output characteristics of 228
 - pump absorption 183
 - pump conversion efficiency 192
 - pump propagation 178
 - ray optics analysis 189
 - ray trajectory 178
 - SBS mirror 208, 210
 - SBS signal 229
 - SBS suppression of 222
 - short pulse amplifier 229
 - slope efficiency for laser 187
 - spectrum and autocorrelation function of amplified signal 229
 - step-like/exponential bowl-shaped tapers 188
 - step-like tapered fiber 188
 - various axial taper profiles 187
 - vignetting pump power 195
 - volume-equivalent cylindrical, length ratio of 198
 - ytterbium ions, effective concentration of 195
 - telecom dispersion shifted fibers 138
 - tellurite fiber lasers 254, 259
 - tellurite glass fiber 259
 - amplifiers 260
 - lasers 260
 - temporal evolution 105, 107
 - mode-locking, affected by 106
 - TE-polarization 50
 - thermal conduction 22
 - third-order dispersion (TOD)
 - contribution 80
 - thulium- and thulium–holmium-doped fibers 4, 137
 - thulium fiber 4
 - time-resolved photoluminescence (TRPL) 159
 - Tm³⁺-doped aluminosilicate
 - refractive index profile of 243
 - Tm³⁺-doped silicate glass fiber 241
 - Tm³⁺-doped silicate glass system
 - advantages 242
 - high-power diode-cladding-pumped 244
 - radiation 243
 - Tm³⁺ emission cross-sections 256
 - Tm³⁺-ion
 - fiber lasers employing 241
 - TM-polarization 50
 - transversal spatial-hole burning (TSHB) 30
- u**
- ultrafast carrier relaxation time 142
 - ultrafast fiber laser systems
 - development, key factors 168
 - numerical modeling 143–146
 - ultrafast pulse generation 137
- v**
- Vignetted pump power 191
 - vignetting effect 185
- w**
- wave-guiding systems 2
 - wavelength-division multiplexing (WDM)
 - pump coupler 161
 - wavelength shift. *See* Stokes shift
 - wavelength-specific reflector 138
 - waveplates 103
 - wave-vector matching conditions 87
 - Whilst internal slope efficiencies 245
- x**
- XFROG spectrogram 78, 80
- y**
- YAG crystal 239
 - Yb-doped fibers 27, 41, 44
 - typical emission and absorption cross section 20

- Yb-doped gain fiber 106
- Yb-doped lasers 103
- Yb-doped nanostructured step-index fiber
 - cladding pumped non-polarizing, amplifier fiber 38
- Yb-gain bandwidth 54
- Yb³⁺ ions
 - three-level system of 193
- ytterbium 136
- ytterbium doped fibers 43
- ytterbium-doped silica fibers 136
 - ultrashort pulse generation 137
- Ytterbium ions
 - effective concentration of 195
- Z**
- ZBLAN fibers 246, 247
 - lasers 254
- ZBLAN glass 248
- zero dispersion wavelength (ZDW) 64,
69, 84
 - launching light 82
 - SC shifts, blue spectral edge 82
 - wavelength 87