

Index

a

- absorption 1, 3, 11, 16, 95, 97, 98, 243, 244, 247, 275, 295, 314, 349
 - measurement 349, 351, 359
 - monotonic, eumelanin 126
 - photoinduced 281
 - spectra, blueshift 241
- acenes 238, 248
- acetylcholine (ACh) 46, 69, 74
- acoustic resonances 240
- activation energy 95, 97, 103, 246, 251, 368, 412, 414
- actuators 28, 48, 76, 77, 328
- ADT-TES-F aggregates 244
 - absorptive aggregates 244, 245
 - emissive aggregates 245, 246
- aggregation, and effect on optoelectronic properties 241
 - disordered H-aggregates in ADT-TES-F films 241, 242
 - J- vs H-aggregate formation 241
 - optical and photoluminescent properties 242
 - photoconductive properties 243, 244
- AgNW electrodes 163
- Alq3-based device 382, 390, 394
 - electrical bipolar switching 381
 - thicknesses 392
- ambipolar LEFETs 190–197
 - blends, utilization, in electrooptical circuits 197
 - charge recombination 194
 - current–voltage characteristics 193
 - disadvantage of narrow bandgap semiconductors 192
 - distinctive transfer, and output characteristics of 193, 194
 - electron and hole channels in 191
 - emission zone, for different gate voltages 194
 - EQE measurements 196
 - gate dielectric 192, 193
 - order of deposition, for bi- or trilayer structure 197
 - photoluminescence efficiencies 197
 - photoluminescence quenching 196
 - position of emission zone 195
 - prerequisite 192
 - quantum efficiencies 195
 - radiative decay efficiency 195, 196
 - Schottky barrier for injection of electrons 192
 - source–drain current 195
 - vs. unipolar LEFETs 190
 - width of recombination zone 195
- ambipolar single-crystal EDLT 313
 - capacitance dependence, of carrier mobilities 315
 - hole and electron threshold voltages 314
- ambipolar single-walled carbon nanotube FET
 - infrared emission 205
- ambipolar transistor 190, 307–309, 422
- amide-functionalized ADT acceptor molecules (ADTA) 253
- amino-alkyne ligands 15
- amino-azide ligands 15
- amino-PEG ligands 15
- amphiphilic polymer 14
- anisotropic magnetoresistance (AMR) 381, 390
- anisotropy 250, 311
- annealing 4, 152, 160, 161, 163, 165, 253, 274, 276, 286, 293, 417
- anthradithiophene (ADT) 234
- Arrhenius plot 413
- artificial muscles 76
- artificial nerve cell 77, 78
- atomic force microscopy (AFM) 4, 40, 124, 129, 180, 351, 404

- Au electrodes 56, 308, 419, 421
- Au nanoparticles (AuNP) 132
- Au–pentacene interfaces 412
- Au source electrode/P13 (bottom)/tetracene
 - energy level diagrams 415
- autofluorescence 16
- autoxidation 117, 118, 120, 128, 129

- b**
- bandgap engineering 283
- band-like transport 107
- benzenethiolate-based magnetic tunnel junction 386
- benzodithiophene (BDT) 281, 285
- benzothiophene 234
- bias conditions 190, 406, 415, 421
 - operating conduction mechanism with energy level under 420
- bifunctional diacetylene fluorene, *in situ* metal-catalyzed polymerization 3
- binding energy 127, 273, 279, 282
- bioelectronics 107, 108
- biomolecule presenting surfaces 72, 73
- 2,5-bis(4-biphenyl)thiophene
 - p-type crystal 203
- 1,4-bis[5-(4-(trifluoromethyl)phenyl)thiophen-2-yl]benzene
 - n-type crystal 203
- bleaching 115, 116, 123, 129, 224
- blood–brain barrier 16
- bolaamphiphile fluorene oligomers 16
 - fluorene derivatives 18
- brain-derived neurotrophic factor (BDNF) 43
- bulk heterojunction OPV device 275
- bulk phenomena 387, 388

- c**
- Ca²⁺ ion 74, 75
- carbon nanotube-enabled vertical field-effect transistors (CN-VFETs) 205
- carbon nanotubes 153, 204
 - film fabrication 156–158
 - improving performance 158–160
 - light-emitting FETs 204–206
 - networks 155, 156
 - structure 153–155
- carboxyl-functionalized F8BT nanoparticles 16
- catecholamines 50, 51, 117, 118
- cell adhesion, controlling via redox state 33, 34
 - direct patterning of proteins to control cell adhesion 38, 39
 - protein characterization
 - as a function of redox state 36–38
 - redox gradients 35, 36
 - redox switches 34, 35
- cell density gradients 35, 72
- cellulose acetate butyrate (CAB) 7
- charge-based DLTS technique (Q-DLTS) 352
- charge carrier mobilities, for crystals 237
- charge density 33, 224, 312, 320, 345, 348, 354, 356, 357, 369
- charge transfer complexes 131
- chemiluminescence 7
- chromophore 1, 94, 292
- complementary metal oxide semiconductor (CMOS) 403, 422
 - air-stable, hysteresis-free organic CMOS inverters 425–427
 - integrated circuits (ICs) 422
 - inverter
 - 3-dimensional schematic of 423
 - organic 422
 - typical VTCs of 426
 - OFETs, characterization 422–425
- conducting polymers (CPs) 27, 28
 - benefits 29, 30
 - ease of processing 30
 - freedom in chemical modification 30
 - mixed conduction and ideal interfaces 29, 30
 - soft mechanical properties 29
 - biocompatibility 30, 31
 - for biological applications 28, 29
 - to control cells 32
 - controlling cell adhesion via redox state 33–38
 - establishing as cell culture environments 32
 - optimizing conducting polymers for cell culture 32, 33
 - controlling cell growth, and development 39
 - alignment control via topographical cues 40–43
 - electrical stimulation 39, 40
 - direct patterning of proteins, to control cell adhesion 38, 39
 - electrochemical properties and tools 31
 - incorporation of biomolecules, to control differentiation 43
 - conducting polymer actuators 48, 49
 - covalent tethering of neurotrophins 45, 46
 - electrochemically controlled presentation 46
 - entrapment and release of neurotrophins 43–45
 - incorporation of neurotrophins 43

- on-demand cell release 48
 - optoelectronic control of cell behavior 49
 - organic electronic ion pumps 46, 47
 - to monitor behavior of nonelectrically active cells 57–59
 - to monitor neuronal function 51
 - conducting polymer electrodes 51–56
 - transistors 57
 - conductivity switching 388–390
 - conjugated polymer nanoparticles exhibiting white emission
 - shelled architecture of 6
 - π -conjugated system 2
 - constant photocurrent method (CPM) 351
 - controlled substance release 73–75
 - copolymerization 3
 - Coulomb interaction 280
 - CPs, *see* conducting polymers (CPs)
 - crystallographic information, for crystals 237
 - cw photocurrents 251
 - cyclic voltammetry (CV) 313
- d**
- dark current 100, 251, 252
 - dearomatization, thiophene ring 285
 - deep level transient spectroscopy (DLTS) 352, 353
 - degradable surfaces, for biomedical applications 73
 - density of states (DOS) 95, 96, 343, 344, 346, 349, 355, 356, 359, 360, 362–364, 369, 370, 372, 385, 386
 - DH6T-based transistors 414
 - DH6T thin films 406
 - two-dimensional micrographs 407
 - dicyanomethylenedihydrofuran (DCDHF)
 - derivative 240
 - 5,6-dihydroxyindole-2-carboxylic acid (DHICA) 117
 - oligomers 122
 - 5,6-dihydroxyindole(s) (DHI)
 - dimers and trimers 120
 - interaction with eumelanin polymer 125
 - oxidative polymerization 118
 - polymerization 120, 126, 132
 - tetramers 121
 - 5,6-dihydroxyphenylalanine (DOPA) 118
 - diketopyrrolopyrrole (DPP) 281, 285, 293
 - ditetracene 199
 - DNA sensing 83
 - DNA transistor-based sensors 83
 - donor–acceptor composites 252–254
 - donor–acceptor interactions 254, 255
 - effects on photocurrent 257–260
 - D/A spatial separation 257–259
 - Δ LUMO 258, 259
 - in spin-coated/drop-cast ADT-TES-F/ADT-TIPS-CN films 260
 - effects on photoluminescence 256
 - drop-cast films 257
 - DOS, *see* density of states (DOS)
 - drain–source current (I_{DS}) 408
 - drain–source voltage (V_{DS}) 408
 - DWCNT-based transparent conductors 155
- e**
- ECoG electrode array 56
 - EGFET (electrolyte-gated field-effect transistor) 81
 - electrical conductivity
 - of conducting polymers 70
 - and photoconductivity findings 100, 101
 - transport model 104–106
 - electrical stimulation, to promote 32, 39, 40, 42–45
 - muscle cell proliferation and differentiation 39, 40
 - neurite formation and extension 39
 - electrical switching 96, 106, 414
 - electric double-layer transistor 312–315
 - electric force microscopy (EFM) 352
 - electrochemical impedance spectroscopy (EIS) 57
 - electrochemical doping 43, 176, 177, 179, 182, 183, 217, 218, 222, 224
 - electrochemical stability window (ESW) 180
 - electrochemiluminescence 7
 - electroluminescence 6, 7, 187, 188, 190, 201, 202–205, 223, 403, 416, 419, 421
 - electrolyte-gated organic light-emitting transistors (EG-OLETs) 216
 - assessment of effect of proximity of electrolyte 226
 - challenges 220–226
 - n-injection in 227
 - observations by time-resolved spectroscopy
 - on conjugated polyelectrolytes 226
 - electrolyte-gated organic transistors 216–218
 - electrolytes employed in 218–220
 - electrolytic solutions used in 218
 - electrochemical stability windows 219, 220
 - ionic conductivity 219
 - ionic liquids 218, 219
 - physicochemical properties 220
 - polyelectrolytes 220
 - polymer electrolyte 220
 - viscosity 219

- electron affinity (EA) 191, 192, 197, 279, 280, 288–290
 - electronic detachment technology, based on PEDOT-S:H thin films 73
 - electronic devices, effect of traps on 345
 - light-emitting diodes 347
 - photovoltaics 348
 - sensors 348
 - transistors 345–347
 - electronic nose 83, 84
 - Aromascan A32S 84
 - Bloodhound ST214 84
 - Cyranose 320 84
 - research on bacterial identification 84
 - electron paramagnetic resonance 101–104
 - electron trap, in organic semiconductors 343, 344. *See also* traps detection
 - in amorphous semiconductors 344
 - configurations, give rise to traps 345
 - electronic distribution of trap states
 - in DOS of a semiconductor 343, 344
 - impurities and 345
 - intrinsic structural defects 344, 345
 - trap depth 344
 - trap states, in bandgap 344
 - electroplating method 10
 - electrospinning 40, 165
 - EL intensity (I_{EL}) 419
 - emergent electrode materials 149
 - carbon nanotubes 153
 - film fabrication 156–158
 - improving performance 158–160
 - networks 155, 156
 - structure 153–155
 - graphene 149, 150
 - electronic band structure 150
 - fabrication 151, 152
 - metal nanowires 161
 - alternative 164–166
 - silver nanowires 161–164
 - emissive aggregates 245, 246
 - EPR spectroscopy 130, 131
 - 1-ethyl-3-methylimidazolium tris (pentafluoroethyl)trifluorophosphate ([EMIM][FAP]) 224
 - eumelanin 113, 114
 - absorption spectra 125, 126
 - coated TiO₂ nanoparticles 133
 - degradation products 116
 - electrochemical methods, for self-assembly of films 132
 - molecular weight 123
 - natural (*see* natural eumelanin)
 - properties 125
 - Mie scattering 125
 - Rayleigh scattering 125
 - strategies involving oxidative polymerization 126
 - true 120
 - used to prepare hybrid structures 132
 - external quantum efficiency (EQE) 9
 - extracellular matrix (ECM) protein 32
- f**
- fabricating high-performance optoelectronic devices 401
 - F8BT particles 7–10, 13, 14, 16, 198, 199, 224, 226
 - ferromagnetic/nonmagnetic/ferromagnetic (FM/N/FM) multilayer 382
 - FETs, *see* field-effect transistors (FETs)
 - FETs ambipolar light-emitting, *see* ambipolar LEFETs
 - fibronectin (Fn) 32
 - field-effect transistors (FETs)
 - between ADT-TES-F and ADT-TIPS-CN molecules dispersed in 255
 - ambipolar 194, 199 (*See also* ambipolar LEFETs)
 - based on rubrene 233
 - curves of ambipolar squarylium dye-based 193
 - devices 113
 - n-channel FET conduction 307
 - unipolar 194, 203 (*See also* unipolar LEFETs)
 - fixed ionic carriers 181–183
 - fixed junction LEC-based photovoltaic devices 183, 184
 - fluorene–acetylene polymer 3
 - fluorene-based π -conjugated systems 1
 - fluorene-based oligomers 16
 - fluorene-based polymers 2
 - fluorene–fluorenone copolymers 7
 - fluorene polymers, nanoparticles based on 2, 3
 - fluorescence-based methods, for probing biomolecular interactions 1
 - fluorescence energy transfer, in nanoparticles 2
 - fluorinated tetracenedithiophenes (TDTs) 236
 - fluorophores 240
 - FM electrodes 388, 389, 391
 - Fermi energy of 386
 - spintronic phenomena 383
 - Förster resonant energy transfer (FRET) 2, 36, 38, 252
 - ratios 37

Fourier transform infrared (FTIR) spectrometers 351
 “frozen junction” devices 184
 fullerene 150, 164, 273, 274, 275, 277, 281, 283, 286, 287, 290, 292
 functionalized ADT derivatives 236
 functionalized benzothiophene (BTBTB) 234
 functionalized IF-R, molecular structures 235
 functionalized pentacene derivatives 236

g

gamma-aminobutyric acid (GABA) 46
 gate dielectric insulator 408
 giant magnetoresistance (GMR) 381
 Gibbs energy 279, 281
 glass transition temperature 4
 glucose oxidase enzyme (GOx) 81
 gold nanowires (AuNWs), in TC electrodes 165
 graphene 149, 150
 – electronic band structure 150
 – fabrication 151, 152
 – preparation 151
 growth factors 33, 43, 72
 – tethered 46

h

H-aggregates 241, 244, 245
 Hanle effect 384
 heterojunction light-emitting FETs 197–200
 hexacene (Hex) 234
 hexamethyldisilazane (HMDS)
 – amphiphilic surfactants 402
 – and OTS surface treatments on crystallinity of films, effect of 408
 – pretreated, and OTS-pretreated SiO₂ substrates 406
 Hex-F8-TCHS derivative 238
 highest occupied molecular orbital (HOMO) 147, 188, 192, 200, 234, 279–281, 306, 384, 421
 homopolymers 275, 283
 “hopping-dominated” conductivity 96
 hybrid devices 107
 hybrid nanoparticles 3
 hydration-dependent conductivity 98
 hydrogenated amorphous silicon (a-Si:H) devices 341, 405

i

imaging and sensing applications 10
 – bioimaging 14–16
 – biosensing 11–14

– nanoparticles characterization 10, 11
 immunosensors 82, 83
 indenofluorene (IF) derivatives 234, 238
 indium tin oxide (ITO) 139, 140
 – properties 140
 – refractive index 140
 – variability 140
 indium tin oxide (ITO) anode forming 7
 indole-based squaraines 241
 5,6-indolequinone 120, 131
 infrared emission from ambipolar single-walled carbon nanotube FET 205
 integrated circuits (ICs) 422
 ionic carriers 178–180
 ionic conductivity 46, 70, 175, 181, 183, 218–220, 227, 312
 ionic liquids 182, 218, 219, 313, 315
 ionization potential (IP) 202, 279, 280, 281, 367
 ISOFET (ion-sensitive organic field-effect transistor) 81, 82
 ITO-coated glass 405

j

J-type aggregates 241

l

La_{0.7}Sr_{0.3}MnO₃ (LSMO) devices 385
 LEFETs, *see* light-emitting field-effect transistor (LEFETs)
 light emission–voltage characteristics 403
 light-emitting ambipolar transistor 309–312. *See also* light-emitting field-effect transistor (LEFETs)
 – ambipolar LET 310
 – p-i-n model 312
 – EQE 310
 – p-n junction structure 310
 – recombination zone width 310, 311
 – single-crystal organic LET 310
 – tetracene single-crystal transistor 309
 light-emitting electrochemical cells (LEECs) 215
 light-emitting field-effect transistor (LEFETs) 187
 – working principle of 188
 – ambipolar 190–197
 – unipolar 188–190
 liquid crystal displays (LCDs) 341
 local field potentials (LFPs) 51
 longer heteroacene derivatives 234
 low-bandgap polymers 283

lowest unoccupied molecular level
(LUMO) 147, 148, 234, 256, 279, 280, 282,
313, 372, 384, 385, 419, 421

m

magnetic tunnel junctions (MTJs) 386
– benzenethiolate-based 386
– fabrication of 386
magnetoresistance (MR) 381, 391
– actual MR of organic spintronic device made
of 392
– curves after application of different high
voltage pulses 395
– defined 383
– due to spin transport between FM
electrodes 389
– at higher voltages 388
– merit of devices 383
– spin polarization 383
– of electrode 383
– in spin valve device 383
matrix-assisted pulsed laser evaporation
(MAPLE) 132
medical diagnosis, and electronic nose 83, 84
melanins 113, 114
– based devices 114
– electrical conductivity, as a function of
hydration 99
– hybrid materials 132, 133
– hydration dependence of conductivity
97–101
– natural (*see* natural melanins)
– photoconduction 100, 104–106
– physical and optical properties 94
– solid state bioelectronic device 109
– solution EPR titration curve, for colloidal
solution 104
– synthetic (*see* synthetic melanins)
melanogenesis 116–118
melanosomes 114
metal chelation 126, 127
metal electrodes 51, 52, 55, 98, 143, 188, 277,
278, 309, 310, 324, 350
metal–insulator–semiconductor field-effect
transistors (MISFETs) 302–307
metal–insulator–semiconductor (MIS)
junctions 97
metal nanowires 161
– alternative 164–166
– silver nanowires 161–164
methanofullerene 197, 275
Miller–Abrahams expression 387
miniaturization 76, 113

miniemulsion method 2, 3
– nanoparticles preparation 2
MISFETs, *see* metal–insulator–semiconductor
field-effect transistors (MISFETs)
modified dielectric Mott–Davis amorphous
semiconductor (MDAS) model 98
molecular packing on spectra, effects of 246
– film morphology, and spectra 247
– molecular structure 246
– solid-state packing 246
Monte Carlo simulations 155, 253
Mott–Davis amorphous semiconductor
(MDAS) 98, 99, 101, 106
Mott–Gurney SCLC equation 354
MR, *see* magnetoresistance (MR)
MTJs, *see* magnetic tunnel junctions (MTJs)
muon spin relaxation spectroscopy
101–104

n

nanobiomedicine 107
nanoparticle–nanoparticle interactions 5
nanoparticles
– based on π -conjugated polymers and
oligomers 1
– based on fluorene polymers 2
– film fabrication 4
– fluorescence energy transfer (FRET) 2
– layers of polyfluorene 4
– preparation, schematic representations of 2
– for sensing and imaging 17, 18
– in water 2
nanoparticles, based on fluorene oligomer 16
– characterization 16, 17
– for sensing and imaging 17, 18
nanoparticles, based on fluorene polymers
– optoelectronic applications 3
– characterization of 3, 4
– film fabrication and characterization 4, 5
– OLEDs 5–8
– solar cell applications 8–10
– sensing applications
– bioimaging 14–16
– biosensing 11–14
– characterization of 10, 11
nanoparticle–substrate interactions 5
nanotubes 156
natural eumelanin
– distribution 115, 116
– isolation 115, 116
natural melanins 114, 115
nerve growth factor (NGF) 43
neuronal device interfaces 78, 79

- neuroprosthetics
 - artificial nerve cell 77, 78
 - neuronal device interfaces 78, 79
 - neuronal signal recording 79, 80
- neurotransmitters 69
- neurotrophins
 - covalent tethering 45, 46
 - entrapment 43–45
 - release 44, 45
- neutral cluster beamdeposition (NCBD)
 - method 401, 403–405
 - apparatus 404
 - single-layer OFET devices 417
- nickel-coated CuNWs 165
- N-methyl-5,6-dihydroxyindole 120
- nonfullerene acceptors 283, 293, 294
- n-type OFETs 238

- o**
- octadecyltrichlorosilane (OTS) 402
- OECT, *see* organic electrochemical transistor (OECT)
- OLEDs, *see* organic light-emitting diodes (OLEDs)
- OLEFETs, *see* organic light-emitting field-effect transistors (OLEFETs)
- oligofluorene derivative OF 17
- optical absorption 239
- optical pump–terahertz (THz) probe spectroscopy 248
- optoelectronic characteristics 140–143
 - optical transparency 146
 - sheet resistance 141
 - four-point probe 142
 - influence of 143–146
 - measurement 141, 142
 - transmittance *vs.* sheet resistance trade-off characteristics 146, 147
 - work function 147–149
- optoelectronic control, of cell behavior 49, 50
- optoelectronic thin-film devices 401
- OPVs, *see* organic photovoltaic devices (OPVs)
- organic bioelectronics 70, 76, 77
- organic devices, fabricated by printing
 - methods 325
 - inkjet printing 328–330
 - soft lithography 325–328
- organic dyes 6
- organic electrochemical transistor (OECT) 31, 35, 57, 59, 81
 - as cell-based sensors. 58
 - to measure cell attachment, and coverage 57
 - PEDOT doped with tosylate 72
 - use of PEDOT:PSS OECT 57
- organic electroluminescent sensors 215
- organic electronic ion pumps (OEIPs) 46, 74, 75, 77
 - based “artificial nerve cell” 78
- organic (opto)electronic materials 233
- organic field-effect transistors (OFETs) 1, 301, 341, 401, 405
 - characteristics
 - device parameters deduced 412
 - characterization of 408–412
 - morphological and structural properties 406–408
 - p- and n-type 422, 427
 - transport phenomena 412–414
- organic large-area electronics (OLAE) technology 319
 - manufacturing processes for 324, 325
 - materials for 322–324
- organic light-emitting devices 175, 252, 310
 - current efficiency 206
- organic light-emitting diodes (OLEDs) 1, 139, 140, 187, 215, 221, 233, 309, 320, 341, 381
 - optoelectronic applications 6
- organic light-emitting electrochemical transistor 222
 - device structure 223
 - electrochemical doping 224
 - p-type output characteristics 223
 - shape of transistor current 223, 224
 - transfer characteristics 223
- organic light-emitting field-effect transistors (OLEFETs) 401
 - ambipolar 414, 415
 - characterization of component 416–419
 - heterojunction- based 402, 415
 - α,ω -dihexylquarterthiophene (DH4T)/P13-based ambipolar 421
 - EL phenomena 421
 - heterojunction-based 416
 - multidigitated, long channel width geometry 415
 - single component- and blend-based 415
- organic magnetoresistance (OMR) 381, 388, 391
- organic photovoltaic cell 319
- organic photovoltaic devices (OPVs) 1, 175, 273, 320, 341
 - device architectures 276
 - active layer 276
 - contacts 277, 278
 - energetics of charge generation 278
 - operating principles 279
 - efficiency 285

- J–V curves 289
 - molecular acceptor materials for 285, 286
 - complementary light absorption 292–295
 - electron affinity 288–290
 - morphology 286–288
 - stabilization of reduced acceptor 290–292
 - open-circuit voltage 281
 - performance 294
 - organic P5V4 single-crystal LEFET 203
 - organic semiconductors (OSs) 96, 108, 381
 - conformation 389
 - ferromagnetic/nonmagnetic/ferromagnetic (FM/N/FM) multilayer 382
 - FM/OS interface, role in 385, 386, 388
 - magnetoresistive phenomena 382–390
 - molecular structures of 202
 - spin-polarized carriers 382
 - spin-polarized electrons hopping from 383
 - spin precession 384
 - spin scattering, competing explanation 388
 - thickness 391
 - organic single crystals 187, 201, 203, 217, 301, 302, 306, 308, 313
 - field-effect transistors 200
 - traps in 358–364
 - organic solar cells, *see* organic photovoltaic devices (OPVs)
 - organic spintronics 381, 382
 - applications 390
 - prototypical device, memristive phenomena in 391–396
 - sensor applications 390, 391
 - organic thin-film transistors (OTFTs) 320
 - bulk heterojunction (BHJ) approach 321
 - conduction 321
 - dielectric 321
 - key parameters for operation 322
 - mobility 321
 - power conversion efficiency (PCE) 321
 - quality 321
 - OTS-pretreated devices 413
 - OTS-pretreated pentacene
 - current–voltage characteristics 410, 411
 - OTS-pretreated thin films 408
 - Output voltage swing (OVS) 426
 - oxidation 29, 31
 - of acid DHICA 121
 - control of cell adhesion using gradients 36
 - CP providing switching mechanism 31, 35
 - 5,6-dihydroxyindole 121, 128
 - dimer and trimer 120
 - DOPA solution 131, 132
 - mono-electronic and bi-electronic 128
 - at PEDOT:PSS electrode 51
 - polymer 84
 - PPy substrate 32
 - products of the catechol 92
 - resistant to 165
 - semiquinone 104
 - states featuring an inner N ring 127
 - thermal 322
 - tyrosine 117
- p**
- p- and n-type organic semiconductors, molecular structures 402
 - paramagnetism 130
 - partial charge transfer, with exciplex formation 253
 - parylene 55
 - P13/DH6T devices 421
 - p*-distyrylbenzene (DSB) 241
 - PEDOT:PSS channel 57
 - PEDOT–silk composite electrodes 79, 80
 - pentacene (Pn) 234, 407
 - pentadithiophenes (PDTs) 236
 - phenyl-C₆₁-butyric acid methyl ester (PCBM) 234
 - phonons 387
 - photoconductivity 97, 251
 - photocurrent 184, 243, 250, 251, 257, 273, 351
 - negative 100
 - photoexcitation 96, 239, 242, 248, 252, 273, 279, 294, 345
 - photoinduced electron transfer 253, 274
 - photoluminescence
 - efficiencies 187, 192, 197, 201, 202, 203, 205
 - quenching 180, 196, 293
 - photorefractive (PR) devices 233
 - photostability 1
 - p-i-n junction 177, 184
 - PLA/PGLA fibers 41
 - plasma immersion ion implantation (PIII) 38
 - P13 layer, electron transport 419
 - PLGA (poly(lactic-co-glycolic acid)) 79
 - pnp-ion bipolar junction transistor (IBJT) 75
 - Pn-TIPS crystals 248, 249, 251
 - polyaniline (PANi) 76
 - polycyclic aromatic hydrocarbons (PAHs) 151
 - 2,7-poly(9,9-dialkylfluorene-co-fluorenone) (PFFO) 7
 - poly(9,9-dihexyl)fluorene (PF) nanoparticle films
 - optical properties of 5
 - polydimethylsiloxane (PDMS) 55, 183
 - polyelectrolytes 220

- poly(3,4-ethylenedioxythiophene) (PEDOT) 28, 31, 71
 - doping with heparin 72
 - PEDOT doped with tosylate (PEDOT:TOS) 71
 - poly(ethylene glycol) (PEG) 14
 - polyfluorene-based organic nanoparticles
 - for optoelectronic applications 3
 - polyfluorene nanoparticles (PF2/6) 6
 - polyfluorene nanoparticles, emission wavelength 3
 - polyfluorenes (PF) 4
 - blue emission of 7
 - chemical structures of 4
 - core–shell particles of 5
 - poly(3-hexylthiophene) (P3HT) 75
 - derivatives 234
 - polyisothianaphthene (PITN) 285
 - poly(lactic-co-glycolic acid) (PLGA) 40–43, 79
 - polymer electrolyte 220
 - polymer–fullerene bulk heterojunction (BHJ) 276
 - polymer–fullerene film 274
 - polymer gate dielectric 402
 - polymeric bulk heterojunction (BHJ) solar cells 234
 - polymerization 118
 - chemiresistive sensors, fabrication by 84
 - DHICA 121
 - electrochemical 43, 70, 83, 132
 - melanin precursors 132
 - oxidative 117, 118, 126
 - of 5,6-dihydroxyindole(s) 118
 - quinones (Q) and semiquinones (SQ) generation by 128
 - of PEDOT using DNA 73
 - Raper–Mason scheme for 117
 - *in situ* metal-catalyzed 3, 30
 - polymer light-emitting electrochemical cells 175–178
 - polymer multielectrode arrays (polyMEAs) 54, 55
 - poly[2-methoxy-5-(2'-ethylhexyloxy)-1,4-phenylene vinylene] (MEH-PPV) 5, 221
 - poly(methyl methacrylate) (PMMA) 192, 199, 201, 223, 239, 240, 242, 243, 254, 255, 324, 424, 425
 - gate dielectric surface, modification of 425
 - single-crystal LEFET 202
 - SiO₂ dielectrics 425
 - poly[3-(4-noctyl)-phenylthiophene] (POPT) 293
 - poly(*p*-phenylene vinylene) 6, 7
 - chemical structure of 6
 - PFO energy donor 7
 - poly(*p*-phenylene vinylene) (PPV) derivatives 234
 - polypyrrole (PPy) 28, 76
 - poly(styrene-*b*-isobutylene-*b*-styrene) (SIBS) 40
 - poly(styrene-co-maleic anhydride) 14
 - poly(styrene sulfonate) (PSS) 73
 - polythiophene 28, 164, 283, 284, 285
 - chemical modifications 284
 - diodes 352
 - polythiophene (poly(octanoic acid 2-thiophen-3-yl-ethyl ester) (pOTE) fibers 40
 - polyvinylalcohol (PVA) 126
 - polyvinylpyrrolidone (PVP) 161
 - power conversion efficiency (PCE) 145, 152, 157, 234, 254, 273, 274, 282, 284, 293, 321, 333, 334, 335, 348
 - evolution 274
 - of OPV, as a function of bandgap of donor and 282
 - PPy-coated PLGA fibers 41
 - pristine materials, (photo)conductive properties of 248
 - charge transport
 - on nanosecond and longer timescales 250, 251
 - on picosecond timescales 248–250
 - cw photocurrent 251, 252
 - dark current 251, 252
 - ultrafast photophysics 248–250
 - prosthetics, and medical devices 75, 76
 - protein characterization 36
 - push–pull effect 283
- q**
- quinone 120
- r**
- Raper–Mason scheme 118
 - receptor-mediated endocytosis 14
 - redox gradients 35, 36
 - redox state 33, 35, 36, 46, 72, 127, 128
 - redox switches 34, 35
 - reprecipitation method 5
 - nanoparticles preparation 2
 - rubrene 201, 202, 214, 301, 302, 304
 - ambipolar transistors 308
 - Au–rubrene interface 308
 - indium–rubrene single-crystal interface, energy band 305
 - molecular structure 302
 - PDS spectra of single crystal 350

- resistance 305
 - single-crystal device 305, 324, 359, 367
 - single-crystal MESFET 306
 - single-crystal transistors 324
 - and tetracene single-crystal LETs, investigation 310
- s**
- saturation mobility 413
 - scaffolds 71
 - scanning transmission X-ray microscopy (STXM) 8
 - Schottky diode 304–307
 - Seebeck coefficient, in gated structure 357
 - semiconductivity 107
 - amorphous 96, 97, 100, 106
 - semiconductor models 131
 - S-galactosylthio-DHI (gal-DHI) derivative 126
 - sheet resistance 141
 - four-point probe 142
 - influence of 143–146
 - measurement 141, 142
 - Shockley–Reed–Hall (SRH) recombination 348
 - signaling interfaces 71
 - silver nanowires (AgNWs) 147
 - single-crystal field-effect transistors (SC-FETs) 361
 - single-crystal growth 302, 303
 - single-crystal light-emitting FETs 200–204
 - single-walled carbon nanotubes (SWCNTs) 147, 154–156, 204, 205
 - infrared light emission 204
 - thin films, uses 205
 - SiO₂ gate dielectric insulator 408
 - XRD patterns for 408
 - small-molecule, and biological metabolite sensing 81, 82
 - small-molecule BHJ (SMBHJ) solar cells 234
 - smoking gun 96
 - solar cell applications 8–10
 - based on separate particles 9
 - solid-state NMR spectroscopy 130
 - sonication 2
 - space-charge limited currents (SCLCs) 238
 - measurements 353–355
 - spin diffusion 388
 - Spin Hall effect 384
 - spin injection coefficient 385
 - spin-polarized injectors 384
 - spin relaxation mechanisms
 - to spin–orbit coupling 387
 - spin-transfer torque 381
 - spin transport 387–390
 - spray deposition, for organic large-area electronics 330
 - large-area, low-cost spray-deposited organic solar cells 334, 335
 - motivation and technical aspects 330–332
 - spray-deposited, organic thin-film transistors 333, 334
 - top electrodes, deposited by spray coating 332, 333
 - surface contact angles
 - two-dimensional micrographs 407
 - surface modulation 71, 72
 - surfaces for novel biomedical applications 71
 - SWCNTs, *see* single-walled carbon nanotubes (SWCNTs)
 - synthetic eumelanins 119
 - literature protocols 119
 - molecular weight 123
 - structural investigations 123
 - synthetic Raper–Mason scheme 117
 - synthetic melanins 118
 - acidic treatments 123
 - laboratory procedure 118
 - precursors 118
 - TEM structure 93
- t**
- t*-bu BTBTB 239, 240, 242
 - (*t*-butyl)ethynyl (*t*-bu) BTBTB 234
 - temperature-dependent SCLC spectroscopy (TD-SCLCS) 355
 - tetracene 199, 201, 248, 301, 309, 415
 - LEFETs based on 188
 - polycrystalline 417
 - semiconductors 421
 - single crystals 307–309
 - surface-pretreated tetracene thin-film device 406
 - two-dimensional micrographs 407
 - tetramethyltetraselenafulvalene (TMTTSF) 362
 - thermal annealing 274
 - thermally post-treated P13/tetracene-based OLEFETs
 - hole and electron mobilities 418
 - output characteristics of 416
 - stress-free ambipolar 419
 - transfer curves of 417
 - thermally stimulated current spectroscopy (TSCS) 353
 - thienopyrazine 285
 - thienopyrroledione (TPD) 285

- thienothiophene (TT) 285
- thin film fabrication 131, 132
- thin-film transistor 320
- thin-film transistors (TFTs) 233
- time-of-flight (TOF) experiments 301
- time-of-flight secondary ion mass spectrometry (ToF-SIMS) 180
- tissue culture polystyrene (TCPS) 32
- transient photoconductivity
 measurements 250
 – changes, as temperature decreased 250, 251
- transistor-based detection of DNA 83
- transparent conductor (TC) 139
- transparent ITO electrode 140
- transport physics, of disordered semiconductors 94
- traps detection, in organic semiconductors 349
 – electrical methods 352, 353
 – electronic devices, use of 353–358
 – experimental data on traps 358
 –– conjugated polymer thin films 368–372
 –– organic single crystals 358–364
 –– polycrystalline thin films 364–368
 – optical methods 349–351
 – scanning probe methods 351, 352
- Trilayer LEFET, energy levels 200
- trimethylolpropane ethoxylate (TMPE) 180
- triode devices 113
- tris(8-hydroxyquinoline) aluminum (Alq₃) films 404
- tunneling behavior 107
- tunneling magnetoresistance (TMR) 381
- tunnel resistance R_T 385
- u**
- unipolar LEFETs 188–190
 – approaches 188, 189
 – brightnesses range 189
 – device and measurement setup 190
 – improvement by adding CPE layer 189
 – limitations 190
 – voltage drop cause distortion 188
- v**
- van der Pauw geometry 98
- van der Waals forces 341, 342
- van der Waals interactions 156, 219, 401
- vapor pressure osmometry 123
- viscosity 123, 218–220, 227, 240, 328, 329, 331
- voltage-dependent resonant tunneling 386
- voltage transfer curves (VTCs) 426
- w**
- whole luminescence process, mobile electron carriers affecting 420

