

Index

a

air mass (AM) 329
 air–silicon interface 37
 alkaline/acidic chemical wet-etching 4
 angularly resolved scattering (ARS) 98–99
 angular restriction 186
 angular-selective reflectance filters 10, 11
 angular selectivity 187
 angular spectrum method 98–99
 anti-reflection (AR) technologies 1
 – air–glass reflection loss 336
 – light-trapping microstructures 338
 – nano-scale technologies 336–338
 – quarter-wavelength AR layer 336
 anti-reflective/antireflection coating (ARC)
 3–4
 – EVA/Si interface 326
 – nano-scale technologies 336–338
 – short circuit current loss 339
 atomic layer deposition (ALD) 131–132
 autocorrelation length 95

b

barium borate glass
 – advantages 303
 – collection efficiency 305–306
 – fluorescence intensity 306–307
 – fluorozirconate-based glass 306–307
 – optical properties 303, 305
 – transmission factor 303, 305
 black body emission spectrum 24
 black silicon
 – chemical etching 124–126
 – ECE 124–126
 – fabrication method 117, 119
 – KOH 117, 118
 – Lambertian light trapping (*see* light trapping)

 – laser processing 122–124
 – RIE 119–122
 – silicon passivation (*see* surface passivation)
 Bragg filter
 – germanium solar cell 201–203
 – hydrogenated amorphous silicon solar cell 197–201
 Bragg stacks 11

c

Chandeson method 59, 96–97
 charge carrier lifetime 42
 charge transfer emission 40
 chemical etching 124–126
 chemical passivation 136
 compound parabolic concentrator (CPC)
 161–162
 concentrated photovoltaic (CPV) system
 – acceptance angle 154–157
 – geometric concentration 154–155
 – HCPV (*see* highly concentrating photovoltaics (HCPVs))
 – low-cost optical design 153–154
 – non-uniformities 158–159
 – optical designs (*see* primary optical element (POE))
 – optical efficiency 157–158
 – SOG (*see* silicone on glass (SOG))
 concentration acceptance product (CAP)
 156–157
 contact tabs 340–342
 crystalline Si 38
 crystalline silicon (c-Si) 1
 – absorption depth 1, 2
 – absorption spectra 2, 3
 – solar cells 1, 2
 Cu(In,Ga)Se₂ 38

d

- 2D gratings 8
- 3D photonic crystal IRLs (3D-IRL) 14–16
- 3D photonic crystals 9–11
- dark current, solar cell 24
- dielectric photonic structures 246–248, 251
- differential reciprocity, Wong and Green theorem 31–33
- diffraction gratings. *See* light trapping
- directional selectivity. *See* light trapping
- distributed Bragg reflectors (DBR) 9
- donor–acceptor interface 40
- doping concentration 243–251
- down-conversion
 - AM1.5 standard solar spectrum 255
 - borate glasses 260
 - down-shifting 256
 - multivalent europium-doping (*see* europium-doping)
 - phonons 259
 - quantum cutting mechanism 256–257
 - rare-earth ions 257–258
 - Sm-doped borate glass (*see* samarium (Sm)-doped borate glass)
 - ZBLAN glass (*see* ZBLAN glasses)
- down-shifting 256
- dye-doped polymer 297
- dynamic depolarization 214

e

- effective acceptance angle
 - angular transmission curve 155–156
 - CAP 156–157
 - concentrator cost 155–156
 - imperfections 155
 - maximum electric power 154–155
- electrochemical etching (ECE) 124–126
- Electroluminescence (EL) emission 25, 36–39
- electron-beam lithography 69–70, 72
- emitted photon flux 23–24
- emitter and collector currents, transistors 29–30
- emitter wrap through (EWT) 342
- energy transfer up-conversion (ETU) 231, 237
- Er³⁺-doped FZ glasses 232
 - absorption coefficient 233–234
 - absorption spectra 233–234
 - nominal compositions 232–233
 - optical density 233–234
 - up-converted fluorescence spectra 234–237
- europium-doping
 - photoluminescence 274
 - trivalent europium 267
 - XANES measurement 274
 - x-ray absorption 268–270
 - XRD 270–272

- exact electrodynamic theory 245
- excited state absorption (ESA) 237
- external quantum efficiency (EQE) 28, 105–106, 231, 237, 266, 276
 - 3D photonic crystal 194–197
 - enhancement 9, 15–17
 - front-side nanostructures 221
 - rear-side nanostructures 222
 - TCO 198–199
- external radiative efficiency (ERE) 34

f

- Fabry–Perot-resonator 55–56
- field effect passivation 136
- finite difference time-domain (FDTD) method 8, 59, 246
 - ARS function 98–99
 - black silicon interface 133–134
 - Maxwell's equation 97
 - optical simulation 99–100
 - properties 100–102
- finite element method (FEM) 172–174
- fluorescence concentrators
 - absorption/emission coefficient 285–286
 - barium borate glass (*see* barium borate glass)
 - bottom-mounted system 288–289
 - factors 284
 - geometrical concentration 307–308
 - IAD 310
 - LBIC 310–312
 - mono crystalline silicon solar cell 308–310
 - NanoFlukos 294
 - non-perfect filter 291–293
 - organic dyes 299
 - plasmonic nanostructures 223
 - polymer matrix material 296–298
 - principles 283–284
 - quantum dots (*see* quantum dots (QDs))
 - quantum efficiency 312
 - rugate filter 286–287
 - side-mounted system 288
 - thermodynamic efficiency 290–291
 - two- and three-dimensional photonic crystals 286–287
- fluorozirconate-based glass 306–307
- focused ion beam (FIB) milling 83
- Förster energy-transfer processes 225
- Fraunhofer diffraction 328
- frequency downconverters 223

g

galvanostatic etching 124
 germanium solar cell 203
 glass ceramics. *See* ZBLAN glasses
 glass-glass modules 343
 gold nanoparticle 245–246

h

highly concentrating photovoltaics (HCPVs)
 – concentrator design 175–179
 – requirements 175–176

i

III/V based solar cells 38
 inductively coupled plasma (ICP) etching
 119–121
 inductively coupled reactive ion etching
 (ICP-RIE) 5–6
 inhomogeneous broadening 212, 216
 interband damping 212, 215
 interband transitions
 – luminescence efficiencies 211
 – optical properties 212
 – in silver, gold and aluminum 210
 interference lithography (IL) 76–77
 intermediate reflective layers (IRLs) 13–16
 internal quantum efficiency (IQE) 266,
 329–330
 ion-assisted deposition (IAD) 310–311
 isolated interface 100
 iterative Fourier transform algorithm (IFTA)
 algorithm 103, 105, 107, 109, 199

k

Kirchhoff's laws 30, 33
 Köhler illumination 164
 Korringa–Kohn–Rostocker (KKR) method
 59

l

Lambertian scatterer 5–6, 328
 laser beam induced current (LBIC) 333
 laser induced periodic surface structure
 (LIPSS) 122–124
 The Law of Entire Equilibrium 22
 LED quantum efficiency 33–34, 36, 39
 levelized cost of electricity (LCOE) 323
 light beam induced current (LBIC) 39, 43,
 310–312
 light guiding efficiency (LGE) 294–295
 light harvesting strings (LHSs) 333
 light management, solar module
 – AR treatment, PV front surface (*see*
 anti-reflection (AR) technologies)

– cell arrangement 324
 – cell interspaces 343
 – cell-to-module efficiency 323
 – encapsulant materials 338–339
 – experimental techniques and equipment
 331–333
 – front and back interface 342–343
 – front glass sheets 334–336
 – incidence angle variation and diffuse light
 331
 – metallization and contact tabs 340–342
 – numerical simulations 333–334
 – reflective and absorption losses 324–326
 – spectral effects and solar concentration
 329–331
 – textured interfaces/surfaces 326–328
 lightning-rod effect 212
 light-scattering patterns 217
 light trapping 1, 35–37
 – AFM 79
 – butt-coupling 55
 – c-Si solar cell, textured surface of 327–328
 – dielectric coatings 130–132
 – electron-beam lithography 69–70, 72
 – Fabry–Perot-resonator 55–56
 – features 126–127
 – FIB 83
 – grating period 53, 55
 – ICP-RIE process 128–130
 – incoming radiation 56
 – interference lithography 76–78
 – light path 57
 – limiting efficiency 132–135
 – linear (1D) rear side grating 51
 – micro-structured front glasses 338
 – nanoimprint lithography 76–77
 – optical simulation (*see* optical simulation)
 – principles 49–50
 – propagation constant 55
 – properties 50–51
 – self-organizing process 73–74
 – SEM 80–81
 – structures 127
 – sub-micron domain 127
 – substrate thickness 132–135
 – textured glass surface 327–328
 light-trapping
 – Bragg filter (*see* Bragg filter)
 – crystalline silicon cell 184
 – 1D layer stack filter 192–194
 – 3D photonic crystal 194–197
 – directional and spectral selective absorber
 191–192
 – grating couplers 184

light-trapping (*contd.*)

- radiative efficiency limit 185–187
- radiative interaction 7, 41–50
- thin-film solar cell 184
- universal limit 188
- wafer solar cell 184

localized surface plasmons. *see*

particle-plasmon (PP) resonances

low-iron soda-lime-silica glass 334–335

luminescence imaging 40–42

luminescent concentrators. *See* fluorescence concentrators

m

Maxwell's equations 96–98

metal assisted chemical etching (MACE)
125–126

metal-assisted wet-chemical etching 5

metal wrap through (MWT) 342

micromorph tandem solar cell 13–16

Mie-theory 245

multicrystalline Si solar cells 41

multifold Köhler concentrators 164–166

multi-junction cells 13

multi phonon relaxation (MPR) 240,
242–243

n

nanoimprint lithography (NIL) 76–77

nanorods (NRs) 214

nanowires 215

near-field effects 212, 217–218

near-field scanning optical microscope
(NSOM) 94, 99–100, 102

normal incidence 157

normalized non-radiative lifetime 26

numerical simulations 333–334

o

Ohmic contact 23

Onsager's reciprocity 29

optical concentration 186–187

optical density 233–234

optical excitations, metal nanoparticle

– interband transitions 210–211

– PPs (*see* particle-plasmon (PP) resonances)

optical path enhancement 1

– energy-selective structures 13–16

– ray optical limit 4–5

– resonant structures 7–10

– scattering structures 5–7

optical simulation

– absorptance 66–67

– Auger recombination 66

– carrier conservation 66

– drift-diffusion equation 65–66

– matrix method 64

– radiative recombination: 66

– RCWA/FMM 58–61

– solar cell simulation 65

– SRH recombination 66

– surface recombination 66

opto-electronic reciprocity

– experimental verifications 37–39

– limitations 43–44

– luminescence imaging 40–42

– principle of detailed balance 21–22

– spectrally resolved luminescence analysis
39–40

– SQ limit 22–24

organic bulk heterojunction solar cells 38

ORMOCER 299

p

particle–particle coupling 215

particle-plasmon polariton 214

particle-plasmon (PP) resonances

– conduction electrons, collective oscillations
of 211–212

– dielectric environment 214

– inhomogeneous broadening 212, 216

– interband damping 212, 215

– light-scattering patterns 217

– metal selection 213

– near-field effects 212, 217–218

– particle–particle coupling 215

– particle shape 214–215

– particle size 214

– radiation damping 212, 216

– scattering quantum efficiency 216–217

perfect electric conductor (PEC) 107

PERL 5

photoluminescence (PL) 256

photoluminescent (PL) emission 25, 38

photonic light trap 10

photovoltaic conversion efficiency 22

planar antireflection coating 2–4

plasma enhanced chemical vapor deposition
(PECVD) 136–139

plasmon hybridization 215

plasmonic effects 8

plasmonic metal nanostructures

– advantages 226

– disadvantages 226

– fluorescence concentrators 223

– frequency downconverters 223

– front-side structures 219–221

- interband transitions (*see* interband transitions)
- intermediate reflectors, tandem cells 222–223
- near-field effects 212
- photoluminescence enhancement 224
- PPs (*see* particle-plasmon (PP) resonances)
- radiative quantum efficiency 223–224
- rear-side structures 221–222
- SPPs 209, 218–219
- plasmon resonance 245–246, 251
- polymethylmethacrylate (PMMA) 296, 297
- polyvinyl butyral (PVB) 339
- potassium hydroxide (KOH) 117, 118
- primary optical element (POE)
 - classical concentrators 160–161
 - cost differences 166
 - flat Fresnel-based architectures 166–168
 - freeform SMS concentrators 163
 - multifold Köhler concentrators 164–166
 - nonimaging secondary optics 161–162
 - spatial and spectral non-uniformity 168–169
- principle of detailed balance 21–22
- The Principle of Microscopic Reversibility 22
- pyramidal surface structures 4–5

q

- quadratic electric field 246
- quantized thermal energy 259
- quantum cutting mechanism 256
- quantum dots (QDs)
 - CdSe/ZnS-QDs types 301–303
 - *ex situ* method 301
 - *in situ* method 301
 - properties 300
 - reabsorption losses 301
- quantum efficiency 12
- quasi-Fermi level splitting 40, 42
- quasi steady state photo conductance (QSSPC) method 140–141

r

- radiation damping 212, 216
- radiative quantum efficiency 223–224
- randomly textured surfaces
 - cell efficiency 91–92
 - geometry/material properties 92
 - impinging photons 92
 - single-junction solar cell (*see* single-junction solar cell)
- rate equation model 240–241
- Rayleigh anomaly 7
- ray optical limit 4–5

- ray tracing approach 331
- receiver antennas 223
- reciprocity theorem
 - derivation 24–29
 - LED quantum efficiency 33–34
 - light trapping 35–37
 - SQ-theory 34–35
 - Tellegen's network theorem 30–31
 - transistors emitter and collector currents 29–30
 - Wong and Green theorem 31–33
 - Würfel's generalization, Kirchhoff's law 33
- referential solar cell 94–96
- relative emission 293–295
- ribs 163
- rugate filter 11–12, 192–194
- rugate stacks 11

s

- samarium (Sm)-doped borate glass
 - barium oxide 275
 - EQE 276
 - fluorescence emission 276–277
 - optical absorption 276–277
 - quantum efficiency 278–279
- scanning electron microscopy (SEM) 80–81
- scanning optical microscopy (SNOM) 99–100
- scattering quantum efficiency 216–217
- second law of thermodynamics 22
- series resistances, luminescence imaging 41, 42
- Shockley–Queisser (SQ) limit 11, 22–24
- Shockley–Queisser (SQ) theory 22–24, 34–35
- Shockley Read Hall (SRH) recombination 66
- short circuit current density 23
- shunt resistances, luminescence imaging 41
- silicone on glass (SOG)
 - advantages 169
 - disadvantages 169
 - distance-temperature-map 173–174
 - efficiency 173–175
 - FEM 172–174
 - lens temperature 170–172
 - Lorentz–Lorentz equation 172
- single-junction solar cell
 - absorption enhancement 104–106
 - angular cone 108–109
 - fabrication method 109–110
 - IFTA algorithm 103, 105, 109, 199
 - PEC 107
 - phase-only transmission function 107–108

- single-junction solar cell (*contd.*)
 - scattering cone 108–109
 - short circuit current density 108
 - unorthodox method 106–107
 - single optical surface (SILO) 164–165
 - solar photons 277
 - sol–gel glass 298
 - spatial distribution 98
 - spatial resolution 40
 - spectral concentration 250
 - spectrally resolved luminescence analysis 39–40
 - spines 163
 - stacked cells 13
 - sub-band-gap photons 231, 242
 - surface passivation
 - chemical passivation 136
 - disadvantages 144
 - efficiency 142–144
 - field effect passivation 136
 - heterojunction 121, 143
 - ICP-RIE processing 140–142
 - intermediate structure 140
 - laser treatment 142
 - parameter variation 140–141
 - PECVD 136–139
 - porous silicon 143
 - sample cleaning 139–140
 - surface damage 139–140
 - surface recombination 135
 - surface-plasmon polaritons (SPPs) 209, 218–219
 - surface plasmons 209–210
- t**
- tandem solar cells 222–223
 - anti-reflection effect 110–112
 - current matching 110
 - intermediate layer optimization 110–111
 - Tellegens's network theorem 30–31
 - thermal equilibrium 22, 188
 - thin-film solar cells 42, 184
 - advantages 209
 - disadvantages 209
 - plasmonic nanostructures (*see* plasmonic metal nanostructures)
 - thinner glass (TG) 333, 339
 - total internal reflection 8
 - transparent conductive front oxide layer (TCO)
 - EQE 198–199
 - Lambert–Beer's law 199–200
 - multi layer stack filter 197–198
 - optical path length 200
 - photovoltaic absorber 197
 - total reflectance 198–199
 - transmission and reflection 197–198
- transparent conductive oxide (TCO)
- EPF 95–96
 - growth condition 93
 - optical properties 102–104
 - sub-wavelength resolution 94
 - surface profile 94–95
 - wafer-based thick solar cell 93–94
- u**
- ultra-light trapping 10–13
 - up-conversion (UC)
 - dielectric photonic structures 246–248, 251
 - doping concentration 243–244, 251
 - Er^{3+} -doped ZBLAN glasses (*see* Er^{3+} -doped FZ glasses)
 - ETU 231
 - external quantum efficiency 231
 - $\beta\text{-NaYF}_4\text{:20\% Er}^{3+}$ 231, 237–240
 - phonon energy 242–243, 251
 - plasmon resonance 245–246, 251
 - rate equation model 240–241
 - spectral concentration 250
 - sub-band-gap photons 231, 242
 - trivalent lanthanide ions 232
 - up-conversion quantum yield (UCQY) 231–232
 - doping concentration 244
 - $\beta\text{-NaYF}_4\text{:20\% Er}^{3+}$ 238–239, 240–241
 - phonon energy 242–243
- v**
- VentanaTM 165
- w**
- Wong and Green theorem 31–33
- x**
- x-ray absorption near edge structure (XANES) 274
 - x-ray diffraction (XRD) 270–272
- y**
- Yablonovitch limit 5–6, 16, 35, 189
- z**
- ZBLAN glasses 259–260
 - absorption 262–264
 - Er^{3+} -doped FZ glasses (*see* Er^{3+} -doped FZ glasses)
 - internal conversion efficiency 265
 - quantum efficiency 266–267
 - short circuit current 264–265
 - sodium borate glass 260–261