

Index

Note: Page numbers in *italics* refer to figures; those in **bold** refer to tables.

a

ACCC (aluminum conductor composite core) 164
 ACCR (aluminum conductor composite reinforced) 164
 ACSS (annealed aluminum conductor steel supported) 164
 active power reduction 230–232, 231
 activity plan 354, 354
 agreed apparent power 217
 agricultural enterprise 18, 21
 aluminum conductor composite core (ACCC) 164
 aluminum conductor composite reinforced (ACCR) 164
 annealed aluminum conductor steel supported (ACSS) 164
 annual increase factor 12
 annuity factor 42, 160
 annuity method 41–42
 ANSI code numbers 269, **270**
 arrester, protection level 276
 assessment of losses 42–48
 – added losses 46
 – energy costs 47
 – energy loss factor 45
 – loss hours 46
 – production costs 47
 asymmetry 247
 atmospheric correction factor 285, **286**, 286
 autoreclosure 262
 autotransformers 87, 88
 available reactive power 218

b

back-flashover 277, 282, 290
 bandwidth 223

BDEW (Bundesverband der Energie- und Wasserwirtschaft) 217, 225
 biomass 215
 breakers 78–79, 338
 Buchholz protection **266**, 267–268
 busbar sectionalizer 75, 200, 200–202, 203, 204
 business enterprises 18

c

cable 115–139, 136, **136**, **351–352**
 – alphanumeric abbreviations **116**, **117**
 – capacitances 119
 – charging currents 119, 119
 – electrical parameters 117, **118**, 118–120
 – impregnated paper insulation **116**
 – inductive reactances 120
 – maximal permissible current 121
 cable abbreviation codes 115
 cable loading **131**, 134
 – cross-bonding **131**, 134
 – example 130, 131
 – flat formation **131**, 134
 – thermally unfavorable areas 133–134
 – triangle formation **131**, 134
 cable losses 120–121, 122–124
 cable routes 131–135
 cable screens 138–139, **139**
 – constants of materials 139, **139**
 – short-circuit temperatures 139
 cable trenches 131, 131, 131–132
 – minimum distance 132
 – rights-of-way 132
 – water pipe 131, 132, 133
 characteristic harmonic 246
 circuit-breakers 78, 79, **349**

- commutation dip 247
- conductor sag 154–155, 160
- conductor shape 115
- conformity certificate 240
- connected apparent power 217
- connecting circuit 217
- continuous power frequency voltage 271, 274–275
- contracting 325–355, 353–355, 354
 - project definition 325–326, 326
- coordination withstand voltage 273, 274
 - deterministic coordination factor 285
 - deterministic procedure 284–286, 285, 286, 286
 - external insulation 285–286
 - internal insulation 285
 - statistical procedure 284
- corona damping 278, 280
- corona discharges 152
- cost 41–42
- cost estimate 160–161, 161
- coupling of busbars 200, 200–201
- cross-linked PE insulation (XLPE) 117, 118, 179
- currents through earth 183–184
 - capacitive earth-fault current 184, 184
 - ground fault residual current 184, 184
 - single-phase short-circuit current 183, 184, 184
- current switching factor 237
- current transformer 79–82, 81, 82, 253, 254, 350
 - accuracy 79
 - categories 81, 82
 - IEC 60044 80
 - overcurrent factor 80, 81
 - remanence flux 81

d

- daily load curves 17
- DC-breaker 179
- degree of electrification 16, 16
- design criteria 326, 337
- development banks 329
- differential protection 253, 256, 263, 265, 266
 - intermediate transformers 265
- DIN EN 50160 236
- DIN EN 50438 225
- DIN EN 61400-21 240
- disconnecting switches 79, 349
- distance protection 252, 258–263, 260, 262, 266, 266–267
 - grading time 260, 260, 261

- single-phase faults 261
- threshold value 261, 261
- dynamization factor 17, 19

e

- earth conductivity 283, 283
- earth-fault compensation 256, 256
- earth-fault factor 274, 299, 301, 302, 303
- earthing electrode 180
- earthing – HV side and LV side 319–323
- earthing impedance 208–209, 210
- earthing of neutrals 9, 319–323
- earthing resistance 283
- earthing with current limitation 300–302
- earth resistance 283, 283, 290
- EEG (renewable energy act) 228
- EHV (extra-high-voltage) systems 35, 36–37
- electrical length 165
- electromagnetic fields 9
- electromagnetic transients program (EMTP/ATP) 289, 291, 292
- emission limit 240–241, 243
- EMTP/ATP (electromagnetic transients program) 289, 291, 292
- EN 50052 78–79
- EN 50064 78–79
- EN 50341-1 153
- EN 50423-1 153
- Energiewende 23
- ENTSO (European Network of Transmission System Operators for Electricity) 216, 228
- equivalent voltage source 184
- evaluation
 - bid 353
 - financial evaluation 353
 - technical evaluation 353
 - tender 348–353
- external insulation 272
- extra-high-voltage (EHV) systems 35, 36–37

f

- FACTS *see* flexible AC transmission system (FACTS)
- fast-front overvoltages 271, 272, 277–284, 285
 - calculation 285
 - detailed calculation 278–281, 279
 - direct strokes 281–284
 - failure rate 281
 - impact radius 281
 - representative overvoltage 282
 - simplified approach 277–278, 278
 - steepness 282

fault-ride-through (FRT) 232–235, 233, 234
 federation international des ingenieurs-
 conseils (FIDIC) 329, 334–335
 Ferranti effect 276
 ferro-resonances 84
 FIDIC (Federation International des
 Ingenieurs-Conseils) 329, 334–335
 flexible AC transmission system
 (FACTS) 9, 165–180, 177, 177–178
 flicker 195, 215, 216, 238, 239–242
 flicker-coefficient 241, 242
 flicker emission 241
 flicker-related current switching factor 238,
 239
 frequency control 230–232
 FRT (fault-ride-through) 232–235, 233,
 234
 fuel-cell 215
 full-load hours 45, 46
 fuses 79, 202

g

GAP-conductor 163
 Gap Thermal Resistant Aluminum Alloy
 Steel Reinforced (GTACSR) 163
 gas-insulated switchgear (GIS) 79, 289,
 290, 337–338, 344–345
 gas losses 339
 GDP (gross domestic product) 13–14
 GEC (gross electrical consumption) 13
 generation
 – connection 213–247
 – flicker 239–242
 – harmonics 242–246
 – interharmonics 242–246
 – protection 224–225
 – reactive power compensation 225–230
 – short-circuit currents 224–225
 – system studies 216–224
 – voltage increase 236–237
 generation plant 217
 generation unit 217
 GIS (gas-insulated switchgear) 79, 289,
 290, 337–338, 344–345
 GNP (gross national product) 13–14
 grading time 226, 256, 257, 260–261, 267
 “green-energy” 51, 215, 216
 gridstations and substations 73–103
 – double busbar 76, 76–77, 77
 – reserve busbar 77–78
 – single busbar 73–74, 74, 268
 – single busbar with sectionalizer 75, 75,
 201–202, 204
 – special H-arrangement 75–75, 76

ground-fault protection 263, 266, 266–267
 – “cos ϕ ” measurement 264
 – fifth harmonic 264
 – isolated neutral 264
 – resonance earthing 264
 – “sin ϕ ” measurement 264
 – transient 264
 GTACSR (Gap Thermal Resistant
 Aluminum Alloy Steel Reinforced) 163

h

harmonic current 246, 317
 harmonics 242–246
 high-temperature conductor 162–164
 high-voltage DC transmission system
 (HVDC) 178–180
 high-voltage (HV) systems 36–37, 51, 55–58,
 67, 72
 Holmgreen arrangement 253, 254
 hot-spot temperature 94, 97, 98
 – actual temperature profile 97
 – simulated temperature profile 97
 – weighted ambient temperature 98–99
 household load 16, 16, 23, 24, 25, 26
 HVDC (high-voltage DC transmission
 system) 178–180
 HVDC-cable 180
 HV (high-voltage) transmission systems
 36–37, 51, 66–68, 67, 72

i

IEC 60038 32, 32, 33, 34, 51, 51, 196–197,
 197, 271, 274
 IEC 60044 302
 IEC 60066 339
 IEC 60071 273
 IEC 60071-1 272, 273, 274
 IEC 60071-2 275, 277, 284
 IEC 60076-2 88
 IEC 60076-7 95, 96, 97–98, 98, 99
 IEC 60076-12 106–107
 IEC 60085 94, 95
 IEC 60287 130
 IEC 60354 94, 99, 102
 IEC 60617 269, 270
 IEC 60617-7 269, 270
 IEC 60853-2 130
 IEC 60865 112, 183
 IEC 60865-1 110–111, 156
 IEC 60890 78–79
 IEC 60909 183, 184, 186, 188, 191
 IEC 60909-0 111, 113, 220
 IEC 60947 78–79
 IEC 61000-3-2 242

- IEC 61000-3-3 240
- IEC 61000-3-7 240, 241
- IEC 61000-3-11 240
- IEC 61000-3-12 242
- IEC 61400-21 240
- IEC 61660 183
- IEC-standards 357–361
- IEC/TR 62095 130
- IEEE C37.2 269, 270
- IGBT (inverse gate bipolar transistor) 177, 179
- impedance voltage 207, 207
- individual load profiles 17, 18
- initial short-circuit current 187, 187, 188
- installed active power 217
- instantaneous active power 217
- instantaneous reactive power 218
- insulation coordination 8, 271, 273–274, 289
 - example 289–294
 - range I 273
 - range II 273
- interest factor 42
- interest rate 42
- interference 9
- interharmonic 242–246, 317
- internal insulation 272
- inverse gate bipolar transistor (IGBT) 177, 179
- I_p limiter 202
- ISO 9000 331
- isoceraunic level 281
- isolated neutral 302–306, 304, 305, 306
 - earth-fault current 301
 - overvoltage factor 307
 - recovery voltage 305
 - reignition of fault 305
 - self-extinguishing 304
 - transient frequency 306
 - voltage displacement 305
- I**
- large generation plants 214, 214
- length of insulation 152–154, 153
- lightning currents, parameters 278–281, 279, 289
- lightning impulse withstand voltage 153, 280, 287, 287, 288, 294
- lightning overvoltage 277, 289
- lightning protection angle 277
- limitation of short-circuit currents 195–211, 205, 206
 - examples 195
- limit distance 278–279, 280
- line-carrier system 247
- line-commutated converter 179, 246
- line corridor, width 158–159
- load
 - constant current 182
 - constant impedance 182
 - constant power 182
 - load pattern 183
 - measurement 182
- load assumptions 16, 16
- load-break switches 78
- load control 23
- load densities 15, 15
- load factor 45, 130
- load flow 182
- load-flow analysis 7, 181–183
 - FACTS 181
 - PQ busbars 182
 - PV busbar 182
- load forecast 11–20
 - degrees of electrification 14–16, 16
 - economic characteristic data 13–14
 - estimated values 14, 15
 - load increase factors 12–13, 13
 - specific loads 14–16
 - standardized load curves 17–20, 18, 19, 20
- loading of cables 129, 129–130
 - characteristic diameter 129, 130
 - cyclic rating 130
 - emergency rating 130
 - standard conditions 129
 - thermal parameters 128
- load profile 17, 18, 21
 - household 18, 18, 23, 24, 25, 26
 - other consumer 18, 22
- load-shedding 275, 276
- load shifting 23
- long-time flicker 239, 240, 241
- losses 42–43
 - energy losses 43–44
 - no-load losses 43
- low-impedance earthing 296–300, 298, 299, 321, 321
- low-voltage (LV) systems 32, 35–36, 51, 52–53, 69–71, 72
- LV (low-voltage) systems 32, 35–36, 51, 52–53, 69–71, 72
- m**
- maximal conductor sag 153
- maximum active power 217
- maximum load portion 43, 44

- degree of utilization 44
- power losses 44–48, 45, 46
- meshed system 52, 66–71, 198, 258
- HV and MV systems 66–71, 67
- LV level 69–71, 70, 71
- multiple-line supply 69–71, 71
- MV systems 68, 68–69
- single-line supply 69, 70
- station-by-station 69, 70, 71
- multiple busbar operation 201, 203
- medium-voltage (MV) systems 33, 36, 51, 54–66, 68, 72
- MV (medium-voltage) systems 33, 36, 51, 54–66, 68, 72

n

- natural power 165
- negative-sequence component 186
- network protection 9–10
- neutral earthing 295–323, 297
- noncharacteristic harmonic 246
- non-self-restoring insulation 272
- norms 357–364

o

- OHL (overhead line) 141–164
- AC resistance 144, 145
- electric field strength 149–152
- mechanical design 152
- minimum distances 152–154, 153
- specific creepage distance 152
- OHL loading 141–142, 146–149
- convection 146–149, 147
- correction factor 146
- emission coefficients 147, 147
- examples 149, 150, 151
- forced convection 148
- Grashof factor 148
- heat balance 142
- modulus of elasticity 141
- Nusselt factor 148
- Prandtl factor 148
- radiation 146–149
- Reynolds factor 148
- tensile strength 141–142, 142, 143
- operable installed active power 217
- overcurrent protection 256–258, 266
- overhead line (OHL) *see* OHL
- overvoltage return rate 277
- overvoltages 271–272, 272

p

- parallel compensation 168, 169, 169–170, 170

- parallel resonance 219, 221–222
- typical values 222–224
- PCC (point of common coupling) 213, 217
- peak short-circuit current 187, 189, 189–191
- accuracy 190
- equivalent frequency 190
- meshed power system 189
- peak factor 187
- safety factor 190
- permissible current of cables 120
- permissible harmonic current 242–243, 243, 244
- permissible harmonic voltage 244
- permissible interharmonic voltage 242–243, 243
- permissible thermal loading 8, 141
- Petersen coil 307–319, 322
- limits 314, 315
- plunger-coil 314
- tuning 314–315, 316, 317
- phase-shifting 168, 172–173, 173, 174
- photovoltaic installations 215
- planning, basics 5, 30–34
- economy 34
- frequency control 32–33
- generation 31–32
- IEC 60038 32, 32, 33, 34
- loading of equipment 31
- preloading conditions 31
- realization times 32
- short-circuit currents 31
- voltage level 32
- planning criteria 34–39
- extra-high-voltage 36–37
- faults 38
- high-voltage 36–37
- IEC 60038 32, 32, 33, 34
- independent outages 37
- loading of equipment 37
- load-shedding 38
- loss of generation 38
- loss of load 38
- low-voltage 35–36
- medium-voltage 36
- multiple outages 37
- single outage 36–37
- stability 38–39
- voltage band 34–35
- voltage tolerance 35
- planning principles 27–30
- disturbance statistics 24
- duration of outages 29
- energy not supplied 25

- frequency of outages 28
 - loss of power 29–30, 30
 - point of common coupling (PCC) 213, 217
 - pole-swing 234, 235
 - positive-sequence component 118, 186, 295, 298
 - power factor 225, 226, 235, 236
 - power quality 213
 - power system 49–51, 50
 - distribution 50–51
 - sub-transmission 49–50
 - transmission grid 49
 - power system impedance 218
 - power system planning 4–5, 6, 7
 - basic planning 5
 - instruments 7–10
 - needs 4
 - objective 5
 - project planning 7
 - systematic approach 4
 - system development planning 7
 - power systems topology 52, 71
 - meshed systems 52, 66–71, 198, 258
 - operating considerations 71–72, 72
 - radial systems 52–54, 53
 - ring-main systems 52, 54–66
 - present value 41–42, 48, 109
 - primary reserve 38, 39
 - project definition 325–326
 - project funding 329
 - project implementation schedule 326
 - project schedule 355
 - protection 249–269
 - criteria 250, 251
 - faults and disturbances 249–250, 251
 - general structure 252–254
 - protection of busbars 268–269
 - current criteria 268–269
 - differential protection 268
 - high-impedance protection 269
 - impedance criteria 269
 - switching image 269
 - UMZ 268
 - protection of lines 256, 256–265
 - protection of transformers 265–268
 - ground-fault protection 266–267
 - protection measures 266
 - protective device 224–225
 - proximity effect 122, 144
- r**
- radial power system 52–54, 53, 266
 - rated voltage 286–287, 287, 288, 289
 - IEC 60071-1 287–288
 - Rayleigh distribution 241
 - reactive power 215, 218, 225, 236
 - reactive power supply 225–230
 - regulations 2
 - reliability 1, 27
 - Renewable Energy Act (EEG) 228
 - representative overvoltage 273
 - required withstand voltage 274, 285
 - residual current 316–318, 318–319, 319
 - resonance earthing 297, 307–319, 308, 321, 321
 - asymmetry 311
 - damping 307, 313
 - detuning factor 309, 312, 313
 - displacement voltage 311, 312, 313, 314
 - earth-fault current 308, 310
 - example 311, 319, 321
 - harmonics 310
 - resonance frequency 309
 - self-extinguishing 310, 310
 - resonance factor 245
 - resonance frequency 318
 - resonance in power system 222, 222–224, 223
 - restrictions, legal, political, social 2–3
 - restructuring of power system 201, 202
 - right-of-way 157–160, 158
 - example 159, 159
 - ring-main systems 52, 54–66
 - application 54–58, 60–63, 65–66
 - base station 63, 63–64
 - cross-link 62, 62–63
 - double-T connection 65–66, 66
 - remote station 56, 56–57, 60, 60–61
 - reserve line 57–60, 58, 59
 - special-spare cable system 64, 64–65
 - topology 54–56, 55
 - triple 61, 61–62
 - ripple-control 247
- s**
- saturation level 12
 - scope of activities 328
 - construction phase 328
 - power system studies 327, 328
 - tender evaluation 328
 - scope of supply 344–346
 - reactors 345
 - switchgear 344–345
 - telecommunication system 346
 - transformers 345
 - scope of work 344
 - security 2, 250

- selection of recommended voltage 196–197, 197
 - selectivity of protection 249
 - self-commutated converter 179, 246
 - self-protection of substation 279, 280
 - self-restoring insulation 272, 304
 - sensitivity 249
 - serial compensation 168, 171, 171–172, 172
 - sheath losses 123
 - short-circuit 155–156, 224–225
 - short-circuit current 81, 183–193, 184, 188, 195
 - calculations 7–8, 183–193, 187
 - contribution of motors 186, 191–193, 194
 - density 112
 - far-from-generator 184, 185
 - impedance correction 188
 - interference 183
 - limitation 195–211, 205, 206
 - near-to-generator 184
 - protection 183, 224–225
 - stability 183
 - voltage factor 186, 186
 - short-circuit limiting reactor 207–208, 209
 - short-circuit power 214, 218, 238
 - short-circuit strength 110, 112–113
 - short-circuit withstand 136, 155–156, 193–195
 - electromagnetic effect 193, 195
 - maximal permissible temperature 155, 155
 - thermal effects 193
 - short-time current 81, 112, 113
 - short-time current density 136, 137, 156, 157
 - short-time flicker 239
 - skin effect 123, 144
 - slack 182
 - slow-front overvoltage 271, 272, 275–276
 - autoreclosing 276
 - case-related analysis 276
 - load-shedding 276
 - phase-related analysis 276
 - statistical dispersion 275
 - small hydro plants 214
 - smart domestic appliances 23–24, 24, 25, 26
 - smart energy system 23–24
 - smart grid 23–24
 - soil characteristic 124–127
 - humidity content 124, 126
 - temperature 124, 125, 126
 - thermal conductivity 126, 126
 - thermally stabilized 126
 - solar radiation 144–146, 146, 147
 - degree of latitude 145–146
 - irradiation angle 144
 - special-spare cable system 64, 64–65
 - specification 326, 329
 - speed protection 250
 - spirality-effect 144
 - SSSC (static synchronous series compensator) 178
 - stability 174, 175, 195
 - FACTS 174–177, 175, 176
 - improvement 174–177, 175, 176
 - stability analyses 8
 - STALUM (steel-aluminum coated) 162
 - standard insulation level 43, 273, 287
 - range I 286–287, 287
 - range II 287, 288
 - standard test voltages 286
 - STATCOM (static synchronous compensator) 178
 - Static synchronous compensator (STATCOM) 178
 - static synchronous series compensator (SSSC) 178
 - static-var compensator (SVC) 177
 - statistic 250
 - statistical withstand voltage 273
 - steady-state conditions 226, 230
 - steady-state short-circuit current 191, 192
 - steel-aluminum coated (STALUM) 162
 - Stefan–Boltzmann law 146, 147
 - subtransient reactance 209, 210
 - superposition of harmonics 245, 246
 - surge impedance 165
 - SVC (static-var compensator) 177
 - switches 78–79
 - switching impulse withstand voltage 153, 287, 288, 289
 - switching voltage change factor 238, 239
 - symmetrical short-circuit breaking current 190–191
 - system separation 197–198, 198
- t**
- TACSR (thermal alloy conductor steel reinforced) 162–163
 - T-connections 53
 - application 54
 - TCR (thyristor controlled reactor) 177–178
 - TCSC (thyristor controlled series capacitor) 177

- technical data sheets 346–348
 - sample 347–352
- technical specifications 336–344
 - AC-supply 343
 - breakers 338
 - cables 342
 - DC-supply 343
 - general parameters 337
 - medium-voltage switchgear 339–340
 - metal-clad switchgear 337
 - overhead lines 340
 - protection 340
 - reactors 343–345
 - scope of tender 337
 - switches 338
 - transformers 342–343
- temperature 121, 155
 - insulation materials 118
 - permissible short-circuit current 137, 138
 - rated short-time current density 136, 139
 - short-circuit 136, 336–337
 - thermal effects 193
- temporary overvoltage 271, 272, 274–275, 291
- tender documents 329–331, 344
 - approval 330
 - awarding of contracts 330
 - environmental aspects 333
 - general technical requirements 336–337
 - planning and design 331–333
 - prequalification 330–331
 - short listing 331
- tendering 325–355
 - project definition 325–326, 326
- tender structure 333–344
 - conditions of contract 334–335
 - lots 333–334
 - sample price sheet 335, 335
 - tender set-up 334
- tensile stress 153
- terms of reference (TOR) 327
- test conversion factor 288
- thermal alloy conductor steel reinforced (TACSR) 162–163
- three-winding transformers 87, 88
- thyristor 177, 179
- thyristor controlled reactor (TCR) 177–178
- thyristor controlled series capacitor (TCSC) 177
- thyristor switched capacitor (TSC) 177
- thyristor switched reactor (TSR) 177
- thyristor switched serial capacitor (TSSC) 177
- TOR (terms of reference) 327
- tower arrangement 157–160, 291
- transducers 252, 252–254, 253, 254, 255
- transferable power 173, 327
- transformer 85–113, 265
 - climatic classes 88–89
 - cooling 89, 97, 102, 102
 - dry-type 87–89, 89, 106–108
 - economical operation 109–110
 - efficiency curve 109–110, 110
 - environmental class 88–89
 - insulation 89
 - Kapp's triangle 90–91
 - Montsinger's law 94
 - oil-immersed 87–89, 89, 99–106
 - permissible loading of neutral 92
 - phase-shift 92
 - rated apparent power 85–86, 86
 - short-circuit strength 110–113, 111, 112
 - standard operating conditions 88
 - tap-changers 91
 - temperature correction 98, 98
 - thermal classes of insulation 94, 95, 95
 - thermal permissible loading 92
 - vector group 92, 93, 94
 - voltage drop 90–91
- transformer loading 99–106
 - continuous loading 100, 102, 102
 - current 101
 - distribution transformers 98, 98, 99, 101
 - dry-type transformers 106–108, 107, 108
 - example 103, 105, 108, 108
 - hot-spot temperature 94, 97, 98, 101–105, 105
 - large power transformers 100, 101
 - loading conditions 100
 - long-time emergency operation 100, 101, 104–106
 - maximal permissible temperature rise 107
 - medium-sized transformers 99–100, 101
 - normal cyclic load 100, 101, 102–104, 103, 104
 - oil-immersed transformers 96–100, 99–106, 107, 108
 - short-time emergency operation 100, 101, 104–106
 - temperature 96, 96, 101, 107
 - thermal class 107, 107
- transient overvoltage 271
- transient stability 8
- Transmission Code 216, 225, 228, 232, 234
- trip-release 252, 253
- TSC (thyristor switched capacitor) 177

TSR (thyristor switched reactor) 177
 TSSC (thyristor switched serial capacitor) 177
 type 1 generation 232–234
 type 2 generation 232, 234–235
 types of cooling 99, 102, **102**
 type testing 285

u

UCTE (Union for the Co-ordination of Transmission of Electricity) 38–39, 39, 49
 UMZ (unabhängiger Maximalstrom-Zeitschutz) protection 256–258, 257, 257–258
 unified power flow controller (UPFC) 178

v

Verband der Netzbetreiber (VDN) 216
 VDE 0127-21 241, **242**
 VDE 0276-1000 128–130, **129**
 VDE-AR-N 4105 217, 225
 VDE-AR-N 4120 217, 226, 227, 228, 233, 235
 VDE-AR-N 4130 217, 229
 VDE/FNN 216
 VDN (Verband der Netzbetreiber) 216
 VDN technical rules 216–217, 219, **220**
 very-fast-front overvoltage 272

voltage change 237–239
 voltage change factor 238–239
 voltage factor 185, **186**
 voltage increase 224–225, 236, 236–237, 237
 voltage level 196, 196, 214, 214
 voltage source converter 179
 voltage transformer 82–84, 252, 253
 – accuracy 83, 83
 – rate voltage factor 83
 voltage unbalance 247

w

width of the line corridor 158–159
 wind energy 241
 wind energy plants 215, **216**, 241

x

XLPE (cross-linked PE insulation) 117, 118, 179

z

ZACIR (zirconium alloy conductor invar steel reinforced) 163
 zero-sequence component 186, 298, 321, **321**
 zero-sequence system 218
 zirconium alloy conductor invar steel reinforced (ZACIR) 163

