

Index

a

- Anisotropic thermoelectric elements 147, 148
- Archimedes' principle. 191

b

- Benedicks effect 12
- Bridgman effect 13

c

- Cascaded thermoelectric generators 230
- CHI *See* Constant heat input (CHI) model
- Classical Ioffe method, thermal conductivity measurement
 - CTEM 193
 - error estimation 194
 - heat equation 194
 - inverse Laplace transformation 202
 - inversion theorem, LT 203
 - Laplace transformation 197
 - original equation LT 198
 - Seebeck coefficient 193
 - temperature profile inversion 205
 - temperatures, s -domain 199
 - theoretical basis 194
- Compatibility
 - and segmented thermogenerators
 - – Carnot efficiency 230
 - – efficiency 230
 - – interface temperature 230
 - – negative reduced efficiency 231
 - – p -type materials 232
 - – TAGS or skutterudite 231
 - cascaded generator 230
 - criterion $u = s$ and calculus of variations 243
 - optimal material grading 241
 - power-related
 - – CPM 241
 - – electrical power output 239
 - – maximum power output 240, 241
 - – power output 238, 239
 - – self-compatible elements 239
 - reduced efficiencies and self-compatibility
 - – efficiency 233
 - – local efficiency dependence, current 235
 - – performance integrals, efficiency and COP 233
 - relative current density
 - – advantage 229
 - – definition 227
 - – FGM 229
 - – temperature dependence, chemical potential 228
 - self-compatibility and optimum material grading
 - – constant and variable Lagrange multiplier 248
 - – constraint variational problems 248
 - – Gerstenmaier/Wachutka approach 249
 - – inhomogeneous generators and coolers 248
 - – optimal TE potential 247
 - – optimal temperature and optimal Seebeck profile relation 247, 248
 - – optimization strategies 246–248
 - – reduced “efficiencies” 247
 - – Snyder's criterion 246
 - – TEG efficiency improvement 247
 - self-compatible TEG and TEC elements
 - – optimal figure of merit 253
 - – performance 251
 - – Seebeck coefficients 255

Compatibility (*contd.*)

- temperature profile, $u = s$ material 256
- thermodynamics 249
- Thomson cooler *see* Thomson cooler
- *vs.* device optimization 276
- Constant heat input (CHI) model 100
- Continuum theory
 - anisotropic thermoelectric elements 147
 - contacts and contact resistances
 - electrical contact resistance 130
 - thermoelectric element, contacting bridge 126
 - convection losses and benefits 144
 - CPM devices
 - inverse performance equations 91
 - single-element device 82
 - TEC *see* Thermoelectric cooler (TEC)
 - TEG *see* Thermoelectric generator (TEG)
 - TEH *see* Thermoelectric heater (TEH)
 - thermoelectric element, performance parameters 84
 - Domenicali's heat balance equation
 - heat balance and source terms 76
 - spatial and temperature averaging 79
 - tensorial character, material properties 75
 - radiation losses and benefits 146
 - temperature dependence *see* Temperature dependent materials
 - thermogenerator element
 - CHI model 100
 - load resistance 96
 - power and efficiency 93
 - transferred heat balance 80

d

- Dirichlet boundary conditions 160, 163
- Dissipative coupling
 - finite-time thermodynamics optimization 133
 - power and efficiency maximization 137
 - temperature difference calculation 136
 - thermal flux and electrical current 135
 - thermoelectric generator model 133
- Domenicali's heat balance equation
 - heat balance and source terms 76
 - spatial and temperature averaging 79
 - tensorial character, material properties 75

e

- eddy currents 157
- Ettingshausen coefficient 21
- Euler–Lagrange differential equation 243, 251
- Explicit Euler method 286–288

f

- FDM *See* Finite difference methods (FDM)
- FEM *See* Finite element method (FEM)
- Finite difference methods (FDM)
 - description 284
 - difference quotient approximation 284
 - 1D temperature distribution 286
 - explicit Euler method 286, 287
 - PDEs 286
 - Taylor series expansion, function $f = f(x)$ 284
- Finite element method (FEM)
 - algorithm scheme 291
 - description 290
 - steps 291
- Finite volume method (FVM)
 - control volume, 2D 288
 - description 288
 - Fourier's heat equation 289
 - PDEs 290
 - procedure 289
- Forces and fluxes, thermoelectric systems
 - and kinetic coefficients 38
 - coefficients
 - coupled processes 41
 - decoupled processes 40
 - dimensionless figure of merit 43
 - energy flux and heat flux 39
 - entropy per carrier 41
 - kinetic coefficients and transport parameters 42
 - thermoelectric effects 37
- Fourier heat conduction 195
- Fourier heat divergence 259, 271
- Fourier's law 50, 171
- Fourier–Mellin integral 204
- Functionally graded materials (FGM) 229, 261
- FVM *See* Finite volume method (FVM)

g

- Galvanomagnetic and thermomagnetic effects
 - devices 22
 - Ettingshausen coefficient 21
 - Hall coefficient 21
 - Nernst coefficient 21

- Righi–Leduc coefficient 22
- Gerstenmaier/Wachutka approach 249
- Green's function (GF) approach
 - continuity equations 208
 - linear Onsager theory 207
 - NEGF 207
 - one-dimensional, steady state 209
 - perturbative approach (1D) 210
 - spin Seebeck effect 207
 - steady state 208
 - time dependent *see* Time dependent Green's function approach

h

- Hall coefficient 21
- Heat and entropy
 - entropy production density 45
 - heat flux and Peltier–Thomson coefficient 46
 - local energy balance 47
 - Onsager expressions 44
 - Peltier–Thomson term 46
 - volumetric heat production 45

i

- Ideal Fermi gas
 - characteristics 28
 - electron gas, thermoelectric cell 29
 - entropy, carrier 30
 - equation of state, ideal electron gas 32
 - mass renormalization 28
 - temperature dependence, chemical potential 34

l

- Laplace transformation (LT) 197
- Laser flash analysis (LFA)
 - calculation routine 191
 - definition 190
 - Fourier series expansion 191
 - mass density, sample 191
 - measurement principle 191
 - radiation heat losses 192
 - thermal diffusivity determination 192
- Linear non-equilibrium thermodynamics
 - forces and fluxes 35
 - linear response and reciprocal relations 36
- Linear Onsager theory 207
- Linear transient approach
 - relaxation time 212
 - response approximation 214
 - transient field equations 213

m

- Magnus' law 10, 13
- Mathematica model, compatibility approach 320
- Millman theorem 158, 169, 170, 172

n

- Nernst coefficient 21
- Networking
 - discretization 171
 - implementation 173
 - Millman theorem 172
 - numerical illustration 174
 - presentation 169
 - useful expressions 171
- Non-equilibrium thermodynamics 56
- Nonlinear material parameters
 - Mathematica model, compatibility approach 320
 - temperature dependent properties
 - coefficient of performance (COP) 318
 - decoupled dependencies 315
 - 1D steady-state model 315
 - Mathematica code 318
 - maximum cooling calculation 316
 - Nabla calculus 317
 - nabla calculus 316
 - relative current 317
 - spatial material profiles 319
 - temperature dependent curves 316
 - temperature profile 319
 - Thomson coefficient 315
- Numerical simulation
 - FDM *see* Finite difference methods (FDM)
 - FEM *see* Finite element method (FEM)
 - FVM *see* Finite volume method (FVM)
 - nonlinear materials *see* Nonlinear material parameters
 - TEG performance calculation
 - averages and performance values 297
 - averages, material properties 294
 - cross-sectional areas adjustment 310
 - FEM 311
 - finite difference scheme, TE element 300
 - optimal performance, averaged material properties 299
 - p-n thermocouple 309
 - performance parameters, current density 326
 - power factor and figure of merit 325
 - processing, material properties 295

o

- Ohm's law 171
- Onsager approach 158, 169
- Onsager force-flux derivation 38
- Onsager theory 13
- Onsager–de Groot–Callen theory 26, 141

p

- Pauli exclusion principle 28, 29
- Peltier cooler 318
- Peltier coolers
 - applications 259
 - characteristics 259
 - CPM 273
 - heat production 265
 - multi-stage 260
 - self-compatibility effect 261
- Peltier effect 8
- Peltier–Thomson coefficient and term 46
- Performance calculation, TEG
 - average, material properties 294
 - averages and performance values 297
 - cross-sectional areas adjustment 310
 - FEM simulation 311
 - finite difference scheme, TE element 300
 - material properties 293
 - optimal performance, averaged material properties 299
 - p-n thermocouple calculation 309
 - parameters, current density 326
 - power factor and figure of merit 325
 - processing, material properties 295
 - thermocouple 292
- Phonon-glass electron-crystal (PGEC) 16
- Prigogine's principle 59

q

- Quasi-stationary processes
 - bismuth telluride 182
 - lunation 179
 - response time 182
 - temperature difference and absolute value, lunation 180
 - temperature, moon's surface 180
 - timescales, transient electrical systems 181
 - transient phenomena, electrical systems 181

r

- Righi–Leduc coefficient 22

s

- Seebeck coefficient 157, 159, 161, 171, 174, 246
- Seebeck effect
 - thermomagnetism 4
 - electromagnetism 6
 - electrometer (Schweigger) 4
 - electromotive forces 3
 - galvanothermal effect (GTE) 4
 - holography invention 5
 - mechanical stress, amorphous transparent material 5
 - power generation 11
 - thermocouple 3
 - thermomagnetism 3, 5, 6
 - unequal heating, metals 6
- Segmented devices
 - double-segmented element 160
 - electrical conductivity 161
 - graded elements, numerical parameter studies 166
 - gradient configurations, usefulness 158
 - material inhomogeneity, effects 157
 - material properties, spatial variation 157
 - multi-segmented elements, algorithm 164
 - Onsager approach 158
 - optimal grading strategies 159
 - Seebeck coefficient 159
 - self-compatibility approach 158
 - thermal conductivity 163
 - Thomson and distributed Peltier heat 159
- Self-compatible elements
 - optimal figure of merit 253
 - Seebeck coefficients 255
 - TEG and TEC elements performance 251
 - temperature profile, $u = s$ material 256
- Shaped thermoelectric elements
 - element shape factor 142
 - conical and cylindrical elements 141
 - disk-shaped thermocouples 142
 - entropy production 141
 - hyperbolic heat conduction model 143
 - non-cylindrical thermoelements 141
 - non-equilibrium thermodynamics 142
 - TEC 142
- Snyder's criterion 245, 246, 271
- Solar thermoelectric generator (STEG) 147
- 6-Stage cooler of Marlow 261
- Supercooling
 - metrics, transient response 182, 183

- parameters 187
- steady state operation, thermoelectric cooler
 - – absorbed thermal power, mixed boundary conditions 185
 - – bismuth telluride sample material properties 185
 - – boundary conditions (BC) 183
 - – CPM 184
 - – Dirichlet BC 184
 - – maximum absorbing heat flux 186
 - – optimum current, maximum cooling case 185
 - – TEC 183
 - – thermal power, sink side 186

t

- Temperature dependent materials
 - algebraic and general
 - – algebraic and general 119
 - Constant Thomson coefficient
 - – averaged coefficients and geometric optimization 114
 - – linear temperature dependence of resistivity 121
 - – TEG performance 116
 - inverse temperature dependence
 - – maximum power output 108
 - – performance equations 106
 - – thermal conductivity 103
 - linear temperature dependence of resistivity 123
- Thermodynamic engine
 - efficiency goal 27
 - endoreversible engine 27
 - energy budget 27
- Thermoelectric coefficients
 - coupled processes 41
 - decoupled processes 40
- Thermoelectric cooler (TEC) 89–91
- Thermoelectric engine
 - efficiency 49
 - electrochemical potential difference 50
 - entropy production, non-adiabatic branches 50
 - Fourier's law 50
 - heating and cooling mode 48
 - traditional steam engines 48
- Thermoelectric generator
 - construction 15
 - for space 16, 17
- Thermoelectric generator (TEG) 86, 88, 89
 - transient behavior 189
- Thermoelectric heater (TEH) 91
- Thermoelectric potential
 - non-equilibrium thermodynamics 56
 - relative current and dissipation ratio 51
 - TEG, TEC and TEH 53
- Thermoelectricity
 - applications
 - – 1920–1970 15
 - – 1970–2000 16
 - – 2000- 17
 - Benedicks effect 12
 - Bridgman effect 13
 - Magnus' law 10
 - Peltier effect 8
 - Seebeck effect 2
 - semiconductors as thermoelectric materials 14
 - thermoelectric devices 11
 - thermoelectric generator 16
 - Thomson effect 9
- Thermopiles 12
- Thomson cooler
 - advantages 266
 - COP 262
 - limits 266
 - phase-space 265
 - self-compatible material, cooling 268
 - – $u = s$ material approximation 272
 - – compatible Seebeck coefficient 269
 - – cooler models comparison 273
 - – CPM 273
 - – CPM Peltier cooler 274
 - – dependence 273
 - – heat flux 271
 - – maximum heat pumping 270
 - – maximum temperature difference 270
 - – optimal current density 269
 - – Peltier cooler 275
 - – scaling integral, TEG 269
 - – temperature difference 274
 - – temperature profile 271
 - – varying gap energies estimation 275
 - – Wiedemann–Franz-law 269
- Thomson effect 9
- Time dependent Green's function approach
 - boundary conditions, Robinson type 216, 217
 - 1D transient problem 217
 - heat conduction equation 215

Time dependent Green's function
 approach (*contd.*)
 – inhomogeneous heat equation 215
 – Laplace transformation 217
 – three dimensions 216
 – time-dependent heat equation 216
Transient behavior, TEG 189

W
Wiedemann–Franz law 232, 269

Z
Zur Farbenlehre 5