

Index

a

- acetonitrile (ACN) 5, 34, 42, 84, 101, 124, 219, 221, 243, 265
- adsorption energy 52, 167, 201
- Ag/ITO/Ag microcavity structures 436
- alloy counter electrodes
 - Cu@M@Pt nanowires 61
 - design principles 62–63
 - in-situ deposition technology 60
 - low-Pt 49–54
 - preparation methods 60–62
 - Pt-free 54–57
 - solvent-based reduction synthesis route 60
 - spontaneous galvanic displacement process 61, 62
 - transparent 57–60
- alloy/polymer composite 254–257
- aluminum (Al) electrodes 438–440
- armchair CNTs 95
- atmospheric-pressure plasma jet (APPJ) technique 98
- atomic force microscopy (AFM) 184
- Au/a-IZO transparent CE 49
- Au-coated Ag nanowire electrodes 428

b

- Berry phase method 498
- binary metal-selenide alloy counter electrodes 57
- bis(trifluoromethane)sulfonamide (TFSI) 264
- Boltzmann constant 326, 328, 358

c

- calcium electrodes 444
- camphor sulfonic acid (CSA) 182
- carbon
 - and carbon films, morphology of 80–82
 - cyclic voltammetry 82–85
 - derived from edible precursors 78
 - electrochemistry 72–73
 - photoconversion efficiency 87
 - structure analysis 78–82
- carbon allotropes 93, 94, 276–279
- carbon black (CB) 200–202
- carbon buck balls 94
- carbon dye (CD) 241
- carbon electrodes
 - for DSC
 - carbon paste fabrication scheme 458–462
 - carbon paste resistibility variation 459, 460
 - characteristics 457
 - monolithic-structured DSC 460, 462
 - structures and fabrication schemes 459, 461
 - for PSC
 - and cell structure 463, 481, 482
 - fabrication scheme 463, 481, 482
 - for perovskite solar cells 463–482
 - research activities 463
- carbon-GNP hybrid CE films 404
- carbon materials 10
 - CNF 276
 - CNTs 274–275

- carbon materials (*contd.*)
 - composites of 280–282
 - graphene 271–274
 - graphite 270–271
 - nanocomposites of 281, 282
 - porous carbons 275–276
 - Pt-loaded 200–218
- carbon nanofibers (CNFs) 217–218, 302
- carbon nanoparticles 298
- carbon nanotubes (CNTs) 93, 244, 274–275
 - carbonaceous cathodes 379, 380
 - carbonaceous materials 384
 - catalytic strength 97
 - chiral vectors 94
 - CNT-Ti wires 98
 - composite 202–207
 - conducting polymers (CP) 105–109
 - CoS_{1.097} nanoclusters (CNT@CoS_{1.097}) 102
 - CVD approach 379
 - features 95–96
 - graphene 109–114
 - iodine-free electrolytes 379
 - nitrogen doped CNTs 100
 - Pod (N)-FeNi catalyst 100
 - pristine 97–98
 - SCNT array 381
 - transition metal chalcogenides 101
 - VASWCNTs arrays 379, 381
- carbon/TiO₂ 298
- carboxymethyl cellulose (CMC) 97, 274
- CB/Pt NPs 201
- CH₃NH₃PbI₃
 - band structures 491–493, 494
 - CH₃NH₃ orientations 489
 - charge density 491, 492
 - conduction band maxima 487
 - crystal structures 488–489
 - cubic perovskite structure 492
 - defect formation energy 494 and DOS 490, 492
 - electronic properties 490–494
 - ferroelectric domains 488
 - ferroelectric properties 498–503
 - first-order phase transition 488
 - Frenkel defects 498
 - intrinsic point defect formation energy 496
 - lattice constants and volumes, of orthorhombic 491
 - PbI₂ vacancies 497, 498
 - photovoltaic properties 487
 - Schottky defects 497
 - spin-orbit coupling effects 493
 - spontaneous polarization 488, 498
 - thermodynamic stable range, for equilibrium growth 495
 - transition levels, for point defects 496
 - valence band maxima 487
 - van der Waals interaction 490
- charge transfer resistance 29, 48, 53, 60, 63, 93, 112, 135–137, 159, 181, 184, 233, 251, 325, 359, 402
- chemical oxidative polymerization 109, 181, 266
- chemical vapor deposition (CVD) method 166, 238, 280, 379
- chiral CNTs 94, 95
- chromium electrodes 443–444
- CNTs-MoS₂-carbon hybrids 103
- Co-complexes 350
- CoCr/CNF 302, 303
- Co-mediated DSSCs 131
 - basal plane HOPG 130
 - efficiency benchmarks 124
 - graphene defects, catalytic activity of 131
 - graphene oxide vs. reduced graphene oxide 131
 - mass transport 135
- composite-hydroxide-mediated (CHM) approach 169
- composite particle size 305
- conducting polymers (CP) 105–109
- conduction band (CB) 155, 199, 323
- conductive polymers 218, 219
 - PEDOT 264–267
 - polyaniline 267–269
 - polypyrrole 269

- CoNi alloy@CNTs embedded carbon cages (CoNi@CNTs-C) 100
- conjugated polymers 11
- constant phase angle (*CPE*) 328
- copper (Cu) electrodes 441–443
- CoS/MWCNT composite CE thin film 101
- CoTe 302
- counter electrode (CE) 231
- current density–voltage measurement 325–327
 - CV 327
 - EIS 327–328
 - electrochemical analysis methods for 324–329
 - efficient reduction on 198
 - electrical conductivity of 208
 - functionalization of 206
 - nanoporous electroactive polymer 179–186
 - operating principle 6–7
 - Pt-loaded composite 200–223
 - regeneration of redox couple 200
 - single-atom catalyst (SAC)-based 220
 - Tafel polarization analysis 328–329
 - types 7
- c-Si solar cells
- I*–*V* curve measurement 523
 - photovoltaic parameters 519
 - power conversion efficiencies 523
 - preparation 525
 - evaluation 525–526
- Cu-mediated DSCs 124
- current collector
- graphene 127–129
 - metals 127
 - transparent conducting oxide 125–126
- current density–voltage measurement 325–327
- cyclic voltammetry (CV) 4, 5, 32, 41, 60, 78, 82–85, 100, 134, 165, 237, 265, 326, 327, 354, 396
- scanning technique 408–409
- cyclic voltammogram 34, 82, 84, 135, 206, 219, 236, 243, 253, 265, 272, 298, 311, 375
- d**
- density functional theory (DFT) 16, 201, 331, 339, 489–490
- dimethylformamide (DMF) 142, 184, 512
- dimethyl sulfoxide (DMSO) 184, 308
- dipping reduction process (DRP) method 222
- direct bandgap 197, 336, 487, 490, 491
- direct mixture process (DMP) 222
- disulfide/thiolate (T_2/T^-) redox couple 369
- 2,2'-dithiobis(1-methyl-3-propyl-2-imidazolium) ditriflate (DT) 382–383
- donor- π -acceptor (D- π -A) sensitizers 370
- dry plasma reduction (DPR) method 36, 206, 208, 212
- dye sensitized solar cells (DSSCs) 234
- advantages 27
 - affecting parameters of 186–187
 - alternative CEs materials for 324
 - capacitance calculation 520
 - carbonaceous materials 379–385
 - carbon materials 10, 93–95
 - counter electrode 8–9, 96–114, 266, 276, 277
 - charge transfer processes
 - counter electrodes 359
 - deleterious processes 357–358
 - mass transport 358–359
 - useful processes 354–357
 - chemical complexity 350, 363
 - cell performance 28
 - component of 156–170
 - conjugated polymers 11
 - with CoS/PEDOT 245
 - cost-effective 198
 - counter electrode 28
 - current–voltage characteristics 141
 - design solar cells 349
 - development of 155

- dye sensitized solar cells (DSSCs)
(*contd.*)
- efficiency and stability of 367
 - efficiency loss in 155
 - electrocatalytic activity of 328
 - electrochemical properties of 327,
352–354
 - energy level diagram 30
 - evolution of 180
 - fabrication techniques 3–5
 - history and cell efficiency level 1–3
 - hole-electron pair in 233
 - hybrid CEs 13–15
 - inorganic polycomponent CEs in
324
 - inorganic transition metal
compounds 371–375
 - internal voltage of 325
 - iodide/triiodide redox electrolytes
41
 - J–V characteristics of 246
 - kinetic processes 367, 368
 - long-term performance of 315
 - mass production 72
 - mesoscopic TiO₂ photoelectrodes
preparation 3–4
 - molecular-and nanometre-scale
components 349
 - MPPT technique 524
 - nanoporous electroactive polymer
179–186
 - operational principles 5, 199–200,
350–351
 - organic conductive polymers
375–379
 - PEDOT–PSS 249
 - performance of 73–74
 - photocurrent–voltage characteristics
33, 78, 241, 247
 - photoelectrode (photoanode) 27
 - photovoltaic parameters 87, 519
 - photovoltaic performance 34, 40, 41
 - photovoltaic properties of 297, 299,
304, 307, 311, 313
 - polymer counter electrode (PCE)
11–13, 233–237, 247, 367
 - polymer/TMC composite electrode
241–245
 - power conversion efficiency 30, 518,
524
 - Pt counter electrode activity 29
 - Pt-free counter electrodes 54–57
 - quality of 325
 - redox electrolyte 28
 - selling points 349
 - sensitizer role 28
 - solar cell device performance
359–362
 - stability assessment, of CE catalysts
395
 - types of counter electrodes 7–8
with SWCNT/rGO 278
 - symmetrical dummy cell fabrication
3–5
 - theory 233
 - thiolate(T) based redox couples
368–371
 - TMC chalcogenide/polymer
composite 245–249
 - TMC counter electrode 10–11,
237–241
 - TMC metal and alloy/polymer
composite 254–257
 - TMC oxide/polymer composite
249–251
 - triiodide reduction in 164
 - working principles 29, 177, 178
- dynamic potentiostat 327
- e**
- edge-carboxylated graphene 138
 - edge-selenated graphene nanoplatelet
142
 - edible precursors
 - carbonization 75
 - chemical structure 74
 - effective charge transfer resistance 137
 - electrocatalysts
 - CNT with dopants 98–101
 - pristine CNTs 97–98
 - PtNP/MWCNT nanocomposite films
99

- electrocatalytic activity 129
 basal plane HOPG 131
 characterization 134–137
 graphite/carbon black mixture 132
 Ni and polypyrrole coatings on cotton
 textile fabric 127
 nitrogen-functionalized graphenes
 142
 electrocatalytic mechanism, of
 MWCNT@MoS₂ 103
 electrochemical deposition 208
 electrochemical impedance
 spectroscopy (EIS) 126, 135,
 136, 166, 185, 206, 251, 265,
 327–328
 porous carbons 137
 technique 409
 tests 369
 electrochemical polymerization 109,
 180, 265, 269, 270, 359
 electrochemical stability, of CE materials
 CV scanning technique 408–409
 dark current–voltage characteristics
 409–410
 electrochemical impedance
 spectroscopy (EIS) 409
 electrochemistry 72–73, 129, 130, 353
 electrodeposition method 101, 168,
 223, 331
 electron collector 156, 157, 164
 electron–hole separation 326, 503
 electrophoretic deposition (EPD)
 method 109, 113, 165, 272, 278,
 279
 electropolymerization 105, 107, 108,
 112, 180, 185, 218, 236, 243, 265,
 268, 312
 electrospun carbon nanofibers (ECNs)
 217
 ethyl cellulose 138, 302, 383, 459
 exfoliated graphene (EFG) 243
- f**
- fabrication, of DSSCs
 characterization 77–78
 device assembly 77
 ethanol 74
 flow chart 77
 glucose 74
 materials used 74–75
 mesoscopic TiO₂ photoelectrodes
 preparation 3–4
 operating principles 5
 photoanode 76
 photocurrent–voltage characteristics
 85–88
 polyvinylpyrrolidone 74
 sucrose/glucose/sugar free derived
 carbon 74, 76
 sugar free 74
 symmetrical dummy cell fabrication
 3–5
 Faraday constant 129, 304, 327, 329
 Fermi energy 199, 200, 495
 Fermi level 324, 325, 351–353, 355,
 423, 430, 441, 491, 496
 ferric *p*-toluene sulfonate (FTS) 182
 ferric *p*-toluene sulfonate (FTS) doped
 poly(3,4-ethylenedioxythiophene)
 (PEDOT:FTS) 184
 ferrocene/ferricenium (Fc/Fc⁺) redox
 couple 352
 field emission gun scanning electron
 microscopy (FEG-SEM) 80
 fill factor (*FF*) 325
 finite length Warburg diffusion
 impedance 136
 first-principles DFT calculations, of
 CH₃NH₃PbI₃ 488
 flower-like Pt counter electrode 33
 fluorine-doped tin oxide (FTO) 72,
 156, 248, 265, 272, 296
 Frenkel defects 497, 498
 FTIR spectra 78
 fuel cells 43, 161, 224, 296, 318
 fullerenes 94
 fully-printed PSC 463
 functionalized graphene sheet (FGS)
 electrodes 138, 383
 functional MWNTs (f-MWNT) 202
- g**
- glucose derived carbon (GDC) 83
 GNS/Pt-NHB 212

gold electrodes 424–428
 graphene 244, 271–274
 adhesion to FTO 132–134
 cathode 137–143
 current collector 127–129
 definition 94
 electrocatalysis on 129–132
 graphene-Ag NW 216
 graphene composite 207–217
 graphene nanoplatelets (GNPs) 383
 graphene nanosheets (GNS)
 208, 214
 graphene oxide (GO) 312
 mechanical abrasion tests of 133
 graphite 93, 270–271
 Grätzel cell 123
 growth detachment transfer process
 100
 GW+SOC calculations 493

h

HAADF-STEM 221
 halide perovskites 487, 499
 charged domain walls 502
 organic–inorganic hybrid 487
 point defects 488
 uncharged domain walls 501
 HfO₂ 305
 hierarchical spheres (HSs) 161
 high capacitance based solar cells
 525
 highest occupied molecular orbital
 (HOMO) 263, 324
 hybrid electrocatalysts
 on carbon and polymer 295–297,
 311–312
 on carbon and TCM 295–306
 on TCM and polymer 295–297,
 306–310
 hybrid metal–organic perovskites (HP)
 421
 hydrodesulfurization 157
 hydrogen oxidation 157
 hydrothermal method 166
 hydrothermal reaction 302

i

ID/IG ratio, of CNTs 73
 I₃⁻/I⁻ redox shuttle, liquid-junction
 DSCs 123
 I-mediated DSSCs
 carbon cathodes 132
 complications 124
 edge-selenated graphene nanoplatelet
 142
 FGS@FTO 138
 GNP@FTO 138
 graphene 127
 graphene-based cathode materials
 138, 139
 LPAH@graphite cathode 141
 metals (current collector) 127
 Na-embedded carbon 142
 nitrogen-functionalized graphenes
 142
 platinized stainless steel cathodes
 127
 platinized Ti-mesh 127
 platinized-tungsten/PEN fabric 127
 Pt@FTO cathode 129
 reductive quenching of photoexcited
 sensitizer 125
 transparent conducting oxide (current
 collector) 125–126
 triiodide reduction rate 129
 indium tin oxide (ITO) 265
 in-situ polymerization 311
 interfacial contacts 522
 iodide–triiodide redox system 351
 ion exchange deposition (IED) method
 165
 ionization potential (IP) 220
 IR spectroscopy 78–79
 ITO-coated polyethylene naphtholate
 (ITO/PEN) 206

l

large-effective-surface-area
 polyaromatic hydrocarbon
 (LPAH) 141
 L-cysteine 238
 light emitting diode (LED) solar
 simulator

- solar cell evaluation 519–520
 - use of 519
 - vs. Xe lamps 519
 - light harvesting
 - efficiency of 198
 - material 330
 - light-to-electric conversion 177
 - lowest unoccupied molecular orbital (LUMO) 27, 72, 263, 324
 - low-Pt alloy counter electrodes 49–54
 - adsorption energy and desorption barrier calculations 52
 - advantages 54
 - CV curves 50
 - dissolution-resistance theory 54
 - electronic distribution 49
 - electron transfer at CE/electrolyte interface 53
 - long-term stability 54
 - photovoltaic parameters 51
 - strain effect 50
 - Tafel polarization curves 50
 - thermodynamically favored reactions 55
 - work function 53
- m**
- magnetron sputtering method 160, 168
 - maximum power point tracking (MPPT) technique 518, 523–525
 - mechanical bending technique 404–406
 - mechanical stability, of CE catalysts 403
 - electrochemical stability assessment 408
 - nano-indentation surface scanning technique 404
 - sonication removal technique 404
 - tape adhesion technique 407–408
 - metal alloy contacts 445
 - metal counter electrodes 48–49
 - aluminum electrode 438–440
 - calcium electrodes 444
 - chromium electrodes 443–444
 - copper electrodes 441–443
 - gold electrodes 424–428
 - metal alloy contacts 445
 - nickel electrodes 443
 - selected material properties 424
 - silver electrodes 428–436
 - silver nanowires 436–438
 - stainless steel electrodes 445
 - standard reduction potential 424
 - titanium electrodes 444–445
 - metal organic framework (MOF) 100
 - metal oxide 280–281
 - metal sulfide 280–281
 - methacrylamide (MAM) 71
 - methanol oxidation 157
 - 1-methyl-3-propylimidazole-2-thione (T) 382
 - microwave-assisted polyol process (MPP) 222
 - modified hill climbing technique 524
 - molybdenum diselenide nanosheets 247
 - MoS₂/CNT 300
 - MoS₂/RGO-CNTs hybrid 113
 - MoS₃/CNT 301
 - Mott–Schottky heterojunctions 343
 - Mott–Schottky plots 126
 - MWCNT@ reduced graphene oxide nanoribbon (MWCNT@rGONR), catalytic activity of 112
 - MWCNT@MoS₂ nanocomposite 103
 - multiwall carbon nanotubes (MWCNTs) 181, 202, 205, 274, 371
 - multiwall CNT/CMC composite film 98
 - multiwalled carbon nanotubes (MWNT) 132
- n**
- Na-embedded carbon 142
 - nanocrystals (NCs)
 - hydrothermal method 162
 - synthesized monodispersed CoS₂ 165
 - nanofibers (NFs) 161, 255

- nanohybrid materials 200, 206, 212, 213
- nano-indentation surface scanning technique 404
- nanoparticles (NPs) 198, 236, 330
- nanopatterned PEDOT 267
- nanoporous electroactive polymer 179–186
- nanorods (NRs) 165
- nanoscaled transition metal carbides 157
- nanosheet networks 164
- nanostructured PEDOTs 267
- nanotube arrays 266
- nanowires (NW) 340
- N-doped graphene 273
- Nernst diffusion impedance 136
- Nernst equation 354
- Nernst potential 325
- nickel electrodes 443
- nickel oxide nanofilament/MWCNTs (NiO-NF/MWCNTs) 105
- NiCo₂O₄ film 342
- NiS/MWCNT/Ti hybrid film performance 103
- N*-methyl-2-pyrrolidone (NMP) 272
- N*-*N'*-methylenebisacrylamide (MBAM) 71
- normal hydrogen electrode (NHE) 368
- O**
- one-electron transfer redox systems 350
- open-circuit voltage 29, 85, 87, 124, 155, 202, 243, 248, 252, 273, 297, 324, 325, 360, 521, 524
- organic conductive polymers 371, 375–379
- oxidation/reduction peaks 327
- oxide–dye–electrolyte interface 350
- P**
- PANI/CoS decorated CNT composite 107
- PANI/GNP/MWCNT composite 112
- PANI–graphene quantum dots (PANI–GQDs) 182
- PANI/graphene nanoplatelet, (G-NP)/multi-walled carbon nanotube (MWCNT) 182
- Pb-free halide perovskite materials 503
- PEDOT doped with poly(styrene sulfonate) (PEDOT:PSS) 218
- PEDOT-ECP composites 106
- PEDOT/EPG
- electropolymerization 243
 - photovoltaic performance of 243
- perovskite materials 487, 488
- perovskite solar cells (PSCs) 422
- anomalous *I*–*V* hysteresis 518
 - boundary modeling 511–517
 - capacitance calculation 520
 - carbon electrodes for 463–482
 - history and architectures 421–422
 - MPPT technique 524
 - photovoltaic parameters 519
 - planar structured 511
 - power conversion efficiency 511, 518, 524
- photoanode 27, 38, 71, 76, 77, 85, 93, 96, 123, 127–129, 130, 132, 135, 155, 188, 189, 243, 247, 249, 263, 323, 325, 328, 383, 421, 443
- photoconversion energy efficiency (PEC) 156, 160, 161, 202, 244, 245, 275, 325
- photoelectrochemical solar cell 197
- photoelectrode 2–5, 27, 28, 33, 355, 396
- photoelectron transfer induced 199
- photoexcitation 60, 177, 199, 323, 351, 354, 428
- photoexcited sensitizer, reductive quenching of 125
- photovoltaic parameters, of DSSCs
- Pt-free CEs 531–544
 - Pt-free nanohybrid CEs 2, 545–573
 - Pt-loaded nanohybrid CEs 566
- photovoltaic (PV) technology 177, 197, 349, 403
- physical constructed device 521–523
- π -electron materials 94
- planar structured perovskite solar cells

- cross-sectional SEM image 512
- double diode equivalent circuit model 512, 515
- equivalent circuit model 514
- I*-*V* curves 512–515
- output voltage vs. operating time 517
- single diode model 513–515
- platinum-based composite counter electrode materials
 - bimetallic PtAu nanoparticles 36
 - carbon black-supported Pt nanoparticles 35
 - chemical/electrical stability 41, 42
 - graphene oxide-Pt NP hybrid composite 40
 - graphene/Pt composites coated FTO films 37
 - platinum-cobalt and platinum-nickel hollow nanospheres 35
 - Pt deposited on ITO/PEN substrates 38
 - Pt-Fe alloy nanoparticles dispersed over nitrogen-doped graphene 37
 - Pt-GO hybrid composite 41
 - Pt nanoparticles/graphene nanosheets film 36
 - PtNi electrodes 35
 - Pt NPs-decorated nickel embedded metal-mesh transparent electrode 38
 - Pt/PEDOT PSS/FTO glass substrate 40
 - research contributions 42
 - ternary alloys 35
 - ZnO nanostructure assisted hollow PtNi alloy microstructure 35
- platinum-coated glass 421
- platinum-cobalt (Pt-Co) hollow nanospheres 35
- platinum counter electrode (CE) 197, 247, 251, 252
 - 3-(2-aminoethylamino)propyl-methyldimethoxysilane 31
 - carbon black (CB) composite 200–202
 - carbon nanofiber composite 217–218
 - carbon nanotubes (CNTs) composite 202–207
 - charge transfer resistance 302
 - electrodeposited Pt/ITO-PEN 33, 34
 - film thickness and surface roughness 30
 - flower-like Pt counter electrode 33
 - graphene composite 207–217
 - materials 29–34
 - Pt nanofibers 31
 - Pt nanotubes 30
 - Pt NPs 32
 - research contributions 42
 - sputter deposition 30
- platinum-nickel (Pt-Ni) hollow nanospheres 35
- podlike nitrogen-doped carbon nanotubes 56, 57, 100
- point defects, in halide perovskites 488
- polyacetylene (PA) 232
- polyaniline (PANi) 11, 105, 181–182, 218, 232, 236, 255, 256, 264, 267–269, 276, 295
- polycomponent-based CE materials
 - other polycomponent materials 340
 - quaternary chalcogenides 336–340
 - ternary chalcogenides 330–336
- polycomponent-based composites 340–343
- polycomponent materials 340, 341
- poly(3,3-diethyl-3,4-dihydro-2H-thieno-[3,4-b][1,4]-dioxepine) (PProDOT-Et2) 218
- poly(dimethylsiloxane) (PDMS) 189, 219, 313, 376
 - cathode 382
 - conductive polymers 264–270
 - electrical conductivity of 265
 - ITO/PEN 265
 - micro-flower arrays of 266
 - nanofibers 266
 - nanotube arrays 266
 - one-dimensional structure 265
- polyelectrolyte 184, 430

- poly(3,4-ethylenedioxythiophene) (PEDOT) 182–183, 218, 232, 233, 263–267, 295
- poly(3,4-ethylenedioxythiophene) doped polystyrene sulfonate (PEDOT:PSS) 184
- poly(3,4-ethylenedioxythiophene)-poly(styrenesulfonate) (PEDOT-PSS) 249
- polyethylene glycol (PEG) 182, 305
- polyethylene glycol 400 (PEG400), 103
- poly(ethylene-2,6-naphthalenedicarboxylate) (PEN) 265
- polyethylene terephthalate (PET) 164, 189
- polyfuran (PF) 232
- polymer, class 218
- polymer counter electrode (PCE) 187–189, 233–237
- polymer/TMC composite electrodes 241–245
- polyoxometalate (POM) 182
- poly(oxyethylene)-segmented imide (POEM) 255
- poly(p-phenylenevinylene) (PPV) 232
- poly(3,4-propylenedioxythiophene) (PProDOT) 184–186, 295
- poly(styrene sulfonate) (PSS) 182
- polypyrrole/MWCNT composite films 109
- polypyrrole (PPy) 180–181, 218, 232, 236, 241, 264, 269, 295
- poly(4-styrenesulfonic acid) (PSSA) 281
- poly(styrene sulfonic acid) (PSS) 184
- polythiophene (PTh) 232
- polyvinylidene fluoride (PVDF) 232, 272
- polyvinylpyrrolidone (PVP) 238
- porphyrins 351
- potentiostatic (PS) techniques 331
- powder of activated carbon fiber (PACF) 305
- power conversion efficiency (PCE) 155, 177, 197, 233, 323, 367
- Pt/CNT 207
- Pt electrodes 253
- Pt-free alloy counter electrodes 54–57
- Pt-free electrocatalysts 314–315
- Pt-free monometal catalysts 49
- PtGONF catalyst 133
- Pt/graphene composites 213
- Pt-loaded CEs
 - carbon materials 203
 - conductive polymer 218–219
 - graphene materials 209
 - other-metal 222–223
 - TCM 219–222
- Pt-NP hybridized 215
- PtNP/RGO nanohybrid CEs 213
- PtNP/Si NWs 222
- pulsed laser deposition (PLD) 208
- pulse potentiostatic
 - electropolymerization 107, 108, 265, 312
- pulse reverse (PR) techniques 331
- pyrrole (Py) monomers 241
- q**
- quantum dots-sensitized solar cells (QDSCs) 381
- quasi-ohmic contact 423
- quasi-reference electrode (QRE) 352
- quaternary chalcogenides 336–340
- r**
- Raman spectroscopy 79–80
- rapid thermal process (RTP) 331
- redox electrolyte 28
- reduced graphene-CNTs 109
- reduced graphene oxide (rGO) 138, 181, 208, 272, 302
- reduction on platinized CE (RCE) 369
- room temperature ionic liquids (RTILs) 186
- ross-stacked (CS) sheet 381
- s**
- sandwich-type DSSC 4, 5
- scanning electron microscopy (SEM) 297
- Schottky defects 497
- sensitizer molecule 155

- series resistance 160, 183, 251, 298, 325, 328, 370, 375, 377, 386, 409, 424, 425, 429, 443, 513, 514, 517
- shear modulus, of CNTs 96
- short-circuit current 155, 202, 252, 273, 304, 325, 326
- shunt resistance 325, 425, 513–515, 517
- silicon nanowires (Si NWs) 222
- silver (Ag) electrodes 428–436
- silver nanowire electrodes 436–438
- single-wall carbon nanotube (SWCNT) 206
- single-wall CNT coated fiber-based substrate, mechanical bending test 405, 406
- single-walled carbon nanotubes (SWCNTs) 274
- sodium decylsulfonate (SDSn) 241
- sodium dodecyl sulfate (SDS) 181, 182
- solar cell 27, 179, 184, 189, 197, 198, 326, 331
- device performance
- copper coordination complexes 360–362
 - iodide and cobalt-based redox mediators 359–360
 - Zombie cells 362–363
- technology 349
- third generation 263
- solar illumination 5, 199
- solar to electric conversion 177
- sol–gel synthesized TiC/SiC 308
- solid polymer electrode (SPE) 244
- solvothermal method 161, 169
- sonication removal technique 404
- spin-coating method 168
- stability assessment, of CE catalysts
- CE degradation 397
 - light-soaking tests 396
 - long-term stability 410–412
 - mechanical stability assessment 403–404
 - multi-cycle successive cyclic voltammetry scanning 396
 - photovoltaic qualification test standards 411
- Pt-free CE materials 397, 398
 - reference values 399, 400
 - systematic evaluation strategy 399
- stainless steel (SS) electrodes 445
- Stokes–Einstein equation 358
- successive ionic layer adsorption and reaction (SILAR) method 169
- sucrose derived carbon (SDC) 83
- sugar free derived carbon (SFDC) 83
- sugar free edible precursors 75
- super-aligned carbon nanotube (SCNT) array 381
- symmetrical dummy cells
- characterization of 135
 - electrocatalytic performance 134
- t**
- Tafel measurements 165, 206
- Tafel polarization analysis 328–329
- tape adhesion technique 407–408
- ternary chalcogenides 330–336
- terpineol 302
- tetradecyl trimethyl ammonium bromide (TTAB) 218
- tetrahydrofuran (THF) 184
- tetramethylthiourea 369
- thermal conductivity, of CNTs 96
- thermal decomposition method 206
- thermally stable boron doped MWCNTs 100
- thiolate(T) based redox couples 368–371
- TiN-CNTs composite 105
- TiN nanoparticles 254
- TiO₂
- conduction band of 263
 - nanowire bundle array 220
 - nitridation of 159
 - by plasma jet calcination 302
- TiO₂ film 263
- TiO₂ nanoparticle 250
- TiO₂ nanotubes (TNT) 219
- TiO₂/electrolyte interface 198, 199
- TiO₂/PEDOT-PSS 310
- TiO₂/Ti anode 223
- TiO₂ nanoparticles 308
- titania slurry 76

- titanium carbide/platinum (TiC/Pt) 222
 - titanium electrodes 444–445
 - titanium isopropoxide (TTIP) 302
 - transition metal carbides 101–105, 237
 - transition metal compounds (TMC) 10, 232
 - alloy/polymer composite 254–257
 - application of 157
 - borides 169–170
 - carbides 157, 159
 - chalcogenide/polymer composite 245–249
 - composite electrodes 158, 237–241
 - hybrid electrocatalysts 298–306
 - metal and alloy/polymer composite 257
 - nanomaterial addition 307
 - nitrides 157–161, 252–254
 - oxide/polymer composite 161–163, 249–251
 - phosphides 163–168
 - photoconversion efficiency of 239
 - Pt-loaded 219–222
 - selenide 168–169
 - silicides 169–170
 - sulfides 163–168
 - tellurides 169–170
 - transition metal nitrides 101–105, 237
 - transition metal oxides 101–105, 237
 - transition metal sulfides 101–105, 255
 - transparent alloy counter electrodes 57–60
 - transparent conducting oxide (TCO) 125–126, 179, 199, 264, 351
 - transparent honeycomb-like h-PEDOT/MWCNT counter electrode 106
 - triiodide/iodide electrolyte 324
 - triiodide reduction
 - graphene electrocatalysts 129–132
 - reduction rate 129
- U**
- ultrasonication 272, 273
 - ultrathin polypyrrole nanosheets (UPNSs) 241, 242
- V**
- vapor phase polymerization (VPP) 269
 - vertically aligned CNTs-graphene paper composite 110
 - vertically aligned single-walled carbon nanotubes (VASWCNTs) 275, 379, 381
- W**
- Warburg impedance 136, 325, 328
 - working electrode (WE) electrolyte 352
 - WS₂/MWCNT electrodes 104
- X**
- X-ray diffraction (XRD) 79–80
- Y**
- Young's modulus, of CNTs 96
- Z**
- zigzag CNTs 94, 95
 - Zombie cells 362–363