

Index

a

ability 1, 39, 67, 71, 82, 90, 185, 190, 345
 absolute visual performance 79, 80
 achromatic channel 12
 adapted white point 17
 alertness 275
 circadian and homeostatic components
 of 52
 in daytime 276–281
 in evening and night hours 275–276
 light effects on 276, 277
 output variables 276
 physiological assessment of 59
 questionnaires on 58–59
 and sleepiness during early shift in
 industrial company, light effect on
 281–283
 amacrine cell 8, 40, 41, 462
 amygdala 47, 48, 461
 artificial intelligence (AI) methods 172,
 339, 346, 396
 artificial light vs. daylight
 brightness parameters for 266–267
 circadian parameters and light quality
 parameters for 266–267
 colorimetric parameters for 266
 attribution 219
 defined 219

b

bead line effect 232
 bead string effect 232
 brain activity

 stimulated by light exposure,
 modulation of 47
 wavelength dependence of 48
 brain imaging method 47
 brain processing for subjective and
 objective behavioural variables
 formation 38–48
 non-visual light effects, processing
 centres and transmission pathways
 for 43–48
 visual signal processing 38–43
 brightness 16, 174, 177, 460
 equations of 178–179
 experimental set-ups for 174–178
 subjective assessment of 100–101
 modelling 102–107
 with circadian stimulus 186
 perception processing in visual brain
 198
 rating scales 175
 brightness metrics 99, 203, 443–457
 brightness parameters, assessments of
 203–205
 brightness perception and modelling
 445–446
 brilliance 114, 143–144

c

CAM02-UCS colour space 18, 19, 21,
 142, 143
 care facilities, development of 336
 ceiling-to-wall luminance ratio 228
 chroma 2, 16, 17, 20, 176, 179, 291

- chromatic adaptation 12, 17–20, 121, 122
- chromatic lightness 143–144
- chromatic signals 11
- chromaticity 122, 123
 - diagram 14
 - of lighting 137
- CIECAM02 colour appearance model 18–20
- CIE 2017 Colour Fidelity Index 142
- CIE colourimetry 2
 - development milestones 3
- CIE CRI method 142
- CIELAB colour space 18
- CIE tristimulus values 13–16
- circadian (C) alertness components 255
- circadian clock 21, 23
- circadian effect of light 21
- circadian effective metrics, correlations 27, 28, 241, 413, 416
- circadian-effective irradiation 307
 - field measurements
 - in winter 310
 - on evening of an autumn day 312–314
 - on summer day 310–312
 - field measurements in winter 309–310
 - mobile field measurement 307–310
- circadian light, defined 249
- circadian rhythm 21, 292
 - of melatonin and cortisol 45, 46
- circadian stimulus (CS) 23–25, 27, 208, 460–462
 - modelling with 184–190
 - models 446–450
- cloud programmes, for luminaire control 339
- cloud software structure 349–352
- colorimetric system 12
- colour appearance, of colour stimulus 17
- colour fidelity 18, 21, 141–144, 146, 152, 153, 162, 165, 166
- colour fidelity index 8, 142, 144, 152, 165, 166
- colourfulness 16, 20, 21, 143, 202
- colour gamut index 18, 143, 152, 153, 160, 202, 203, 403
- colourimetry
 - lighting technology and 12–13
- 2° - colour matching functions 12
- colour preference 144, 174, 177, 460
 - equations of 180–183
 - experimental set-ups for 174–178
 - for skin tone lighting 153–162
 - modelling
 - with circadian stimulus 187
 - at 2000 lx 149–150
 - at 750 lx 146–149
 - red object colours, consideration of 150–153
 - rating scales 175
 - visualising model in contour diagrams 188–190
- colour preference index 18, 144, 160, 212, 269
- colour quality 140, 172, 207, 460
 - chromatic lightness/brilliance 143–144
 - colour preference 144
 - defined 111–166
 - memory colours 144–146
 - naturalness/colour fidelity 141–143
 - perceptual aspects of 141
 - vividness 143
- colour rendering of light source 141–142
- colour rendering index 2, 142, 162, 199
 - and colour gamut index, correlation between 203
 - evaluation of 202–203
 - luminous efficacy and 206
 - melanopic effect and 205–206
 - semantic interpretation of 162–166
- colour sensing, matrix types for 376
- colour spaces 2, 11, 16–18, 320
- colour stimulus 1, 12, 13, 14, 16–20, 24, 143
- colour temperatures 122, 123, 460
 - on age and gender for activation and relaxation 135–136

- experimental method 123–127
 - and illuminance
 - combined effect of 134–135
 - visual experiments on 132–134
 - in literature 130–132
 - mean visual preference values
 - and confidence intervals 127–128
 - vs. two luminance levels at CCT 129
 - nature of 129–130
 - Connected Lighting 337, 338
 - data processing levels 338–339
 - contrast 72
 - of typical reading materials 73
 - core body temperature
 - during nocturnal hours with quasi-monochromatic light 248
 - time courses of 247
 - corpus geniculatum laterale (CGL) of primates 41
 - correctness factor 78
 - correlated colour temperatures (CCT) 15, 115, 120, 124, 176, 184, 217, 252, 443, 453
 - of illumination 98
 - correlation analysis 452
 - of HCL parameters
 - general considerations of 197–210
 - input parameters, structure and categories of 210–214
 - output parameters 207, 208
 - light sources and photometric and colourimetric quantities in 452
 - linear brightness metrics vs. non-visual-effect parameters 452–455
 - non-linear brightness metrics vs. non-visual-effect parameters 455–456
 - correlation coefficients 212
 - of brightness multiplier signal 212–213
 - of chromaticity coordinates 213
 - of circadian stimulus 213
 - of colour quality metrics 213
 - cortisol 22, 34, 45, 46, 50, 51, 60, 63, 294, 391, 432
 - CQS metric (Colour Quality Scale) 144
 - CSS-45 spectroradiometer 321
- d**
- daylight 261, 404, 405
 - advantage of 271
 - design standardisation 405–407
 - vs. electric light, quantitative characteristics of 265–271
 - health aspects of 263–265
 - illuminance and exposure data 409
 - psychological aspects of 261–271
 - spectral measurement of 314–319
 - supply recommendations 406
 - daylight components in interior space 368–371
 - daylight planning for non-visual effects 407–408
 - daytime, HCL lighting systems
 - specification for 409, 410
 - circadian-effective illuminance level 410–418
 - dynamic lighting, control curves 418–425
 - illumination level 410–418
 - time factor 421
 - daytime light recommendations, for indoor environments 281
 - daytime vision 1, 10, 12, 39, 197, 291, 428
 - D65-equivalent illuminance 27–28, 418, 425, 461, 462
 - dim light melatonin onset (DLMO), timing of 51
 - DIN EN 12464 European standard, for interior lighting
 - extracts from DIN EN 12464-1:2011-08 68–69
 - illuminance levels, importance of 68, 70
 - photometric parameters 67, 68
 - duty cycle 230, 232–235, 237–240

e

- electroencephalography (EEG) analysis
 - 59, 242
- emotions 52
 - defined 217
- emotional influencing factors 219
 - in an interior 220
- entrainment 49
 - theory 50
- equivalent luminance (L_{eq}) 99, 100
- evening light recommendations, for residential and other indoor environments 281

f

- α_{me1} factors 462
- fidelity index 18, 142, 144, 152, 165, 166
- flicker and stroboscopic effects 229
- flicker effects 230–231
- Fotios formula 462
- free-running circadian period duration 51

g

- gain control of receptor signals 10
- Gamut index 18, 143, 144, 152, 153, 160, 202, 203, 403
- general colour rendering indices 124, 141, 364
- geniculohypothalamic tract (GHT) 44
- German DIN standardisation 298
- Gimenez formula 444
 - for nocturnal melatonin suppression 450–451
- glare
 - relative visual acuity and ageing factor 430
 - subject of lighting 229

h

- handheld colour meters 210, 295, 300
- HCL oriented lighting design
 - conceptions and thought processes, on lighting quality (until 2002) 387–393

- goals and classification of 397–399
- lighting quality
 - conceptions and thought processes on 393
 - definition 395
 - literature analysis and new thoughts 393–396
 - research topics for 395
- process steps of 399–403
 - project-specific (individual) user requirements 399–400
 - lighting solution, evaluation of 403
 - using design tools 400
- quality concepts, classification of 387–397
- heart rate
 - during nocturnal hours with quasi-monochromatic light 248
 - time courses of 247
- Helmholtz-Kohlrausch effect 111, 143
- high-power and mid-power LEDs 2
- Hockey model 82
- homeostatic (S) alertness components 255
- hue 2, 11, 16, 19, 20, 97, 111, 121, 137–139, 143, 144, 152, 153, 172, 291, 459
- Human Centric Lighting (HCL)
 - complex, system diagram of 56
 - with constant colour temperature circadian effectiveness, data of 353–355
 - white LED light generation 355–356, 358, 360
- description 54
- levels of implementation options 353, 354
- light measurements, at office workplaces
 - measured variables and measurement technology 320–321
 - measurement setup 321–322
 - results 324–326
 - spectral radiance 322, 324

- light measurement technology
 - hypotheses and questions for 293–296
 - lighting system
 - for elderly people's homes 431–433
 - people suffering from dementia 431–433
 - parameters, structure and flow diagram of 55
 - with variable colour temperature and variable illuminance 361–363
 - and daylight consideration 365–371
 - and high colour quality 364–365
 - human eye
 - choroid 7
 - ipRGC 9, 10
 - macula lutea* 9
 - optical parameters 8
 - optical system of 7
 - retina 7, 9
 - sclera 7
 - structure of 7, 8
 - vitreous body 7
 - human light processing apparatus
 - parameters structure at input and output of 292
 - human visual system 7–13, 20, 99, 122, 141, 197, 205
- i**
- IES TM-30-15 Color Fidelity Index 142
 - IES TM-30-15 Gamut Index 143
 - IES TM-30-15 method 143
 - IF (image forming) 34, 43
 - IGL (*Intergeniculate Leaflet*) 44, 162
 - illuminance 173, 460
 - on age and gender for activation and relaxation 135–136
 - and colour temperature
 - combined effect of 134–135
 - visual experiments on 132–134
 - in literature 130–132
 - nature of 129–130
 - illuminance levels
 - preferred horizontal 112–114
 - recommendations, for light therapy 265, 266
 - illuminance meters 210, 295
 - indoor lighting
 - daylight variation and consequences for 366–368
 - information technology 2, 335, 408
 - input parameters, of HCL system
 - photometrically based parameters 210
 - physiologically based parameters 210
 - research questions 210
 - integrative lighting technology 197
 - intelligent LED luminaires 197, 371
 - intelligent lighting system 70, 210, 342, 397, 398
 - in connection with daylight systems 398
 - interior/indoor lighting, standardisation for 67
 - International Commission on Illumination 1, 37, 202
 - intrinsic circadian period duration 51
 - intrinsically photosensitive ganglion cells (ipRGCs) 9–10, 38, 405
 - distribution on retina 297
 - receptors 292
- k**
- Karolinska Sleepiness Scale (KSS) 58–59, 243–248, 276–277, 280, 283
 - Kruithof diagram 111, 130–132, 135, 185
- l**
- lamp types for matrix optimisation
 - properties of 377–378
 - spectra of 377–378
 - Landolt rings 72, 77–79, 84, 88, 89, 91
 - photometric properties of 84
 - larks 51
 - lateral geniculate nucleus (LGN) 41, 42
 - Lateral Hypothalamic Area (LHA) 47
 - light effects
 - alertness and sleepiness during early shift in an industrial company 281–284

- light effects (*contd.*)
 - on cognition, emotion and alertness 47–48
 - on human
 - input variables, systematic approach 35–38
 - on mood and learning 46–47
 - psychological – emotional aspects of 217–227
- light effects on human
 - influencing variables, overview of 34
 - input variables, overview of 34
 - output variables, overview of 34
- light-emitting diode (LED) 229
 - ageing model 350
 - constant current regulation 230
 - flicker effects 230–231
 - luminaires, with variable colour temperatures 337
 - pulse width modulation 229–230
 - state of research 231–233
 - stroboscopic effects 230–231
 - technology 172, 336
- lighting
 - design, for elderly people’s and nursing homes 433–436
 - and HCL lighting 337
 - psychological effect, of variable 220–227
 - quality features 197
 - quality research 464
 - research, milestones of 171
 - systems, parameters for HCL-oriented characterisation of 200
- lighting-specific modules structure, in cloud software 349–352
- lighting technology
 - and colorimetry 12–13
 - components of 197, 198
 - development of 1, 95
 - focus points 95
 - in 21st Century 293
- light measurement
 - circadian effective irradiance 297–302
 - DIN evaluation procedure 298–300
 - MDER and MEDI metrics 302
 - procedure according to M.Rea 300–302
- circadian stimulus calculation from vertical illuminance and chromaticity coordinate 302–305 and correlated colour temperature 305–307 size of human viewing field 296–297 technology 291
- light metrology 291
- lightness 2, 16–21, 143–144, 291
- light quality models
 - equations of 178–184
 - experimental set-ups for 174–178
 - in Japan’s museums, validation of 191–192
 - input parameters 173
 - output parameters 173–174
- light source technology
 - correlation coefficients between parameters of 201–202
 - in correlation analysis 201
 - development milestones 1–2
 - melanopic effect factors 299–300
 - source types 201
- light therapy 265, 266, 310
- Lindner’s experiments 90–91
- LiTG questionnaire
 - lighting situations, uniform assessment of 63
- LMK 5 camera 320
- luminaire development, evolutionary stages of 337
- luminance 12, 13
 - channel 12
 - levels of paper materials 73
 - signal 99
- luminance-dependent factor $c(L)$ for the eye ageing model 427
- luminous efficacy
 - and colour rendering index 206

m

machine learning (ML) 346, 347
 based user models, in lighting
 technology 347–348
 sensor fusion and modelling using
 347–348

magnocellular layers 41

MCTQ (Munich Chrono Type
 Questionnaire) 58, 282

MDER metrics 327–328
 calculation, mathematical
 transformation 328–331
 measurement 378–382, 383

melanopic action factor (of visible
 radiation) 23–25

melanopic-equivalent daylight
 illuminance (MEDI) 26
 levels, for optimum sleep and daytime
 environments 28–29
 metrics 327, 328
 calculation, mathematical
 transformation for 328–331
 with RGB colour sensors
 matrix transformation in practice
 378
 value verification with colour sensor
 380, 383

melanopic effect 204
 and colour rendering index 205, 206
 factors 299–300

melanopic equivalent D65 quantities
 327

melanopic illuminance 27–28, 416, 450,
 461–462

melanopic light effects 200, 298

melanopically evaluated radiation
 quantity 298–299

melanopsin 10, 23
 containing ipRGC ganglion cells 43
 containing pigments 462

melatonin production 59

melatonin suppression 250, 251, 444,
 462
 vs. absorption, relative signal of 211

action spectrum determination, test
 conditions for 249

at night 21–23
 with circadian stimulus and
 melanopic action factor 23–25

in nocturnal hours, causes of 253–254
 during nocturnal hours with
 quasi-monochromatic light 248
 time courses of 247
 time-dependent 249–252

memory colours 111, 144–146, 172

mesopic area 10, 42

midget cells of retina 42

modern luminaires, signal and data
 structures of 341

motivation, defined 82

MSLT-30 state of well-being 116

M-system (magnocellular) 41

Multiple Sleep Latency Test 116

n

natural skin tone colours 153

naturalness 141
 colour fidelity 141–143
 modelling at 750 lx 146–149

“n-back test” 60, 276

networking technology
 components, terms, meanings, and
 applicability of 343–344
 development of 340, 341

NIF (non-image-forming) 43

night time light recommendations, for
 sleep environment 281

non-visual aspects, basics of 21–29

non-visual light effects 3, 207, 241
 daylight planning for 407–408
 in night hours with polychromatic
 white light 242–246
 in nocturnal hours with
 quasi-monochromatic light
 246–249
 processing centres and transmission
 paths for 44

numerical analysis, of brightness vs.
 non-visual metrics 451–457

O

- objectively assessed sleep behaviour 274
- objective measurement parameters, for non-visual light effects determination 59
- object-specific colour rendering indices, for white or neutral objects 125–126
- ocular media
 - optical density of 428
 - spectral transmittance 428–429
- olivary pretectal nucleus (OPN) 47
- opic-efficacy of luminous radiation 327
- α -opic equivalent daylight (D65) illuminance $E_{v,\alpha}^{D65}$ 26
- α -opic irradiance 25, 26
- α -opic quantities 326, 327
- α -opic spectral weighting function 25, 298
- opponent neural channel 11
- opponent signals 11
- optic chiasm 41
- orexinergic neurons 47
- output variables, of visual and non-visual brain processing apparatus 52–54

P

- paced Landolt ring procedure 84
- parasol cells of retina 42
- parvocellular layers 42
- Pearson's correlation coefficient, PAI and horizontal illuminance 114
- Perceived Adequacy of Illumination (PAI) 114
- perceived colour attributes 16
- perceived colour characteristics, of colour stimulus 17, 18
- perceived room brightness 227, 228
- performance-oriented influence spheres, of lighting level 81
- phantom array 232
- Phase Response Curve (PRC) 50–51, 256, 257
 - course of 50
- phase shift of night shift workers 257, 258
- photic information 44
- photopic vision 10, 12, 162, 300
- photometric parameters 19, 54, 67–68, 95, 192, 197, 205, 291, 352, 371, 413, 462
- photometry 1, 3, 11, 99
- photopic illuminance 280, 450
- photoreceptors 459
 - relative sensitivities in CIE S 026/E:2018 326
 - spectral sensitivities 23
- photosensitive cell 9
- physical sensors
 - for creating user profiles in room 342
- pineal gland, function of 45, 59
- Pittsburgh Sleep Quality Index (PSQI) 58, 59, 264, 274, 282
- Planckian curve, for CCTs 137
- Pleasure-Arousal-Dominance (PAD) model 218
 - human emotions, characterisation of 218
- position sensors 371, 372
- practical lighting engineering and planning research questions 445
- preferred horizontal illuminance levels 112–114
- processing centres and transmission pathways
 - of ipRGC signal with SCN 44–45
 - for non-visual light effects 43–48
- psychological effect, of variable lighting situations 220
 - field trial by Fleischer 221–223
 - laboratory experiment 223–227
 - research questions 221
- P-system (parvocellular) 41
- purely visual performances 81

q

- questionnaires
 - for comprehensive subjective
 - determination of indoor lighting quality 57–58
 - on sleep behaviour, sleepiness, alertness 58–59

r

- random forest (RF) method 450
- raphe-hypothalamic tract 45
- receptive field 40
- relative photoreceptor sensitivities in CIE S 026/E:2018 326
- relative spectra of modern semiconductor LEDs 37
- relative spectral radiant power of
 - blackbody radiators 16
- Relative Visual Performance (RVP) model 70, 74–77, 80, 387
- retinal circuits in humans 8
- RGB colour sensors 371
 - characterisation of 372–376
 - examples of 372–373
 - matrix transformation in practice 377–378
 - relative spectral sensitivity curves of 375
 - signal transformation method from 376, 377
 - spectral sensitivity measurement 374
- rods and cones 9, 10, 39, 448
- room preference 174
 - defined 178
 - experimental set-ups for 174–178

s

- Saccades 41
- saturation, colour attributes 16
- scene preference 174
 - equations of 183, 184
 - modelling with Circadian Stimulus 188–191

- rating scales 174–175
- visualising model in contour diagrams 188–191
- self-paced Landolt ring procedure 84
- scotopic vision 10
- semantic scaling for weighting user requirements 400
- shiftwork, lighting aspects for 254–261
- sight-independent performances 81
- signal components of human visual system 99
- skin tone illumination, colour preference
 - experiment for 154
 - light sources used, characterisation of 156–159
 - mean subjective colour preference values 159, 162
 - spectral measurement, of skin tones 154–156
- sleep behaviour
 - light intensity and timing of light exposure on 274–275
 - questionnaires on 58–59
 - and time zone 49
- sleep homeostat 51
- sleep hormone 22, 59
- sleep quality and maintenance 461
- sleepiness
 - and alertness during early shift in an industrial company, light effect on 281–283
 - during nocturnal hours with quasi-monochromatic light 248
 - questionnaires on 58–59
- Smart City 335
- Smart Lighting 463
 - with RGB colour sensors 372–384
 - technical principles of 340–349
- spatial brightness 96, 114, 174, 178
- spectral chromaticities 15
- spectral daylight measurements 314–315, 318
- spectral luminous efficiency function 12, 35–36, 39, 129, 291, 299–300

- spectral radiance $L_{\lambda}(\lambda)$ of the colour stimulus 14
 - spectral reflectance values, of white and grey (neutral) objects 125, 126
 - spectral sensitivities
 - functions 25, 26
 - of L, M and S cones 11
 - of photoreceptors/retinal mechanisms 23
 - spectra, of daylight phases 122
 - spectra, of Planckian (blackbody) radiators 122
 - spectroradiometers 14, 125, 154–155, 175, 315, 320–324, 330, 370
 - standard chromaticity coordinates 14, 16–17
 - 2° standard colour matching functions 1
 - stroboscopic effects 229–240
 - stroboscopic effects, in pulse-width modulated LED illumination
 - experimental procedure 235–236
 - experimental results
 - age distribution of test subjects 236
 - conspicuity, mean subjective ratings of 237
 - disturbance factor, mean subjective assessment of 238
 - duty cycle 238, 239
 - gender, mean conspicuity assessments according to 240
 - mean subjective ratings of conspicuity 237–240
 - experimental settings 233–234
 - parameters investigated 234
 - luminance distribution 234, 235
 - signal types used in 234
 - subjective fatigue
 - during nocturnal hours with quasi-monochromatic light 248
 - time courses of 247
 - subjectively assessed sleep behaviour 274
 - suprachiasmatic nucleus (SCN) 41, 44–47, 50, 246
- t**
- three-dimensional colour atlas 16, 17
 - time-dependent melatonin suppression 249–252
 - timer problems for night shift workers 255
 - timing system
 - chronotypes and sleep behaviour 51–52
 - entrainment 49–50
 - fundamental questions 48–49
 - PRC curve 50–51
 - twilight 10
- u**
- UCS chromaticity diagram 15
 - use cases 339, 341, 349–350, 352
- v**
- ventro-lateral preoptic nucleus (VLPO) 47
 - vision in old age 426, 431
 - visual clarity (VC) 96, 98, 174, 460
 - with achromatic and chromatic contrasts 97
 - defined 177
 - equations of 179
 - experimental set-up for subjective assessment of 100–101
 - experimental set-ups for 174–178
 - modelling 102–107
 - modelling with Circadian Stimulus 187
 - rating scales 175
 - visualising model in contour diagrams 188–191
 - visual comfort 229
 - flicker effects and 230–231
 - stroboscopic effects and 230–231, 233
 - visual cortex 8, 11, 42–43
 - visually coordinated motor performances 81
 - visual pathways in brain 41–42
 - visual performance 207
 - absolute 79

- definition 71–74
 - experimental results 91
 - influencing factors 72–74
 - model of Kokoschka 77–80
 - Relative Visual Performance (RVP)
 - model 74–77
 - visual signal processing channels 10–11
 - visual signal processing systems 38–39
 - bipolar cell layer, horizontal cells of 39–40
 - ganglion layer 40–41
 - mesopic visual sensitivity function 39
 - overall network structure 42–43
 - visual pathway 41–42
 - vividness 143
 - modelling at 750 lx 146–147
 - $V(\lambda)$ function 197, 198
 - for daytime vision 12
 - $V(\lambda)$ -weighted parameters 98
- W**
- wagon wheel effect 232
 - wake-sleep cycle 51, 59
 - wall luminance levels, for computer monitor 114–115
 - experimental method 115–116
 - filling up current state of well-being questionnaire 116
 - most comfortable display brightness at constant, typical wall luminance 116–118
 - most pleasant luminance and colour temperature with constant display luminance 118–119
 - result evaluation 119–121
 - test setup 115, 116
 - and preferred luminance ratios 114, 115
 - white chromaticity 137
 - experimental method 139
 - results 139–140
 - whiteness preference 137, 139
 - white points, industrial 137
 - white tone of light spectrum 137
 - work performance 72
 - assignment of 80–81
 - compensation phases 83
 - experimental results 91
 - generation and control, process and components for 82
 - in industrial workplaces, lighting level influence on 88–91
 - mental work, lighting level influence on 83–88
 - in office environment 81
 - stress regulation model under poor lighting 82–83
 - working and leisure time, division of 335
- Z**
- zeitgeber 49, 50

