

Index

a

- abnormal state 547, 549, 550, 559
- absorbed dose 541–543
- absorption power 299–300, 311
- absorption spectroscopy 518
- accelerator 4, 334
- accident 458
- activated corrosion products 539
- activated dust 394, 539, 552, 559
- activation products, water and air 539
- active electromagnetic wave
 - measurement 518–522
- active measurement 511–512, 522
- active particle measurement 528
- active power 484, 495, 498, 579
- active safety system 548
- actuator 506
- additional heating 273
- adiabatic equation 65
- Alcator scaling law 147
- Alfvén eigenmode 130
 - characteristics 98–99
 - dispersion relation 99–100
 - instability condition 100–102
 - stabilization method 100–102
- Alfvén wave 69, 98, 101, 130, 301–303, 338
- allowable stress intensity 212, 576
- alpha heating power 143, 144, 147
- analysis codes 563
 - design flow 563
 - detailed 567
 - equipment analysis/design codes 567
 - plasma 566–567
 - reactor design, flow of 563–566
 - reactor design system code 567–570
 - safety 567
- anisotropy 316
- annual fuel cost 580–581
- anomalous transport 116
- apparent power 484
- armor material 210, 212
- articulated boom 465
- ASDEX-H scaling 571
- as low as reasonably achievable (ALARA)
 - principle 546, 547, 552
- aspect ratio 58, 59, 64
- assembly drawing 563
- associated particle time-of-flight method 526
- atmosphere detritiation system 406, 418, 420, 422
- attached state 196, 586
- austenitic stainless steel 238, 399, 447, 450
- avalanche phenomena 133
- axisymmetric system 10–12

b

- bad curvature 64, 77
- baking 385–387
- balance of plant (BOP) cost 580
- ballooning instability
 - characteristics 78
 - energy integral 79–81
 - stabilization method 81–82

- ballooning instability (*contd.*)
 - ballooning mode 69, 78, 81, 82
 - banana orbit 115, 278, 283, 285, 286
 - banana trajectory (banana orbit) 278
 - batch system 409
 - beam ion, trajectory of 278, 279
 - beamlet 334
 - beam power 14, 283
 - beam profile control unit 334
 - bellows 390, 391
 - bending stress 575
 - beryllium, wear amount of 178
 - Bessel function 45, 75, 77, 113, 114, 359
 - β limit 127, 584
 - beta value 25, 58
 - BGK mode 34
 - biological half-life, radioactive material 543
 - biological hazard potential (BHP) 544–545
 - bioshield 432
 - bismuth-based oxide 229, 231
 - blanket 157
 - classification 181
 - configuration 181–183
 - coverage 164
 - energy multiplication factor of 165–166
 - functions required for 157, 158
 - module, maintenance 466–467
 - size 183
 - thickness 175–176
 - blanket structural material 167, 189
 - blanket tritium recovery system 405
 - blistering 444
 - Bohm diffusion 116, 118
 - boiling water reactor (BWR) 171
 - bolometer 517, 518
 - Boltzmann equation 31, 32
 - bootstrap current 25
 - neoclassical tearing mode (NTM) 88
 - ratio of 286
 - spontaneous current 286
 - trapped electron orbit and 285–286
 - bootstrap current (spontaneous current) 124
 - boundary conditions, plasma 67
 - breakdown phase 26, 28, 266
 - break even condition 22, 28
 - breeding blanket 164, 176, 181
 - Bremsstrahlung radiation 17, 145
 - bucking cylinder 575–576
 - bulk damage, reactor material 444
 - bumpy torus 13
 - bundle divertor 205, 206
 - burn control 508
 - burn phase 26–28, 155
 - burn-up fraction 148, 150
- C**
- cable in conduit conductor type (CIC type) 234
 - capture reaction 54, 165
 - carbon dioxide lasers 14
 - carbon fiber reinforced carbon composite material (CFC composite material) 202
 - cask 553
 - centering force 242, 575
 - central solenoid coil
 - coil structure 268
 - conductor design 267–268
 - cooling method 268
 - design example 268–270
 - functions of 265
 - magnetic field 266
 - power supply voltage 494
 - self-inductance 493
 - structural materials, selection 268
 - supplied magnetic flux 266–267
 - support structure 268
 - CFC composite material 211
 - charge conservation equation 65
 - charged particle beams 14
 - charge exchange recombination spectroscopy 528, 529
 - charge separation 9, 13, 70, 77, 78
 - chemical and volume control system (CVCS) 479

- chemical reaction energy 540
- chemical sputtering 442
- chilled water system (CHWS) 480
- circular corrugated waveguide 356
- classical diffusion coefficient 115
- Clemmow–Mullaly–Allis (CMA) diagram 297
- closed divertor 206, 208, 210
- closed loop control 502
- closed magnetic surface 17, 18, 192–194
- coherent nonlinear phenomena 33, 34
- coil current 239
- coil operating current 236
- coil protection 491, 495
- coil rated current 236, 239
- coil shape 242, 243
- coil structure 237, 238
- co-injection 277, 278
- cold plasma 333
- collective Thomson scattering 520, 521
- command control and data acquisition and communication (CODAC) system 530
- commercial power grid 484, 489
- commissioning 458
- committed effective dose 543–544
- committed effective dose coefficient 544
- committed equivalent dose 543
- common leg 250, 251
- Compact Reversed Shear Tokamak (CREST) 430
- component replacement, annual cost of 580
- compressional Alfvén wave (CAW) 69, 98, 303
- Compton scattering 442
- conceptual design 568
- conductance 410–412
- conductor shell 97, 183, 184, 258
- conductor structure 234
 - coil average current density 237
 - conductor design 237
 - critical current 235–236
 - limited current 236
 - stability margin 236–237
- conductor wall 96–98, 128
- confinement barrier 547, 548
 - energy damage 553–556
 - radioactive materials 552–553
- confinement improvement factor 122
- confinement of high energy particles 129, 130
- confinement time 23, 98, 113–114, 119–120
- constant-tension D-shaped coil 242, 243
- contingency factor 581
- continuous spectrum 514, 516
- controlled thermonuclear fusion reaction 4
- controlled variables 506, 508
- control methods 502, 503
- control system 20
- convection loss power 143
- conversion efficiency 338, 344
- coolant characteristics 168, 171
- coolant temperature 166, 168
- coolant, tritium 167
- cooling system
 - chilled water system (CHWS) 480
 - component 479
 - configuration of 478–480
 - cooling method 474
 - draining and refilling system 479
 - drying system 479
 - functions of 473
 - heat rejection system (HRS) 480
 - heat reservoir 474–476
 - operation mode 473–474
 - performance 476–478
- cooling tower 474, 476
- cooling type, with gas 474
- copper ratio 235
- copper stabilizer 234–236, 436, 438
- copper to superconductor ratio 235
- core plasma conditions
 - break even condition and self-ignition condition 22
 - Lawson criterion 22–24
 - typical reactor concept 24
- correction coil 97, 533

- correlation length 115, 118
 - correlation time 115
 - cost of electricity (COE) 564, 579–580
 - Coulomb collision term 317
 - Coulomb logarithm 126, 144, 147, 279, 584
 - Coulomb scattering 5, 313
 - counter-injection 277–279
 - countermeasures against disruption 135, 136, 139
 - coupling system 339, 344, 353
 - coverage 160, 164
 - critical current ratio 236, 237
 - critical energy 280, 281
 - critical fluence 444
 - cross section 161–163
 - cryogenic system 19, 22, 495
 - cryopanel area 412
 - cryopump 335, 408
 - cryostat 19
 - characteristics 426
 - design example of 429–432
 - functions of 425–426
 - structure 425–427
 - cryostat thermal shield (CTS) 432
 - current drive 274, 275
 - efficiency 25–26, 284, 313, 315, 316
 - mode 69
 - power 25, 284, 313, 318
 - current quench 131–133
 - current-sharing temperature 236, 237
 - current transformer coil 227, 262, 275, 350
 - cusplike 7
 - cutoff and resonance 292
 - cyclotron angular frequency 44, 115, 288, 305
 - cyclotron damping 299
 - cyclotron frequency 302
- d**
- daily inspection, reactor 459
 - DC electric field 318, 320
 - Debye length 194, 520
 - decay constant 160, 446, 447, 524, 541
 - decay heat 435, 446, 480, 540
 - decommissioning
 - annual cost 580–582
 - reactor 458
 - defense in depth (multiple protection) 547, 548, 552
 - degree of vacuum 385–386
 - demonstration/commercial reactor 28
 - demonstration reactor/commercial reactor 29
 - demo reactor 29
 - density limit 129, 584–585
 - density ratio 408, 527, 585
 - desired value 502, 504
 - detached state 196, 215, 586
 - detailed design 563
 - deuterium 2, 158
 - deuterium consumption 407
 - diagnostic system
 - electromagnetic wave measurements 514–521
 - passive and active measurements 511–512
 - probe measurements 512–514
 - diagnostic systems 533–535
 - diamagnetic coil 513–514
 - diamagnetic drift velocity 101
 - diamagnetic property 59
 - diamond detector 523, 526, 528
 - dielectric constant 32
 - dielectric tensor 287, 289, 303
 - diffusion
 - coefficient 49
 - by collision 114–115
 - equation 82
 - by turbulence 116–119
 - dipole magnetic field 257
 - direct cost, construction 580–581
 - direct current break (DC break) 340, 344, 353
 - direct cycle 171, 172
 - direct integration method 440
 - directional coupler 340
 - direct irradiation method 14
 - disc type 237

- dispersion relation 43, 287, 288
 - Alfvén eigenmode 99–100
 - of cold plasma 288–289
 - of hot plasma 289–290
 - kink instability 74–76
 - of plasma with Maxwell distribution 290
 - of resistive drift mode 94
 - displacement damage 179, 444–445, 450
 - disruption 130
 - causes of 133–139
 - control 509, 533–535
 - thermal load of 202
 - dissipative drift instability 95
 - divertor 17
 - cassette 468–469
 - chamber 18
 - configuration 204–205
 - plasma transport analysis 199
 - divertor characteristics
 - electromagnetic force 203
 - in non-steady state, ELM 201–202
 - runaway electron 203
 - stored energy 202–203
 - divertor design
 - conditions and items 208–222
 - cooling tube 213–214
 - design example 214–216
 - eddy current suppression structure 213
 - heat receiving plate structure 212–213
 - material selection 210–212
 - stress and strain reduction 213–214
 - divertor/limiter (DIV/LIM) PHTS 478
 - divertor plasma
 - attached state 196
 - average heat flux to divertor plate 200–222
 - characteristics 193–194
 - detached state 196
 - impurity control 200
 - particle control 200
 - reducing particle, measures for 200
 - thermal loads 200
 - two-dimensional divertor analysis
 - model 197–199
 - two point model 194–196
 - divertor plate 18, 19, 217
 - Doppler effect 515–516, 584
 - Doppler shift 515, 520, 521, 529
 - dose equivalent 541–543
 - dose limit 546, 551–552
 - dose rate 435, 441, 450
 - by Skyshine 452
 - double charge exchange reaction 332
 - double crystal spectrometer 525, 526
 - double-crystal time-of-flight spectrometer 525, 526
 - double walls 390, 394, 399, 400
 - dpa distribution 449–450
 - draft drawing 563
 - Dreicer electric field 132
 - Dreicer field 319
 - drift instability
 - density gradient 90–92
 - drift wave on plasma transport 95–96
 - resistive drift mode 92–95
 - temperature gradient 90–92
 - drift surface 115, 278
 - drift wave 90, 95–96
 - driven current 283, 284, 318
 - duty cycle 26
 - dwelt phase 26, 392
 - dyadic expression 36
- e**
- E×B drift 9
 - economic evaluation methods 579
 - cost of electricity (COE) 579–580
 - net electric power 579
 - eddy current 96–98, 134–135, 213
 - edge localized mode (ELM) 82, 102, 121
 - divertor characteristics 201–202
 - energy released 125–126
 - measures against 127
 - types of 124–125, 139
 - edge transport barrier (ETB) 121
 - effective charge 144, 145

- effective dose 542, 543
 - coefficient 544
 - equivalent 541–542
- effective half-life, radioactive material 543
- effective power 484
- effective pumping speed 386, 409–413
- Ejima coefficient 154
- elastic scattering 54
- electrical insulator 263, 271, 390
- electrical resistivity 144, 148
- electric energy reservoir 498
- electric field 31, 34
- electromagnetic force 134, 184, 392, 393
 - TF coil 573–575
- electromagnetic force generated in coil 241
- electromagnetic induction 19, 27, 28, 96, 227, 274
- electromagnetic wave measurement 514, 521
 - active 518–522
 - passive 514–518
- electromagnetic waves 43, 292, 354, 514–518
- electron Bernstein wave 312
- electron current 281
- electron cyclotron current drive (ECCD) 88, 329, 330
- electron cyclotron emission (ECE) 516, 517
- electron cyclotron heating (ECH) 26, 88, 488
- electron cyclotron range of frequency (ECRF) 310
- electron cyclotron resonance 296, 311, 312, 351
- electron cyclotron wave (ECW) 310, 311
 - absorption power 311
 - excitation method 351–352
 - injection system (launcher) 355
 - propagation path 311–312
 - required functions 350
 - resonance and cut off 311
 - RF source 354–355
 - specifications 356–358
 - system configurations 353–354
 - system efficiency 352
 - transmission system 355
- electron-ion energy equipartition time 144
- electron pair production 442
- electron temperature gradient instability 92
- electrostatic approximation 33
- electrostatic probe 511–513
- electrostatic wave (longitudinal wave) 295
- ellipticity (elongation) 64
- embossed panel 218–220
- emergency power supply 480, 495, 554
- energy balance 142
- energy balance equation 583–584
- energy confinement 119
- energy confinement time 23, 114
 - parameter dependence of 119–120
- energy conservation law 39
- energy density 36, 48
- energy driver 14
- energy flux vector 36–37
- energy integral 68–69
- energy multiplication factor 21, 165–166
- energy relaxation time 143, 279–281
- energy reservoir 26, 498, 535
- energy sources 1, 3
- enrichment rate 164, 177, 178
- epithermal neutrons 442, 522
- E-plane junction 346, 347
- equation of continuity 37–38
- equilibrium equation 59, 61
- equipment analysis/design code 567
- equivalent dose 542, 543
- equivalent fixed charge rate on capital 579
- error field 134
- ETG mode 92
- Evaluated Nuclear Data File Version B (ENDF/B) 440
- event analysis 550, 556–558
- excimer lasers 14

- exhaust duct 397, 410–412
 - experimental reactor 29, 222, 330, 473
 - exposure dose 541
 - extensional force 241, 242
 - external air cooling type 474
 - external kink mode 77
 - extraordinary wave (X-mode) 297, 306, 311, 312, 338, 351
 - ex-vessel transport system 463, 468
- f**
- facility design 563
 - failure criticality 469
 - failure mode and effect analysis (FMEA) 550
 - Faraday effect 519
 - Faraday shield 338, 342
 - fast neutrons 442, 522
 - fast wave 294, 304–306
 - fast wave current drive (FWCD) 327, 328
 - Fault Tree Analysis (FTA) 550
 - feedback control 258, 502–504
 - feedforward control system 502
 - flexible plate 393
 - field reversed configuration (FRC) 9, 10
 - field reversed mirror (FRM) 9, 10
 - finite Larmor radius effect 306, 351
 - first wall 17
 - classification 219
 - design example 220–221
 - features 220
 - particle load 217–218
 - structure 218–220
 - thermal load 217–218
 - fishbone oscillation 77, 102
 - fission reactors 546–547, 582
 - fixed mirror 357
 - flow of kinetic energy 37
 - flute instability 77
 - flywheel 489, 579
 - focusing mirror 355
 - foil activation detector 524
 - Fokker–Planck equation 281, 282, 316, 317, 320, 321, 323
 - force balance equation 57
 - forced flow cooling method 233, 234
 - fossil fuel 1
 - Fourier–Laplace transformed 47
 - Fourier transform 39, 116
 - frequency gap 100
 - fuel clean up system 405, 414–416
 - fuel cycle system 22, 148, 387
 - fueling amount 407–408
 - fueling method 407
 - functions required for 405–406
 - fueling system 407–408
 - fuel purification system 405
 - fuel storage system 405, 419, 423
 - fuel supply scenario 22
 - full width at half maximum (FWHM) 515
 - fully detached state 196
 - function-specific coil systems 258–260, 485
 - fusion experimental reactor 501
 - fusion–fission hybrid reactor 24
 - fusion power control 508
 - fusion power generation 175, 176
 - fusion power shutdown system (FPSS) 530
 - fusion reaction rate 5–6
 - fusion reactivity 6, 23
 - fusion reactor 438
 - coils 227–228
 - cross section of 4–5
 - energies contained in 540
 - energy classification 1–2
 - energy consumption 1–2
 - nuclear fusion power generation 2–3
 - nuclear reaction used 4
 - operation period of 458
 - structure 19–20
 - fusion triple product 25, 124
- g**
- Galeev–Sagdeev diffusion coefficient 115
 - gas exhaust system
 - configuration 409
 - cryopanel area 412

- gas exhaust system (*contd.*)
 exhaust time 413
 helium accumulation on cryopanel
 412–413
 helium pumping speed 411–412
 initial ultimate pressure 409–411
 plasma vacuum 408–409
 by source 408
 gas puffing 407
 general public (the public) 157
 glass lasers 14
 Goldston scaling 571
 good curvature 64, 77, 78
 Grad–Shafranov equation 61
 Greenwald density 129, 584, 589
 Greenwald–Hugill–Murakami parameter
 129
 grid resistor 491
 group velocity 291
 Gyro-Bohm diffusion 118–120, 124
 gyrotron 345, 352–356
- h**
- half-life 159
 halo current 131, 132, 135, 136, 203
 Hasegawa–Mima equation 95
 heat exchanger 474
 heat flux 37, 220
 heat receiving area 200, 202, 215, 586
 heat receiving surface 193, 200, 203, 212,
 217, 218
 heat rejection system (HRS) 478, 480
 heat reservoir 26, 275, 474–476, 487
 heat sink material 210, 212
 heat transfer model 587–588
 heavy ion beam probe (HIBP) method
 529
 heavy ion beams 14, 529
 heliotron 12
 helium accumulation rate 149, 411, 412
 helium production 177, 179, 450
 helium pumping speed 411, 412
 Hermitian operator 68
 hexapole magnetic field 257
 high n ballooning mode 81, 82
 high poloidal beta mode 123, 129
 high temperature irradiation
 embrittlement 445
 H mode (high confinement mode) 120,
 204
 hoop force 62
 horizontal pulling out 462
 hot cell building 469
 hot cell maintenance method 462, 463
 hot cell room air atmosphere detritiation
 system (HC-ADS) 423
 hot isostatic pressing (HIP) 555
 hot plasma 289–290
 H-plane junction 346
 hybrid coil system 258–260, 262, 485
 hybrid matrix 262
 hybrid wave 297
 hybrid wave mode (HE mode) 355
 hydroelectric power energy 1
 hydroelectric power generation 2
 hydrogen embrittlement 445
 hydrogen gas clean up system 423
 hydrogen isotope separation system 405,
 416, 418, 422
 hysteresis loss 231–233, 235
- i**
- ice pellet 136, 137
 ideal magnetohydrodynamic
 approximation 82, 151
 ideal magnetohydrodynamics 66
 ideal MHD equation 39, 66–67
 ideal mode 82
 ideal PID controller 505
 ideal wall beta limit 96
 ideal wall MHD limit 96
 improved confinement mode 122, 124
 impulse response 504
 impurities 191
 impurity contamination model 586–587
 incident 552, 557
 incoherent Thomson scattering 520–521
 indentation 64
 independent leg 250
 indirect cost, construction 580

- indirect cycle 171–173, 175
 - induced activity 435, 446–447
 - inductive current drive 26, 274, 486
 - inelastic scattering 54
 - inertial confinement fusion (ICF) 13–15
 - infrared imaging video bolometer (IRVB) 518
 - initial capitalized investment 579, 580
 - initial loading 159
 - injection direction 276
 - injection system 340
 - in-service nondestructive inspection 401
 - intake time 543
 - interchange instability 77
 - interferometry 518–519
 - ITER grade (IG) 216
 - interlock system 530–531
 - intermediate neutrons 442
 - internal conductor system 12
 - internal energy density 36
 - internal inductance, of plasma 62
 - International Thermonuclear Experimental Reactor (ITER) 201
 - International Tokamak Reactor (INTOR) 204
 - internal kink mode 77, 102
 - internal transport barrier (ITB) 123, 342
 - interstitial atoms 445
 - INTOR/Alcator scaling 571
 - inverse aspect ratio 59
 - inverse scattering method 34
 - in-vessel maintenance method 461–463
 - in-vessel transport system 463, 465, 466, 469
 - ion Bernstein wave 306, 338
 - ion current 281, 282, 334
 - ion cyclotron range of frequency (ICRF) 303, 337
 - excitation method 338
 - required functions 337
 - specifications 341
 - system efficiency 338
 - ion cyclotron resonance 296
 - ion cyclotron resonance heating (ICRH) 152
 - ion cyclotron wave
 - design requirements 337–338
 - system configuration 339–340
 - ion cyclotron wave (ICW) 303, 306
 - ionization action 522
 - ionization chamber 523
 - ionization phenomena 522–523
 - ion temperature gradient instability 92
 - irradiation amount 444
 - irradiation creep 444
 - irradiation embrittlement 444
 - irrational surface 71
 - isobaric surface 58
 - isotope chemical exchange 416
 - ITER divertor 216, 467–468
 - ITER 89P scaling law 121
 - ITER test blanket 186, 188, 189
 - ITER vacuum vessel 398, 399
 - ITG mode 92, 95, 118
- j**
- Japanese Evaluated Nuclear Data Library (JENDL) 440
 - jelly-roll process 230
 - JET neutron profile monitors 527
 - Joint Evaluated Fission and Fusion File (JEFF) 440
 - Joule heating 485
 - Ohmic heating 273
 - power 144, 273, 584
- k**
- Kaye–Goldston scaling law 120
 - killer pellets 137
 - Kinetic Energy Released in Materials (KERMA) 441
 - kinetic equation 39–41, 43, 52
 - kink ballooning mode 81, 97
 - kink instability
 - characteristics 74
 - dispersion relation 74–76
 - stabilization method 76–77
 - kink modes 69, 509
 - klystrons 344, 345
 - Korteweg–de Vries equation 34

L

- Landau contour 41
- Landau damping 41, 43, 298, 306, 344
- Langmuir wave 43
- Laplace transform 40, 503
- large amplitude electric field 34
- Larmor motion 295, 306, 351, 354
- Larmor radius 9, 115, 118, 120, 306, 351
- laser induced fluorescence (LIF)
 - measurement 521
- laser spectroscopy 518
- launcher 339, 340
- Lawson criterion 22–24
- leak before break (LBB) 401, 556
- left-handed cut off 304–305
- left-handed polarized wave 293, 305
- L–H transition 121, 122
- LIDAR Thomson scattering 521
- light detection and ranging (LIDAR) 521
- light ion beams 14, 273
- limited current ratio 236
- limiter 17
- limiter and divertor 192, 193
 - divertor shape 206–208
 - limiter and pumped limiter 204
 - pumped limiter 205
 - shape and type 203–204
 - single null divertor and double null divertor 206–222
- linearized kinetic analysis
 - one dimension 41–43
 - three dimensions 43–46
- linearly polarized wave 294
- linear system (open end system) 7–9
- line radiation 145, 147, 584
- line spectrum intensity 516
- Liouville's theorem 31
- liquid breeder blanket 185–187
- liquid cooling type 474
- liquid helium 228, 233, 238, 246, 408
- liquid phase chemical exchange (LPCE) 417
- lithium, wear amount of 177–178
- L mode (low confinement mode) 120, 204
- local heating 88, 89
- local tritium breeding ratio (local TBR) 164
- locked mode 103
- longitudinal wave 295–297
- long-term storage 420
- loop antenna 338, 340
- loop voltage 151
- Lorentz force 83, 134, 241
- lower hybrid current drive (LHCD) 88, 152, 328, 329
 - one-dimensional analysis 318
 - two-dimensional analysis 320
- lower hybrid wave (LHW) 297, 307
 - accessibility condition 309–310
 - excitation method 343–344
 - multi junction launcher 346–347
 - PAM launcher 347
 - phase shifter 347–350
 - resonance and cut off 307–309
 - RF source 345
 - specification 349
 - standard launcher 346
 - system configuration 344
 - system efficiency 344
 - transmission system 345–346
- low radioactivation 176
- luminescence phenomenon 523–524
- L wave 304

m

- Mach–Zehnder interferometer 519
- macroscopic cross section 5, 54
- macroscopic physical quantity 35
- magnetic confinement 7
- magnetic energy 540
- magnetic field 31, 57, 83
 - decay index (n-index) 71
 - with magnetic shear 83
- magnetic field configuration 256, 257
- magnetic flux 152, 266–267
- magnetic flux density 31
- magnetic island evolution equation 86–88
- neoclassical tearing mode (NTM) 89

- tearing mode 88–89
 - magnetic island width 85–86
 - magnetic loop 513
 - magnetic mirror 277
 - magnetic moment 277
 - magnetic probe 513
 - magnetic recoil proton spectrometer 526
 - magnetic shear 71, 78, 83
 - magnetic surfaces 17, 58
 - magnetohydrodynamic equation (MHD)
 - 64
 - control 509–510, 535
 - energy conservation law 39
 - energy density 36
 - energy flux vector 36–37
 - instability 69
 - internal energy density 36
 - macroscopic physical quantity 35
 - mode 69–71
 - momentum conservation law 38
 - momentum flow tensor 36
 - particle number conservation law 37–38
 - pressure tensor 36
 - magnetomotive force 239
 - magnetosonic wave 303
 - magnetron 345
 - magnet system 227
 - maintenance device failure 469
 - maintenance method
 - remote maintenance method 180
 - wear amount and replacement frequency 179–180
 - maintenance scenario 461
 - manipulated variables 506
 - manufacturing design 563
 - mass conservation equation 65
 - mass flow rate 477
 - material accountancy of tritium 406, 420
 - maximum magnetic field 236, 245
 - Maxwell distribution 32
 - Maxwell's equations 31, 57, 64, 65, 72, 95, 142
 - mean free path 275, 276
 - mechanical limiter 204
 - Meissner effect 228
 - MgB₂ 231
 - MHD stability
 - energy principle 67–68
 - linearized ideal MHD equation 66–67
 - MHD equation 64–66
 - Michelson interferometer 519
 - microscopic cross section 54
 - minimum magnetic field 7
 - minor failure, reactor 459
 - minority heating 306
 - Mirnov scaling 571
 - mirror magnetic field 7
 - mirror ratio 7
 - miter bend 346
 - mode converter 349, 350
 - molybdenum alloy 167
 - momentum conservation law 38
 - momentum flow tensor 36
 - momentum of wave 315, 316
 - monoblock type 213
 - Monte Carlo method 198
 - motional Stark effect (MSE) 529
 - multi junction launcher 346–347
 - multilayer thermal insulator 428, 432
 - multivariable system 506
 - mutual inductance 492
- n**
- natural circulation mode 480
 - Nb₃Al 230–231
 - NBI current drive
 - driven current 281–282
 - efficiency 282–285
 - shine through rate 284
 - NBI heating 275–281
 - NBI PHTS 478
 - NBI system 405
 - Nb₃Sn 230
 - negative ion generator 332, 334
 - negative ion NBI 332
 - negative ion source 332–334, 337
 - negative magnetic shear type 123
 - neo-Alcator scaling 571
 - neoclassical diffusion 115, 116

- neoclassical scaling law 147
 - neoclassical tearing mode (NTM) 88, 129
 - bootstrap current 89
 - characteristics 88
 - magnetic island evolution equation 89
 - stabilization method 89
 - net electric power 20
 - net tritium breeding ratio 164
 - neural network 135, 136
 - neutralization cell (neutralizer) 334
 - neutralization efficiency 330, 331
 - neutral particle analyzer (NPA) 528
 - neutral particle beam
 - attenuation method 528
 - ionization of 275–276
 - scattering method 528
 - neutral particle beam injection (NBI) 273
 - beam transport system 334–335
 - design example 335–336
 - design requirements 330–331
 - negative ion source 332
 - system configuration 331–332
 - neutral particles 18, 527–528
 - neutron energy spectrometers 524–525
 - neutron fluence 445
 - neutron flux 163, 164, 449
 - distribution 53
 - and gamma ray flux 440
 - neutron multiplier materials 163
 - neutron profile 526–527
 - neutron source, intensity 440
 - neutron transport analysis
 - interaction between neutrons and materials 54
 - transport equation 53–54
 - neutron wall loading 177
 - non-axisymmetric system 12–13
 - non-fossil fuel 1
 - noninductive current drive 274, 313, 314
 - nonlinear Langmuir waves 34
 - nonlinear wave-particle interaction 52
 - non-planar magnetic axis 12
 - nonuniform plasma 300–301
 - normalized beta 128
 - normalized current drive efficiency 314, 315
 - normal operation, reactor 458
 - no rotational transform system 9–10
 - n-p reaction 522, 524, 525
 - NTM control 532
 - nuclear damage 179
 - nuclear data 440
 - nuclear design
 - design example 448–453
 - dose rate 441
 - items required for 435–437
 - nuclear heating 441–442
 - radiation damage 442–447
 - radioactive waste 447–448
 - nuclear fission
 - energy 1
 - power generation 2–3
 - power plant 170
 - reactions 3
 - nuclear fusion power generation 2–3
 - nuclear heating 233, 436, 441–442, 452, 586
 - nuclear reactions 526
 - composition change due to 446
 - used fusion reactor 3–4
 - nuclear transmutation 54, 436, 444–446
 - null point (X point) 193
 - number of coils 239, 241
- O**
- Ohmic heating coil 227
 - Ohm's equation 65, 150
 - once-through cycle 172
 - Onsager reciprocal relations 290
 - open divertor 206, 209, 210
 - open-end system 7
 - open loop control 502
 - open magnetic surface 17
 - operation and maintenance
 - annual cost of 580–581
 - design examples 466–469
 - frequency 461–466
 - functions required for 457–458

- inspected and maintained, equipment 459–461
 - in-vessel transport system 465
 - operation period 458–459
 - remote maintenance method 461–463
 - remote maintenance process 463
 - operation control and diagnostic systems 501–502
 - operation control system
 - central 507
 - interlock level 530–531
 - plant 530
 - plasma control 507–535
 - operation scenario 26–28
 - optimized scaling 571
 - ordinary wave (O-mode) 296
 - outermost magnetic surface 192
 - output efficiency (duty cycle) 26
 - oversized circular corrugated waveguide 353
 - overturning force 242, 575
- p**
- palladium diffuser 415
 - PAM launcher 347
 - pancake type 237
 - paramagnetic property 59
 - parametric instability 34
 - part drawing 563
 - partially detached state 196
 - particle balance equation 582–583
 - particle balances 141
 - particle confinement time 113, 114, 146, 148, 200, 443, 444
 - particle diffusion coefficient 113–114
 - particle drift 9, 77
 - particle measurement 522, 535
 - particle number conservation law 37–38
 - passive electromagnetic wave
 - measurement 514
 - passive measurements 511
 - passive particle, neutron number 522–524
 - passive safety system 548
 - pedestal 121, 124–126
 - peeling ballooning mode 81
 - peeling mode 81
 - pellet injection 127
 - periodic inspection, reactor 458, 459
 - perpendicular injection 276
 - PF coil
 - current 260–262
 - number of 260
 - position 260
 - power supply capacity 578
 - specifications 264
 - systems 259
 - Pfirsch–Schlüter diffusion coefficient 115
 - phase average 46, 48, 52
 - phase locked state 103
 - phase shifter 340, 347, 348, 350
 - phase velocity 291
 - photodetachment neutralization method 334
 - photoelectric effect 442
 - physical half-life, radioactive material 543
 - physical sputtering 442
 - piping cutting/welding tool 469
 - piping resistance 410
 - plant availability 444, 457, 580
 - plant efficiency 21–22
 - plasma analysis
 - code 566–568
 - external electromagnetic field 33
 - main plasma theories 33–35
 - nonlinear effects 33
 - numerical simulation 33
 - velocity information 33
 - plasma circuit 150, 152
 - plasma confinement 7, 8, 113
 - plasma control
 - disruption control 509–511, 535
 - fusion power 508–509
 - MHD control 509
 - plasma cross section 63, 64
 - plasma cross section, shape of 129
 - plasma current 59, 142
 - channel 150

- plasma current (*contd.*)
 - drive system 19
 - profile 128
- plasma design 141
- plasma disruption 495
- plasma dynamics evaluation 582
 - analysis example 588–590
 - beta limit 584
 - density limit 584–585
 - energy balance equation 583–584
 - heat transfer model 587–588
 - impurity contamination model 586–587
 - nuclear heating rate distribution 586
 - particle balance equation 582–583
 - thermal load 585–586
- plasma experimental data 568
- plasma facing components 17
 - impurity control 191
 - plasma particle control 191–192
 - thermal treatment 192
- plasma facing wall 191
- plasma frequency 302
- plasma heating 273
 - by energy relaxation 279–281
 - methods 273, 306–307
 - principle of 297–300
 - system 19
- plasma heating and current drive system (H&CD) 497–498
- plasma ignition method 389
- plasma inductance 62
- plasma operation
 - current, position and shape 532
 - disruption control 533
 - normal operation scenario 531–532
 - NTM control 532
 - RWM control 533
- plasma positional instability 71, 73
- plasma pressure 57, 59, 128
- plasma resistance 151, 388
- plasma rotation velocity 97
- plasma shut-down phase 26
- plasma start-up phase 26
- plasma stored energy 145
- plasma temperature and density 146, 148
- plasma transport 113, 116
- plasma vacuum exhaust system 387, 405, 409, 410
- Poisson equation 39
- polarimetry 519
- polarization converter 354
- polarized light 292
- polarized wave 292
- poloidal beta value 59
- poloidal divertor 204–206
- poloidal limiter 204
- poloidal magnetic field 9, 59, 62, 63, 258–259
- poloidal magnetic field coil
 - coil structure 263
 - conductor design 263
 - control of plasma position and shape 257–258
 - cooling method 263
 - current control of 256
 - design example 264
 - functions of 254–255
 - magnetic field configuration 256–257
 - mutual inductance 492
 - plasma position and shape 255
 - position of 256
 - power supply capacity 494
 - power supply system 492–495
 - self-inductance 492–493
 - stored energy 495
 - structural materials, selection 263
 - support structure 264
- pool boiling cooling method 233–234
- positive ion NBI 331
- positive magnetic shear 123
- power balance (energy balance per unit time) 570–571
- power balances 142
- power factor 484
- power flow 17–18, 20–21
- power generation blanket 181
- power generation efficiency 20, 166–168
- power generation method 171–172, 175

- power reactor 29
 - power supply capacity 494, 578–579
 - power supply system
 - capacity 483–484
 - characteristics 483–489
 - coil configuration 488–489
 - design example 495–498
 - equipment and facilities 484
 - functions required for 483
 - poloidal magnetic field coil 492–495
 - reduce coil capacity 485–488
 - toroidal magnetic field coil 489–492
 - power supply voltage
 - central solenoid coil 494
 - toroidal magnetic field coil 490–491
 - practical interference type PID controller
 - 506
 - preferential sputtering 442
 - preionization 389
 - pre-sheath 194
 - pressure tensor 36
 - pressurized water reactor (PWR) 171
 - primary coolant processing system 405
 - primary cooling system 474
 - primary energy 1
 - primary first wall/blanket (PFW/BLK)
 - PHTS 478
 - primary heat transfer system (PHTS)
 - 478
 - primary knock-on atom (PKA) 444
 - principal value 42
 - principle of the transformer 274
 - production design 563–566
 - proportional counter 523
 - proportional-integral-differential (PID)
 - controller 505
 - ideal 505
 - practical noninterference type
 - 505–506
 - protection resistor 491–492
 - proton ratio 332
 - prototype reactor 29, 501
 - pulsed power distribution system 495
 - pulse height analysis (PHA) 528
 - pulse operation 26
 - pulse reactor 486
 - pumping speed 411
 - effective 409, 411
 - vacuum pump 410
 - pumping speed, of particles 211
 - pure-tension D-shaped coil 242
- q**
- quadruple vacuum tube 338
 - quadrupole magnetic field 257
 - quality factor 542
 - quasi-linear theory 34, 46, 47, 49, 116
 - quasi-optical transmission 353–355
 - quasi-steady state operation 27, 267
 - quench 228
 - of PF coils 495
- r**
- radial build 571–572
 - radiation by impurities 18
 - radiation loss power 145
 - radiation shield 394, 577
 - air and cooling water activation 439
 - analysis code 440
 - analysis procedure 440–441
 - equipment and biological 437–439
 - evaluation method 440–441
 - function 175
 - installation position 438–439
 - neutron source 440
 - nuclear data 440
 - radiation weighting factor 543
 - radiation workers (the workers) 20, 157,
 - 386, 435, 458, 530, 544
 - radioactive materials 540
 - absorbed dose 541
 - biological hazard potential (BHP)
 - 544–545
 - committed effective dose 543–544
 - confinement 553
 - confinement of 394–395
 - dose equivalent/effective dose
 - equivalent 541–542
 - equivalent dose/effective dose
 - 542–543

- radioactive materials (*contd.*)
 - exposure dose 541
 - radioactivity 540–541
 - tritium concentration limit 544–561
- radioactivity 540, 541
- radio frequency wave (RF) heating 273
- random noise 35
- random phase approximation 48
- rapid heating, quenching and transformation (RHQT) 230
- rational surface 71
- Rayleigh–Taylor instability 77
- ray trace method 300
- react and wind 230
- reactive power 484
- reactor conceptual design 568
 - bucking cylinder 575–576
 - power balance (energy balance) 570–571
 - power supply capacity 578–579
 - radial build 571–572
 - radiation shield 577
 - TF coil electromagnetic force 573–575
 - TF coil shape 573
 - vertical shield 577–578
 - volt-second 572–573
- reactor design flow
 - constraints, clarification 565
 - construction 564–565
 - economic evaluations 566
 - plant design 566
 - plasma design 565
 - power requirements 564
 - reactor structure design 566
 - safety design 566
- reactor design system code
 - code role 567–568
 - system code 567–568, 570
- reactor structure
 - magnetic flux, operation 153–154
 - magnetic flux to be supplied 154–155
 - maintenance method 457–458
 - radial build 152–153
- recharge phase 27
- recoil proton counter telescope 525, 526
- reconnection 83
- recycling rate 148
- reductive perturbation method 34
- reflectometry 519
- refractive index 287, 292
- relative biological effectiveness (RBE) 542
- relativistic effect 323–324
- relativistic electron beams 14
- remote maintenance 180, 184, 458, 461, 462
- renewable energy 1
- renormalization theory 35
- required functions 342
- residual ion bending magnet 335
- residual ion dump 335
- residual resistance ratio (RRR) 236
- resistive ballooning mode 125
- resistive bolometer 517
- resistive drift mode 92–95
- resistive instability 82, 83
- resistive interchange mode 125
- resistive mode 82
- resistive wall instability
 - characteristics 96–97
 - stabilization method 97–98
- resistive wall mode (RWM) 77, 96
- resonance 292
- resonant magnetic perturbation (RMP) 127, 203
- resonant rational surface 71
- resonant surface 69, 71
- reversed field pinch (RFP) 11
- RF amplifiers 338, 344–345
- RF current drive 313
- RF heating 287, 314
- RF source 339
- RF Waves
 - cutoff and resonance 292
 - phase velocity and group velocity 291
 - polarization 292–294
 - propagation of 293–297
- ribbed panel 219
- ridge waveguide 340
- right-handed cut off 296, 304–305

- right-handed polarized wave 293
- Rogowski coil 512, 513
- root mean square error (RMSE) 121
- rotating shear 96
- rotational transform 70
 - angle 9, 70, 71
 - system 10–13
- roughing pump 408, 409, 413
- runaway electron 131–133
- R wave 305
- RWM control 533

- S**
- saddle type 213
- safety
 - analysis code 558, 567
 - design 548–550, 555–556
 - design example 551–558
 - evaluation, fission reactor 550
 - factor 71
 - features 545–551
 - radioactive material 540–545
 - requirements 539–540
- safety goal
 - emergency exposure situation 547
 - normal time 546–547
- sausage instability 74
- sawtooth oscillation 77, 102
- scaling law 120, 122
- scheme drawing 563
- scintillation detector 524
- scrape-off layer 17
- scrape-off plasma 17
- screw tube 214
- secondary cooling system 172, 173, 474, 476
- secondary energy 1
- secondary neutrons 435, 440
- second stability region 82
- self-adjoint operator 68
- self-ignition condition 22
- self-inductance 62
 - central solenoid coil 493
 - poloidal magnetic field coil 492–493
 - toroidal magnetic field coil 489
- self-sputtering 442–444
- semicircular tubes with plate 219
- semi-closed divertor 206, 209
- separatrix 17
- sextupole magnetic field 257, 258, 260
- shear Alfvén wave (SAW) 69, 98, 303
- shear key 249, 250
- shear panel 249, 250
- shear parameter 81
- sheath 194, 195
- sheath condition 198
- sheath heat transfer coefficient 195, 198
- shell effect 152
- shield blanket 181
- shine through rate 283, 284
- short-term storage 420
- SiC/SiC composite materials 167
- simple equipment evaluation equations 565
- simple mirror 7
- simply plasma 17
- single failure criterion 548
- Si semiconductor detector 523, 525
- skyshine 437, 439, 452
- SlimCS 429
- slow wave 294, 304, 305
- Sn method 440
- Sokhotski–Plemelj theorem 42
- solenoid type 237
- solid breeder blanket designs 186
- solid state lasers 14
- solitons 34
- sound velocity 194, 198
- sound wave 69
- specific radioactivity 541
- spectral gap 329
- spherical torus 10
- spheromak 11
- spontaneous current 25
- sputtering 442, 443
 - erosion 210
 - ions 194
 - yield 443
- stability condition 100–102
- stabilizing material (stabilizer) 232

- stagnation point 193
 - standby room air atmosphere detritiation system (S-ADS) 423
 - standing wave 291
 - STARFIRE 214, 215
 - Stark effect 516
 - steady state electric power network 495
 - steady state operation 28, 486–488
 - steady state reactor 486
 - steady state tokamak reactor (SSTR) 429
 - steering mirror 356, 357
 - stellarator 12
 - step response 504
 - stored energy 133, 491, 495
 - streaming 435–437, 439
 - stress accelerated grain boundary oxidation (SAGBO) 247
 - stress analysis 238
 - stress intensity, allowable 576
 - strike point 193
 - strong turbulence 34
 - strong turbulence theory 53
 - stub tuner (stub matching device) 340
 - subignition 22
 - subsystem control system 530
 - superconducting coils 82, 227, 228
 - stored energy 554
 - thermal load 233
 - superconducting materials 228–230
 - superconducting wire
 - cooling performance 232
 - hysteresis loss 231–232
 - manufacturing method of 229
 - stabilizing material (stabilizer) 232
 - twist 232
 - superconductivity 228, 485–486
 - superconductor 228
 - supercritical pressure helium (SHe) 233
 - superfluid state 233
 - supervisory control system (SCS) 530
 - support thermal shields (STS) 432
 - super shot 123
 - surface damage, radiation 442
 - surface dose rate 448
 - surface generation method 332
 - surface occupation rate 164
 - swelling 445
 - swirl tube 214
 - synchrotron radiation 18, 145, 514, 583
 - system code 568
 - system efficiency 25
- t**
- T-11 scaling 571
 - tandem mirror 7, 8
 - tangential injection 277
 - tapered waveguide 352, 353
 - tearing mode
 - basic equations 84–85
 - characteristics 83–84
 - magnetic island evolution equation 86–88
 - magnetic island width 85–86
 - stabilization method 88
 - temperature profile 168, 170
 - tensile stress 212, 242, 574–576
 - test blanket module (TBM) 220
 - tetrode 338, 339
 - TF coil
 - electromagnetic force 573–575
 - power supply capacity 578
 - shape 573
 - start-up time 578
 - thermal conduction loss power 143
 - thermal conductivity 37, 168, 173, 195, 198, 212, 221
 - thermal cycle 487, 579
 - thermal diffusion coefficient 114, 121, 143, 169
 - thermal efficiency 20, 21
 - thermal energy 131, 165, 166, 171, 540, 553
 - thermal fatigue 26, 179, 275
 - thermalization 279
 - thermal load 133, 173, 232, 233, 347
 - divertor plasma 200
 - first wall 217–218
 - on plasma facing wall 585–586
 - thermal neutrons 442, 522

- thermal quench 131–133, 202
- thermal shield (TS) 425, 429, 432
 - panel 432
 - plate 428
- thermal transport barrier 121, 123
- thermonuclear fusion reaction 4
- θ pinch 7
- Thomson scattering 520–521
- three arc approximation 243, 244
- three-dimensional circuit 344
- time of flight method 525–526
- tissue weighting factor 543, 544
- tokamak 10, 17
 - cooling water system 478
 - equilibrium 61, 63
 - exhaust processing system 422
- toroidal Alfvén eigenmode (TAE) 100, 509
- toroidal β value 58
- toroidal divertor 205, 206
- toroidal field ripple 239, 240, 386, 391, 400
- toroidal limiter 204
- toroidal magnetic field 9, 241
- toroidal magnetic field coil 239, 241
 - centering force, support structure for 247–248
 - coil case (coil container) material 247
 - coil structure 246
 - conductor design 246
 - conduit (jacket) material 247
 - cooling method 246
 - current 233, 263
 - damping time 491
 - design example 249–254
 - gravity support structures of 250
 - overturning force, support structure for 249
 - power supply system 489–492, 496–497
 - power supply voltage 490–491
 - protection resistance in 491–492
 - radial plate material 247
 - self-inductance 489
 - specifications 251
 - start-up time 486–488, 490
 - stored energy in 241
 - structural materials, selection 246
- toroidal magnetic field ripple 130, 239
- toroidal peaking factor 135, 136
- toroidal ripple ratio 239, 240, 279, 391
- toroidal system 9
- torque ring 249, 250
- torsatron 12
- torsional Alfvén wave 303
- total capital cost 579
- transfer function 503
- transformer, principle of 274
- transition thermal shields (TTS) 432
- transit time damping 298–299, 306
- transmission system 339–340, 344–346, 349, 350, 353, 355
- transport carriage 465, 466
- transport equation 53–54
- transverse electric wave mode (TE mode) 355
- transverse magnetic wave mode (TM mode) 355
- transverse wave 295, 296
- trapped condition 277, 278
- trapped effect 324, 327
- trapped electron orbit 285–286
- trapped particle 278
- traveling wave 291, 340
- tritiated water 414
- tritium 2, 405, 539
 - breeding material 161, 189
 - cooling and gas recovery 184
 - decay constant of 160
 - doubling time 159–160
 - initial loading 159
 - inventory 159
 - material accountancy of 420
 - production 157–159
 - recovery of 165
 - temperature of breeder and multiplier materials 166

- tritium breeding material 20
 - tritium breeding ratio (TBR) 159
 - improvement of 160, 164
 - ${}^6\text{Li}(n, T)\alpha$ reaction 161
 - ${}^7\text{Li}(n, n'T)\alpha$ reaction 161
 - tritium concentration limit 544–561
 - tritium doubling time 22
 - Troyon factor 128
 - Troyon scaling 127
 - tubes with plate 219
 - tungsten material 202
 - tunneling effect 309
 - turbo molecular pump 335, 408
 - turbulence 35
 - turbulence theory 49–53
 - turbulent transport 34
 - twist 232
 - two-dimensional divertor analysis model
 - 197–199
 - two-point model, of stagnation point
 - 194
- U**
- ultra-high vacuum 386, 387, 398, 399
 - untrapped particle 278, 279
 - upper hybrid resonance 311, 312
 - upper hybrid wave 297
- V**
- vacancy 445
 - vacuum exhaust pump 408–409
 - vacuum exhaust system 19, 335
 - vacuum vessel (VV) 19, 385
 - assembly 395–401
 - degree of vacuum 385–386
 - design example 398
 - design items 396
 - electrical resistance 390–391
 - electrical resistance of 387–390
 - flexible support 401
 - functions required for 385–386
 - high temperature baking 387
 - maintenance 395–401
 - PHTS 478
 - plasma position control 391
 - secure method of electrical resistance of 390
 - structural standard 396
 - support method 393
 - surface cleaning system 399
 - thin-walled structure 390
 - toroidal field ripple 391
 - vacuum vessel thermal shield (VVTS)
 - 432, 577
 - vanadium alloys 167
 - vapor phase chemical exchange (VPCE)
 - 417
 - vapotron 214, 335
 - vehicle 465
 - vertical build 573, 577, 578
 - vertical displacement event (VDE) 131, 132
 - vertical magnetic field 63, 257, 258
 - vertical pulling out 462
 - vertical shield 577–578
 - Vlasov equation 31–34, 39, 40, 43, 46, 49, 53
 - volt-second 154, 572–573
 - volume flow rate 477
 - volume generation method 332–334
 - VV pressure suppression system (VVPSS)
 - 553, 554
- W**
- wall locked state 103
 - waste disposal 550, 551, 580–582
 - water detritiation system 405, 414, 418, 419, 423, 474
 - waveguide array 343, 347
 - wave kinetic equation 34, 52
 - wave number vector 44, 71, 83, 287, 288, 294–296
 - wave-particle interaction 51, 52
 - wave propagation 292, 300, 301, 303, 351
 - wave-wave (3 waves) interaction 52
 - wave-wave (4 waves) interaction 52
 - weak magnetic shear type 123
 - weak turbulence theory 34, 49–51

wedge 247, 248, 250
weighting factor 542–544
wind and react 230, 235

y

yin-yang coil 7
yttrium-based oxide 229, 231

z

Zakharov equation 259, 260
Zeeman effect 516, 529
zero-dimensional particle 145–146
zirconium cobalt 419, 423
zonal flow 96
zoning management 555

