

## Index

### **a**

- AB-stacked bilayer graphene (AB-BLG)
  - 169, 170
- advanced electronic cooling 381–392
- Al<sub>2</sub>O<sub>3</sub> nanoparticles 185
- alkali metals 17, 18, 27, 38, 39, 41, 71, 323, 324, 365–368, 379–381
- alloy preparation 192–201
  - morphology formation 197–201
  - structure formation 194–197
- alloying-dealloying process 199
- alternating current (AC) voltage
  - 108–109, 112, 113, 278, 295
- alternating magnetic field (AMF) 100, 114–117, 122, 123, 315, 316
- aluminum oxide membranes (AAMs) 84
- angiography 328–330
  - X-ray imaging 329
- aqueous polyethylene glycol 75
- artificial heart based on LM
  - 350, 351
- atmospheric pressure CVD (APCVD)
  - 165

### **b**

- bendability 10, 270
- Bernoulli's principle 228
- Bi nanowires 52, 53
- biodevice applications of LM
  - 341–352
- biomedical imaging 328–332
  - photoacoustic imaging 331–332
  - X-ray imaging 328–331

### **biomimetic materials**

- description 332–334
- flexible exoskeleton 336–337
- nerve connector 337–341
- reversible bone cement 334–336
- biosensors based on LM 341–346
- biphasic liquid metal mix 16, 24–26
- body-centered cubic (BCC) phase 193, 195, 196
- Brownian-like motion 133
- bulk liquid metal 49, 138, 146, 372, 373

### **c**

- cancer magnetic hyperthermia 123
- carbon fiber cloth/K (CFC/K) electrode
  - 375
- carbon fiber cloth/Na (CFC/Na) electrode
  - 375
- carbon fiber cloth/Na–K(CFC/Na–K) electrode
  - 376
- carbon nanotube/liquid metal (CNT/LM) composites 241, 242
- carbon nanotubes (CNTs) 83, 104
- carbon-dosed silicone (cPDMS) 227
- catalysis, liquid metal 392
- catalyst-assisted methods 72, 82–83
- catalytic mechanism of Pd–Ga mixture
  - 393
- channelless fluidic jetting 76, 77, 91
- chemical additive 135, 136
- chemical tuning
  - chemical-induced deformation
    - 125–130

- chemical tuning (*contd.*)
    - chemical-induced locomotion 130–134
    - chemical-tuned properties 134–136
  - chemical vapor deposition (CVD) 157, 158, 160, 162, 164, 165, 167, 169, 172, 178, 179, 183, 188–190
  - chemotherapy 311, 314, 315
  - chemothermal treatment based on LM 323
  - clusters 21, 22, 24, 29, 79, 122, 124, 156–158, 190, 290, 380
  - coercive force ( $H_c$ ) 195
  - cold-wall physical vapor deposition (CWPVD) 83
  - complementary
    - metal-oxide-semiconductor (CMOS) 266, 268
  - composite materials, flexible electronics 267–269
  - computed tomography (CT) imaging
    - based on LM 328
  - computer simulation 16
  - conductive fiber 137, 272
  - conductive polymers 337
  - confined nitridation method 173
  - confinement heteroepitaxy (CHet)
    - approach 72, 88, 90, 92
  - construct liquid metals-based architectures
    - direct writing
      - definition 231–232
      - inkjet printing 232–234
      - micro-extrusion printing 234–242
    - external field guiding
      - electric field-guided patterning 246–248
      - magnetic field-guided patterning 243–246
    - imprinting 225–227
    - injection
      - definition 219
      - direct injection 219–222
      - vacuum filling 222–225
    - laser ablation 243
    - mask-assisted deposition 227–231
  - contact angle equation 44
  - continuous electrowetting (CEW) 101, 102, 106, 113, 246, 247
  - cooling systems, optimization 381–392
  - core-shell array (CSA) 187
  - core-shell particles 159
  - coulomb explosion 79, 80, 92
  - $Cr_2O_3/Al_2O_3$  catalysts 393, 394
  - crystallography theory 16
- d**
- dealloying 141, 156, 194, 198–203, 368, 377
  - 1-decylphosphonic acid (DPA) 135
  - deformation
    - chemical-induced 125
    - electric-induced 107
    - force field-induced 136
    - magnetic-induced 114
  - deoxygenated silicone oil 75
  - dielectrics 138, 267
  - direct injection process 219–222
  - direct printing method 364
  - direct-current (DC) voltage 101
  - disease therapeutics 310
  - dispersive liquid metal nanoparticle (LMNP) electrode 311, 372, 373
  - drug carrier 311, 316, 320
  - drug delivery system (DDS) 311, 314
  - 2D superordered structure (2DSOS) arrays 185
- e**
- edge covalent bonding 188
  - EGaIn electrodes based electrochemical therapy 326
  - EGaIn nanorices 319, 320
  - “egg-box” crosslinkers 233
  - elastic cooling stability 198
  - elastomer composite 250, 251
  - electric field-guided patterning 246–248
  - electric-induced deformation 107–113
  - electric-induced locomotion 101–107

- electrical conductivity 100  
   liquid alloy system 37  
   resistance change at melting point 34  
   solid and liquid state 34–35  
   temperature dependency 36–37  
 electrical double layer (EDL) 101–104,  
   126, 127, 130–133, 388  
 electrical field tuning 101–114  
 electrical resistance 34–37, 107, 274,  
   285, 337  
 electrocapillarity phenomenon 107, 108,  
   110  
 electrochemical behavior 110  
 “electrochemically controlled capillarity”  
   (ECC) approach 247  
 electrochemical therapy based on LM  
   325–327  
 electrode systems 362  
 electromagnetic heating effect 122  
 electromigration 104–106  
 electron-rich metallic cores 122  
 electroosmotic flow (EOF) pump 349  
 electrowetting process 42, 43  
 elementary substances of flexible  
   electronics 264–268  
 embolization therapy based on LM 326,  
   327  
 embolotherapy 326–328  
 energy sources 131  
 eutectic alloy 22, 28, 311, 335, 336  
 exoskeleton 336–337  
 external energy source supply 100  
 external magnetic field 122, 123
- f**
- fabricate liquid metal 158, 225, 250  
 face-centered cubic (FCC) phase 193,  
   195–197  
 Faraday waves 110  
 fast Fourier transform (FFT) 175, 190  
 ferromagnetic materials 100, 114, 116,  
   119, 122, 124  
 flexible electronics  
   advantages of LM 268  
   bendability 270  
   construction strategy 269–270  
   LM-TENG 294–296  
   soft sensors 284–293  
   stretchability 270  
   stretchable antennas 281–284  
   stretchable circuit elements 276–281  
   stretchable conductors 272–276  
   traditional materials for flexible  
     electronics  
       composite materials 267–268  
       elementary substances and inorganic  
       materials 264–266  
       organic materials 266–267  
 flexible exoskeleton based on LM  
   336–337  
 flexible TFTs 265  
 fluorescence colocalization technology  
   314  
 fluorescence quantitative analysis  
   314  
 free electron model 34  
 fuel energy problem 5–6
- g**
- Ga-based alloy 20, 113, 173, 365, 367,  
   371, 379, 382, 385, 386  
   wettability of 367  
 Ga-based defense layer 377, 378  
 Ga-based liquid coolants 383–385  
 Ga-based liquid metals 30, 39, 131, 143,  
   144, 218, 371–373, 390, 396  
 Ga-based metal anodes 371–373  
 Ga-Cu galvanic corrosion couple 111  
 Ga oxide monohydroxide (GaOOH) 141,  
   144, 199  
 Ga<sub>67</sub>In<sub>20.5</sub>Sn<sub>12.5</sub> alloy  
   for peripheral neurotmesis treatment  
   338  
 Ga-In system 28, 29, 49  
 Ga-In-Sn system 29  
 GaInSn surface 101, 126  
 gallene (2D Ga) 54  
 gallium (Ga) 27, 50, 54  
 gallium arsenide (GaAs) 5  
   applications 5

- gallium nitride (GaN) 5, 89, 158, 159, 172, 173, 175, 176
- gallium–indium–tin ternary alloy 173
- galvanic displacement 84–86
- gel-like LM integrated system for wireless human motion sensing 342
- Gibbs free energy 49, 173, 174, 366, 367
- glass transition temperature 196
- graphene 142
- array 184–186
- single-layer graphene 163–165, 167, 168
- graphene quantum dots (GQDs) 142, 313
- graphene super ordered structure (GSOS) 184, 185
- h**
- Hafner’ theory 17
- hard-sphere-like structure 17, 19, 20, 34, 58
- heterogeneous stacking control 188–191
- hexadecafluorocopper phthalocyanine (F-CuPc) 267
- hexagonally closed packed (HCP) phase 193
- hierarchical graphene architectures (HGAs) 180, 181
- high-angle annular dark-field scanning transmission electron microscope (HAADF-STEM) 161, 172, 175, 176
- high-performance electrogenerated chemiluminescence (ECL) biosensor for exosomes detection 345, 346
- high-resolution transmission electron microscope (HRTEM) 78, 165, 172, 189, 190
- high-temperature liquid metal electrodes 362, 363, 368–371, 396
- metal-metal design 368–370
- metal-nonmetal design 370–371
- Hildebrand’s fluidity model 140
- Hot-Pressing (HP) 12, 88, 89
- hybrid coolants, design 385–390
- hydrochloric acid (HCl) 31, 128–131, 165, 174, 231, 234
- hydrogen chloride (HCl) electrolyte 108
- hydrogen evolution reaction (HER) 189, 191
- hydrophobicity 44, 225
- hyperthermia therapy 314
- chemothermal treatment 323–324
- magnetic hyperthermia 315–316
- microwave dynamic therapy 324–325
- photothermal therapy 317–322
- radio-frequency 322–323
- hysteresis loss (Pu) 195
- i**
- IL-LM-ZrO<sub>2</sub> nanoparticles fabrication 324
- implantable electrodes based on LM 346–348
- imprinting liquid metal 218, 225
- In nanowires 50–51
- in-plane WC/graphene heterostructure 190, 191
- injection
- definition 219
- direct injection 219–222
- vacuum filling 222–225
- inkjet printing 219, 232–234, 274
- inorganic materials, flexible electronics 264–268, 321
- inorganic/organic hybrid flexible electronics 268
- integrated cooling system with hybrid coolants 387, 389
- intelligent liquid metal-based motors 146
- intermetallic compounds 24, 156, 197
- intracellular delivery of Dox-loaded LMNP/L 311, 314
- iron (Fe) alloy 193
- isopropyl alcohol (IPA) solution 88
- isotropic graphene grains (IGGs) 181, 182

## L

- Laplace barriers 220
- laser ablation 218, 219, 243, 244, 249
- laser irradiation 141, 142, 243, 314, 318–320, 331, 333
- laser-responsive drug delivery based on LM 313
- lead (Pb) nanowire 52
- lead-bismuth eutectic (LBE) alloy 380, 381
- Lennard–Jones potential 106
- Li–S liquid batteries 370
- light alkali metals 17
- light emitting diodes (LEDs) 5, 236, 267, 277, 278, 286, 287, 291, 294, 296, 297, 343, 382, 384, 391
- light-responsive EGaIn NPs with graphene quantum dots 313
- light-responsive LM carriers for controllable drug release 312
- Lippmann equation 101
- liquid alloy droplet 109, 110
- liquid alloy system
  - electrical conductivity 37
- liquid crystal display (LCD) 285, 286
- liquid ethanol 140, 144, 250
- liquid eutectic gallium indium (EGaIn) droplet 103
- liquid exfoliation 158, 162
- liquid Ga–In–Sn alloy droplet 108
- liquid gallium–indium (Ga–In) alloy 363
- liquid gallium–tin (Ga–Sn) nanoparticles 363
- liquid-liquid phase transitions 21
- liquid metal (LM)
  - alloyed elements 6–7
  - atomic weight 6–7
  - base elements 8
  - biodevice applications 341–351
  - biomedical imaging applications 328–332
  - biomimetics 332–341
  - dealloying 156, 194, 198–201
  - drug delivery carriers 314
  - flexible electronics 264–268
  - melting point 6–7
  - nanocarriers 311
  - patterns 239
  - self-limiting oxide layer 176
  - therapeutic applications 310–328
  - for tumor therapeutics 310
- liquid metal alloy
  - thermal conductivity 38–39
- liquid metal-assisted rapid growth 178–179
- liquid metal assisted synthesis
  - alloy preparation 194–201
  - heterogeneous stacking control 188–191
  - morphology control 179–181
  - morphology formation 197–201
  - one-dimensional nanomaterials 159–161, 162
  - ordered assembly control 184–187
  - oriented stitching control 181–184
  - oxide skins synthesis 173–176
  - sliding transfer 191–192
  - structure formation 194–197
  - substrate synthesis 162–173
  - two-dimensional nanomaterials 161–192
  - vapor synthesis 176–178
  - zero-dimensional nanomaterials 158–159
- liquid metal-based motors 133, 146
- liquid metal-based self-powered motor 293
- liquid metal-based TENG (LM-TENG) 293–297
- liquid metal battery
  - based on solid-state electrolyte 365
- liquid metal catalysts 161, 392–397
- liquid metal composites (LMC) 120, 140, 141, 250
- liquid-metal coolant 378–392
- liquid metal electrodes
  - advantages 362–363
- liquid metal-embedded elastomer (LMME) film 230, 250, 251
- liquid metal fiber sensor 343–344

- liquid metal flexible capacitor sensor 344
  - liquid Pb
    - local structure 19
  - liquid-phase exfoliation 88, 157, 188
  - liquid-phase preparation method 73
  - lithium ion batteries (LIBs) 363
  - LM@GOX 322
  - LM/DSPC/Dox particles 312
  - locomotion 119, 145
    - chemical-induced locomotion 130–134
    - electric-induced locomotion 101–107
    - magnetic-induced locomotion 116–122
  - Lorentz force 30, 114, 116, 117, 118, 122, 123, 124
  - low melting point 26
    - alkali metals 27
    - liquid metal 362–378
    - metal alloys 27–29
    - post transition metals 27
    - zinc group metals 26
- m**
- magnesium (Mg) alloy 193
  - magnesium–aluminum (Mg–Al) series alloys 193
  - magnetic field
    - guided patterning 243–246
    - tuning
      - magnetic-induced deformation 114–116
      - magnetic-induced locomotion 116–122
      - magnetic-tuned properties 122–125
  - magnetic force 43, 44, 114, 115, 119, 125
  - magnetic hyperthermia based on LM 315–316
  - magnetic repulsion force 120
  - magnetism 269
  - Marangoni effect 108, 133
  - Marangoni flow 108, 111, 130, 387–389
  - mask-assisted deposition 218, 219, 227–231
  - maximum magnetic flux density ( $B_m$ ) 195
  - mechanical exfoliation 157, 162, 169
  - melting mechanism 20
  - Mendeleev’s prediction 4–5
  - merely distorted structure 16, 17
  - metal nano/micro-particles 33
  - metal-chalcogen battery 370
  - metal-organic chemical vapor deposition (MOCVD) 158, 159
  - metal–metal design for liquid metal electrodes 368–370
  - metal–metal halide battery 370
  - metal–nonmetal design for liquid metal electrodes 370–371
  - metallic glass 193
  - metallic Zn 85
  - Mg–GaIn material for skin tumor therapy 317
  - micro-motors 133
  - microfluidic channels 75, 77, 111, 112, 116, 138, 139, 223, 234, 247, 248, 343, 351
  - microfluidic flow focusing system 73, 75, 76, 91
  - microfluidic pump based on LM 341, 348–351
  - microfluidics 6, 29, 41, 160, 222, 348
  - microwave dynamic therapy based on LM 324–325
  - microwave thermal therapy (MWTT) 324, 325
  - molding forces 79
  - molecular beam epitaxy (MBE) method 72, 77–79, 86, 89–92, 158
  - mono-component liquid metal 16–24
  - monoatomic liquid metals 123, 124
  - monolayer graphene (MLG) 163–169, 170, 177, 189
  - monophasic liquid metal alloy 16, 22, 24, 58
  - Mott potential 47
  - movement monitoring of LM-based biosensors 289, 341, 342

**n**

Na-metal halide high-temperature  
batteries 368

Na-K alkali metal anodes 373–376

nanofluids 389, 390

nanomaterial synthesis 157–192

nanosheets (NSs) 56, 72, 86

2D Sn 56, 86

synthesis 40, 88

nanowires (NWs) 49–53, 81

catalyst-assisted methods 82

catalyst-free methods 83–84

near infrared (NIR) laser irradiation  
141

nerve autografting 337

neutron diffraction 16, 22

NeverWet-coated channel 220, 221

nickel particles 33

NIR laser-stimulated LM nanocapsule  
320

non-limiting surface oxidation 47

non-reactive wetting behavior 366–368

nuclear energy system 362

**o**

one-dimensional liquid metal 49

Bi nanowires 53

Ga nanowires 50

In nanowires 50–51

Pb nanowires 52

Sb nanowires 53

Sn nanowires 51–52

ordered assembly control 184–187

organic materials, flexible electronics  
264–268, 272, 321

oriented stitching control 181–184

oscillation process 131

oscillatory tests 125

oxidative stress 127

oxidized GaIn (O-GaIn) for AMF-based  
tumor therapy 315

**p**

pair distribution function (PDF,  $g(r)$ ) 16

particle internalization effect 131, 390

passivating surface oxide of liquid metal  
220

PDMS microfluidic device 223

peripheral nerve injury (PNI) repair based  
on LM 337, 338

pH-responsive drug delivery based on LM  
312

pH-responsive LM nanocarriers for drug  
delivery 311

phase-change-based method 129

phosphatization process 175

photoacoustic imaging based on LM  
nanocapsules 331–333

photothermal conversion efficiency for  
EGaIn nanorice 314, 319, 322

photothermal therapy (PTT) 100,  
317–322

piezoresponse force microscopy (PFM)  
175

planar Na-nickel chloride ( $\text{NiCl}_2$ ) battery  
371

plasma enhanced chemical vapor  
deposition (PECVD) 160

poly (methyl methacrylate) (PMMA)  
coating 165, 184, 191, 192, 250,  
334

poly(1-octadecene-alt-maleic anhydride)  
(POMA) 75

polycrystalline Si 264, 265

polydimethylsiloxane (PDMS) 138

microchannels 272

polydopamine (PDA)-coated liquid metal  
nanodroplets 141

polyethylene naphthalate (PEN) 270

polyimide (PI) substrate 268

polymeric nanocapsule 142

polymethacrylates (PMA) 229, 230

polytetrafluoroethylene (PTFE) 79, 80

polyvalent liquid metals 17

polyvalent metal 18, 140

portable LM pulse sensor 342

portable smart glove 343

post-transition metals 27

pressure induced structure changes 21

Pt/ $\text{Al}_2\text{O}_3$  catalysts 394

**q**

quantum dots  
OD 157

**r**

radio-frequency (RF) hyperthermia based  
on LM 322–323  
Raman spectroscopy 163–165  
reactive wetting behavior 366, 367  
reactor coolants 379  
advanced electronic cooling 381–392  
liquid alkali metal 379  
liquid heavy metals 380–381  
recapillarity 247, 248  
rheological properties 29–31, 33, 58  
formation of composite effects 31–34  
oxide surface effects 30–31  
Riger's solution 338  
room-temperature liquid metal electrodes  
362, 365, 371  
Ga-based metal anodes 371–373  
Na–K alkali metal anodes 373–376  
room-temperature liquid  
sodium–potassium (Na–K) alloy  
364  
room-temperature liquid-metal coolants  
382  
rotating magnetic field (RMF) 118,  
120–122

**S**

saturation magnetization ( $M_s$ ) 195  
Sb nanosheets 56–57  
Sb nanowires 53  
scanning electron microscope (SEM) 4,  
25, 84, 89, 105, 128, 134, 137, 138,  
159, 164, 172, 179, 183–186, 191,  
195, 200, 229, 230, 238, 239, 241,  
242, 244, 272, 291, 364, 373–375,  
393, 394  
sedimentation methods 251  
selected area electron diffraction (SAED)  
patterns 85, 165, 189  
Selenium (Se) atoms 83  
self-driven cooling system 391, 392  
self-electrophoresis 130, 131, 133  
self-healing Li–bismuth system 368, 369  
self-healing stretchable wire (SHS wire)  
281, 282  
self-limiting reaction 125, 136  
self-propulsion locomotion 130  
semiconducting elementary substances  
264  
 $\alpha$ -sexithiophene ( $\alpha$ -6T) 267  
shear mixing 249, 250  
shearing liquids into complex particles  
(SLICE) 79–81, 92, 221, 222, 330,  
339  
shearmixing liquid metal 140  
Si nanowire (NW) 160–162, 264  
silicon (Si) 77, 264  
single-crystalline *h*-BN (SC-*h*-BN) films  
183, 184  
single-layer graphene 163, 164, 165, 167,  
168  
smart glove 292, 293, 343  
smart silicone-based glove with integrated  
sensing system 343  
smart wearable devices 293  
Sn nanowires 56  
Sn nanowire 51–52  
sodium–potassium (NaK) alloy for  
chemothermal treatment 323  
sodium–sulfur (Na–S) high-temperature  
batteries 368  
soft sensors 10, 270, 284–293  
solid Ga 6, 20, 27  
solid-solution phase 156, 192–194, 196,  
202  
solid-state technologies (SSTs) 286  
solution-phase chemistry 73, 76, 90  
solution–liquid–solid (SLS) method 160,  
161, 202  
sonication 33, 73, 75, 77, 90, 91, 141,  
151, 319, 320  
static structure factor (SSF,  $S(q)$ ) 16  
stretch–shrink patterning (SSP) process  
229  
stretchability 10, 224, 229, 270, 271, 274,  
275, 281, 283, 284, 296, 344



- stretchable and healing triboelectric nanogenerator (SH-TENG) 250, 251
- stretchable antennas 270, 281–284
- stretchable circuit elements 270, 276–281
- stretchable conductors 225, 229, 270–277
- stretchable electronics 72, 136, 217, 219, 222, 233, 266, 270, 273, 274, 283, 290
- stretchable noninvasive pulse LM-based sensor 341
- strong anomaly structure 17
- superconductivity 51–53, 56, 58, 59, 169
- surface engineering of liquid metal 320, 321
- surface layering 47–49
- surface modification 6, 125, 134–136, 139, 145
- surface morphology 143, 226
- surface properties 40
  - high surface activity 44–47
  - internalization 44–46
  - oxidation 46–47
  - high surface energy 41–44
    - non-reactive surface wetting 42–44
    - surface tension 41–42
  - ordered surface state 47–49
- surface self-limiting oxidation 46–47
- surface tension 41–42, 44, 47, 49, 59, 72, 74–76, 80, 92, 101–102, 107–111, 113, 116, 120, 127, 130–131, 133–134, 145, 156–157, 168, 172, 185, 198, 218–219, 243, 363
- surface-coated tungsten oxide (WO<sub>3</sub>) nanoparticles 102
- surface-initiated atom transfer radical polymerization (SI-ATRP) 252
- t**
- tensile force 136–139
- thermal conductivity 37
  - liquid metal alloy 39
  - oxide surface effect 39–40
  - pure liquid metal 37–39
- thermal deposition 77–79, 91
- thermal energy 139, 331
- thermal stability 196, 310, 394
- thermal-field-induced movement 140–141
- thermosiphon effect 391–392
- thin film transistors (TFTs) 264–265, 267–268
- three-dimensional LM injection electrode 348
- time-of-flight secondary ion mass spectra (TOF-SIMS) 178–179
- TMDs/h-BN heterostructures 188
- touch-ablation process 376–378
- transition metal carbides (TMCs) 169–170
- transition metal dichalcogenides (TMDs) 161, 169, 176, 178, 188–190, 265
- transmission electron microscope (TEM) 74, 78, 80, 84, 104–105, 142, 165, 172, 189, 192, 232–233, 319–320, 333, 372
- triboelectric nanogenerator (TENG) 250, 293
- tumor therapy 311–312, 314–317, 320–322, 324–325, 331
- twelve-pointed graphene grains (TPGGs) 180
- two-dimensional liquid metal 53
  - Bi 57–58
  - Ga 54
  - In 54
  - Pb 56
  - Sb 56–57
  - Sn 56
- U**
- uncured silicone elastomer 140
- V**
- vacuum filling 218–219, 222–225
- van der Waals (vdW) exfoliation approach 80, 173

van der Waals (vdW) (*contd.*)  
  stacking 188  
  squeeze-printing approach 176  
vapor-phase preparation 72, 77–79, 90  
vapor–liquid–solid (VLS) mechanism  
  82–83, 157, 159–162, 202

**W**

Waseda's classification 17  
wettability, of Ga-based alloys  
  367  
wetting behavior 226–227, 366–368,  
  375–376  
Wiedemann–Franz Law 37–38

**X**

X-ray diffraction (XRD) pattern 16, 20,  
  23, 25, 46, 74, 84, 167, 169–170,  
  195, 229, 291  
X-ray photoelectron spectroscopy (XPS)  
  30, 166–167, 192, 377

**Y**

Young's module 269  
Young–Laplace equation 102, 220, 225,  
  389

**Z**

Zn hydrometallurgy 72











